GWS ENGINGEERING & INDUSTRIAL SUPPLIES LTD.
Link Road, Poulavone, Ballincollig, Co. Cork.
Tel: 021 4875878 Fax: 021 4875882
E: info@gwscork.ie Web: www.gwscork.ie POSTCODE: P31 YK61

中国认可
国际互认
检测
TESTING
CNAS L4525

CE

0343/CPR/SHA/BJG6041035/02 QUALITY CERTIFICATE EN 10204 3.1

REPORT NO.:YF25GW537-2-51035 DATE（日期):JUN.2025

PURCHASER(客户):G.W.S ENGINEERING & INDUSTRI	ISO NO .(ISO号码):ISO 9001 – 0070445
MANUFACTURING DATE(生产日期):MAY.2025	QUANTITIES(数量):1856 PCS
COMMODITY(品名):EN15048-8.8/8-Non- Preloaded structural bolting assemblies	

CONTRACT NO.(合同号):61912	SIZE(规格):M20X60
MATERIAL(材料):10B33	FINISH(色别):ZP
LOT NO.(批号): 3040351035	

DIMENSIONAL INSPECTION(外形检测)

HEX BOLT-ISO4017-M20X60-8.8

SAMPLING DATE :MAY.2025 SAMPLES : 8 PCS

INSPECTION ITEM (检测项目)	STANDARD （标准值)	ACTUAL RESULT （实测值）	RESULT
APPEARANCE外观	OK	OK	OK
HEAD MARK 标记	XYLX-8.8SB	OK	OK
WIDTH ACROSS FLATS 对边	29.67-30	29.75-29.84	OK
HEAD HEIGHT 头部厚度	12.285-12.715	12.520-12.570	OK
BODY DIAMETER 杆径	F/T	F/T	OK
LENGTH 长度	59.4-60.6	59.89-60.24	OK
THREAD LENGTH 螺纹长度	F/T	F/T	OK
GO-GAGE	6h/T	GO	OK
NO-GO-GAGE	6g/Z	NO GO	OK
STRAIGHTNESS直线度	0.2MAX	OK	OK
ZINC THICKNESS锌层厚度um	5MIN	7.2-8.8	OK

HEX NUT-ISO4032-M20-8

SAMPLING DATE :MAY.2025 SAMPLES : 8 PCS

INSPECTION ITEM (检测项目)	STANDARD （标准值)	ACTUAL RESULT (实测值)	RESULT
APPEARANCE外观	OK	OK	OK
HEAD MARK 标记	XYLX-8SB	OK	OK
WIDTH ACROSS FLATS 对边	29.16-30	29.74-29.82	OK
HEAD HEIGHT 头部厚度	16.9-18	17.38-17.43	OK
ZINC THICKNESS锌层厚度um	5MIN	8.1-8.4	OK

WASHER-ISO7091-M20

SAMPLING DATE :MAY.2025 SAMPLES: 8 PCS

Inspection item	Standard	Actual result	Result
Marking	XYLX-SB	OK	OK
Hole diameter(d1)	22-22.52	22.18-22.24	OK
Outer diameter (d2)	35.4-37	35.89-35.96	OK
Thickness(h)	2.4-3.6	3.54-3.59	OK

MECHANICAL PROPERTIES(机械性能检测)

HEX BOLT-ISO 898-1

SAMPLING DATE :MAY.2025 SAMPLES : 8 PCS

TEST ITEM 检测项目	STANDARD （标准值)	ACTUAL RESULT (实测值)	RESULT
HARDNESS硬度(HRC)	23-34	28-30.5	OK
		26.5-28	OK
TENSILE STRENGTH 抗拉强度(MPa)	830MIN	923-927	OK
YIELD STRENGTH屈服强度(MPa)	660MIN	815-846	OK
ELONGATION(延伸率）	12MIN	/	/
REDUCTION AREA (缩面率)	52MIN	/	/
PROOF LOAD(保载）(KN)	147	147	OK
Impact strenght冲击功KV[J]	27MIN	77.9/80.6/78.2	OK

HEX NUT-ISO 898-2

SAMPLING DATE :MAY.2025 SAMPLES : 8 PCS

TEST ITEM 检测项目	STANDARD （标准值)	ACTUAL RESULT (实测值)	RESULT
HARDNESS硬度(HRC)	34.8MAX	27-28	OK
PROOF LOAD(保载）(KN)	225.4	225.4	OK

WASHER-ISO7091

SAMPLING DATE MAY.2025 SAMPLES: 8 PCS

TEST ITEM	STANDARD	ACTUAL RESULT (实测值)	RESULT
Hareness(HV)	100HV	136-144	OK

SUITABILITY TEST组合实验-EN 15048-1/2

SAMPLING DATE :MAY.2025 SAMPLES : 8 PCS

TENSILE RESISTANCE OF BOLT/NUT ASSEMBLIES(KN)	203MIN	224.84-231.55	OK

CHEMICAL COMPOSITION (化学成分检测)

SAMPLING DATE :MAY.2025

Item	Material	Heat No.	C	Mn	P	S	SI		
BOLT	10B33	B2-2503288	0.32	0.74	0.013	0.004	0.17		
NUTS	35K	G532004952	0.37	0.74	0.01	0.003	0.14		
Washer	A3	EB42305180	0.023	0.33	0.012	0.001	0.167		

(SIGNATURE)

We certify that the information detailed above has been reproduced from the original test certificate furnished by the manufacturer.

Niall Crowley, Quality Manager

江苏甬怡紧固件有限公司 Jiangsu Yongyi Fastener Co., Ltd
质量部
INSPECTION DEPARTMENT