# Mathematical Methods of Classical Mechanics – V. I. Arnold

Notes by Gene

2026

## Contents


**I Newtonian Mechanics** **3**

**1 Experimental Facts (p. 3 – 11)** **3**
1.1 The Galilean Group . . . 4
1.2 Motion, Velocity, and Acceleration . . . 5

**2 Investigation of the Equations of Motion (p. 15 – 50)** **6**
2.1 Systems with 1 Degree of Freedom . . . 6
2.1.1 Phase Plane . . . 6
2.1.2 Phase Flow . . . 7
2.2 Systems with 2 Degrees of Freedom . . . 7
2.3 Conservative Force Fields . . . 9
2.4 Angular Momentum . . . 10
2.5 Motion in a Central Field . . . 11
2.6 Motion in Three-Space . . . 12
2.7 Motion of a System of $n$ points . . . 12
2.7.1 Conservation of Momentum . . . 13
2.7.2 Conservation of Angular Momentum . . . 13
2.7.3 Conservation of Energy . . . 14

**II Lagrangian Mechanics** **15**

**3 Variational Principles (p. 55 – 74)** **16**
3.1 Calculus of Variations . . . 16
3.1.1 Functionals . . . 16
3.1.2 Euler-Lagrange Equations . . . 17
3.2 Lagrange's Equations . . . 18
3.3 Legendre Transformations . . . 18
3.4 Hamilton's Equations . . . 19
3.5 Cyclic Coordinates . . . 21
3.6 Liouville's Theorem . . . 21
3.7 Poincaré's Recurrence Theorem . . . 22

**4 Lagrangian Mechanics on Manifolds (p. 75 – 97) 22**
4.1 Holonomic Constraints . . . 23
4.2 Differentiable Manifolds . . . 24
4.2.1 Definitions . . . 24
4.2.2 Tangent Space & Tangent Bundle . . . 25
4.2.3 Riemannian Manifold . . . 25
4.2.4 The Derivative Map . . . 26
4.3 Lagrangian Dynamical Systems . . . 26
4.3.1 Natural Systems . . . 27
4.3.2 Non-Autonomous Systems . . . 27
4.4 Noether's Theorem . . . 28
4.5 D'Alembert's Principle . . . 29
4.5.1 Equivalence with the Variational Principle . . . 30
4.5.2 Equilibrium Positions . . . 31

**5 Oscillations (p. 98 – 122) 31**
5.1 Linearization . . . 31
5.2 Linearizing a Lagrangian System . . . 32
5.3 Small Oscillations . . . 33
5.3.1 Example: Connected Pendulums . . . 34
5.3.2 Weak Spring . . . 35
5.3.3 General case . . . 36
5.4 Rayleigh-Courant-Fischer Theorem . . . 36
5.4.1 Behavior of Characteristic Frequencies: Change in Rigidity . . . 37
5.4.2 Behavior of Characteristic Frequencies: Imposition of Constraint . . . 37
5.5 Parametric Resonance . . . 38
5.5.1 Relation to Traces . . . 39
5.5.2 Parametric Resonance . . . 39

**6 Rigid Bodies (p. 123 – 162) 41**
6.1 Motion in a Moving Coordinate System . . . 41
6.1.1 Addition of Velocities . . . 41
6.2 The Coriolis Force . . . 42
6.3 Rigid Bodies . . . 43
6.3.1 The Inertia Tensor . . . 44
6.3.2 The Inertia Ellipsoid . . . 45
6.4 Euler's Equations . . . 45
6.5 Lagrange's Top . . . 46
6.5.1 The Lagrangian . . . 47
6.5.2 Nutation . . . 48
6.5.3 Precession . . . 49
6.6 Lagrange's Top: Special Cases . . . 49
6.6.1 Sleeping Top . . . 49
6.6.2 Fast Top . . . 50

**III Hamiltonian Mechanics 52**

**7 Differential Forms (p. 163 – 200)** **52**
7.1 Exterior Forms . . . 52
7.1.1 $k$-Forms . . . 52
7.1.2 Exterior Product of $k$-Forms . . . 54
7.1.3 Exterior Multiplication . . . 56
7.2 Differential 1-Forms . . . 56
7.3 Differential $k$-Forms . . . 57
7.3.1 Change of Basis . . . 57
7.4 Integration of Differential Forms . . . 58
7.4.1 Boundaries . . . 60
7.5 Exterior Differentiation . . . 61
7.5.1 Exterior Derivative . . . 61
7.5.2 Stokes' Formula . . . 62

**8 Symplectic Manifolds (p. 201 – 232)** **63**
8.1 Symplectic Structure on Manifolds . . . 63
8.2 Hamiltonian Phase Flow . . . 64
8.2.1 Generalization of Liouville's Theorem . . . 64
8.2.2 Integral Invariants . . . 65
8.3 Lie Algebra of Vector Fields . . . 65
8.4 Lie Algebra of Hamiltonian Functions . . . 67
8.5 Symplectic Geometry . . . 67
8.6 Parametric Resonance . . . 68
8.7 Darboux's Theorem . . . 69

**9 Canonical Formalism (p. 233 – 270)** **70**
9.1 Integral Invariant of Poincaré-Cartan . . . 70
9.1.1 Stokes' Theorem in 3 Dimensions . . . 70
9.1.2 Stokes' Theorem in $n$ Dimensions . . . 70
9.1.3 Hamilton's Equations . . . 71
9.1.4 Applications . . . 72
9.2 Huygen's Principle . . . 73
9.2.1 Action Function . . . 74
9.2.2 Hamilton-Jacobi Equation . . . 75

## Part I

# Newtonian Mechanics

## 1 Experimental Facts (p. 3 – 11)

Certain experimental facts form the basis of classical mechanics. We can't verify them for certain, but they hold approximately, according to accurate tests.

1. **Space and time**: Space is 3D and Euclidean. Time is 1D.
2. **Galileo's Principle of Relativity**: There exist inertial coordinates such that

- Laws of physics are same in all inertial coordinate systems.
- Coordinate systems in uniform rectilinear motion w.r.t an inertial one is also inertial.

3. **Newton's Principle of Determinacy**: Initial state of a mechanical system uniquely determines its motion.

## 1.1 The Galilean Group

Let $\mathbb{R}^n$ denote an $n$-dimensional real vector space.

An **affine $n$-dimensional space**, denoted $A^n$, is similar to $\mathbb{R}^n$ but has no "fixed origin." The group $\mathbb{R}^n$ acts on $A^n$ as the **group of parallel displacements**.

$$a \to a + \mathbf{b}\ , \quad a \in A^n,\ \mathbf{b} \in \mathbb{R}^n,\ a + \mathbf{b} \in A^n$$

The sum of two points on $A^n$ is not defined, but their difference is a vector in $\mathbb{R}^n$. The distance between points of an affine space $A^n$ can be defined using the scalar product:

$$\|x - y\| = \sqrt{(x - y, x - y)}$$

An affine space with this distance function is called a **Euclidean space**, denoted $E^n$.

---

The Galilean spacetime structure has 3 elements:

1. **The universe**: A 4D affine space $A^4$. Points of $A^4$ are called *events*. Parallel displacements of $A^4$ form the vector space $\mathbb{R}^4$.
2. **Time**: A linear mapping $t : \mathbb{R}^4 \to \mathbb{R}$ from a parallel displacement to the "time axis." The time interval between $a, b \in A^4$ is $t(b - a)$.
3. **Distance Between Simultaneous Events**: Given by $\|a - b\| = \sqrt{(a - b, a - b)}$. This is a scalar product on $\mathbb{R}^3$. The space of simultaneous events is thus a 3D Euclidean space $E^3$.

| A Galilean space is a space $A^4$ that has a Galilean spacetime structure. |
|---|

| The Galilean group is the group of all transformations of a Galilean space which preserves its structure. |
|---|

Elements of a Galilean group are called **Galilean transformations**: affine transformations on $A^4$ which preserve the time interval & distance between simultaneous events.

The **Galilean coordinate space** is the direct product $\mathbb{R} \times \mathbb{R}^3$ of the $t$ axis with the 3D vector space $\mathbb{R}^3$. There are 3 examples of Galilean transformations of this space:

1. Uniform motion with velocity $\vec{v}$: $g_1(t, \vec{x}) = (t, \vec{x} + \vec{v}t)$
2. Translation of origin: $g_2(t, \vec{x}) = (t + s, \vec{x} + \vec{s})$
3. Rotation of coordinate axes: $g_3(t, \vec{x}) = (t, G\vec{x})$, $G : \mathbb{R}^3 \to \mathbb{R}^3$ is orthogonal transformation.

Every Galilean transformation of the space $\mathbb{R} \times \mathbb{R}^3$ can be written as the composition of the above, thus the dimension of the Galilean group is $3 + 4 + 3 = 10$.

Let $M$ be a set. A one-to-one correspondence $\phi_1 : M \to \mathbb{R} \times \mathbb{R}^3$ is called a **Galilean coordinate system** on the set $M$.

## 1.2 Motion, Velocity, and Acceleration

A motion in $\mathbb{R}^n$ is a differentiable mapping $\mathbf{x} : I \to \mathbb{R}^N$, where $I$ is an interval on the real axis. The image of a mapping $\mathbf{x} : I \to \mathbb{R}^N$ is called a **trajectory** or **curve** in $\mathbb{R}^N$. The velocity vector is the derivative $\dot{\mathbf{x}}(t_0)$, while the acceleration vector is the second derivative $\ddot{\mathbf{x}}(t_0)$.

Let $\mathbf{x} : \mathbb{R} \to \mathbb{R}^3$ be a motion in $\mathbb{R}^3$. The graph of this mapping ($\mathbb{R}^3$ against $\mathbb{R}$) is a curve in $\mathbb{R} \times \mathbb{R}^3$. A curve in Galilean space that appears in some Galilean coordinate system (as the graph of a motion) is called a **world line**.




Galilean worldlines

Consider a system with $n$ points. In Galilean space, this gives $n$ world lines, described by $n$ mappings $\mathbf{x}_i : \mathbb{R} \to \mathbb{R}^3$ in a Galilean coordinate system. In total, we have

$$\mathbf{x} : \mathbb{R} \to \mathbb{R}^N \ , \quad N = 3n$$

as the total motion of our system with $n$ points.

---

Newton's principle of determinacy states that all motions of a system are uniquely determined by their initial positions and velocities. Acceleration is not needed: it's determined by the initial position and velocities. I.e. there's a function $\mathbf{F} : \mathbb{R}^N \times \mathbb{R}^N \times \mathbb{R} \to \mathbb{R}^N$ such that

$$\ddot{\mathbf{x}} = \mathbf{F}(\mathbf{x}, \dot{\mathbf{x}}, t)$$

This is called **Newton's equation**. By the theorem of existence and uniqueness (recall from diff eq), the initial conditions $\mathbf{F}$, $\mathbf{x}(t_0)$, and $\dot{\mathbf{x}}(t_0)$ uniquely determine a motion. The form of $\mathbf{F}$ can be determined experimentally.

Galileo's principle of relativity requires that Galilean spacetime structure must be invariant w.r.t the group of Galilean transformations. This is a condition on Newton's equation, and leads to three properties of spacetime:

1. **Invariance under time translations**: Laws of nature remain constant regardless of time.
2. **Invariance under spatial translations**: Space is homogeneous; has the same properties at all of its points.
3. **Invariance under spatial rotations**: Space is isotropic; no preferred directions.

We may also introduce the "potential energy" $U$ to write Newton's equation. Let $E^{3n} = E^3 \times \cdots \times E^3$ be the configuration space of a system of $n$ points in the Euclidean space $E^3$. Let $U : E^{3n} \to \mathbb{R}$ be a differentiable function. The motion of the $n$ points (of masses $m_1, \ldots, m_n$) is given by the system of differentiable equations

$$m_i \ddot{\mathbf{x}}_i = -\frac{\partial U}{\partial \mathbf{x}_i} \ , \quad i = 1, \ldots, n$$

where $\mathbf{x} = (\mathbf{x_1}, \ldots, \mathbf{x_k})$ and $\partial U / \partial \mathbf{x} = (\partial U / \partial \mathbf{x_1}, \ldots, \partial U / \partial \mathbf{x_k})$. The equations of motion for many other mechanical systems can be written in this form.

# 2 Investigation of the Equations of Motion (p. 15 – 50)

This chapter deals with configurations for which Newton's equations can be solved.

## 2.1 Systems with 1 Degree of Freedom

Systems with 1 degree of freedom are described by the differential equation

$$\ddot{x} = f(x) \ , \quad x \in \mathbb{R}$$

The kinetic and potential energies are given by

$$T = \frac{1}{2}\dot{x}^2 \ , \quad U(x) = -\int_{x_0}^{x} f(\xi) \, d\xi$$

The total energy is $E = T + U$. In general, this is a function of $x$ and $\dot{x}$: $E(x, \dot{x})$.

---

**Theorem (law of conservation of energy)**: the total energy of points moving according to $\ddot{x} = f(x)$ is conserved. That is, $E(x(t), \dot{x}(t))$ is independent of $t$.

**Proof**:

$$\frac{d}{dt}(T + U) = \dot{x}\ddot{x} + \frac{dU}{dx}\dot{x} = \dot{x}(\ddot{x} - f(x)) = 0$$

### 2.1.1 Phase Plane

Note that the equation $\ddot{x} = f(x)$ is equivalent to the system of 2 equations: $\dot{x} = y$ and $\dot{y} = f(x)$. The **phase plane** is a plane with coordinates $x$ and $y$. A **phase point** is a point on the phase plane. Our system of differential equations determines a vector field on the phase plane, called the phase velocity **vector field**.

A particular solution $\phi : \mathbb{R} \to \mathbb{R}^2$ is the motion of a phase point in the phase plane, mapping time to the velocity vector. The image of $\phi$ is called the **phase curve**, given by

$$x = \phi(t) \ , \quad y = \dot{\phi}(t)$$

By existence & uniqueness, there's only one phase curve through every phase point. Note that a phase curve could consist of just one point. Such a point is called the **equilibrium position**, and the phase velocity vector there is zero.

From the law of conservation of energy, total energy must be conserved on a phase curve. Thus each phase curve lies on the energy level set $E(x, y) = h$.

---

As an example, consider the basic equation of oscillations, $\ddot{x} = -x$. The phase plane is

---




Phase plane of basic oscillation

### 2.1.2 Phase Flow

Let $M$ be a point in the phase plane. Assume that any solution to the system can be extended along the time axis. The resulting phase point at time $t$ can be written as

$$M(t) = g^t M(0)$$

This is a mapping of the phase plane to itself, $g^t : \mathbb{R}^2 \to \mathbb{R}^2$. We say $g^t$ is a **diffeomorphism**: it's a one-to-one differentiable mapping with a differentiable inverse.

The diffeomorphisms $g^t$ form a group: $g^{t+s} = g^t \circ g^s$, identity $g^0$, inverse $g^{-t}$, etc. The mapping $g : \mathbb{R} \times \mathbb{R}^2 \to \mathbb{R}^2$, defined by $g(t, M(0)) = g^t M(0)$, is also differentiable. Combined, we say that the transformations $g^t$ form a **one-parameter group of diffeomorphisms** on the phase plane. This group is called the **phase flow**.

## 2.2 Systems with 2 Degrees of Freedom

These become more difficult. A system with 2 degrees of freedom is defined by the system of differential equations

$$\ddot{x} = f(x) \ , \quad x \in E^2$$

Here $f(x)$ is a vector field on the plane. A system is **conservative** if there exists a function $U : E^2 \to \mathbb{R}$ such that $f = -\partial U / \partial x$. Then the equation of motion becomes

$$\ddot{x} = -\frac{\partial U}{\partial x}$$

---

**Theorem (law of conservation of energy)**: The total energy of a system is conserved, and given by

$$\frac{dE}{dt} = 0$$
$$E = \frac{1}{2}\dot{x}^2 + U(x) \ , \ \ \dot{x}^2 = (\dot{x}, \dot{x})$$

**Proof**: Use the equation of motion and form of $E$ to get

$$\frac{dE}{dt} = (\dot{x}, \ddot{x}) + (\partial U/\partial x, \dot{x}) = 0$$

**Corollary**: If at the initial moment the total energy is $E$, all trajectories will lie in the region where $U(x) \leq E$. In a system with 1 degree of freedom, it's always possible to find $U(x) = -\int f(\xi)d\xi$. But if we have 2 degrees of freedom, this isn't always possible.

I.e. there might not be a $U(x)$ such that $f(x) = -\partial U/\partial x$, which means the system isn't conservative.

---

An interesting example is **Lissajous figures**. Consider a system of small oscillations with 2 degrees of freedom:

$$\ddot{x}_1 = -x_1 \ , \ \ \ddot{x}_2 = -\omega^2 x_2$$

The potential energy ($U$) and total energy ($E$) are given by

$$U = \frac{1}{2}x_1^2 + \frac{1}{2}\omega^2 x_2^2$$
$$E = \frac{1}{2}(\dot{x}_1^2 + \dot{x}_2^2) + U(x_1, x_2)$$

From the law of conservation of energy, all motions will take place inside the ellipse $U(x_1, x_2) \leq E$. If we split into 1-dimensional systems in $x_1$ and $x_2$, the following quantities are conserved:

$$E_1 = \frac{1}{2}\dot{x}_1^2 + \frac{1}{2}x_1^2 \ , \ \ E_2 = \frac{1}{2}\dot{x}_2^2 + \frac{1}{2}x_2^2$$

Thus we have the bounds $|x_1| \leq \sqrt{2E_1(0)}$ and $|x_2| \leq \sqrt{2E_2(0)}$. We have the elliptical boundary from the 2-dimensional case and a rectangular boundary from the 1-dimensional cases.




Lissajous curve boundaries

Depending on the value of $\omega$, we get some interesting shapes.




Lissajous curve example with $\omega = 1$

## 2.3 Conservative Force Fields

Here we want to connect work with potential energy. The work of a constant force $F$ is defined as the scalar product of the path $S$:

$$A = (F, S) = |F||S| \cos\theta$$

Furthermore, we said a system is **conservative** if there exists a function $U : E^2 \to \mathbb{R}$ such that $f = -\partial U/\partial x$, for some force $f$.

**Theorem**: A vector field $F$ is conservative if and only if the work along any path $M$ depends only on the endpoints of the path.

**Proof**: First, suppose the work of a field $F$ doesn't depend on the path. Then

$$U(M) = -\int_{M_0}^{M} (F, dS)$$
$$F = -\frac{\partial U}{\partial x}$$

So we see that the field is conservative. Next, suppose the field $F$ is conservative and $U$ is its potential energy. Then

$$\int_{M_0}^{M} (F, dS) = -U(M) + U(M_0)$$

So the work doesn't depend on the path.

---

A vector field in the plane $E^2$ is called **central** with center 0 if it's invariant w.r.t the group of motions of the plane that fix 0. All vectors of a central field lie on rays through 0. The magnitude of the vector field at a point depends only its distance from the center. For example, $F = -k\hat{r}/r^3$ is central.

| Every central field is conservative, and its potential energy depends only on its distance to the center: $U = U(r)$. |
|---|

## 2.4 Angular Momentum

The invariance of an equation of a mechanical problem w.r.t some group of transformations **always implies a conservation law**. For example, we saw previously that energy is conserved because the system is invariant under a time translation. The central field is invariant w.r.t the group of rotations. This implies a conserved quantity that we call **angular momentum**.

The angular momentum of a point of mass relative to the point 0 (central point) is the cross product

$$M = r \times \dot{r}$$

where $r$ is the radius vector beginning at the center of the field.

**Theorem (law of conservation of angular momentum):** Under motions in a central field, the angular momentum $M$ relative to the center of the field doesn't change with time.

**Proof:** We know that $M = r \times \dot{r}$. Taking the derivative, $\dot{M} = \dot{r} \times \dot{r} + r \times \ddot{r}$. Since the field is central, $r$ and $\ddot{r}$ are colinear. Thus $\dot{M} = 0$.

---

We can use polar coordinates to express angular momentum. Some care is required to differentiate constants and vectors. Parametrize with $r$ and $\varphi$. Let $\mathbf{e}_r$ be the unit radius vector and $\mathbf{e}_\varphi$ be the unit angle vector. Then we have the radius vector $\mathbf{r} = r\mathbf{e_r}$. Differentiate to get

$$\dot{\mathbf{r}} = \dot{r}\mathbf{e_r} + r\dot{\mathbf{e}}_\mathbf{r} = \dot{r}\mathbf{e_r} + r\dot{\varphi}\mathbf{e}_\varphi$$

Thus the angular momentum is

$$\mathbf{M} = \mathbf{r} \times \dot{\mathbf{r}} = \mathbf{r} \times \dot{r}\mathbf{e_r} + \mathbf{r} \times r\dot{\varphi}\mathbf{e}_\varphi$$
$$\mathbf{M} = \mathbf{r} \times r\dot{\varphi}\mathbf{e}_\varphi = r^2\dot{\varphi}(\mathbf{e_r} \times \mathbf{e}_\varphi)$$
$$|\mathbf{M}| = r^2\dot{\varphi}$$

This is a familiar result from first-year physics: $L = I\omega$, etc.

## 2.5 Motion in a Central Field

Conservation of angular momentum allows us to reduce motion in a central field to a problem with 1 degree of freedom. Thus, the motion in a central field can be completely determined.

Consider the motion of a point mass in a central field on the plane:

$$\ddot{r} = -\frac{\partial U}{\partial r} \ , \ \ U = U(r)$$

**Theorem:** For the motion of a point mass in a central field, the equation of motion is the same as the 1-dimensional problem with potential energy

$$V(r) = U(r) + \frac{M^2}{2r^2}$$

**Proof:** Using $\dot{\mathbf{r}} = \dot{r}\mathbf{e_r} + r\dot{\varphi}\mathbf{e}_\varphi$ with $\dot{\mathbf{e}_r} = \dot{\varphi}\mathbf{e}_\varphi$ and $\dot{\mathbf{e}_\varphi} = -\dot{\varphi}\mathbf{e_r}$, we have

$$\ddot{\mathbf{r}} = (\ddot{r} - r\dot{\varphi}^2)\mathbf{e_r} + (2\dot{r}\dot{\varphi} + r\ddot{\varphi})\mathbf{e}_\varphi$$

Since the field is central, we know that

$$\frac{\partial U}{\partial \mathbf{r}} = \frac{\partial U}{\partial r}\mathbf{e_r}$$
$$\ddot{r} - r\dot{\varphi}^2 = -\frac{\partial U}{\partial r} \ , \ \ 2\dot{r}\dot{\varphi} + r\ddot{\varphi} = 0$$

From conservation of angular momentum, we can say $\dot{\varphi} = M/r^2$. Therefore,

$$\ddot{r} = -\frac{\partial U}{\partial r} + r\frac{M^2}{r^4}$$
$$\ddot{r} = -\frac{\partial V}{\partial r} \ , \ \ V = U + \frac{M^2}{2r^2}$$

---

The total energy is given by $E = \dot{r}^2/2 + V(r)$. This is conserved, thus $\dot{r} = dr/dt = \sqrt{2(E - V(r))}$. We know that $\dot{\varphi} = d\varphi/dt = M/r^2$. Substituting $dt$, we get

$$\frac{d\varphi}{dr} = \frac{M}{r^2\sqrt{2(E - V(r))}}$$

This is the equation of the orbit in polar coordinates.

---

As an example, we'll try to solve Kepler's problem for celestial motion. Consider the central field with potential $U = -k/r$ (it turns out that this and $U = ar^2$ are the only cases for which all bounded orbits are closed). Anyways, then $V(r) = -k/r + M^2/(2r^2)$. The general formula for $\varphi$ above gives

$$\begin{aligned}\varphi &= \int \frac{M}{r^2\sqrt{2(E - V(r))}}\, dr \\ &= \arccos\left(\frac{M/r - k/M}{\sqrt{2E + k^2/M^2}}\right)\end{aligned}$$

Let $p = M^2/k$ and $e = \sqrt{1 + 2EM^2/k^2}$. Then we get

$$\varphi = \frac{\arccos(p/r - 1)}{e}$$
$$r = \frac{p}{1 + e\cos\varphi}$$

This is the focal point of a conic section, specifically an ellipse for $e < 1$. Thus the motion of planets describe ellipses, with the sun at one focus.

## 2.6 Motion in Three-Space

Here we want to define angular momentum relative to an axis. In an axially symmetric field, angular momentum is still conserved. First, consider motion in a conservative field

$$\ddot{\mathbf{r}} = -\frac{\partial U}{\partial \mathbf{r}}\ , \quad U = U(\mathbf{r})\ , \quad \mathbf{r} \in E^3$$

The law of conservation of energy holds: $dE/dt = 0$, where $E = \frac{1}{2}\dot{\mathbf{r}}^2 + U(\mathbf{r})$.

---

Recall that every central field is conservative, and the angular momentum doesn't change: for $M = \mathbf{r} \times \dot{\mathbf{r}}$, we have $d\mathbf{M}/dt = 0$. For motion in a central field, every orbit is planar. To see this, note that

$$\mathbf{M} \cdot \mathbf{r} = (\mathbf{r} \times \dot{\mathbf{r}}) \cdot \mathbf{r} = 0$$

Thus all orbits lie in the plane perpendicular to $\mathbf{M}$.

We say a vector field in $E^3$ is **axially symmetric** if it's invariant w.r.t the group of spatial rotations that fix every point of some axis. The moment $M_z$ is the projection of the moment of the vector $\mathbf{F}$ applied at $\mathbf{r}$ onto the $z$ axis (or any axis of symmetry).

$$M_z = \mathbf{e_z} \cdot (\mathbf{r} \times \mathbf{F})$$

**Theorem:** For motion in a conservative field with axial symmetry around the $z$ axis, the moment of velocity relative to the $z$ axis is conserved.

**Proof:** Since $\ddot{\mathbf{r}} = \mathbf{F}$, both $\mathbf{r}$ and $\ddot{\mathbf{r}}$ must lie in a plane passing through the $z$ axis. Thus their cross product is perpendicular to $\mathbf{e_z}$, and

$$\dot{M}_z = \mathbf{e_z} \cdot (\dot{\mathbf{r}} \times \dot{\mathbf{r}}) + \mathbf{e_z} \cdot (\mathbf{r} \times \ddot{\mathbf{r}}) = 0$$

## 2.7 Motion of a System of $n$ points

First, write Newton's equation for the force acting on each point (mass $m_i$ and radius vector $\mathbf{r}_i \in E^3$).

$$m_i \ddot{\mathbf{r}}_i = \mathbf{F}_i$$

For some systems, the force acting on two points are equal in magnitude and opposite in direction. These are called **forces of interaction** (e.g. universal gravitation). If all forces acting on a point in

the system are forces of interaction, then the system is **closed**. The force acting on the $i$-th point of a close system is

$$\mathbf{F}_i = \sum_{j=1,\ j\neq i}^{n} \mathbf{F}_{ij}$$

Here, $\mathbf{F}_{ij}$ is the force with which the $j$-th point acts on the $i$-th.

If the system is not closed, the force acting on the $i$-th point can be represented with the **external force $\mathbf{F}'_i$**:

$$\mathbf{F}_i = \sum \mathbf{F}_{ij} + \mathbf{F}'_i$$

---

### 2.7.1 Conservation of Momentum

The momentum of a system is the vector

$$\mathbf{P} = \sum_{i=1}^{n} m_i \dot{\mathbf{r}}_i$$

**Theorem:** The rate of change of a system's momentum is equal to the sum of all external forces acting on points of the system.

**Proof:** Note that

$$\frac{d\mathbf{P}}{dt} = \sum_{i=1}^{n} m_i \ddot{\mathbf{r}}_i = \sum_{i=1}^{n} \mathbf{F}_i = \sum_{i,j} \mathbf{F}_{ij} + \sum_i \mathbf{F}'_i$$

Further, $\sum_{i,j} \mathbf{F}_{ij} = 0$ since for forces interaction, $F_{ij} = -F_{ji}$. Thus we find that the change in momentum is equal to the sum of external forces.

$$\frac{d\mathbf{P}}{dt} = \sum_i \mathbf{F}'_i$$

This also implies that the **momentum of a closed system is conserved**. To simplify calculations, we can treat the total momentum of the system as the momentum of a particle lying at the center of mass $\mathbf{r} = \frac{\sum m_i \mathbf{r}_i}{\sum m_i}$ with mass $\sum m_i$.

### 2.7.2 Conservation of Angular Momentum

The angular momentum of a system (relative to 0) is defined as

$$\mathbf{M} = \sum_{i=1}^{n} \mathbf{r}_i \times m_i \dot{\mathbf{r}}_i$$

**Theorem:** The rate of change of a system's angular momentum is equal to the sum of the moments of external forces acting on the system's points.

**Proof:** Find the derivative as

$$\frac{d\mathbf{M}}{dt} = \sum_{i=1}^{n} \dot{\mathbf{r}}_i \times m_i \dot{\mathbf{r}}_i + \sum_{i=1}^{n} \mathbf{r}_i \times m_i \ddot{\mathbf{r}}_i$$
$$\frac{d\mathbf{M}}{dt} = \sum_{i=1}^{n} \left[ \mathbf{r}_i \times \left( \sum_{i \neq j} \mathbf{F}_{ij} + \mathbf{F}'_i \right) \right]$$

Since $\mathbf{F}_{ij} = -\mathbf{F}_{ji}$, we have that $(\mathbf{r}_i \times \mathbf{F}_{ij}) + (\mathbf{r}_j \times \mathbf{F}_{ji}) = (\mathbf{r}_i - \mathbf{r}_j) \times \mathbf{F}_{ij} = 0$. So the $\mathbf{F}_{ij}$ sum vanishes and we're left with

$$\frac{d\mathbf{M}}{dt} = \sum_{i=1}^{n} \mathbf{r}_i \times \mathbf{F}'_i$$

Thus, **angular momentum of a closed system is conserved**.

### 2.7.3 Conservation of Energy

The kinetic energy of a system of mass points is defined as

$$T = \sum_{i=1}^{n} \frac{1}{2} m_i \dot{\mathbf{r}}_i^2$$

**Theorem:** The increase in a system's kinetic energy is equal to the sum of the work of all forces acting on the system's points.

**Proof:** First, find $dT/dt$ as

$$\frac{dT}{dt} = \sum_{i=1}^{n} m_i (\dot{\mathbf{r}}_i \cdot \ddot{\mathbf{r}}_i) = \sum_{i=1}^{n} \dot{\mathbf{r}}_i \cdot m_i \ddot{\mathbf{r}}_i = \sum_{i=1}^{n} \dot{\mathbf{r}}_i \cdot \mathbf{F}_i$$

Then we can find the change in kinetic energy as

$$T(t) - T(t_0) = \int_{t_0}^{t} \frac{dT}{dt}\, dt = \sum_{i=1}^{n} \int_{t_0}^{t} \dot{\mathbf{r}}_i \cdot \mathbf{F}_i \, dt$$
$$T(t) - T(t_0) = \int_{r(t_0)}^{r(t)} \mathbf{F} \cdot d\mathbf{r}$$

It can be seen that the increase in kinetic energy is equal to the work of $\mathbf{F}$ along the path $\mathbf{r}(t)$.

---

Now consider potential energy. From previous definitions, a system is **conservative** if the forces only depend on the location of a point in the system ($\mathbf{F} = \mathbf{F}(r)$) and the work of $\mathbf{F}$ along any path depends only on the endpoints of the path. A system is conservative if and only if there exists a potential energy $U(\mathbf{r})$ such that

$$\mathbf{F} = -\frac{\partial U}{\partial \mathbf{r}}$$

Consider the forces acting on points in a system:

$$\mathbf{F}_i = \sum_{i \neq j} \mathbf{F}_{ij} + \mathbf{F}'_i$$

**Theorem:** If the forces of interaction only depend on distance, such that $f_{ij} = f_{ij}(|\mathbf{r}_i - \mathbf{r}_j|)$ for $\mathbf{F}_{ij} = -\mathbf{F}_{ji} = f_{ij}\mathbf{e}_{ij}$, then the forces are conservative.

**Proof:** Now, the potential energy of interaction is

$$U_{ij}(\mathbf{r}) = \int_{r_0}^{r} f_{ij}(\rho)\, d\rho$$

The potential energy of the interaction of all the points is

$$U(\mathbf{r}) = \sum_{i>j} U_{ij}(|\mathbf{r}_i - \mathbf{r}_j|)$$

If the external forces are also conservative, then $\mathbf{F}'_i = -\partial U'_i / \partial \mathbf{r}_i$. The system here is conservative, and the total potential energy is $U(\mathbf{r}) = \sum_{i>j} U_{ij} + \sum_i U'_i$. Furthermore, note that the kinetic energy is the same at two different times if the potential energy is conservative:

$$T(t_1) - T(t_0) = \int_{\mathbf{r}(t_0)}^{\mathbf{r}(t_1)} \mathbf{F} \cdot d\mathbf{r} = U(\mathbf{r}(t_0)) - U(\mathbf{r}(t_1))$$

Thus, for a system with a conservative potential energy, the total mechanical energy

$$E = T + U = \sum_i \frac{1}{2}\dot{\mathbf{r}}_i^2 + \sum_{i>j} U_{ij} + \sum_i U'_i$$

is conserved.

## Part II

# Lagrangian Mechanics

Lagrangian mechanics uses a manifold ("configuration space") and a function on its tangent bundle ("Lagrangian function") to define its system. A conservation law is defined by every 1-parameter group of diffeomorphisms of the configuration space which fixes the Lagrangian function.

The Newtonian potential system is a special case of a Lagrangian system: the configuration space is Euclidean, and the Lagrangian function is $L = T - V$.

# 3 Variational Principles (p. 55 – 74)

## 3.1 Calculus of Variations

### 3.1.1 Functionals

Consider functions whose domains are in an infinite-dimensional space: the space of curves. Such functions are called **functionals**. The calculus of variations examines the extremals of functionals.

In general, a functional is **any mapping from the space of curves to** $\mathbb{R}$. For example, the length of a curve in the Euclidean plane is a functional:

$$\gamma = \{(t, x) \mid x(t) = x_0, t_0 \leq t \leq t_1\}$$
$$\Phi(\gamma) = \int_{t_0}^{t_1} \sqrt{1 + \dot{x}^2}\, dt$$

Now we consider an "approximation" $\gamma' = \{(t, x) \mid x = x(t) + h(t)\}$. Call this $\gamma' = \gamma + h$. Also consider the resulting increment in the functional: $\Phi(\gamma + h) - \Phi(\gamma)$.




Variation of a curve (Arnold 56)

A functional $\Phi$ is called **differentiable** if $\Phi(\gamma + h) - \Phi(\gamma) = F + R$, where $F$ depends linearly on $h$ and $R(h, \gamma) = O(h^2)$. We call $F(h)$ the **differential**.

By "depending linearly on $h$," we mean: $F(h_1 + h_2) = F(h_1) + F(h_2)$ and $F(ch) = cF(h)$ for fixed $\gamma$.

If $\Phi$ is differentiable, its differential is uniquely defined. The differential $F(h)$ of a functional $\Phi$ can also be called its **variation**, and $h$ is a **variation of the curve**.

---

**Theorem:** The functional $\Phi(\gamma) = \int_{t_0}^{t_1} L(x, \dot{x}, t)\, dt$ is differentiable, and its differential is given by

$$F(h) = \int_{t_0}^{t_1} \left[\frac{\partial L}{\partial x} - \frac{d}{dt}\frac{\partial L}{\partial \dot{x}}\right] h\, dt + \left(\frac{\partial L}{\partial \dot{x}} h\right)\Bigg|_{t_0}^{t_1}$$

**Proof:** Find the difference in the functional as

$$\begin{aligned}\Phi(\gamma+h)-\Phi(\gamma) &= \int_{t_0}^{t_1}\Big[L(x+h,\dot{x}+\dot{h},t)-L(x,\dot{x},t)\Big]\ dt \\ &= \int_{t_0}^{t_1}\left[\frac{\partial L}{\partial x}h+\frac{\partial L}{\partial \dot{x}}\dot{h}\right]dt+O(h^2)\end{aligned}$$

The right hand side can be represented as $F(h)+R$, where $R=O(h^2)$ and $F(h)$ is the integral. Using integration by parts, we can also find

$$\int_{t_0}^{t_1}\frac{\partial L}{\partial \dot{x}}\dot{h}\ dt = -\int_{t_0}^{t_1} h\frac{d}{dt}\left(\frac{\partial L}{\partial \dot{x}}\right)dt+\left(h\frac{\partial L}{\partial \dot{x}}\right)\Bigg|_{t_0}^{t_1}$$

$$F(h)=\int_{t_0}^{t_1}\left(\frac{\partial L}{\partial x}h+\frac{\partial L}{\partial \dot{x}}\dot{h}\right)dt=\int_{t_0}^{t_1}\left[\frac{\partial L}{\partial x}-\frac{d}{dt}\frac{\partial L}{\partial \dot{x}}\right]h\ dt+\left(\frac{\partial L}{\partial \dot{x}}h\right)\Bigg|_{t_0}^{t_1}$$

### 3.1.2 Euler-Lagrange Equations

An **extremal** of a differentiable functional $\Phi(\gamma)$ is a curve $\gamma$ such that $F(h)=0$ for all $h$. It's kind of like $x$ being a stationary point of a function $f$ if $df/dx=0$. But here, we're finding the "stationary point" across *functionals*, not points.

**Theorem:** The curve $\gamma : x=x(t)$ is an extremal of the functional $\Phi(\gamma)=\int_{t_0}^{t_1}L(x,\dot{x},t)\ dt$ on the space of curves passing through $x(t_0)=x_0$ and $x(t_1)=x_1$ if and only if

$$\frac{d}{dt}\left(\frac{\partial L}{\partial \dot{x}}\right)-\frac{\partial L}{\partial x}=0 \quad \text{along the curve } x(t)$$

**Proof:** First, we prove the "if" direction. Assume that $\gamma$ is an extremal. Recall from the previous theorem that

$$F(h)=\int_{t_0}^{t_1}\left[\frac{\partial L}{\partial x}-\frac{d}{dt}\frac{\partial L}{\partial \dot{x}}\right]h\ dt+\left(\frac{\partial L}{\partial \dot{x}}h\right)\Bigg|_{t_0}^{t_1}$$

Since we're finding the extremal of the functional with set endpoints $t_0$ and $t_1$, the variation $h$ must be 0 at those points: $h(t_0)=h(t_1)$. Otherwise we're not considering the same functional. Thus the second term vanishes, and $F(h)=0$ for an extremal, so

$$\int_{t_0}^{t_1} f(t)h(t)\ dt=0\ ,\quad f(t)=\frac{d}{dt}\left(\frac{\partial L}{\partial \dot{x}}\right)-\frac{\partial L}{\partial x}$$

This must hold for all $h$, thus $f(t)=0$.

Proving the converse is easy: if $f(t)=0$, then obviously $F(h)=0$.

---

The equation

$$\frac{d}{dt}\left(\frac{\partial L}{\partial \dot{x}}\right)-\frac{\partial L}{\partial x}=0$$

is called the **Euler-Lagrange equation** for the functional $\Phi=\int_{t_0}^{t_1}L(x,\dot{x},t)\ dt$. The Euler-Lagrange equation must be satisfied along the curve $\gamma$ for $\gamma$ to be an extremal of $\Phi$.

## 3.2 Lagrange's Equations

Recall Newton's equations of dynamics:

$$m_i \ddot{r}_i = -\frac{\partial U}{\partial r_i}$$

**Theorem (Hamilton's principle of least action):** Motions of the system described above coincide with the extremals of the functional

$$\Phi(\gamma) = \int_{t_0}^{t_1} L \, dt$$

where $L = T - U$ is the difference between kinetic and potential energy.

**Proof:** From $U = U(\mathbf{r})$ and $T = \sum \frac{1}{2} m_i \dot{\mathbf{r}}_i^2$, we have

$$\frac{\partial L}{\partial \dot{\mathbf{r}}_i} = m_i \dot{\mathbf{r}}_i \ , \quad \frac{\partial L}{\partial \mathbf{r}_i} = -\frac{\partial U}{\partial \mathbf{r}_i}$$

We see that the Euler-Lagrange equation holds:

$$\frac{d}{dt}\left(\frac{\partial L}{\partial \dot{x}}\right) - \frac{\partial L}{\partial x} = m_i \ddot{\mathbf{r}}_i + \frac{\partial U}{\partial \mathbf{r}_i} = 0$$

---

Thus a motion is an extremal of the functional $\int L \, dt$. In any system of coordinates, the Euler-Lagrange equation written in that coordinate system is satisfied.

The terminology is as follows.

1. Lagrange function/Lagrangian: $L(\mathbf{q}, \dot{\mathbf{q}}, t) = T - U$
2. Generalized coordinates: $q_i$
3. Generalized momenta: $\partial L / \partial \dot{q}_i = p_i$
4. Generalized forces: $\partial L / \partial q_i = F_i$
5. Action: $\int_{t_0}^{t_1} L(\mathbf{q}, \dot{\mathbf{q}}, t) \, dt$

So the previous theorem is finding the extremal of the action functional $\int L \, dt$. In many cases, the action is not just an extremal, but a **minimum value**. Thus the evolution of the system follows the path that minimizes the action, which is why the theorem is sometimes called "Hamilton's principle of least action."

---

There's a neat connection between conservation laws and the Lagrangian. Call a coordinate $q_i$ **cyclic** if it doesn't enter into the Lagrangian: $\partial L / \partial q_i = 0$. The generalized momentum $p_i$ corresponding to a cyclic coordinate is conserved: $p_i =$ const.

## 3.3 Legendre Transformations

Legendre transformations transforms functions on a vector space to functions on a dual space. In physics, they're used to convert functions of one quantity to functions of its conjugate quantity: E.g. position to momentum, temperature to entropy.

Let $y = f(x)$ be a convex function: $f''(x) > 0$. Draw $f$ in the $xy$-plane. Now consider lines of the form $y = px$. Take the point $x = x(p)$ for which the curve is farthest from the straight line vertically: that is, the choice of $x$ maximizes $px - f(x)$. Now we can find one point of $g$, **the Legendre transformation of** $f$, as $g(p) = px - f(x)$.

The point $x(p)$ is defined by the condition $\partial F/\partial x = 0$ where $F(p, x) = px - f(x)$, i.e. $f'(x) = p$.




Legendre transformation (Arnold 62)

For example, consider $f(x) = x^2$. Then $F(p, x) = px - x^2$, and by finding the stationary point, we have $x(p) = \frac{1}{2}p$. Now we find the Legendre transformation of $f$ as

$$g(p) = px - f(x) = \frac{1}{2}p^2 - x^2 = \frac{1}{4}p^2$$

For a system with many variables, the procedure is the same. Let $f(\mathbf{x})$ be a convex function of $\mathbf{x} = (x_1, \ldots, x_n)$. The Legendre transformation $g(\mathbf{p})$ of $f(\mathbf{x})$ is defined by the $n$ equalities $F(\mathbf{p}, \mathbf{x}) = \max_{\mathbf{x}} F(\mathbf{p}, \mathbf{x})$, over each component $\mathbf{x}$. Here, $F(\mathbf{p}, \mathbf{x}) = \mathbf{p} \cdot \mathbf{x} - f(\mathbf{x})$ and $\partial f/\partial \mathbf{x} = \mathbf{p}$.

The Legendre transformation is involutive: i.e. If the Legendre transformation of $f$ is $g$, then the Legendre transformation of $g$ will be $f$.

Two functions $f$ and $g$ that are Legendre transformations of each other are called **dual in the sense of Young**. Note that in the Legendre transform, $F(x, p) = px - f(x)$ is always less than or equal to $g(p)$. Thus we have Young's inequality:

$$px \leq f(x) + g(p)$$

## 3.4 Hamilton's Equations

A Legendre transformation can be used to turn a Lagrangian system of differential equations into a Hamiltonian system of equations ("canonical equations").

Hamilton's equations are useful because 1) They allow us to describe systems in terms of position and momentum (quantum mechanics, anyone?), and 2) They simplify the $n$ second-order differential equations of Lagrange to $2n$ first-order differential equations.

Consider the system of Lagrange's equations $\dot{\mathbf{p}} = \partial L/\partial \mathbf{q}$, where $\mathbf{p} = \partial L/\partial \dot{\mathbf{q}}$ with a given Lagrangian function $L : \mathbb{R}^n \times \mathbb{R}^n \times \mathbb{R} \to \mathbb{R}$. Assume this is convex w.r.t the second argument $\dot{\mathbf{q}}$.

**Theorem:** The system of Lagrange's equations is equivalent to the system of $2n$ first-order equations (Hamilton's equations)

$$\dot{\mathbf{p}} = -\frac{\partial H}{\partial \mathbf{q}}$$
$$\dot{\mathbf{q}} = \frac{\partial H}{\partial \mathbf{p}}$$

where $H(\mathbf{p}, \mathbf{q}, t) = \mathbf{p}\dot{\mathbf{q}} - L(\mathbf{q}, \dot{\mathbf{q}}, t)$ is the Legendre transform of the Lagrangian w.r.t $\dot{\mathbf{q}}$. The function $H$ is called the **Hamiltonian**. Thus, if $\mathbf{q}(t)$ satisfies Lagrange's equations, then $(\mathbf{p}(t), \mathbf{q}(t))$ satisfies Hamilton's equations.

---

If the equations are mechanical, so that the Lagrangian has the form $L = T - U$, then the Hamiltonian is the total energy: $H = T + U$. The proof of this uses Euler's theorem on homogeneous functions.

Anyway, as an example, consider 1-dimensional motion:

$$\ddot{q} = -\frac{\partial U}{\partial q}$$

Then $T = \frac{1}{2}\dot{q}^2$ and $U = U(q)$, so the Hamiltonian is $H = \frac{1}{2}p^2 + U(q)$. As before, consider the generalized momentum $p = \partial L/\partial q$. Also note that $\ddot{q} = \dot{p}$, so $\dot{q} = p$. Hamilton's equations take the form

$$\dot{p} = -\frac{\partial U}{\partial q}$$
$$\dot{q} = p$$

---

For a system whose Hamiltonian doesn't depend on time ($\partial H/\partial t = 0$), the law of conservation of energy in a Hamiltonian system takes the form

$$\frac{dH}{dt} = 0$$

which makes sense, as $H = T + U = E_{total}$. But to prove this, differentiate:

$$\begin{aligned}
\frac{dH}{dt} &= \frac{\partial H}{\partial \mathbf{p}}\left(\frac{d\mathbf{p}}{dt}\right) + \frac{\partial H}{\partial \mathbf{q}}\left(\frac{d\mathbf{q}}{dt}\right) + \frac{\partial H}{\partial t} \\
&= \frac{\partial H}{\partial \mathbf{p}}\left(-\frac{\partial H}{\partial \mathbf{q}}\right) + \frac{\partial H}{\partial \mathbf{q}}\left(\frac{\partial H}{\partial \mathbf{p}}\right) + \frac{\partial H}{\partial t} \\
&= \frac{\partial H}{\partial t}
\end{aligned}$$

## 3.5 Cyclic Coordinates

We can exploit the symmetry of a given problem to reduce the coordinates the Hamiltonian depends upon. If a coordinate $q_1$ doesn't enter into the Hamiltonian $H(p_1, \ldots, p_n, q_1, \ldots, q_n, t)$, it's a **cyclic coordinate**.

Let $q_1$ be a cyclic coordinate. Then the variation of the remaining coordinates w.r.t time is the same as the Hamiltonian system with $n-1$ independent coordinates:

$$H(p_2, \ldots, p_n, q_2, \ldots, q_n, t)$$

This allows us to simplify mechanical systems a lot.

## 3.6 Liouville's Theorem

Here we show that the phase flow of Hamilton's equations preserves the phase volume.

Consider the $2n$-dimensional space with coordinates $p_1, \ldots, p_n$ and $q_1, \ldots, q_n$. This is called the **phase space**. Hamilton's equations give a vector field $(-\partial H/\partial \mathbf{q}, \partial H/\partial \mathbf{p})$ associated with each point $(\mathbf{p}, \mathbf{q})$ of phase space.

The **phase flow** is the 1-parameter group of phase space transformations:

$$g^t : (\mathbf{p}(0), \mathbf{q}(0)) \mapsto (\mathbf{p}(t), \mathbf{q}(t))$$

**Theorem (Liouville's theorem):** The phase flow preserves volume. For any region $D$, we have

$$\text{volume}(g^t D) = \text{volume}(D)$$

**Theorem (Liouville's theorem, general):** Consider a system of ordinary differential equations $\dot{\mathbf{x}} = \mathbf{f}(\mathbf{x})$, where $\mathbf{x} = (x_1, \ldots, x_n)$. Assume that the solution can be extended to the whole time axis. Let $\{g^t\}$ be the group of transformations

$$g^t(\mathbf{x}) = \mathbf{x} + \mathbf{f}(\mathbf{x}) + O(t^2) \ , \quad t \to 0$$

Let $D(t)$ be a region in $\mathbf{x}$-space. If $\nabla \cdot \mathbf{f} = 0$, then $g^t$ preserves volume:

$$\text{volume}(D(t)) = \text{volume}(D(0)) \ , \quad D(t) = g^t D(0)$$

---

Note that for Hamilton's equations, we have

$$\nabla \cdot \mathbf{f} = \frac{\partial}{\partial \mathbf{p}} \left( -\frac{\partial H}{\partial \mathbf{q}} \right) + \frac{\partial}{\partial \mathbf{q}} \left( \frac{\partial H}{\partial \mathbf{p}} \right) = 0$$

Thus Liouville's theorem (version 1) is proven.

By Liouville's theorem, a Hamiltonian system cannot have an asymptotically stable equilibrium position. That would mean that the divergence of $\mathbf{f} = (\dot{\mathbf{p}}, \dot{\mathbf{q}})$ is nonzero at the equilibrium position.

### 3.7 Poincaré's Recurrence Theorem

**Theorem:** Let $g$ be a volume-preserving continuous one-to-one mapping that maps a bounded region $D \subset E^3$ to itself: $gD = D$. Then in any neighborhood $U$ of any point of $D$, there exists a point $x \in U$ which returns to $U$, i.e. $g^t x \in U$ for some $t > 0$.

**Proof:** Consider images in the neighborhood of $U$: $U$, $gU$, $g^2U$, etc. All of these have the same volume by Liouville's theorem. If they never intersect, $D$ would have infinite volume. Thus, for some $k, l \geq 0$ with $k > l$,

$$g^k U \cap g^l U \neq \emptyset \quad \longrightarrow \quad g^{k-l} U \cap U \neq \emptyset$$

Consider a point $y = g^{k-l}x$ in this intersection, where $x \in U$. Then $g^{k-l}x \in U$, and we've proved Poincaré's theorem.

---

That is, almost every moving point returns repeatedly to the vicinity of its original position. The details of the motion may not be known, but this conclusion can still be drawn.

---




Example: the exact motion of a ball in an asymmetrical cup is unknown. But Poincaré's theorem predicts that it'll return to a neighborhood of the original position (Arnold 71)

---

There seems to be a conflict with the 2nd Law of Thermodynamics: if you open a partition separating two chambers (the left one full of gas, the right one a vacuum), then eventually all the gas will return to the left side? But this isn't a problem since the Poincaré recurrence time is extremely long, maybe longer than the duration of the solar system's existence.

## 4 Lagrangian Mechanics on Manifolds (p. 75 – 97)

Here, the differentiable manifold and its tangent bundle are introduced. We construct Lagrangian functions on the tangent bundle, which defines a Lagrangian "holonomic system" on a manifold.

## 4.1 Holonomic Constraints

Imagine a smooth curve $\gamma$ in a plane. If there's a strong force field in the neighborhood of $\gamma$ directed towards the curve, a moving point will be close to $\gamma$. If the field is infinite, the point will be on $\gamma$. In that case, we say a constraint is put on the system.

Introduce the curvilinear coordinates $q_1$ and $q_2$ in a neighborhood of $\gamma$. $q_1$ is in the direction of $\gamma$ and $q_2$ is the distance from the curve. Consider a system with potential energy $U_N = Nq_2^2 + U_0(q_1, q_2)$.




Constraint as an infinitely strong field (Arnold 76)

**Theorem:** Let $q_1 = \varphi(t, N)$ be the evolution of $q_1$ under the field $U_N$. As $N \to \infty$, the limit

$$\lim_{N\to\infty} q_1 = \lim_{N\to\infty} \varphi(t, N) = \psi(t)$$

exists, and $q_1 = \psi(t)$ satisfies Lagrange's equation

$$\frac{d}{dt}\left(\frac{\partial L_*}{\partial \dot{q}_1}\right) = \frac{\partial L_*}{\partial q_1}$$

where $L_*(q_1, \dot{q}_1) = T|_{q_2=\dot{q}_2=0} - U|_{q_2=0}$, and $T$ is the kinetic energy of the motion along $\gamma$.

This even works in 3 dimensions. If the potential energy has the form

$$U = U_0(\mathbf{q_1}, \mathbf{q_2}) + N\mathbf{q_2}^2$$

then as $N \to \infty$, a motion on $\gamma$ follows Lagrange's equations with the Lagrangian

$$L_* = T|_{\mathbf{q_2}=\dot{\mathbf{q}}_2=0} - U_0|_{\mathbf{q_2}=0}$$

Let $\gamma$ be an $m$-dimensional surface in the $3n$-dimensional configuration space of the points $\mathbf{r}_1, \ldots, \mathbf{r}_n$ with masses $m_1, \ldots, m_n$. Let $\mathbf{q} = (q_1, \ldots, q_m)$ be some coordinates on $\gamma$, such that $\mathbf{r}_i = \mathbf{r}_i(\mathbf{q})$. The system described by the equations

$$\frac{d}{dt}\frac{\partial L}{\partial \dot{\mathbf{q}}} = \frac{\partial L}{\partial \mathbf{q}}\ , \quad L = \frac{1}{2}\sum m_i \dot{\mathbf{r}}_i^2 + U(\mathbf{q})$$

is called a system of $n$ points with $3n - m$ ideal **holonomic constraints**. The surface $\gamma$ is called the **configuration space of the system with constraints**.

## 4.2 Differentiable Manifolds

### 4.2.1 Definitions

The configuration space of a system with constraints is a differentiable manifold. Manifolds are spaces that locally resemble Euclidean space.

A set $M$ is given the structure of a differentiable manifold if it's provided with a countable collection of **charts**, so that every point is represented in at least one chart.

Define a **chart** to be an open set $U$ in the Euclidean coordinate space $\mathbf{q} = (q_1, \ldots, q_n)$, together with the one-to-one mapping $\varphi$ of $U$ onto some subset of $M$. That is, $\varphi : U \to \varphi U \subset M$. A chart acts as a local coordinate system and "map" of a manifold to $\mathbb{R}^n$.

Let $p$ and $p'$ be two points in the charts $U$ and $U'$, respectively. Assume that $p$ and $p'$ have neighborhoods $V \subset U$ and $V' \subset U'$ with the same image in $M$. Then we can get the mapping $\varphi'^{-1}\varphi : V \to V'$. This is a mapping of one Euclidean space onto another. The charts $U$ and $U'$ are **compatible** if the function $\varphi'^{-1}\varphi$ is infinitely differentiable.




Compatible charts (Arnold 78)

An **atlas** is a union of compatible charts. This union of all charts $\{(U_i, \varphi_i)\}$ must cover the entire manifold: $\bigcup U_i = M$. Intuitively, think of covering the surface of earth with a lot of paper sheets ("charts").

Two atlases are **equivalent** if their union is also an atlas. A differentiable manifold is a **class of equivalent atlases**.

---

For example, Euclidean space $\mathbb{R}^n$ is a manifold, and its atlas consists of one chart.

The sphere $S^2 = \{(x, y, z) \mid x^2 + y^2 + z^2 = 1\}$ is a manifold, and its atlas consists of two charts supplied by stereographic projection.

The circle $S^1$ is a manifold, and its atlas can be supplied by two charts in the angular coordinates $\varphi : \mathbb{R}^1 \to S^1$. For example, $U_1 = (-\pi, \pi)$, $U_2 = (0, 2\pi)$. Note that a single chart can't cover the entire circle, because $\varphi$ must be one-to-one. Thus, we need two charts to fully cover the manifold.

The configuration space of a planar double-pendulum is the direct product of two circles. This turns out to be the torus: $T^2 = S^1 \times S^1$.

---

The dimension of the configuration space is called the **number of degrees of freedom**. For example, a system of $k$ rods in the plane has a configuration space of dimension $k$, so $k$ degrees of freedom.

We say that a manifold $M$ is an embedded $k$-dimensional sub-manifold of Euclidean space $\mathbb{R}^n$ if in every neighborhood $U$ of every point $\mathbf{x} \in M$, there are $n-k$ functions $f_i = U - \mathbb{R} \mid i \in [0 \dots n-k]$ such that the intersection of $U$ with $M$ is given by $f_i = 0 \mid i \in [0 \dots n-k]$, and the vectors $\nabla f_i \mid i \in [0 \dots n-k]$ at $\mathbf{x}$ are linearly independent. That is, when $U$ is on the manifold, the $n-k$ "extraneous components" are zero, but the gradient vectors must still form a basis.

Every manifold can be embedded in some Euclidean space.

### 4.2.2 Tangent Space & Tangent Bundle

If $M$ is a $k$-dimensional manifold embedded in $E^n$, then at every point $\mathbf{x}$, there's a $k$-dimensional tangent space $TM_{\mathbf{x}}$. Here, $TM_{\mathbf{x}}$ is the orthogonal complement to $\{\nabla f_i \mid i = 0 \dots n-k\}$. Intuitively, vectors on the tangent space are tangent to the "curve" of the manifold at $\mathbf{x}$. These vectors can also be defined as "velocity vectors":

$$\dot{\mathbf{x}} = \lim_{t \to 0} \frac{\varphi(t) - \varphi(0)}{t} \ , \quad \varphi(0) = \mathbf{x}, \varphi(t) \in M$$

We can also define the tangent vetors without saying anything about embedded manifolds. Let $U$ be a chart of an atlas for a manifold $M$ with coordinates $q_1, \dots, q_n$. The components of the tangent vector to the curve $\mathbf{q} = \varphi(t)$ are the numbers $\xi_1, \dots, \xi_n$, where

$$\xi_i = \left. \frac{d\varphi_i}{dt} \right|_{t=0}$$

---

The union of the tangent spaces to $M$ at the various points $\mathbf{x}$ has a differentiable manifold structure. The dimension is twice that of $M$. We call this the manifold the **tangent bundle** of $M$, denoted

$$TM = \bigcup_{\mathbf{x} \in M} TM_{\mathbf{x}}$$

Let $q_1, \dots, q_n$ be local coordinates on $M$, and $\xi_1, \dots, \xi_n$ be the components of the tangent vector: $\xi_i = dq_i$. The local coordinate system on $TM$ can be defined with the $2n$ components $(q_1, \dots, q_n, \xi_1, \dots, \xi_n)$.

We call the mapping $p : TM \to M$, taking a tangent vector $\xi$ to the point $\mathbf{x} \in M$ where the vector is tangent to $M$, the **natural projection**.

The inverse image of a point $\mathbf{x} \in M$, $p^{-1}(\mathbf{x})$, is the tangent space $TM_{\mathbf{x}}$. This space is called the **fiber of the tangent bundle over the point** $\mathbf{x}$.

### 4.2.3 Riemannian Manifold

If $M$ is a manifold embedded in Euclidean space, the Euclidean metric lets us measure lengths, angles, etc. Here we extend that notion using the tangent space $TM_{\mathbf{x}}$.

A differentiable manifold with a fixed positive-definite quadratic form $\langle \xi, \xi \rangle$ on every tangent space $TM_{\mathbf{x}}$ is called a **Riemannian manifold**. The quadratic form is called the **Riemannian metric**. Let $U$ be a chart of an atlas for $M$ with coordinates $q_1, \ldots, q_n$. Then a Riemannian metric is given by

$$ds^2 = \sum_{i,j=1}^{n} a_{ij}(q) dq_1 dq_j \ , \quad a_{ij} = a_{ji}$$

### 4.2.4 The Derivative Map

Let $f : M \to N$ be a mapping from manifold $M$ to manifold $N$. We say $f$ is differentiable if in local coordinates on $M$ and $N$ it's given by differentiable functions.

The derivative of a differentiable mapping $f : M \to N$ at a point $\mathbf{x} \in M$ is the linear map of the tangent spaces

$$f_{*\mathbf{x}} : TM_{\mathbf{x}} \to TN_{\mathbf{f}(\mathbf{x})}$$

For example, let $\mathbf{v} \in TM_{\mathbf{x}}$, a velocity vector. Consider the curve $\varphi : \mathbb{R} \to M$ with $\varphi(0) = \mathbf{x}$ and $(d\varphi/dt)_{t=0} = \mathbf{v}$. Then $f_{*\mathbf{x}}\mathbf{v}$ is the velocity vector of the curve $f \circ \varphi : \mathbb{R} \to N$.

$$f_{*\mathbf{x}}\mathbf{v} = \left.\frac{d}{dt}\right|_{t=0} f(\varphi(t))$$

---

Let $\mathbf{x} = (x_1, \ldots, x_n)$ be coordinates in a neighborhood of $\mathbf{x} \in M$, and $\mathbf{y} = (y_1, \ldots, y_n)$ be coordinates in a neighborhood of $\mathbf{y} \in N$. Let $\xi$ be the set of components of the vector $\mathbf{v}$, and $\eta$ be the set of components of the vector $\mathbf{f}_{*\mathbf{x}}\mathbf{v}$. Then

$$\eta = \frac{\partial \mathbf{y}}{\partial \mathbf{x}} \xi \ , \quad \eta_i = \sum_i \frac{\partial y_i}{\partial x_i} \xi_i$$

Each component simply transforms according to $\partial y / \partial x$.

## 4.3 Lagrangian Dynamical Systems

Let $M$ be a differentiable manifold, $TM$ its tangent bundle, and $L : TM \to \mathbb{R}$ a differentiable function. The map $\gamma : \mathbb{R} \to M$ is called a motion in the Lagrangian system with configuration manifold $M$ and Lagrangian function $L$ if $\gamma$ is an extremal of the functional

$$\Phi(\gamma) = \int_{t_0}^{t_1} L(\dot{\gamma}) \, dt$$

where $\dot{\gamma} \in TM_{\gamma(t)}$ is the velocity vector in the tangent bundle.

Let $L(\mathbf{q}, \dot{\mathbf{q}})$ be the expression for the function $L : TM \to \mathbb{R}$ in the coordinates $\mathbf{q}, \dot{\mathbf{q}}$ on the tangent bundle. The evolution of local coordinates $\mathbf{q} = (q_1, \ldots, q_n)$ on a manifold (under motion in a Lagrangian system) satisfies

$$\frac{d}{dt} \frac{\partial L}{\partial \dot{\mathbf{q}}} = \frac{\partial L}{\partial \mathbf{q}}$$

### 4.3.1 Natural Systems

A Lagrangian system on a Riemannian manifold is called **natural** if the Lagrangian is equal to the difference in kinetic and potential energies.

$$L = T - U$$
$$T = \frac{1}{2}\langle \mathbf{v}, \mathbf{v} \rangle \ \mid \ \mathbf{v} \in TM_{\mathbf{x}} \ , \ U : M \to \mathbb{R}$$

---

Now consider the case of holonomic constraints (given earlier). Consider the $3n$-dimensional configuration space of $n$ free points. The embedded Riemannian manifold $M$ with potential energy $U$ can be used to write the potential energy of the system as $U_{sys} = U + N\mathbf{q_2}^2$, which grows rapidly outside $M$. So a particle on $M$ would tend to stay on the manifold.

To solve:

1. Determine configuration manifold; introduce coordinates $q_1, \ldots, q_k$ in a neighborhood of each point on the manifold.
2. Find the kinetic energy as a quadratic form of the generalized velocities:

$$T = \frac{1}{2}\sum_{i,j=1}^{n} a_{ij}(\mathbf{q})\dot{q}_i\dot{q}_j$$

3. Construct Lagrangian $L = T - U(\mathbf{q})$ and solve Lagrange's equations.

This can be used to find, for example, geodesics on surfaces of rotation. Assume constant potential energy $U$ on the manifold, and $U_{sys} = U + N\mathbf{q_2}^2$ outside.

### 4.3.2 Non-Autonomous Systems

Until now, we've been looking at autonomous Lagrangian systems. A non-autonomous Lagrangian system depends on time. Both the kinetic and potential energies might also depend on time.

$$L : TM \times \mathbb{R} \to \mathbb{R} \ \Big| \ L = L(\mathbf{q}, \dot{\mathbf{q}}, t)$$
$$T : TM \times \mathbb{R} \to \mathbb{R} \ , \ U : M \times \mathbb{R} \to \mathbb{R} \ \Big| \ T = T(\mathbf{q}, \dot{\mathbf{q}}, t) \ , \ U = U(\mathbf{q}, t)$$

A system of $n$ mass points (constrained by holonomic constraints that depend on $t$) are defined using a time-dependent submanifold of the free system's configuration space. This is given by the mapping

$$i : M \times \mathbb{R} \to E^{3n} \ , \ i(\mathbf{q}, t) = \mathbf{x}$$

For a fixed $t \in \mathbb{R}$, this defines an embedding $M \to E^{3n}$. Then the Lagrangian $L = T - U(\mathbf{q})$ for autonomous systems can be used here.

Essentially, we've shown that the Lagrangian can also be applied to time-dependent systems.

## 4.4 Noether's Theorem

Let $M$ be a smooth manifold and $L : TM \to \mathbb{R}$ be a smooth function on its tangent bundle. Let $h : M \to M$ be a smooth map. We say that a Lagrangian system $(M, L)$ **admits the mapping** $h$ if for any tangent vector $\mathbf{v} \in TM$,

$$L(h_* \mathbf{v}) = L(\mathbf{v})$$

For example, if $M = \{(x_1, x_2)\}$ and $L = \frac{m}{2}(\dot{x}_1^2 + \dot{x}_2^2) - U(x_2)$, the system admits the translation $h : (x_1, x_2) \to (x_1 + s, x_2)$ along the $x_1$-axis, but generally doesn't admit a translation in the $x_2$-axis.

---

**Noether's Theorem:** If the system $(M, L)$ admits the one-parameter group of diffeomorphisms $h^s : M \to M$ with $s \in \mathbb{R}$, then the Lagrangian system of equations corresponding to $L$ has a first integral $I : TM \to \mathbb{R}$. That is, $\frac{dI}{dt} = 0$ along the curve.

In local coordinates $q$ on $M$, the integral is

$$I(\mathbf{q}, \dot{\mathbf{q}}) = \frac{\partial L}{\partial \dot{\mathbf{q}}} \frac{dh^s(\mathbf{q})}{ds}\bigg|_{s=0}$$

**Proof:** Let $M = \mathbb{R}^n$ be the coordinate space and $\varphi : \mathbb{R} \to M$, $\mathbf{q} = \varphi(t)$ be a solution to Lagrange's equations. Since $h^s$ preserves $L$ (given), $h^s \circ \varphi : \mathbb{R} \to M$ also satisfies Lagrange's equations for any $s$.

Consider the mapping $\Phi : \mathbb{R} \times \mathbb{R} \to \mathbb{R}^n$, given by $\mathbf{q} = \Phi(s, t) = h^s(\varphi(t))$. Denote $t$-derivatives with a dot and $s$-derivatives with a primed mark. Note that since $h^s$ preserves the Lagrangian,

$$0 = \frac{\partial L(\Phi, \dot{\Phi})}{\partial s} = \frac{\partial L}{\partial \mathbf{q}} \Phi' + \frac{\partial L}{\partial \dot{\mathbf{q}}} \dot{\Phi}'$$

---




Noether's theorem (Arnold 89)

Since $\Phi|_{s \text{ const}}$ preserves the Lagrangian for any fixed $s$, it must satisfy Lagrange's equation

$$\frac{d}{dt}\left[\frac{\partial L\left(\Phi(s,t), \dot{\Phi}(s,t)\right)}{\partial \dot{\mathbf{q}}}\right] = \frac{\partial L\left(\Phi(s,t), \dot{\Phi}(s,t)\right)}{\partial \mathbf{q}}$$

So we can let $\frac{d}{dt}\frac{\partial L}{\partial \dot{\mathbf{q}}} = \frac{\partial L}{\partial \mathbf{q}}$. Return to the Lagrangian a few steps back and substitute. Note that $s$ is held constant, so $\mathbf{q} = \Phi(s,t)$ and $\dot{\mathbf{q}} = \dot{\Phi}(s,t)$. The combination is $\dot{\mathbf{q}}' = d\mathbf{q}'/dt$.

$$0 = \left(\frac{d}{dt}\frac{\partial L}{\partial \dot{\mathbf{q}}}\right) + \frac{\partial L}{\partial \dot{\mathbf{q}}}\left(\frac{d}{dt}\mathbf{q}'\right) = \frac{d}{dt}\left(\frac{\partial L}{\partial \dot{\mathbf{q}}}\mathbf{q}'\right) = \frac{dI}{dt}$$

Note: the first integral $I = (\partial L/\partial \dot{\mathbf{q}})\mathbf{q}'$ is defined with local coordinates $\mathbf{q}$. $I$ is the rate of change of $L(\mathbf{v})$ when the vector $\mathbf{v} \in TM_{\mathbf{x}}$ varies with velocity $(d/ds)|_{s=0}\, h^s\mathbf{x}$.

---

In plain English, Noether's theorem is: for every continuous symmetry in a physical system, there's an associated conserved quantity.

Noether's theorem is the general theorem from which the laws of conservation (momentum, angular momentum, etc.) can be derived. For example, to derive the conservation of momentum, consider the system of point masses:

$$L = \sum \frac{1}{2} m_i \dot{\mathbf{x}}_i^2 - U(\mathbf{x}) \ , \ \ \mathbf{x}_i = x_{i1}\mathbf{e_1} + x_{i2}\mathbf{e_2} + x_{i3}\mathbf{e_3}$$

Assume that the system admits translations along the $\mathbf{e_1}$ axis, $h^s : \mathbf{x}_i \to \mathbf{x}_i + s\mathbf{e_1}$. Since $(d/ds)|_{s=0}\, h^s\mathbf{x}_i = \mathbf{e_1}$, the first integral is

$$I = \sum \frac{\partial L}{\partial \dot{\mathbf{x}}}\frac{dh^s\mathbf{x}_i}{ds} = \sum \frac{\partial L}{\partial \dot{\mathbf{x}}}\mathbf{e_1} = \sum m_i \dot{x}_{i1}$$

This is conserved since $dI/dt = 0$ by Noether's theorem. Above is the first component of the momentum vector. So there's the law of conservation of momentum.

---

What about angular momentum? Let $h^s$ be a rotation around the $\mathbf{e_1}$ axis by an angle $s$. Then $(d/ds)|_{s=0}\, h^s\mathbf{x}_i = \mathbf{e_1} \times \mathbf{x}_i$, thus the first integral is

$$I = \sum_i \frac{\partial L}{\partial \dot{\mathbf{x}}_i}(\mathbf{e_1} \times \mathbf{x}_i) = \sum_i (m_i\dot{\mathbf{x}}_i) \cdot (\mathbf{e_1} \times \mathbf{x}_i) = \sum_i (\mathbf{x}_i \times m_i\dot{\mathbf{x}}_i) \cdot \mathbf{e_1}$$

Since $dI/dt = 0$ by Noether's theorem, the quantity $(\mathbf{x}_i \times m_i\dot{\mathbf{x}}_i)$ is conserved. That's the law of conservation of angular momentum.

---

The law of conservation of energy is related to a time symmetry: If $L$ doesn't depend on time, then $E$ is conserved.

## 4.5 D'Alembert's Principle

This is a new definition of a system of point masses with holonomic constraints. But it's equivalent to the definition given previously.

Consider the holonomic system $(M, L)$, where $M$ is a surface in 3-dimensional space $\{\mathbf{x}\}$ and

$$L = \frac{1}{2}m\dot{\mathbf{x}}^2 - U(\mathbf{x})$$

The mass point $\mathbf{x}$ of the mass must remain on $M$. But consider a motion $\mathbf{x}(t)$ of the point and Newton's equation $m\ddot{\mathbf{x}} + (\partial U/\partial \mathbf{x}) = 0$. If there are no external forces, $U = 0$ and the motion is a straight line, thus it can't always lie on $M$.

So we introduce a new force that "forces" the point to stay on $M$. This is called the **constraint force** and is given by

$$\mathbf{R} = m\ddot{\mathbf{x}} + \frac{\partial U}{\partial \mathbf{x}}$$

Then Newton's equations are satisfied again:

$$m\ddot{\mathbf{x}} = -\frac{\partial U}{\partial \mathbf{x}} + \mathbf{R}$$

---

Tangent vectors to the configuration manifold are called **virtual variations**. The D'Alembert-Lagrange principle states that for any virtual variation $\xi$, the work of the constraint force on $\xi$ is zero.

$$\mathbf{R} \cdot \xi = \left( m\ddot{\mathbf{x}} + \frac{\partial U}{\partial \mathbf{x}} \right) \cdot \xi = 0$$

For a system of points $\mathbf{x}_i$ with masses $m_i$, we have $\mathbf{R}_i = m_i\ddot{\mathbf{x}}_i + (\partial U/\partial \mathbf{x}_i)$. According to D'Alembert's principle, $\sum(\mathbf{R}_i \cdot \xi_i) = 0$. The sum of the works of the constraint forces on **any virtual variation** $\{\xi_i\} \in TM_{\mathbf{x}}$ is zero.

Constraints with the property above (like $\mathbf{R}$) are called **ideal**.

---

We can also derive conservation laws from D'Alembert's principle. For example, assume translation along the $\mathbf{e_1}$-axis is among the virtual variations. The sum of the work of the constraint forces on this variation is zero:

$$\sum (\mathbf{R}_i \cdot \mathbf{e_1}) = \left( \sum \mathbf{R}_i \right) \cdot \mathbf{e_1} = 0$$

This implies that the sum of the 1st component of the constraint forces are zero: $\sum \mathbf{R}_{i1} = 0$. Considering the constraint forces as external forces, this must mean that the first component of momentum, $\mathbf{P}_1 = \sum d\mathbf{R}_{i1}/dt$, is conserved.

### 4.5.1 Equivalence with the Variational Principle

D'Alembert's principle is equivalent with the variational principle introduced earlier. Let $M \in \mathbb{R}^N$ be a submanifold of Euclidean space. Let $\mathbf{x} : \mathbb{R} \to M$ be a curve with $\mathbf{x}(t_0) = \mathbf{x}_0$ and $\mathbf{x}(t_1) = \mathbf{x}_1$. The curve $\mathbf{x}$ is called a conditional extremal of the action functional

$$\Phi = \int_{t_0}^{t_1} \left( \frac{\dot{\mathbf{x}}^2}{2} - U(\mathbf{x}) \right) dt$$

if the differential $\delta\Phi = 0$ for **variations consisting of nearby curves** joining $\mathbf{x}_0$ to $\mathbf{x}_1$ in $M$.

**Theorem:** A curve $\mathbf{x} : \mathbb{R} \to M \subset \mathbb{R}^N$ is a conditional extremal of the action iff. it satisfies D'Alembert's equation

$$\left( \ddot{\mathbf{x}} + \frac{\partial U}{\partial \mathbf{x}} \right) \cdot \xi = 0 \ , \quad \forall \xi \in TM_{\mathbf{x}}$$

So the variational principle (principle of least action) is equivalent to D'Alembert's principle. The principle of least action is the "integral form," while D'Alembert's principle only considers constraints at a point.

### 4.5.2 Equilibrium Positions

An alternative account of D'Alembert's principle can be stated in terms of equilibrium positions.

Suppose that a point mass moves along a smooth surface $M$ under the force $\mathbf{f} = -\partial U/\partial \mathbf{x}$. We call a point $\mathbf{x}_0 \in M$ an **equilibrium position** iff. the force is orthogonal to the surface at $\mathbf{x}_0$. That is, $\mathbf{f}(\mathbf{x}_0) \cdot \xi = 0$ for all $\xi \in TM_{\mathbf{x}_0}$. This is the case in D'Alembert's equation where $\ddot{\mathbf{x}} = 0$.

Denote $-m\ddot{\mathbf{x}}$ as the **force of inertia**.

**Theorem (alternative account of D'Alembert's principle):** If the forces of inertia $-m\ddot{\mathbf{x}}$ are added to the acting forces, $\mathbf{x}$ becomes an equilibrium position.

This can be seen from D'Alembert's equation below, since

$$\left(\ddot{\mathbf{x}} + \frac{\partial U}{\partial \mathbf{x}}\right) \cdot \xi = 0 \ , \quad \forall \xi \in TM_{\mathbf{x}}$$
$$(-m\ddot{\mathbf{x}} + \mathbf{f}) \cdot \xi = 0$$

So we can reduce a problem about motion into a problem about equilibrium.

# 5 Oscillations (p. 98 – 122)

## 5.1 Linearization

Linearization is used to model small oscillations. These models are usually good enough. First, define $\mathbf{x}_0$ to be an **equilibrium position** of the system

$$\frac{d\mathbf{x}}{dt} = \mathbf{f}(\mathbf{x}) \ , \quad \mathbf{x} \in \mathbb{R}^n$$

if $\mathbf{x}(t) \equiv \mathbf{x}_0$ is a solution of the system. Intuitively, the vector field $\mathbf{f}$ is zero at the equilibrium position.

---

**Theorem:** Consider the system with the Lagrangian $L(\mathbf{q}, \dot{\mathbf{q}}) = T - U$, where $T = \frac{1}{2}\sum a_{ij}(\mathbf{q})\dot{q}_i\dot{q}_j$ and $U = U(\mathbf{q})$. The point $(\mathbf{q}_0, \dot{\mathbf{q}}_0)$ is an equilibrium position if and only if

$$\dot{\mathbf{q}}_0 = 0 \ , \quad \left.\frac{\partial U}{\partial \mathbf{q}}\right|_{\mathbf{q}_0} = 0$$

I.e. when the velocity is zero and $\mathbf{q}_0$ is a critical point of the potential energy.

**Theorem:** If the point $\mathbf{q}_0$ is a local minimum of the potential energy $U$, then $\mathbf{q} = \mathbf{q}_0$ is stable. That is, for initial conditions $\mathbf{p}(0)$,$\mathbf{q}(\mathbf{0})$ close enough to $(0, \mathbf{q}_0)$, every phase trajectory $(\mathbf{p}(t), \mathbf{q}(t))$ is close to $(0, \mathbf{q}_0)$.

Here $\mathbf{p}$ is the momentum and $\mathbf{q}$ is the position. It also helps to think graphically: the point mass will "drop down" to a local minimum and tend to stay there unless we disturb the system.

---

To actually solve the general system (or at least, approximate), we linearize the equation. Start from the general equation

$$\frac{d\mathbf{x}}{dt} = \mathbf{f}(\mathbf{x}) \quad , \quad \mathbf{x} \in \mathbb{R}^n \tag{1}$$

Assume $\mathbf{x}_0 = 0$. Taylor expanding $\mathbf{f}$, we get

$$\mathbf{f}(x) \approx A\mathbf{x} + O(\mathbf{x}^2) \quad , \quad A = \left.\frac{\partial \mathbf{f}}{\partial \mathbf{x}}\right|_0$$

We can **linearize** the system in (1) with this approximation, so that

$$\frac{d\mathbf{y}}{dt} = A\mathbf{y}$$

---

The linearized system is easily solvable with $\mathbf{y}(t) = e^{At}\mathbf{y}(0)$. Here, $e^{At} = E + At + \frac{A^2t^2}{2!} + \cdots$. But can we use this? Well, as long as the original system stays close to the initial conditions $\mathbf{y}(0) = \mathbf{x}(0) = \mathbf{x}_0$. Specifically,

| |
|---|
| For any $T > 0$ and $\epsilon > 0$, there exists a $\delta > 0$ such that if $\lvert\mathbf{x}(0)\rvert < \delta$, then $\lvert\mathbf{x}(t) - \mathbf{y}(t)\rvert < \epsilon\delta$ for all $0 < t < T$. |

## 5.2 Linearizing a Lagrangian System

To linearize a Lagrangian system $\frac{d}{dt}\frac{\partial L}{\partial \dot{\mathbf{q}}} = \frac{\partial L}{\partial \mathbf{q}}$ in a neighborhood of the equilibrium position $\mathbf{q} = 0$, replace the kinetic and potential energies by

$$T_2 = \frac{1}{2}\sum a_{ij}\dot{q}_i\dot{q}_j \quad , \quad a_{ij} = a_{ij}(0)$$
$$U_2 = \frac{1}{2}\sum b_{ij}q_iq_j \quad , \quad b_{ij} = \left.\frac{\partial^2 U}{\partial q_i \partial q_j}\right|_{q=0}$$

If we solve Lagrange's equation for the linearized system $T_2 = \frac{1}{2}a\dot{q}^2$ and $U_2 = \frac{1}{2}bq^2$, where $b = (\partial^2 U/\partial q^2)|_{q=q_0}$, we get

$$\ddot{q} = -\omega_0^2 q \quad , \quad \omega_0^2 = \frac{b}{a}$$

Smells like springs and pendulums!

---

For example, consider a bead on the wire $y = U(x)$ in a gravitational field. Take $m = 1$ (mass) and $g = 1$ (gravity). The equilibrium position is $x = x_0$. What's the period of small oscillations?




Bead on wire (Arnold 102)

Well, initially, we have

$$U = mgy = U(x)$$
$$T = \frac{1}{2}mv^2 = \frac{1}{2}\left[\left(\frac{dx}{dt}\right)^2 + \left(\frac{dy}{dt}\right)^2\right] = \frac{1}{2}\left[1 + \left(\frac{\partial U}{\partial x}\right)^2\right]\dot{x}^2$$

In the linearized system with $q = x - x_0$, we have

$$T_2 = \frac{1}{2}\dot{q}^2$$
$$U_2 = \frac{1}{2}\left(\left.\frac{\partial^2 U}{\partial x^2}\right|_{x_0}\right)^2 q^2$$

Thus the period of small oscillations and the period is given by

$$\omega^2 = \left.\left(\frac{\partial^2 U}{\partial x^2}\right)\right|_{x_0}, \quad \tau = \frac{2\pi}{\omega}$$

## 5.3 Small Oscillations

Consider a system whose kinetic and potential energies have the form

$$T = \frac{1}{2}(A\dot{\mathbf{q}}, \dot{\mathbf{q}}) = \frac{1}{2}A\dot{\mathbf{q}} \cdot \dot{\mathbf{q}}$$
$$U = \frac{1}{2}(B\mathbf{q}, \mathbf{q}) = \frac{1}{2}B\mathbf{q} \cdot \mathbf{q}$$

where $\mathbf{q} \in \mathbb{R}^n$. Using linear algebra (Gram-Schmidt, anyone?) we can find $\mathbf{Q} = C\mathbf{q}$ such that $(A\mathbf{q}, \mathbf{q}) = (\mathbf{Q}, \mathbf{Q})$. This is helpful because it removes the "mixing" of $\mathbf{q}$'s components through non-diagonal entries in $A$. Then our energies simply become $n$ ordinary differential equations:

$$T = \frac{1}{2}\sum_{i=1}^{n} \dot{Q}_i^2$$
$$U = \frac{1}{2}\sum_{i=1}^{n} \lambda_i Q_i^2$$

Earlier, applying Lagrange's equation for the linearized system $T_2 = \frac{1}{2}a\dot{q}^2$ and $U_2 = \frac{1}{2}bq^2$ resulted in $\ddot{q} = -\omega^2 q$. Applying this result to the above $n$ equations, we can see that $A$ and $B$ must satisfy

$$\det|B - \lambda A| = 0 \ \ , \ \ \lambda = \omega^2$$

- If $\lambda = \omega^2 > 0$, the solution is $Q = C_1\cos(\omega t) + C_2\sin(\omega t)$. This is an oscillation.
- If $\lambda = 0$, the solution is $Q = C_1 + C_2 t$. This is a neutral equilibrium.
- If $\lambda = -k^2 < 0$, the solution is $Q = C_1\cosh(kt) + C_2\sinh(kt)$. This is unstable.




Diagram for the intuition of "orthogonalizing" $(q_1, q_2)$ to $(Q_1, Q_2)$. From Arnold 104.

After solving the $n$ equations, we have $n$ eigenvalues $\lambda_k = \omega_k^2$ and $n$ eigenvectors $\xi_k$. Each of them satisfies $(B - \lambda_k A)\xi_k = 0$. A general solution for $\lambda \neq 0$ has the form

$$\mathbf{q}(t) = \text{Re}\sum_{k=1}^{n} C_k e^{i\omega_k t}\xi_k$$

### 5.3.1 Example: Connected Pendulums




Connected pendulums (Arnold 106)

Consider pendulums of length $l_1 = l_2 = 1$, attached masses $m_1 = m_2 = 1$, and gravitational field $g = 1$. Let $q_1, q_2$ be the angle between the vertical for each pendulum. After Taylor expanding cosines

and disregarding higher orders, we get

$$T = \frac{1}{2}(\dot{q}_1^2 + \dot{q}_2^2)$$
$$U = \frac{1}{2}(q_1^2 + q_2^2 + \alpha(q_1 - q_2)^2)$$

To get rid of the pesky $(q_1 - q_2)^2$, transform to the axes

$$Q_1 = \frac{q_1 + q_2}{\sqrt{2}} \quad , \quad Q_2 = \frac{q_1 - q_2}{\sqrt{2}}$$
$$T = \frac{1}{2}(\dot{Q}_1^2 + \dot{Q}_2^2) \quad , \quad U = \frac{1}{2}(\omega_1^2 Q_1^2 + \omega_2^2 Q_2^2)$$

Where $\omega_1 = 1$ and $\omega_2 = \sqrt{1 + 2a}$. The two characteristic oscillations are:

1. $Q_2 = 0$: This means $q_1 = q_2$, so the pendulums are in phase, $\omega_1 = 1$. The spring doesn't matter.
2. $Q_1 = 0$: This means $q_1 = -q_2$, so the pendulums move opposite each other. The frequency $\omega_2 = \sqrt{1 + 2\alpha}$ is increased due to the spring.

### 5.3.2 Weak Spring

In between, interesting effects can happen. For example, consider $\alpha \ll 1$ (weak spring). If the initial conditions are $Q_1(0) = Q_2(0) = 0$, from the general solution, we have $Q_1 = c_1 \sin t$ and $Q_2 = c_2 \sin(\omega t)$ with $\omega = \sqrt{1 + 2\alpha} \approx 1 + \alpha$. With initial velocities $\dot{Q}_1(0) = \dot{Q}_2(0) = v/\sqrt{2}$, we have

$$q_1 = \frac{v}{2}\left(\sin t + \frac{1}{\omega}\sin(\omega t)\right) \approx \frac{v}{2}\left(\sin t + \sin(\omega t)\right) = v\cos(\epsilon t)\sin(\omega' t)$$
$$q_2 = \frac{v}{2}\left(\sin t - \frac{1}{\omega}\sin(\omega t)\right) \approx \frac{v}{2}\left(\sin t - \sin(\omega t)\right) = -v\cos(\omega' t)\sin(\epsilon t)$$

Where $\epsilon = (\omega - 1)/2 \approx \alpha/2$ and $\omega' = (\omega + 1)/2 \approx 1$. Therefore, $q_1$ undergoes an oscillation of frequency $\omega'$ while the amplitude changes as $v\cos(\epsilon t)$. After time $t = \pi/(2\epsilon)$, only the second pendulum is oscillating. After $2t$, only the first, and so on. The pendulums appear to "exchange" energy.




"Beats" of $q_1$ and $q_2$ (Arnold 107)

### 5.3.3 General case

Now consider with actual variables: $m_1$ and $m_2$, $l_1$ and $l_2$ , and a spring with energy $\frac{1}{2}\alpha(q_1 - q_2)^2$. We have

$$T = \frac{1}{2}(m_1 l_1 \dot{q}_1^2 + m_2 l_2 \dot{q}_2^2)$$
$$U = \frac{1}{2} m_1 l_1 q_1^2 + \frac{1}{2} m_2 l_2 q_2^2 + \frac{\alpha}{2}(q_1 - q_2)^2$$

The matrices $A$ and $B$ are

$$A = \begin{pmatrix} m_1 l_1^2 & 0 \\ 0 & m_2 l_2^2 \end{pmatrix} \quad , \quad B = \begin{pmatrix} m_1 l_1 + \alpha & -\alpha \\ -\alpha & m_2 l_2 + \alpha \end{pmatrix}$$
$$\det(B - \lambda A) = 0$$

Solving the above gives an expression of the form

$$a\lambda^2 - (b_0 - b_1\alpha)\lambda + (c_0 + c_1\alpha) = 0$$

Which is a hyperbola in the $(\alpha, \lambda)$ plane. Depending on $\alpha$, the strength of the spring, the frequencies approach different values.

## 5.4 Rayleigh-Courant-Fischer Theorem

This theorem can be used to study the behavior of characteristic frequencies under increases in rigidity and imposed constraints.

**Theorem:** Let $E$ be an $n$-dimensional ellipsoid with semi-axes $a_1 \geq a_2 \geq \cdots \geq a_n$. Consider a cross section of $E$ by a subspace $\mathbb{R}^k$. The smallest semi-axis of the cross section is less than or equal to $a_k$.

$$a_k = \max_{\{\mathbb{R}^k\}} \min_{\mathbf{x} \in \mathbb{R}^k \cap E} \|\mathbf{x}\|$$

**Proof:** (It helps to think of $n = 3$ and $k = 2$) Consider the subspace $\mathbb{R}^{n-k+1}$ spanned by the axes $a_k \geq a_{k+1} \geq \cdots \geq a_n$. This is the intersection of $\mathbb{R}^k$ and $E$. Let $\mathbf{x} \in \mathbb{R}^{n-k+1}$ be a point of the intersection lying on the ellipsoid. Then $\|\mathbf{x}\| \leq a_k$. QED.




Case for $n = 3$ and $k = 2$ (Arnold 112)

### 5.4.1 Behavior of Characteristic Frequencies: Change in Rigidity

**Theorem:** If an $n$-dimensional ellipsoid $E$ with semi-axes $a_1 \geq a_2 \geq \cdots \geq a_n$ contains the ellipsoid $E'$ with semi-axes $a'_1 \geq a'_2 \geq \cdots \geq a'_n$, and both ellipses have the same center, then the semi-axes of $E'$ are smaller.

$$a_k \geq a'_k \quad , \quad k = 1, 2, \ldots, n$$

**Proof:** Consider the $k$-dimensional subspace $\mathbb{R}^k$ that creates the intersection $\mathbb{R}^k \cap E'$ on the smaller ellipsoid. Any semi-axis here must be less than or equal to the smallest semi-axis of $\mathbb{R}^k \cap E$, since $E' \subseteq E$. That is,

$$a'_k = \max_{\{\mathbb{R}^k\}} \min_{\mathbf{x} \in \mathbb{R}^k \cap E'} \|\mathbf{x}\| \leq \max_{\{\mathbb{R}^k\}} \min_{\mathbf{x} \in \mathbb{R}^k \cap E} \|\mathbf{x}\| = a_k$$

---

A system with the same kinetic energy and new potential energy $U'$ is called **more rigid** if $U' \geq U$. Note that if $U'$ is more rigid than $U$, then the corresponding ellipsoid $E'$ lies inside $E$. Also note that the major semi-axes of the ellipsoid are inversely proportional to the characteristic frequencies $\omega_i$, such that $\omega_i \propto 1/a_i$. Thus, by the above theorem, **all characteristic frequencies are increased under an increase in rigidity**.

$$\omega_k \leq \omega'_k \quad , \quad k = 1, 2, \cdots, n$$

E.g. if the mass on a spring is increased (increase in rigidity), we expect the frequency to increase.

### 5.4.2 Behavior of Characteristic Frequencies: Imposition of Constraint

**Theorem:** Consider the cross-section of the $n$-dimensional ellipsoid $E$ by a hyperplane $\mathbb{R}^{n-1}$. Let the cross section be an $(n-1)$-dimensional ellipsoid $E'$. Then the semi-axes of $E'$ separate the semi-axes of the ellipsoid $E$.

$$a_1 \geq a'_1 \geq a_2 \geq a'_2 \geq \cdots \geq a_{n-1} \geq a'_{n-1} \geq a_n$$

**Proof:** In the previous section, we proved $a'_k \leq a_k$. To prove $a'_k \geq a_{k+1}$, intersect $\mathbb{R}^{n-1}$ with a $k$-dimensional subspace $\mathbb{R}^{k+1}$. The smallest semi-axis of $E' \cap \mathbb{R}^{k+1}$ must be greater than or equal to

the smallest semi-axis of $E \cap \mathbb{R}^{k+1}$. Combining the two inequalities,

$$a'_k = \max_{\{\mathbb{R}^k \subset \mathbb{R}^{n-1}\}} \min_{\mathbf{x} \in \mathbb{R}^k \cap E'} \|\mathbf{x}\| \geq \max_{\{\mathbb{R}^{k+1} \subset \mathbb{R}^{n-1}\}} \min_{\mathbf{x} \in \mathbb{R}^{k+1} \cap E'} \|\mathbf{x}\| = a'_{k+1}$$

$$\min_{\mathbf{x} \in \mathbb{R}^{k+1} \cap E'} \|\mathbf{x}\| \geq \min_{\mathbf{x} \in \mathbb{R}^{k+1} \cap E} \|\mathbf{x}\|$$

$$a'_k = \max_{\{\mathbb{R}^k \subset \mathbb{R}^{n-1}\}} \min_{\mathbf{x} \in \mathbb{R}^k \cap E'} \|\mathbf{x}\| \geq \max_{\{\mathbb{R}^{k+1} \subset \mathbb{R}^{n-1}\}} \min_{\mathbf{x} \in \mathbb{R}^{k+1} \cap E} \|\mathbf{x}\| = a_{k+1}$$

---

Consider a physical system with $n$ degrees of freedom. Let $T$ and $U$ be the kinetic and potential energies under a small oscillation. The system under an **imposition of a linear constraint** is the $(n-1)$-dimensional subspace found by restricted $T$ and $U$ to $\mathbb{R}^{n-1}$. As before, the characteristic frequencies $\omega_i$ are inversely proportional the axes lengths of the ellipsoids. By the above theorem, the **characteristic frequencies of the system with constraints separate the characteristic frequencies of the original system**.

$$\omega_1 \leq \omega'_1 \leq \omega_2 \leq \omega'_2 \leq \cdots \leq \omega_{n-1} \cdots \omega'_{n-1} \leq \omega_n$$

E.g. if a pendulum oscillating in both $x$ and $y$ is restricted to $x$, we expect its frequency to be between that the original frequency in the $x$ and $y$ directions.

## 5.5 Parametric Resonance

Consider a system with a stable equilibrium point for each fixed value of the parameter. If the parameters vary periodically with time, then the overall equilibrium position can be unstable. This makes it possible to, e.g., "rock" on a swing to gain momentum.

We'll consider systems with periodically varying parameters. I.e. for a system with a varying force with period $T$,

$$\dot{\mathbf{x}} = \mathbf{f}(\mathbf{x}, t) \quad , \quad \mathbf{f}(\mathbf{x}, t+T) = \mathbf{f}(\mathbf{x}, t) \tag{1}$$

Let the initial solution of the system be $\varphi(0) = \mathbf{x}$. Denote $g^t : \mathbb{R}^n \to \mathbb{R}^n$ as the mapping of $\mathbf{x}$ to the solution at time $t$, $\varphi(t) = g^t \mathbf{x}$. In general, the mappings $g^t$ don't form a group:

$$g^{t+s} \neq g^t g^s \neq g^s g^t$$

But if $T$ is the period of $\mathbf{f}$, and $n$ is an integer, then $\{g^{nT}\}$ form a group. Consider $n = 1$, the simplest non-trivial case. The mapping $g^T : \mathbb{R}^n \to \mathbb{R}^n$ is the **mapping at a period**, denoted by

$$A : \mathbb{R}^n \to \mathbb{R}^n \quad , \quad A\mathbf{x}(0) = \mathbf{x}(T)$$

---

Let $\mathbf{x}_0$ be a fixed point of the mapping $A$, such that $A\mathbf{x}_0 = \mathbf{x}_0$. The periodic solution $\mathbf{x}(t)$ is stable if and only if the fixed point $\mathbf{x_0}$ of the mapping $A$ is stable. That is, for every $\epsilon > 0$, there exists $\delta > 0$ such that if $|\mathbf{x} - \mathbf{x}_0| < \delta$, then $|A^n \mathbf{x} - A^n \mathbf{x}_0| < \epsilon$ for all $0 < n < \infty$.

If the system given in (1) is Hamiltonian (preserves energy), then $A$ preserves volume: $\det A = 1$. This follows from Liouville's theorem: the phase flow of Hamilton's equations preserves the phase volume.

Intuitively, rotations in the plane are stable mappings. Hyperbolic rotations are unstable mappings (where do they go as $t \to \infty$?)

### 5.5.1 Relation to Traces

**Theorem:** Let $A$ be a linear mapping of the plane to itself that preserves area, such that $\det A = 1$. The mapping $A$ is stable if $|\text{tr}(A)| < 2$ and unstable if $|\text{tr}(A)| > 2$. Assume that $\text{tr}(A) = a_{11} + a_{22}$.

**Proof:** Let $\lambda_1$ and $\lambda_2$ be the eigenvalues of $A$. Then the characteristic equation is given by

$$\lambda^2 - \text{tr}(A)\lambda + \det(\lambda) = 0$$
$$\lambda^2 - \text{tr}(A)\lambda + 1 = 0$$

Using the quadratic formula, we get two real eigenvalues if $|\text{tr}(A)| > 2$ and two complex eigenvalues if $|\text{tr}(A)| < 2$.




Left: 2 real eigenvalues. Right: eigenvalues that are complex conjugates. (Arnold 116)

The left case is a hyperbolic rotation, since one of the eigenvalues is greater than 1 and one is less. Thus $A$ is unstable. In the right case, the eigenvalues satisfy $|\lambda| = 1$. The mapping $A$ is equivalent to a rotation through angle $\alpha$, where $\lambda = e^{\pm i\alpha}$. Thus $A$ is stable, since it can be reduced to a rotation by coordinate transforms.

So to check the stability of a solution to a system, we just need to trace the periodic transformation matrix $A \equiv g^T$. But this is usually more difficult than it looks.

---

We call the trivial solution of a Hamiltonian system **strongly stable** if 1) it's stable, 2) the trivial solution of every "sufficiently close" Hamiltonian system is also stable.

If $|\text{tr}(A)| < 2$, the trivial solution is strongly stable.

### 5.5.2 Parametric Resonance

Consider a system with a slightly varying frequency. E.g. for $a(t + 2\pi) = a(t)$ (a periodic function),

$$\ddot{x} = -\omega^2(1 + \epsilon a(t))x \quad , \quad \epsilon \ll 1$$




Oscillating frequency (Arnold 117)

The stable systems are given by $|\text{tr}(A)| < 2$. The unstable systems are given by $|\text{tr}(A)| > 2$. These form distinct open regions in the $(\omega, \epsilon)$-plane.




White regions: stable. Dashed regions: unstable. (Arnold 118)

The set of unstable systems only approach the $\omega$-axis when $\omega = k/2$, where $k$ is an integer. Thus, it's possible to change the frequency of the system, but only if the period of the change is close to an integer number of half-periods of characteristic oscillations $\omega$. Imagine rocking a swing. We usually don't jump on it constantly, we push down once at the high point and again at the second high point.

---

If $\epsilon = 0$, what's the transformation matrix $A$? Consider the period $T = 2\pi$ and basis $x, \dot{x}$. The general solution is $x = c_1 \cos(\omega t) + c_2 \sin(\omega t)$.

$$\text{Initial conditions } x = 1,\ \dot{x} = 0 : x = \cos(\omega t),\ \dot{x} = -\omega \sin(\omega t)$$
$$\text{Initial conditions } x = 0,\ \dot{x} = 1 : x = \frac{1}{\omega} \sin(\omega t),\ \dot{x} = \cos(\omega t)$$

Thus the transformation matrix $A \equiv g^T = g^{2\pi}$ is

$$A = \begin{pmatrix} \cos(2\pi\omega) & \frac{1}{\omega}\sin(2\pi\omega) \\ -\omega \sin(2\pi\omega) & \cos(2\pi\omega) \end{pmatrix}$$

The trace $|2\cos(2\pi\omega)|$ is less than 2 if $\omega \neq k/2$ for $k \in \mathbb{Z}$. This is why we have regions of instability at those points when $\epsilon \ll 1$. In that case, the equilibrium is unstable and an arbitrarily small periodic change ($\epsilon$) causes an oscillation. This is called **parametric resonance**. In practice, it's easier to observe when $k$ is small.

# 6 Rigid Bodies (p. 123 – 162)

## 6.1 Motion in a Moving Coordinate System

Works as expected, but now with a shiny *mathematical formalism*. First, consider the Lagrangian system described by coordinates $\mathbf{q}$. The Lagrangian is $L = L(\mathbf{q}, \dot{\mathbf{q}}, t)$, and satisfies

$$\frac{d}{dt}\frac{\partial L}{\partial \dot{\mathbf{q}}} = \frac{\partial L}{\partial \mathbf{q}}$$

We can shift to another **moving coordinate system** with coordinate $\mathbf{Q} = \mathbf{Q}(\mathbf{q}, t)$, independent of $\dot{\mathbf{q}}$. Then $\mathbf{Q}$ also satisfies Lagrange's equations

$$\frac{d}{dt}\frac{\partial L}{\partial \dot{\mathbf{Q}}} = \frac{\partial L}{\partial \mathbf{Q}}$$

---

Let $k$ and $K$ be oriented Euclidean spaces. A **motion** of $K$ relative to $k$ is a mapping that smoothly depends on $t$. Furthermore, the mapping must preserve the metric and orientation.

$$D_t : K \to k$$

**Theorem:** Every motion $D_t$ can be uniquely written as the composition of a rotation $B_k : K \to k$ and a translation $C_k : k \to k$.

$$D_t = C_t B_t$$

The mapping is called **translational** if the rotational mapping $B_t$ doesn't depend on $t$.

Let the translational motion $C_t$ act as $C_t\mathbf{q} = \mathbf{q} + \mathbf{r}(t)$, with $\mathbf{q}, \mathbf{r} \in k$. Then the general transformation of the system $K$ into a moving coordinate system $k$ is given by

$$\mathbf{q}(t) = D_t\mathbf{Q}(t) = B_t\mathbf{Q}(t) + \mathbf{r}(t) \tag{1}$$

### 6.1.1 Addition of Velocities




Relative motion for stationary $\mathbf{q}$ and moving $\mathbf{Q}$ (Arnold 125)

Differentiating (1) gives

$$\dot{\mathbf{q}} = \dot{B}\mathbf{Q} + B\dot{\mathbf{Q}} + \dot{\mathbf{r}}$$

If the moving system $K$ has only **translational** motion relative to $k$, then $\dot{B} = 0$. The absolute velocity of the point within $k$ is

$$\mathbf{v} = \mathbf{v}' + \mathbf{v}_0 \ \ , \ \ \mathbf{v}' = B\dot{\mathbf{Q}} \in k \text{ and } \mathbf{v}_0 = \dot{\mathbf{r}} \in k$$

What if the system $K$ rotates relative to $k$? Then the relative velocity (considering only rotation) is $\dot{\mathbf{q}} = \omega \times \mathbf{q}$, where $\omega = \omega(t)$ is the instantaneous angular velocity in $k$. Thus, our general motion combining both translation and rotation in $k$ relative to $K$ is

$$\mathbf{v} = \mathbf{v}' + \mathbf{v}_n + \mathbf{v}_0$$

$$\begin{aligned} \mathbf{v} &= \dot{\mathbf{q}} && \text{(absolute velocity)} \\ \mathbf{v}' &= B\dot{\mathbf{Q}} && \text{(relative velocity)} \\ \mathbf{v}_n = \dot{B}\mathbf{Q} &= \omega \times (\mathbf{q} - \mathbf{r}) && \text{(transferred velocity of rotation)} \\ \mathbf{v}_0 &= \dot{\mathbf{r}} && \text{(velocity of moving coordinate system } K\text{)} \end{aligned}$$

## 6.2 The Coriolis Force

**Theorem:** In a coordinate system $K$ that moves by a translation relative to an inertial system $k$, the motion within $K$ takes place as if $K$ were initial, but on every point mass there's the additional "inertial force"

$$\mathbf{F} = -m\ddot{\mathbf{r}}$$

where $\ddot{\mathbf{r}}$ is the acceleration of $K$.

**Proof:** If $\mathbf{Q} = \mathbf{q} - \mathbf{r}(t)$, then $m\ddot{\mathbf{Q}} = m\ddot{\mathbf{q}} - m\ddot{\mathbf{r}}$.

---

Now we consider rotating systems. What are the inertial forces?

**Theorem:** Let $B_t : K \to k$ be a rotation of $K$ relative to the stationary coordinate system $k$. Let $\mathbf{Q}(t) \in K$ be the radius vector of the moving point in $K$. Then $\mathbf{q}(t) = B_t\mathbf{Q}(t) \in k$ is its counterpart in the stationary system $k$. Assume that the motion of $\mathbf{q}$ in $k$ is subject to Newton's equation $m\ddot{\mathbf{q}} = \mathbf{f}(\mathbf{q}, \dot{\mathbf{q}})$.

Then the motion in $K$, the rotating system with angular velocity $\Omega$, happens as if three additional inertial forces act on $\mathbf{Q}$ within $K$:

1. Inertial force of rotation: $m(\dot{\Omega} \times \mathbf{Q})$
2. Coriolis force: $2m\,(\Omega \times \mathbf{Q})$
3. Centrifugal force: $m\,(\Omega \times (\Omega \times \mathbf{Q}))$

Thus if $B\mathbf{F}(\mathbf{Q}, \dot{\mathbf{Q}}) = \mathbf{f}(B\mathbf{Q}, \dot{B}\dot{\mathbf{Q}})$, then the total force on $\mathbf{Q} \in K$ is

$$m\ddot{\mathbf{Q}} = \mathbf{F} - \underbrace{m(\dot{\Omega} \times \mathbf{Q})}_{\text{inertial}} - \underbrace{2m(\Omega \times \dot{\mathbf{Q}})}_{\text{Coriolis}} - \underbrace{m\,(\Omega \times (\Omega \times \mathbf{Q}))}_{\text{centrifugal}}$$

**Proof:** From the previous section, $\dot{B}\mathbf{X} = \omega \times \mathbf{x} = B(\Omega \times \mathbf{X})$, where $\mathbf{X} \in K$ and $\mathbf{x} \in k$. Since $\mathbf{q} = B\mathbf{Q}$, differentiating gives

$$\dot{\mathbf{q}} = \dot{B}\mathbf{Q} + B\dot{\mathbf{Q}} = B(\dot{\mathbf{Q}} + (\Omega \times \mathbf{Q}))$$

Differentiate again to get

$$\begin{aligned}
\ddot{\mathbf{q}} &= \dot{B}(\dot{\mathbf{Q}} + (\Omega \times \mathbf{Q})) + B(\ddot{\mathbf{Q}} + (\dot{\Omega} \times \mathbf{Q}) + (\Omega \times \dot{\mathbf{Q}})) \\
&= B\left(\Omega \times \left(\dot{\mathbf{Q}} + (\Omega \times \mathbf{Q})\right) + \ddot{\mathbf{Q}} + (\dot{\Omega} \times \mathbf{Q}) + (\Omega \times \dot{\mathbf{Q}})\right) \\
&= B\Big(\ddot{\mathbf{Q}} + \underbrace{2(\Omega \times \dot{\mathbf{Q}})}_{\text{Coriolis}} + \underbrace{(\Omega \times (\Omega \times \mathbf{Q}))}_{\text{centrifugal}} + \underbrace{(\dot{\Omega} \times \mathbf{Q})}_{\text{inertial}}\Big)
\end{aligned}$$

---

In the case of the Earth's rotation, we can approximate $\dot{\Omega} = 0$ since the rotation is close to uniform. The centrifugal force has its largest value at the equator. But it's already taken care of in the internal calculations for $\mathbf{g}$. What's remaining is the Coriolis force. So in the coordinate system $K$ as the Earth, we can approximate

$$m\ddot{\mathbf{Q}} = m\mathbf{g} + 2m(\dot{\mathbf{Q}} \times \Omega)$$

A free-falling object appears to skew to the right/left (depending on hemisphere) to an observer on the surface. For a height of 250m, the displacement is about 4cm.

## 6.3 Rigid Bodies

A rigid body is a system of point masses constrained by the holonomic relations

$$|\mathbf{x}_i - \mathbf{x}_j| = r_{ij} = \textit{const.}$$

As long as there are more than three distinct points on the rigid body (not all in a straight line), the configuration manifold is 6-dimensional and given by $\mathbb{R}^3 \times SO(3)$. I.e. 3-dimensional position and 3-dimensional rotation.

---

Conserved quantities of a rigid body are found with Noether's theorem. Consider a rigid body moving only under its own inertia (no external forces). Translational displacements don't affect the Lagrangian function, so by Noether's theorem, there exist 3 first integrals: the 3 components of momentum.

| |
|---|
| Under free motion, a rigid body's center of mass moves uniformly and linearly. |

Now consider the inertial coordinate system in which the center of mass is stationary. Then the rigid body rotates about that center of mass, call it $O$. The Lagrangian is invariant under rotations about $O$. Thus, by Noether's theorem, there exist 3 first integrals: the 3 components of angular momentum. The total energy of the system is also conserved.

| |
|---|
| Under rotation about its center of mass, the angular momentum and energy of a rigid body are conserved. |

### 6.3.1 The Inertia Tensor

Remember the $I$ from $K = \frac{1}{2}I\omega^2$? That's the inertia tensor. Here it's introduced with more math.

Consider a mass $m$. Let $k$ be an inertial coordinate system. Let $K$ be a coordinate system rotating around the point $O$. In $K$, the mass is at rest. Every vector in $K$ is mapped to $k$ by a rotation operator $B : K \to k$.

By the definition of angular velocity, $\mathbf{v} = \omega \times \mathbf{q}$. Let $\mathbf{l}$ be the angular momentum of the mass $m$ with respect to the pivot $O$. Then $\mathbf{l} = \mathbf{q} \times m\mathbf{v}$, so

$$\mathbf{l} = m(\mathbf{q} \times \mathbf{v}) = m\left(\mathbf{q} \times (\omega \times \mathbf{q})\right)$$
$$\mathbf{L} = m\left(\mathbf{Q} \times (\Omega \times \mathbf{Q})\right)$$

Notice that there's a linear operator transforming $\Omega$ to $\mathbf{L}$. Call that $A$, such that $A : K \to K$ and $A\Omega = \mathbf{L}$. Now note that for $\Omega \in K$,

$$A\Omega \cdot \Omega = m(\mathbf{Q} \times (\Omega \times \mathbf{Q})) \cdot \mathbf{\Omega} = m(\Omega \times \mathbf{Q}) \cdot (\Omega \times \mathbf{Q})$$
$$A\Omega \cdot \Omega = m(\Omega \times \mathbf{Q})^2 = \mathbf{V}^2 = \mathbf{v}^2$$

Thus the kinetic energy of a rotating point, usually $K = \frac{1}{2}\mathbf{v}^2$ for $m = 1$, becomes

$$K = \frac{1}{2}(A\Omega \times \Omega) = \frac{1}{2}\mathbf{L} \times \Omega$$

The symmetric operator $A$ is called the **inertia tensor** of the point $\mathbf{Q}$. If the rigid body consists of multiple points $\mathbf{Q}_i$, the total inertia tensor is the sum of the individual inertia tensors.

---

Let $\mathbf{e_i} \in K$ be the unit vectors. Let $I_i$ be the eigenvalues of the inertia tensor $A$. In 3 dimensions, these satisfy

$$L_i = I_i\Omega_i$$
$$T = \frac{1}{2}(I_1\Omega_1^2 + I_2\Omega_2^2 + I_3\Omega_3^2)$$

**Theorem:** For a rigid body rotating around point $O$ with angular velocity $\mathbf{\Omega} = \Omega\mathbf{e}$ around the $\mathbf{e}$-axis, the kinetic energy is

$$T = \frac{1}{2}I_{\mathbf{e}}\mathbf{\Omega}^2 \quad , \quad I_{\mathbf{e}} = \sum_i m_i r_i^2$$

**Proof:** By definition, $T = \frac{1}{2}\sum m_i \mathbf{v}_i^2$. Since $|\mathbf{v}_i| = \mathbf{\Omega}\mathbf{r}_i$, $T = \frac{1}{2}(\sum m_i r_i^2)\mathbf{\Omega}^2$

$I_{\mathbf{e}} = \sum_i m_i r_i^2$ is the **moment of inertia of the body** with respect to the $\mathbf{e}$-axis. Thus, the moments of inertia of the body w.r.t the principal axes $\mathbf{e}_i$ are the eigenvalues $I_i$ of $A$. If $A$ is a diagonal matrix (the situations we usually encounter in problems), the eigenvalues are just on the diagonal. If $A$ has off-diagonal elements, more work is required to find the eigenvalues.

### 6.3.2 The Inertia Ellipsoid

The ellipsoid $\{\Omega \mid A\Omega \cdot \Omega = 1\}$ is called the **inertia ellipsoid of the body** at point 0. If $\mathbf{e}_i$ are the principal axes, the inertia ellipsoid has the equation

$$I_1\Omega_1^2 + I_2\Omega_2^2 + I_3\Omega_3^2 = 1$$

Thus the lengths of the ellipsoid's axes are inversely proportional to $\sqrt{I_i}$. The inertia ellipsoid completely determines the rotational characteristics of the body: if two bodies have the same inertia ellipsoid, then for identical initial conditions, they'll move identically. They have the same Lagrangian function $L = T$. In this view, **the space of all rigid bodies is 3-dimensional**.

---

Some handy theorems concerning moments of inertia are below. They hold for planar rigid bodies. Be cautious if the shapes are weird 3D ones.

- (Perpendicular axis theorem) $I_z = I_x + I_y$
- (Parallel axis theorem) $I_r = I_0 + mr^2$

## 6.4 Euler's Equations

The motion of a free rigid body around a stationary point is studied. This motion has two frequencies.

**Theorem (Euler equations):** Consider a rigid body rotating around a point $O$. Let $\mathbf{L}$ be the angular momentum, $\Omega$ the angular velocity, and $A$ the inertia operator ($A\Omega = \mathbf{L}$). These are in the moving coordinate system $K$. In $k$, the angular momentum $\mathbf{l} = B\mathbf{L}$ must be conserved, i.e. no dependence on time.

It turns out that

$$\frac{d\mathbf{L}}{dt} = \mathbf{L} \times \Omega$$

Or, writing out the moments of inertia,

$$\begin{aligned} I_1\frac{d\Omega_1}{dt} &= (I_2 - I_3)\Omega_2\Omega_3 \\ I_2\frac{d\Omega_2}{dt} &= (I_3 - I_1)\Omega_3\Omega_1 \\ I_3\frac{d\Omega_3}{dt} &= (I_1 - I_2)\Omega_1\Omega_2 \end{aligned}$$

---

To find the solutions, note that energy and angular momentum must be conserved:

$$\begin{aligned} 2E &= \frac{L_1^2}{I_1} + \frac{L_2^2}{I_2} + \frac{L_3^2}{I_3} \\ L^2 &= L_1^2 + L_2^2 + L_3^2 \end{aligned}$$

Thus $\mathbf{L}$ lies in the intersection of an ellipsoid and a sphere.




Curves for intersection of ellipsoid and sphere (Arnold 144)

Note: this is **not** an inertia ellipsoid. An inertia ellipsoid has axes variables $\Omega_i$, but here we have $L_i$.

Assume $I_1 > I_2 > I_3$, so the inertia ellipsoid has axes $\sqrt{2EI_1} > \sqrt{2EI_2} > \sqrt{2EI_3}$. Call a motion a **stationary rotation** if its angular velocity remains constant ($\omega = \textit{const}$). A rigid body admits stationary rotations around any of the three principal axis: $\mathbf{e}_1$, $\mathbf{e}_2$, and $\mathbf{e}_3$.

However, by geometry, the stationary solutions $\mathbf{L} = L_1\mathbf{e}_1$ and $\mathbf{L} = L_3\mathbf{e}_3$ of the Euler equations (corresponding to the largest & smallest principal axes) are stable, while the solution $\mathbf{L} = L_2\mathbf{e}_2$ (corresponding to the middle axis) is unstable.

If we fix the ellipsoid and change the radius of the sphere, a small deviation won't affect the intersection curve at the $\mathbf{e}_1$ and $\mathbf{e}_3$ axes. But it'll cause a huge variation in the $\mathbf{e}_2$ axis.

This is sometimes called the **tennis racket theorem**.

## 6.5 Lagrange's Top

This is a cool problem that serves as a "capstone" for Lagrangian mechanics. Consider a spinning, symmetric top.

We want to convert to stationary frame $(\mathbf{e}_x, \mathbf{e}_y, \mathbf{e}_z)$ to the moving frame $(\mathbf{e}_1, \mathbf{e}_2, \mathbf{e}_3)$. To do this, we rotate using the three **Euler angles**: $\varphi$, $\psi$, and $\theta$. For convenience, let $\mathbf{e}_N = \mathbf{e}_z \times \mathbf{e}_3$.

1. Rotate by $\varphi$ around $\mathbf{e}_z$ axis
2. Rotate by $\theta$ around $\mathbf{e}_N$ axis
3. Rotate by $\psi$ around $\mathbf{e}_3$ axis

Note that to keep the transformation $B(\varphi, \theta, \psi) \in SO(3)$ one-to-one, the following conditions are set:

$$0 < \varphi < 2\pi \ , \ 0 < \psi < 2\pi \ , \ 0 < \theta < \pi$$




Lagrange's top and (Arnold 149)

### 6.5.1 The Lagrangian

**Lemma:** If $\varphi = \psi = 0$, the angular velocity of a top is expressed as

$$\omega = \dot{\theta}\mathbf{e}_1 + (\dot{\varphi}\sin\theta)\mathbf{e}_2 + (\dot{\psi} + \dot{\varphi}\cos\theta)\mathbf{e}_3$$

**Proof:** Consider a point of the top occupying $\mathbf{r}$ at time $t$. Now increment the time by $dt$. Let $d\varphi = \dot{\varphi}dt$, $d\theta = \dot{\theta}dt$, and $d\psi = \dot{\psi}dt$. Then after time $dt$, the top's position is approximately (within $(dt)^2$) given by

$$B(\varphi + d\varphi, \theta + d\theta, \psi + d\psi)B^{-1}(\varphi, \theta, \psi)\mathbf{r}$$

Furthermore,

1. $B(\varphi + d\varphi, \theta, \psi)B^{-1}(\varphi, \theta, \psi)\mathbf{r} - \mathbf{r} = (\omega_\varphi \times \mathbf{r})dt$
2. $B(\varphi, \theta + d\theta, \psi)B^{-1}(\varphi, \theta, \psi)\mathbf{r} - \mathbf{r} = (\omega_\theta \times \mathbf{r})dt$
3. $B(\varphi, \theta, \psi + d\psi)B^{-1}(\varphi, \theta, \psi)\mathbf{r} - \mathbf{r} = (\omega_\psi \times \mathbf{r})dt$

The total angular velocity of the point at $\mathbf{r}$ is $\omega = \omega_\varphi + \omega_\theta + \omega_\psi$. Now impose the conditions $\varphi = \psi = 0$. Then equation (1) above just becomes a rotation around the $\mathbf{e}_z$ axis by $d\varphi$, so $\omega_\varphi = \dot{\varphi}\mathbf{e}_z$. Similar reasoning shows that $\omega_\theta = \dot{\theta}\mathbf{e}_1$, and $\omega_\psi = \dot{\psi}\mathbf{e}_3$.

From the diagram, note that $\mathbf{e}_z = \mathbf{e}_3\cos\theta + \mathbf{e}_2\sin\theta$. Thus, the total angular velocity at $\mathbf{r}$ is

$$\omega = \underbrace{\dot{\theta}}_{\omega_1}\mathbf{e}_1 + \underbrace{\dot{\varphi}\sin\theta}_{\omega_2}\mathbf{e}_2 + \underbrace{(\dot{\psi} + \dot{\varphi}\cos\theta)}_{\omega_3}\mathbf{e}_3$$

By choosing our coordinate axes, we can always make $\varphi = \psi = 0$. So this formula works for all $\varphi$ and $\psi$. We can finally find the Lagrangian of the top:

$$\begin{aligned}
T &= \frac{1}{2}(I_1\omega_1^2 + I_2\omega_2^2 + I_3\omega_3^2) = \frac{I_1}{2}(\dot{\theta}^2 + \dot{\varphi}^2\sin^2\theta) + \frac{I_3}{2}(\dot{\psi} + \dot{\varphi}\cos\theta)^2 \\
V &= mgl\cos\theta \\
L &= \frac{I_1}{2}(\dot{\theta}^2 + \dot{\varphi}^2\sin^2\theta) + \frac{I_3}{2}(\dot{\psi} + \dot{\varphi}\cos\theta)^2 - mgl\cos\theta
\end{aligned}$$

### 6.5.2 Nutation

Note that $\varphi$ and $\psi$ don't appear in the integral. They're **cyclic coordinates**. By Noether's theorem, they give a conserved quantity – in this case, $L_z$ (angular momentum projected on $\mathbf{e}_z$) and $L_3$ (angular momentum projected on $\mathbf{e}_3$).

$$\begin{aligned}
\frac{\partial L}{\partial \dot{\varphi}} &= L_z = \dot{\varphi}(I_1\sin^2\theta + I_3\cos^2\theta) + \dot{\psi}I_3\cos\theta \\
\frac{\partial L}{\partial \dot{\psi}} &= L_3 = \dot{\varphi}I_3\cos\theta + \dot{\psi}I_3
\end{aligned}$$

We want to study the motion with respect to the inclination $\theta$. The total energy is

$$E = \frac{1}{2}I_1\omega_1^2 + \frac{1}{2}I_2\omega_2^2 + \frac{1}{2}I_3\omega_3^2 \quad \Big| \quad \dot{\varphi} = \frac{L_z - L_3\cos\theta}{I_1\sin^2\theta}$$

We can use the value $L_3$ found previously. Additionally, from the two equations, $\dot{\varphi} = (L_z - L_3\cos\theta)/(I_1\sin^2\theta)$. And we know that $\omega_2 = \dot{\varphi}\sin\theta$ from earlier. Finally, because of symmetry, $I_1 = I_2$. Then our equation becomes

$$E = \frac{I_1}{2}\dot{\theta}^2 + \frac{L_3^2}{2I_3} + \frac{(L_z - L_3\cos\theta)^2}{2I_1\sin^2\theta} + mgl\cos\theta \tag{1}$$

Since the $L_3^2/(2I_3)$ term is independent of $\theta$, we can consider the conservation of $E'$ with that left out:

$$E' = \frac{I_1}{2}\dot{\theta}^2 + \frac{(L_z - L_3\cos\theta)^2}{2I_1\sin^2\theta} + mgl\cos\theta \tag{2}$$

---

To simplify, introduce the following constants:

$$a = \frac{L_z}{I_1} \qquad b = \frac{L_3}{I_1}$$
$$\alpha = \frac{2E'}{I_1} \qquad \beta = \frac{2mgl}{I_1}$$

Additionally let $u = \cos\theta$, for $-1 \le u \le 1$. Then our equation becomes

$$\begin{aligned}
\alpha &= \frac{1}{1-u^2}\dot{u}^2 + \frac{(a-bu)^2}{1-u^2} + \beta u \\
\dot{u}^2 &= \underbrace{(\alpha - \beta u)(1-u^2) - (a-bu)^2}_{f(u)}
\end{aligned}$$

$f(u)$ is a polynomial of degree 3, and within $-1 \leq u \leq 1$, it has two real roots: call them $u_1$ and $u_2$, corresponding to $\theta_1$ and $\theta_2$. Since $u$ itself is periodic, the inclination $\theta$ of the top must change periodically between $\theta_1$ and $\theta_2$. This is called a **nutation**.

### 6.5.3 Precession

Now consider the motion of the azimuth of the top's axis. We found $\dot{\varphi}$ previously, substitute the constants we defined above. Then

$$\dot{\varphi} = \frac{L_z - L_3 \cos\theta}{I_1 \sin^2\theta} = \frac{a - bu}{1 - u^2}$$

Let $u'$ be the solution of $a - bu = 0$.

1. If $u'$ lies outside of $[-1, 1]$, then $\dot{\varphi}$ changes monotonically, and the axis traces a sinusoidal curve.
2. If $u'$ lies inside $(-1, 1)$, the axis traces a looping curve.
3. If $u'$ is on the boundary of $[-1, 1]$, the axis traces a curve with cusps.




Summary of the three cases (Arnold 153)

## 6.6 Lagrange's Top: Special Cases

### 6.6.1 Sleeping Top

If the top is "sleeping," i.e. $\theta = 0$, then $L_z = L_3 = I_3\omega_3$. Recall the equation for energy $E'$:

$$E' = \frac{I_1}{2}\dot{\theta}^2 + \frac{(L_z - L_3\cos\theta)^2}{2I_1\sin^2\theta} + mgl\cos\theta$$

We can group the terms without $\dot{\theta}$ as the **effective potential energy** $U_{\text{eff}}$:

$$\begin{aligned} U_{\text{eff}} &= \frac{(L_z - L_3\cos\theta)^2}{2I_1\sin^2\theta} + mgl\cos\theta \\ &\approx \frac{I_3^2\omega_3^2(\theta^4/4)}{2I_1\theta^2} + mgl - mgl\frac{\theta^2}{2} \\ &= mgl + \underbrace{\left(\frac{I_3^2\omega_3^2}{8I_1} - \frac{mgl}{2}\right)}_{A}\theta^2 \end{aligned}$$

If $A > 0$, the potential energy is concave up and the equilibrium position $\theta = 0$ is stable. If $A < 0$, it's unstable. The **condition for stability** is thus

$$\omega_3^2 > \frac{4mglI_1}{I_3^2}$$

### 6.6.2 Fast Top

If the top is very fast, i.e. $\frac{1}{2}I_3\omega_3^2 \gg mgl$, then what happens? By similarity, multiplying $\omega_3$ by $N$ is equivalent to dividing the weight by $N^2$. Thus, a very fast top approaches the case of $g = 0$. Then the potential energy reduces to

$$U_{\text{eff}} = \frac{(L_z - L_3\cos\theta)^2}{2I_1\sin^2\theta}$$

For small deviations from the equilibrium $\theta_0$, i.e. $\theta = \theta_0 + x$, we have

$$U_{\text{eff}} \approx \frac{L_3^2(\cos\theta_0 - \cos(\theta_0 + x))^2}{2I_1\sin^2\theta_0} \approx \frac{L_3^2(x\sin\theta_0)^2}{2I_1\sin^2\theta_0} = \frac{I_3^2\omega_3^2}{2I_1}x^2$$

The total energy of our system is

$$E = \frac{1}{2}I_1\dot{\theta}^2 + U_{\text{eff}}$$

It's a known fact that if $T = \frac{1}{2}a\dot{q}^2$ and $U = \frac{1}{2}bq^2$, then the oscillation frequency is $\omega = \sqrt{b/a}$. By applying that here, we get the **nutation frequency**, since this is the frequency of deviation from $\theta_0$.

$$\omega_{\text{nut}} = \frac{I_3\omega_3}{I_1}$$

---

Furthermore, for the initial conditions $\dot{\varphi} = \dot{\theta} = 0$ (i.e. a rapidly thrown top), the following holds if $\omega_3 \to \infty$:

$$a_{\text{nut}} \sim \frac{I_1 mgl}{I_3^2\omega_3^2}\sin\theta_0$$

$a_{\text{nut}}$ is the amplitude of nutation.




Amplitude of nutation (Arnold 159)

By Taylor expanding $U$ around $\theta = \theta_0 + x$, we had

$$mgl\cos\theta \approx mgl\cos\theta_0 - xmgl\sin\theta_0$$
$$U_{\text{eff}} \approx \frac{I_3^2\omega_3^2}{2I_1}x^2$$

Then $dU/dx = I_3^2\omega_3^2 x/I_1$. Approximate the energy difference between the initial and equilibrium positions and use that to find $x_g$, the amplitude of nutation:

$$\Delta U_g = xmgl\sin\theta_0 \approx \left(\frac{dU}{dx}\right)x_g = \frac{I_3^2\omega_3^2 x}{I_1}\cdot x_g$$
$$x_g \approx \frac{I_1 ml\sin\theta_0}{I_3^2\omega_3^2}g$$

---

The angular precession is found from the general formula for $\dot{\varphi}$:

$$\dot{\varphi} = \frac{L_z - L_3\cos\theta}{I_1\sin^2\theta} \approx \frac{L_3 x\sin\theta_0}{I_1\sin^2\theta_0} = \frac{L_3}{I_1\sin\theta_0}x$$

Since $x$ oscillates between 0 and $2x_g$, the average value of the precession velocity is taken over the period of nutation. Then the precession frequency is proportional to the precession velocity.

$$\overline{\dot{\varphi}} \sim \frac{1}{2x_g}\int_0^{2x_g}\frac{L_3}{I_1\sin\theta_0}x\,dx = \frac{L_3}{I_1\sin\theta_0}x_g \approx \frac{mgl}{I_3\omega_3}$$
$$\omega_{\text{prec}} \sim \frac{mgl}{I_3\omega_3}$$

---

In sum, for a fast top with $\omega_3 \to \infty$ (equivalent to $g \to 0$),

1. The frequency of nutation increase: $\omega_{\text{nut}} \to \infty$

2. The amplitude of nutation decreases: $a_{\text{nut}} \to 0$
3. The frequency of precession decreases: $\omega_{\text{prec}} \to 0$

So a fast-spinning top will tend to stay in its position without much variation in $\theta$.

# Part III

# Hamiltonian Mechanics

Lagrangian Mechanics is a special case of Hamiltonian mechanics. To fully describe Hamiltonian mechanics, we'll need concepts of phase space geometry and symplectic manifolds. Hamiltonian mechanics is useful for complex mechanical problems and perturbation theory.

## 7 Differential Forms (p. 163 – 200)

### 7.1 Exterior Forms

#### 7.1.1 $k$-Forms

Let $\mathbb{R}^n$ be a vector space and $\xi_1, \xi_2 \in \mathbb{R}^n$ be two vectors in it. Let $\lambda_1, \lambda_2 \in \mathbb{R}$ be constants. A **1-form** (or an **exterior form of degree 1**) is a linear function $\omega : \mathbb{R}^n \to \mathbb{R}$ such that

$$\omega(\lambda_1\xi_1 + \lambda_2\xi_2) = \lambda_1\omega(\xi_1) + \lambda_2\omega(\xi_2)$$

The set of 1-forms becomes a real vector space if addition and scalar multiplication are defined:

$$(\omega_1 + \omega_2)(\xi) = \omega_1(\xi) + \omega_2(\xi)$$
$$(\lambda\omega)(\xi) = \lambda\omega(\xi)$$

The space of 1-forms on $\mathbb{R}^n$ is $n$-dimensional, and called the **dual space** $(\mathbb{R}^n)^*$.

We can also represent 1-forms with a linear coordinate system $x_1, \ldots, x_n$ on $\mathbb{R}^n$. $x_1(\xi), \ldots, x_n(\xi)$ give the components of $\xi \in \mathbb{R}^n$ in the chosen coordinate system. Then for some constants $a_i \in \mathbb{R}$, every 1-form $\omega \in (\mathbb{R}^n)^*$ satisfies

$$\omega = a_1x_1 + \cdots + a_nx_n$$
$$\omega(\xi) = a_1x_1(\xi) + \cdots + a_nx_n(\xi)$$

An example of 1-forms is the horizontal vector. E.g. $(0, 1, 2) \in (\mathbb{R}^3)^*$, while $(0, 1, 2)^T \in \mathbb{R}^3$. You can see that the action of the 1-form on a vector is a scalar in $\mathbb{R}$ – here, it's just the dot product. As another example, the work of a force $\mathbf{F}$ on a displacement $\xi$ is a 1-form acting on $\xi$: $\omega(\xi) = \mathbf{F} \cdot \xi$.

---

We can also define **2-forms** (or an **exterior form of degree 2**). This is a function $\omega^2$ on pairs of vectors, not just one, such that $\omega^2 : \mathbb{R}^n \times \mathbb{R}^n \to \mathbb{R}$. The 2-form is **bilinear**, not linear, and **skew symmetric**. For $\lambda_i \in \mathbb{R}$ and $\xi_i \in \mathbb{R}^n$,

$$\omega^2(\lambda_1\xi_1 + \lambda_2\xi_2, \lambda_3\xi_3) = \lambda_1\omega^2(\xi_1, \xi_3) + \lambda_2\omega^2(\xi_2, \xi_3)$$
$$\omega^2(\xi_1, \xi_2) = -\omega^2(\xi_2, \xi_1)$$

As before, the set of all 2-forms on $\mathbb{R}^n$ becomes a real vector space if we define addition and scalar multiplication:

$$(\omega_1 + \omega_2)(\xi_1, \xi_2) = \omega_1(\xi_1, \xi_2) + \omega_2(\xi_1, \xi_2)$$
$$(\lambda\omega)(\xi_1, \xi_2) = \lambda\omega(\xi_1, \xi_2)$$

An example of a 2-form is the oriented area of a parallelogram constructed by $\xi_1, \xi_2 \in \mathbb{R}^2$. This is just the determinant:

$$S(\xi_1, \xi_2) = \begin{vmatrix} \xi_{11} & \xi_{21} \\ \xi_{12} & \xi_{22} \end{vmatrix}$$



Oriented area is a 2-form (Arnold 165)

A $k$**-form** (or **exterior form of degree** $k$) is a function of $k$ vectors. As expected, this is $k$-linear and antisymmetric.

$$\omega(\lambda_1\xi_1' + \lambda_2\xi'', \xi_2, \ldots, \xi_k) = \lambda_1\omega(\xi_1', \xi_2, \ldots, \xi_k) + \lambda_2\omega(\xi_1'', \xi_2, \ldots, \xi_k)$$
$$\omega(\xi_{i_1}, \ldots, \xi_{i_k}) = (-1)^\nu\omega(\xi_1, \ldots, \xi_k)$$

where

$$\nu = \begin{cases} 0 & \text{if permutation } i_1, \ldots, i_k \text{ is even} \\ 1 & \text{if permutation } i_1, \ldots, i_k \text{ is odd} \end{cases}$$

The set of all $k$-forms in $\mathbb{R}^n$ form a real vector space if we define addition and scalar multiplication:

$$(\omega_1 + \omega_2)(\xi) = \omega_1(\xi) + \omega_2(\xi)$$
$$(\lambda\omega)(\xi) = \lambda\omega(\xi)$$

An example of a $k$-form is oriented volume in $k$ dimensions, given by

$$V(\xi_1, \dots \xi_n) = \begin{vmatrix} \xi_{11} & \cdots & \xi_{n1} \\ \vdots & & \vdots \\ \xi_{1n} & \cdots & \xi_{nn} \end{vmatrix}$$




Oriented volume is a 3-form (Arnold 166)

### 7.1.2 Exterior Product of $k$-Forms

Let $\omega^k$ be a $k$-form and $\omega^l$be an $l$-form on $\mathbb{R}^n$. Then the exterior product $\omega^k \wedge \omega^l$ will be a $k + l$ form.

But first, consider 1-forms. Let $\omega_1$ and $\omega_2$ be 1-forms on $\mathbb{R}^n$. The value of the exterior product $\omega_1 \wedge \omega_2$ on a pair of vectors $\xi_1, \xi_2 \in \mathbb{R}^n$ is the oriented area of the parallelogram with sides $\omega(\xi_1)$ and $\omega(\xi_2)$. I.e. $\omega_1 \wedge \omega_2$ is a 2-form.

$$(\omega_1 \wedge \omega_2)(\xi_1, \xi_2) = \begin{vmatrix} \omega_1(\xi_1) & \omega_2(\xi_1) \\ \omega_1(\xi_2) & \omega_2(\xi_2) \end{vmatrix}$$




Exterior product of two 1-forms (Arnold 167)

Suppose $x_1, \dots, x_n$ are $n$ independent 1-forms that comprise a system of linear coordinates on $\mathbb{R}^n$. These forms are called **basic**. By geometry, $x_i \wedge x_i = 0$ and $x_i \wedge x_j = -x_j \wedge x_i$. The action of $(x_i \wedge x_j)$ on vectors $\xi_1, \xi_2 \in \mathbb{R}^n$ is its oriented area of the parallelogram spanned by $\xi_1, \xi_2$ in the coordinate plane spanned by $x_i, x_j$.

Every 2-form in an $n$-dimensional space with coordinates $x_1, \ldots, x_n$ is represented by

$$\omega^2 = \sum_{i \leq j} a_{ij} x_i \wedge x_j$$

---

If we're given $k$ 1-forms $\omega_1, \ldots, \omega_k$, the exterior product works similarly: its action on $\xi_1, \ldots, \xi_k \in \mathbb{R}^n$ is the volume of the $k$-dimensional parallelogram spanned by $\xi_i$ in the oriented Euclidean space $\mathbb{R}^k$ under the mapping $\xi \to (\omega_1(\xi), \ldots, \omega_k(\xi))$.

$$(\omega_1 \wedge \cdots \wedge \omega_k)(\xi_1, \ldots, \xi_k) = \begin{vmatrix} \omega_1(\xi_1) & \cdots & \omega_k(\xi_1) \\ \vdots & & \vdots \\ \omega_1(\xi_k) & \cdots & \omega_k(\xi_k) \end{vmatrix}$$

Consider a coordinate system on $\mathbb{R}^n$ given by **basic forms** $x_1, \ldots, x_n$. The exterior product of these $k$ basic forms is the oriented volume of the image of a $k$-dimensional parallelepiped on the $k$-plane $(x_{i_1}, \ldots, x_{i_k})$ under a project **parallel to the remaining** $n - k$ **coordinates**.

$$\text{Vol}(x_{i_1}, \ldots, x_{i_k}) = x_{i_1} \wedge \cdots \wedge x_{i_k}$$
$$1 \leq i_m \leq n$$

Every $k$-form on $\mathbb{R}^n$ can be uniquely represented as the linear combination of basic forms:

$$\omega^k = \sum_{1 \leq i_1 < \cdots < i_k \leq n} a_{i_1, \ldots, i_k} x_{i_1} \wedge \cdots \wedge x_{i_k}$$

By combinatorics, the dimension of the vector space of $k$-forms on $\mathbb{R}^n$ is equal to $C_n^k$. That's the number of ways to choose $k$ basic forms out of $n$ total.

---

Okay, now consider 2 basic forms, a $k$-form $\omega^k$ and an $l$-form $\omega^l$. We can rewrite these as an exterior product:

$$\omega^k = \omega_1 \wedge \cdots \wedge \omega_k$$
$$\omega^l = \omega_{k+1} \wedge \cdots \wedge \omega_{k+l}$$
$$\omega^k \wedge \omega^l = \omega_1 \wedge \cdots \wedge \omega_k \wedge \omega_{k+1} \wedge \cdots \wedge \omega_{k+l}$$

This exterior product is both associative and skew-commutative, so it's indeed an exterior form, specifically a $(k + l)$-form.

$$(\omega^k \wedge \omega^l) \wedge \omega^m = \omega^k \wedge (\omega^l \wedge \omega^m)$$
$$\omega^k \wedge \omega^l = (-1)^{kl} \omega^l \wedge \omega^k$$

### 7.1.3 Exterior Multiplication

Let $\omega_k$ be a $k$-form on $\mathbb{R}^n$ and $\omega_l$ be an $l$-form on $\mathbb{R}^n$. The exterior multiplication $\omega_k \wedge \omega_l$ is a $(k+l)$-form on $\mathbb{R}^n$ on the $k+l$ vectors $\xi_1, \ldots, \xi_k, \xi_{k+1}, \ldots, \xi_{k+l} \in \mathbb{R}^n$ is

$$(\omega^k \wedge \omega^l)(\xi_1, \ldots, \xi_{k+1}) = \sum (-1)^\nu \omega^k(\xi_{i_1}, \ldots, \xi_{i_k}) \omega^l(\xi_{j_1}, \ldots, \xi_{j_l})$$

Where $i_1 < \cdots < i_k$ and $j_1 < \cdots < j_l$ are permutations of the numbers $(1, 2, \ldots, k+l)$, and

$$\nu = \begin{cases} 1 & \text{if permutation is odd} \\ 0 & \text{if permutation is even} \end{cases}$$

The properties of the exterior product are:

1. **Skew-commutative:** $\omega^k \wedge \omega^l = (-1)^{kl} \omega^l \wedge \omega^k$
2. **Distributive:** $(\lambda_1 \omega_1^k + \lambda_2 \omega_2^k) \wedge \omega^l = \lambda_1 \omega_1^k \wedge \omega^l + \lambda_2 \omega_2^k \wedge \omega^l$
3. **Associative:** $(\omega^k \wedge \omega^l) \wedge \omega^m = \omega^k \wedge (\omega^l \wedge \omega^m)$

Think of the exterior product as a generalization of the cross product. It gives the $n$-dimensional directed volume.

---

As an example, if $k = l = 1$, then $(\xi_1, \xi_2)$ and $(\xi_2, \xi_1)$ are the only partitions. Thus

$$(\omega_1 \wedge \omega_2)(\xi_1, \xi_2) = \omega_1(\xi_1)\omega_2(\xi_2) - \omega_2(\xi_1)\omega_1(\xi_2)$$

---

**Behavior under mappings:** Let $f : \mathbb{R}^m \to \mathbb{R}^n$ be a linear map, and $\omega^k$ an exterior $k$-form on $\mathbb{R}^n$. Then there exists a $k$-form $f^*\omega^k$ on $\mathbb{R}^m$, whose action on the $k$ vectors $\xi_1, \ldots, \xi_k \in \mathbb{R}^m$ is equal to the action of $\omega^k$ on their images.

$$(f^*\omega^k)(\xi_1, \ldots, \xi_k) = \omega^k(f\xi_1, \ldots, f\xi_k)$$

## 7.2 Differential 1-Forms

We usually take the exterior product of differential forms. But what's a differential form? Just like the exterior product was a generalization of the cross product, a differential form is like a generalization of a function's differential.

E.g. for the function $f(x) = x^2$, the differential is $df = 2x\ dx$. (Mathematicians may not like this)

Let $f : M \to \mathbb{R}$ be a differentiable function on the manifold $M$. The differential $df|_x$ of $f$ at $\mathbf{x}$ is a linear map, denoted

$$df|_{\mathbf{x}} : TM_{\mathbf{x}} \to \mathbb{R}$$

Note that $df_{\mathbf{x}}$, the differential of $f$, is a 1-form on the tangent space $TM_{\mathbf{x}}$. Now let $\xi \in TM_{\mathbf{x}}$ be the velocity vector of the curve $\mathbf{x}(t) : \mathbb{R} \to M$. Let $\mathbf{x}(0) = \mathbf{x}$ and $\dot{\mathbf{x}}(0) = \xi$. Then we define

$$df_{\mathbf{x}}(\xi) = \frac{d}{dt} f(\mathbf{x}(t)) \Big|_{t=0}$$

---

This is a map from the **tangent space at a certain point** to $\mathbb{R}$. More generally, a differential form of degree 1 (a 1-form) on a manifold $M$ is the smooth map from the **tangent bundle** $TM$ to the line $\mathbb{R}$.

$$\omega : TM \to \mathbb{R} \ \ , \ \ TM = \bigcup_{\mathbf{x}} TM_{\mathbf{x}}$$

So $df_{\mathbf{x}} : TM_{\mathbf{x}} \to \mathbb{R}$, but $df : TM \to \mathbb{R}$.

---

Every differential 1-form on the space $\mathbb{R}^n$ with a given coordinate system $x_1, \ldots, x_n$ can be uniquely written in the form

$$\omega = a_1(x)dx_1 + \cdots + a_n(x)dx_n$$

where $a_i(x)$ are smooth functions. The 1-forms $dx_i$ form a basis for the $n$-dimensional space of 1-forms on $T\mathbb{R}^n_{\mathbf{x}}$.

## 7.3 Differential $k$-Forms

A differential $k$-form $\omega^k|_{\mathbf{x}}$ at a point $\mathbf{x}$ of a manifold $M$ is an exterior $k$-form on the tangent space $TM_{\mathbf{x}}$ to $M$ at $\mathbf{x}$. If $\omega^k|_{\mathbf{x}}$ exists and is differentiable for all $\mathbf{x} \in M$, we say we're given a $k$-form on the manifold $M$.

Let the manifold $M$ be the vector space $\mathbb{R}^n$ with coordinate functions $x_1, \ldots, x_n : \mathbb{R}^n \to \mathbb{R}$. For a point $\mathbf{x} \in M$, the $n$ 1-forms $dx_1, \ldots, dx_n \in T\mathbb{R}^n_{\mathbf{x}}$ form a basis for the space of 1-forms on the tangent space. Every exterior $k$-form on $T\mathbb{R}^n_{\mathbf{x}}$ can be uniquely written as

$$\sum_{i_1 < \cdots < i_k} a_{i_1,\ldots,i_k} dx_{i_1} \wedge \cdots \wedge dx_{i_k}$$

Let $\omega$ be a differential $k$-form on $M$. At every point $\mathbf{x}$, it's uniquely expressed with the basis above. So every differential $k$-form on $\mathbb{R}^n$ with a given coordinate system $x_1, \ldots, x_n$ can be uniquely written as

$$\omega^k = \sum_{i_1 < \cdots < i_k} a_{i_1,\ldots,i_k}(\mathbf{x})\ dx_{i_1} \wedge \cdots \wedge dx_{i_k}$$

### 7.3.1 Change of Basis

Let there be 2 coordinate systems on $\mathbb{R}^3$: $x_1, x_2, x_3$ and $y_1, y_2, y_3$. Let $\omega$ be a 2-form on $\mathbb{R}^3$. If $X_i$ are functions depending on $x_i$, and $Y_i$ are functions depending on $y_i$, we can write

$$\omega = X_1 dx_2 \wedge dx_3 + X_2 dx_3 \wedge dx_1 + X_3 dx_1 \wedge dx_2$$
$$\omega = Y_1 dy_2 \wedge dy_3 + Y_2 dy_3 \wedge dy_1 + Y_3 dy_1 \wedge dy_2$$

To change between basis, sum the partial derivatives:

$$dx_i = \frac{\partial x_i}{\partial y_1} dy_1 + \frac{\partial x_i}{\partial y_2} dy_2 + \frac{\partial x_i}{\partial y_3} dy_3$$

Then substitute to solve for each $Y_i$ in terms of $x_1, x_2, x_3$.

## 7.4 Integration of Differential Forms

Let $\omega^1$ be a 1-form on a manifold $M$. Let $\gamma : \mathbb{R} \to M$ be a smooth map, the "path of integration" parametrized by $0 \leq t \leq 1$.

Divide this interval into by points $t_i$, so that $\Delta_i : t_i \leq t \leq t_{i+1}$. The tangent vector in $TM$ is

$$\xi_i = d\gamma(\Delta_i)|_{t_i} \in TM_{\gamma(t_i)}$$

Then we define the integral of the 1-form $\omega^1$ along the path $\gamma$ as the sum of the tangent vectors.

$$\int_\gamma \omega^1 = \lim_{\Delta \to 0} \sum_{i=1}^{n} \omega^1(\xi_i)$$




Integrating a 1-form along a path (Arnold 181)

Now consider a $k$-form on an oriented coordinate system $x_1, \ldots, x_k$ of $\mathbb{R}^k$. Every $k$-form on $\mathbb{R}^k$ has the form $\omega^k = \varphi(x) dx_1 \wedge \cdots \wedge dx_k$, where $\varphi(x)$ is a smooth function. Let $D$ be a bounded convex polyhedron in $\mathbb{R}^k$. The integral of the form $\omega^k$ on $D$ is the integral of $\varphi$.

$$\int_D \omega^k = \int_D \varphi(x)\ dx_1, \ldots, dx_k$$

Let $f : M \to N$ be a differentiable map of $M$ to $N$ (both smooth manifolds). Let $\omega$ be a differential $k$-form on $N$. Then we can also define a $k$-form on $M$, denoted $f^*\omega$, as

$$(f^*\omega)(\xi_1, \ldots, \xi_k) = \omega(f_*\xi_i, \ldots, f_*\xi_k)$$

where $\xi_1, \ldots, \xi_k \in TM_{\mathbf{x}}$ are tangent vectors on $M$. The action of $f^*\omega$ on $\xi_i$ is equal to the action of $\omega$ on the images of $\xi_i$ in $N$.




Diagram of maps (Arnold 183)

For example, if $y = f(x_1, x_2) = x_1^2 + x_2^2$ and $\omega = dy$, then $f^*\omega = 2x_1\,dx_1 + 2x_2\,dx_2$.

---

Let $\omega$ be a differential $k$-form on the $n$-dimensional manifold $M$. Let $D$ be a bounded convex $k$-dimensional poyhedron in $\mathbb{R}^k$. The "path of integration" here is a $k$-dimensional cell $\sigma \in M$ represented by $\sigma = \sigma(D, f, \text{Or})$.

1. Convex polyhedron $D \subset \mathbb{R}^k$
2. Differentiable map $f : D \to M$
3. Orientation Or on $\mathbb{R}^k$. If orientation flips, $\sigma$ flips sign.

$$\int_{-\sigma} \omega = -\int_{\sigma} \omega$$




$k$-dimensional polyhedron (Arnold 184)

Let $\sigma_1, \ldots, \sigma_r \in M$ be $k$-dimensional oriented cells and $m_1, \ldots, m_r$ be the integer **multiplicities**. **chain of dimension** $k$ on $M$ is a finite collection of the cells $\sigma_i$, denoted

$$c_k = m_1\sigma_1 + \cdots + m_r\sigma_r$$

### 7.4.1 Boundaries

Let $D$ be a convex oriented $k$-dimensional polyhendron in $\mathbb{R}^k$. The **boundary of** $D$ is the $(k-1)$-chain $\partial D$ on $\mathbb{R}^k$.

$$\partial D = \sum \sigma_i \quad , \quad \sigma_i = (D_i, f_i, \mathrm{Or}_i)$$

The cells of the chain $\partial D$ are defined by the $(k-1)$-dimensional faces $D_i$, and maps $f_i : D_i \to \mathbb{R}^k$ to embed the faces in $\mathbb{R}^k$. $\mathrm{Or}_i$ is the orientation of the $i$-th cell.




Diagram of boundary $\partial D$ (Arnold 185)

We can also find boundaries of chains. Let $c_k$ be a $k$-dimensional chain in $M$. The boundary $\partial c_k$ is the $(k-1)$-dimensional chain $\partial c_k = \sum \sigma_i$, consisting of the cells $\sigma_i(D_i, f_i, \mathrm{Or}_i)$ in $\sigma$. $\sigma_i(D_i, f_i, \mathrm{Or}_i)$ is given by

1. The $(k-1)$-dimensional face $D_i \subset D$
2. The mapping $f : D \to M$ restricted to $D_i$
3. Orientation $\mathrm{Or}_i$

The boundary of the chain is

$$\partial c_k = \partial(m_1\sigma_1 + \cdots + m_r\sigma_r) = m_1\partial\sigma_1 + \cdots + m_r\partial\sigma_r$$




Boundary of a chain (Arnold 186)

Note that the "overlapping sides" cancel out, so we're only left with the boundary. We can also note that the boundary of a boundary of a chain is 0: $\partial\partial c_k = 0$. Intuitively, it's because the boundary is like a line, so how do we find the boundary of that?

---

Let $\omega^k$ be a $k$-form on $M$, and $c_k = \sum m_i \sigma_i$ a $k$-chain on $M$. The integral of the form $\omega^k$ over the chain $c_k$ is the sum

$$\int_{c_k} \omega^k = \sum m_i \int_{\sigma_i} \omega^k$$

The integral of the form $\omega = p\,dq$ over a chain $c$ representing the boundary of a region is equal to the area of the region. Easiest to see this with a diagram on the $(p, q)$-plane. Signs may differ depending on orientation.

$$\int_c p\,dq = \text{Area enclosed by } c$$

Let $M$ be the oriented space $\mathbb{R}^3$. Every 1-form and 2-form on $M$ correspond to a vector field **A** such that

$$\omega^1_{\mathbf{A}}(\xi) = \mathbf{A}\xi$$
$$\omega^2_{\mathbf{A}}(\xi, \eta) = \eta^T \mathbf{A}\xi$$

- The integral of $\omega^1_{\mathbf{A}}$ on a chain $c_1$ (a curve $l$) is the **circulation of the field A over the curve** $l$.

$$\int_{c_1} \omega^1_{\mathbf{A}} = \int_l \mathbf{A}\,dl$$

- The integral of $\omega^2_{\mathbf{A}}$ on a chain $c_2$ (oriented surface $S$) is the **flux of the field A through the surface** $S$.

$$\int_{c_2} \omega^2_{\mathbf{A}} = \int_S \mathbf{A} \cdot d\mathbf{n}$$

So the concept of a $k$-form can be used to generalize the characteristics of vector fields.

## 7.5 Exterior Differentiation

### 7.5.1 Exterior Derivative




Curvilinar parallelepiped $\Pi$ (Arnold 189)

Consider a manifold $M$ with a curvilinar parallelepiped $\Pi$. Let $\mathbf{x}$ be a point on $M$ with $k+1$ tangent vectors $\xi_1, \ldots, \xi_{k+1}$. The pre-images of those vectors under $f$ lie in the tangent space $\mathbb{R}^n$ at 0 (which maps to $\mathbf{x}$).

$$\xi_1^*, \ldots, \xi_{k+1}^* \in \mathbb{R}^n$$

The map $f$ takes these vectors to the sides of the $(k+1)$-dimensional cell on $M$. The boundary of that cell $\Pi$ is $\partial\Pi$.

The integral over the boundary of a $(k+1)$-dimensional cell is an exterior $(k+1)$-form on the tangent space $TM_{\mathbf{x}}$ to $M$ at $\mathbf{x}$. This form is called the **exterior derivative/differential** of the form $\omega^k$ at $\mathbf{x}$, and is denoted

$$d\omega^k = \int_{\partial\Pi} \omega^k$$

---

If the local coordinate system is $x_1, \ldots, x_n$ on $M$, the form is

$$\omega^k = \sum a_{i_1,\ldots,i_k}\, dx_{i_1} \wedge \cdots \wedge dx_{i_k}$$
$$d\omega^k = \sum da_{i_1,\ldots,i_k} \wedge dx_{i_1} \wedge \cdots \wedge dx_{i_k}$$

For sums and products,

$$d(\omega_1 + \omega_2) = d\omega_1 + d\omega_2$$
$$d(\omega^k \wedge \omega^l) = d\omega^k \wedge \omega^l + (-1)^k \omega^k \wedge d\omega^l$$

### 7.5.2 Stokes' Formula

Technically the Newton-Leibniz-Gauss-Green-Ostrogradskii-Stokes-Poincaré formula.

$$\boxed{\int_{\partial c} \omega = \int_c d\omega}$$

where $c$ is any $(k+1)$-chain on $M$ and $\omega$ is any $k$-form on $M$.

**Proof:** Consider the case of a single cell $\sigma$, given by an oriented parallelepiped $\Pi \subset \mathbb{R}^{k+1}$. Partition $\Pi$ into $N^{k+1}$ parallelepipeds $\Pi^i$. Then

$$\int_{\partial\Pi} \omega = \sum_{i=1}^{N^k+1} F_i \quad , \quad F_i = \int_{\partial\Pi_i} \omega \approx d\omega(\xi_1^i, \ldots, \xi_{k+1}^i)$$

where $\xi_1^i, \ldots, \xi_{k+1}^i$ are the edges of $\Pi_i$. By geometry,

$$\lim_{N\to\infty} \sum_{i=1}^{N^k+1} F_i = \lim_{N\to\infty} \sum_{i=1}^{N^k+1} d\omega(\xi_1^i, \ldots, \xi_{k+1}^i) = \int_{\Pi} d\omega$$
$$\int_{\partial\Pi} \omega = \int_{\Pi} d\omega$$

The argument can be generalized to any convex polyhedron, by partitioning them into simplices. A $k$-dimensional cube can be mapped onto a $k$-dimensional simplex.

E.g. let $\omega^1$ be the 1-form given by

$$\omega^1 = p_1\, dq_1 + \cdots + p_n\, dq_n = \mathbf{p}\, d\mathbf{q}$$

Then the exterior derivative is

$$d\omega^1 = dp_1 \wedge dq_1 + \cdots + dp_n \wedge dq_n = d\mathbf{p} \wedge d\mathbf{q}$$

Thus

$$\iint_{c_2} d\mathbf{p} \wedge d\mathbf{q} = \int_{\partial c_2} \mathbf{p}\, d\mathbf{q}$$

In 3D Riemannian space, every vector field $\mathbf{A}$ corresponds to a 1-form $\omega^1_{\mathbf{A}}$ and a 2-form $\omega^2_{\mathbf{A}}$. 0-forms are the functions themselves. Exterior differentiation of the 3 forms correspond to gradient, curl, and divergence:

$$\begin{aligned} df &= \omega^1_{\mathbf{grad}\ f} \\ d\omega^1_{\mathbf{A}} &= \omega^2_{\mathbf{curl}\ \mathbf{A}} \\ d\omega^2_{\mathbf{A}} &= (\text{div } \mathbf{A})\omega^3 \end{aligned}$$

Then

$$f(y) - f(x) = \int_l \mathbf{grad}\ f\ d\mathbf{l} \qquad (\partial l = y - x)$$

$$\int_l \mathbf{A}\ d\mathbf{l} = \iint_S \mathbf{curl}\ \mathbf{A} \cdot d\mathbf{n} \qquad (\partial S = l)$$

$$\iint_S \mathbf{A}\ d\mathbf{n} = \iiint_D (\text{div } \mathbf{A})\omega^3 \qquad (\partial D = S)$$

# 8 Symplectic Manifolds (p. 201 – 232)

## 8.1 Symplectic Structure on Manifolds

Let $M^{2n}$ be an even-dimensional differentiable manifold. A **symplectic structure** on $M^{2n}$ is a closed, nondegenerate, differential 2-form $\omega^2$ on $M^{2n}$.

| |
|---|
| 1) $d\omega^2 = 0$ |
| 2) For all $\xi \neq 0$, there exists $\eta$ such that $\omega^2(\xi, \eta) \neq 0$. Here $\xi, \eta \in TM_{\mathbf{x}}$ |

$(M^{2n}, \omega^2)$ is the **symplectic manifold**. For example, if $\mathbb{R}^{2n}$ has coordinates $p_i, q_i$, let $\omega^2 = \sum dp_i \wedge dq_i$. Then $(\mathbb{R}^{2n}, \omega^2)$ is a symplectic manifold. For $n = 1$, this is $(\text{plane}, \text{area})$.

Let $V$ be an $n$-dimensional manifold. At a point $\mathbf{x} \in V$, we have a tangent space $TV_{\mathbf{x}}$. A 1-form on $TV_{\mathbf{x}}$ is called a **cotangent vector to $V$ at $\mathbf{x}$**. This takes the $n$-dimensional tangent vectors in $TV$ to $V$. The set of all cotangent vectors to $V$ at $\mathbf{x}$ forms an $n$-dimensional vector space $T^*V_{\mathbf{x}}$. This is called the **cotangent space to $V$ at $\mathbf{x}$**. It's dual to the tangent space $TV_{\mathbf{x}}$.

The union of all cotangent spaces to $V$ is called the **cotangent bundle of** $V$, denoted $T^*V$. This is a differentiable manifold of dimension $2n$. A point in $T^*V$ is a 1-form acting on the tangent space $TV_{\mathbf{x}}$ at some point $\mathbf{x} \in V$. For example, let $\mathbf{q} \in V$ and $\mathbf{p} \in T^*V$. Then $(\mathbf{p}, \mathbf{q})$ are $2n$ coordinates that describe points in $T^*V$.

The cotangent bundle $T^*V$ has a symplectic structure given by

$$\omega^2 = d\mathbf{p} \wedge d\mathbf{q} = dp_1 \wedge dq_1 + \cdots + dp_n \wedge dq_n$$

For a physics example, consider a Lagrangian system on a manifold $V$ and Lagrangian $L = T - U$. The generalized velocity $\dot{\mathbf{q}}$ is a tangent vector to $V$, and the generalized momentum $\dot{\mathbf{p}} = \partial L / \partial \dot{\mathbf{q}}$ is a 1-form acting on the tangent space, i.e. a cotangent vector. Then the Lagrangian phase space $(\mathbf{p}, \mathbf{q})$ is the cotangent bundle on $V$. The phase space has a symplectic manifold structure.

---

Let $\xi$ be a vector tangent to the symplectic manifold $(M^{2n}, \omega^2)$ at $\mathbf{x}$. To $\xi$, we associate the 1-form $\omega^1_{\mathbf{x}}$ on $TM_{\mathbf{x}}$. This maps a tangent vector on $TM_{\mathbf{x}}$ to $M^{2n}$.

$$\omega^1_\xi(\eta) = \omega^2(\eta, \xi) \quad , \quad \forall \eta \in TM_{\mathbf{x}}$$

Consider $\mathbb{R}^{2n} = (\mathbf{p}, \mathbf{q})$. The mapping $\omega^1_\xi \to \xi$ is the transformation $\mathbb{R}^{2n} \to \mathbb{R}^{2n}$. Denote this transformation with the isomorphism $I : T^*M_{\mathbf{x}} \to TM_{\mathbf{x}}$. In the $(\mathbf{p}, \mathbf{q})$-basis, this has the form

$$I = \begin{pmatrix} 0 & E \\ -E & 0 \end{pmatrix}$$

Let $H$ be a function on the symplectic manifold $M^{2n}$. Then the differential 1-form $dH$ acts on a tangent vector to $M$, so it's in the cotangent space. I.e. $dH \in T^*M_{\mathbf{x}}$. We can get the vector field $I\,dH$ on $M$, and this is called the **Hamiltonian vector field**. $H$ is the **Hamiltonian function**. If $M^{2n} = \mathbb{R}^{2n} = \{(\mathbf{p}, \mathbf{q})\}$, then we get

$$\dot{\mathbf{x}} = I\,dH(\mathbf{x})$$
$$\dot{\mathbf{p}} = -\frac{\partial H}{\partial \mathbf{q}} \quad , \quad \dot{\mathbf{q}} = \frac{\partial H}{\partial \mathbf{p}}$$

$I\,dH$ is the velocity vector of the phase flow.

## 8.2 Hamiltonian Phase Flow

### 8.2.1 Generalization of Liouville's Theorem

Liouville's theorem says that phase flow preserves volume. This is a general case of Hamiltonian phase flow, which preserves the symplectic structure.

Let $(M^{2n}, \omega^2)$ be a symplectic manifold. Let $H : M^{2n} \to \mathbb{R}$ be a function on the manifold. Let $g^t$ be the 1-parameter group of diffeomorphisms $g^t : M^{2n} \to M^{2n}$, where

$$\frac{d}{dt} g^t \mathbf{x} \bigg|_{t=0} = I\,dH(\mathbf{x})$$

$g^t$ is called the **Hamiltonian phase flow** with the **Hamiltonian function** $H$. The Hamiltonian phase flow preserves the symplectic structure:

$$(g^t)^*\omega^2 = \omega^2$$

This reduces to Liouville's theorem (preservation of area) if $n = 1$ and $M^{2n} = \mathbb{R}^2$.

### 8.2.2 Integral Invariants

Let $g : M \to M$ be a differentiable map. A differential $k$-form $\omega$ is called an **integral invariant of** $g$ if

$$\int_{gc} \omega = \int_c \omega$$

That is, the integral of $\omega$ is the same on any $k$-chain $c$ and its image $gc$ under $g$. For example, if $M = \mathbb{R}^2$ and $\omega^2 = dp \wedge dq$ is the area element, $\omega^2$ is an integral invariant of any map $g$ that ensures the Jacobian is 1.

We can see that the form $\omega^2$ giving the symplectic structure is an integral invariant of the Hamiltonian phase flow.

---

A map $g : \mathbb{R}^{2n} \to \mathbb{R}^{2n}$ is called **canonical** if it has $\omega^2$ as an integral invariant. This map is called a **canonical transformation**. The form $\omega^2$ is conserved, and so is $(\omega^2)^k = \omega^2, \omega^4, \omega^6, \ldots$ Consider the symplectic manifold $M^{2n} = \mathbb{R}^{2n} = \{(\mathbf{p}, \mathbf{q})\}$, with symplectic structure $\omega^2 = d\mathbf{p} \wedge d\mathbf{q}$. Then

$$\begin{aligned} \omega^2 &= \sum dp_i \wedge dq_i \\ \omega^{2k} &= \sum_{i_1 < \cdots < i_k} dp_{i_1} \wedge \cdots \wedge dp_{i_k} \wedge dq_{i_1} \wedge \cdots \wedge dq_{i_k} \end{aligned}$$

The integral of $\omega^{2k}$ is the sum of oriented volumes of projections onto the planes $(p_{i_1}, \ldots, p_{i_k}, q_{i_1}, \ldots, q_{i_k})$. Under a canonical transformation, this sum is preserved. So we can say that **canonical transformations preserve phase space volume**.

The Hamiltonian phase flow given by $\dot{\mathbf{p}} = -\partial H/\partial \mathbf{q}$ and $\dot{\mathbf{q}} = \partial H/\partial \mathbf{p}$ are canonical transformations. They preserve phase space volume.

## 8.3 Lie Algebra of Vector Fields

A Lie algebra is a vector space $L$ with a bilinear skew-symmetric operation $L \times L \to L$ that satisfies the Jacobi identity

$$[(A \times B) \times C] + [(B \times C) \times A] + [(C \times A) \times B] = 0$$

The operation $L \times L \to L$ is called the **commutator** and denoted with square brackets. The common example is $[A, B] = AB - BA$.

Let $M$ be a manifold and $\mathbf{A}$ a smooth vector field on $M$. At every $\mathbf{x} \in M$, there's a tangent vector $\mathbf{A}(\mathbf{x}) \in TM_{\mathbf{x}}$. To the vector field $\mathbf{A}$, we associate:

1. **Flow**, or the **1-parameter group of diffeomorphisms** $A^t : M \to M$

$$\left.\frac{d}{dt}\right|_{t=0} A^t\mathbf{x} = \mathbf{A}(\mathbf{x})$$

2. **First-order differential operator** $L_{\mathbf{A}}$. For any function $\varphi : M \to \mathbb{R}$, the derivative in the direction of $\mathbf{A}$ is $L_{\mathbf{A}}\varphi$, defined by

$$(L_{\mathbf{A}}\varphi)(\mathbf{x}) = \left.\frac{d}{dt}\right|_{t=0} \varphi(A^t\mathbf{x})$$

This is called the **Lie derivative**, and it's both linear & satisfies Leibniz's formula.

$$L_{\mathbf{A}}(\lambda_1\varphi_1 + \lambda_2\varphi_2) = \lambda_1 L_{\mathbf{A}}\varphi_1 + \lambda_2 L_{\mathbf{A}}\varphi_2$$
$$L_{\mathbf{A}}(\varphi_1\varphi_2) = \varphi_1 L_{\mathbf{A}}\varphi_2 + \varphi_2 L_{\mathbf{A}}\varphi_1$$

If $(x_1, \ldots, x_n)$ are the local coordinates on $M$, and the vector field is $\mathbf{A}(\mathbf{x}) = (A_1(\mathbf{x}), \ldots, A_n(\mathbf{x}))$, then the flow $A^t$ is given by

$$\dot{x}_1 = A_1(\mathbf{x}) \ , \ \ldots, \ \dot{x}_n = A_n(\mathbf{x})$$

The derivative of a function $\varphi(x_1, \ldots, x_n)$ is

$$L_{\mathbf{A}}\varphi = A_1\frac{\partial\varphi}{\partial x_1} + \cdots + A_n\frac{\partial\varphi}{\partial x_n}$$

Thus the operator has the form

$$L_{\mathbf{A}} = A_1\frac{\partial}{\partial x_1} + \cdots + A_n\frac{\partial}{\partial x_n}$$

---

The **Poisson bracket** or **commutator** of two vectors fields $\mathbf{A}$, $\mathbf{B}$ on a manifold $M$ is the vector field $\mathbf{C}$ for which

$$L_{\mathbf{C}} = L_{\mathbf{B}}L_{\mathbf{A}} - L_{\mathbf{A}}L_{\mathbf{B}}$$

(note: some authors use opposite signs.) The field $\mathbf{C}$ is denoted

$$\mathbf{C} = [\mathbf{A}, \mathbf{B}]$$

The Poisson bracket makes the vector space on a manifold $M$ a valid Lie algebra. It's both linear and skew-symmetric. Additionally, it satisfies the Jacobi identity. We have (where $[\mathbf{A}, \mathbf{B}] = \mathbf{A} \times \mathbf{B}$)

$$L_{[[\mathbf{A},\mathbf{B}],\mathbf{C}]} = L_{\mathbf{C}}L_{[\mathbf{A},\mathbf{B}]} - L_{[\mathbf{A},\mathbf{B}]}L_{\mathbf{C}} = L_{\mathbf{C}}L_{\mathbf{B}}L_{\mathbf{A}} - L_{\mathbf{C}}L_{\mathbf{A}}L_{\mathbf{B}} + L_{\mathbf{A}}L_{\mathbf{B}}L_{\mathbf{C}} - L_{\mathbf{B}}L_{\mathbf{A}}L_{\mathbf{C}}$$
$$L_{[[\mathbf{B},\mathbf{C}],\mathbf{A}]} = L_{\mathbf{A}}L_{[\mathbf{B},\mathbf{C}]} - L_{[\mathbf{B},\mathbf{C}]}L_{\mathbf{A}} = L_{\mathbf{A}}L_{\mathbf{C}}L_{\mathbf{B}} - L_{\mathbf{A}}L_{\mathbf{B}}L_{\mathbf{C}} + L_{\mathbf{B}}L_{\mathbf{C}}L_{\mathbf{A}} - L_{\mathbf{C}}L_{\mathbf{B}}L_{\mathbf{A}}$$
$$L_{[[\mathbf{C},\mathbf{A}],\mathbf{B}]} = L_{\mathbf{B}}L_{[\mathbf{C},\mathbf{A}]} - L_{[\mathbf{C},\mathbf{A}]}L_{\mathbf{B}} = L_{\mathbf{B}}L_{\mathbf{A}}L_{\mathbf{C}} - L_{\mathbf{B}}L_{\mathbf{C}}L_{\mathbf{A}} + L_{\mathbf{C}}L_{\mathbf{A}}L_{\mathbf{B}} - L_{\mathbf{A}}L_{\mathbf{C}}L_{\mathbf{B}}$$
$$L_{[[\mathbf{A},\mathbf{B}],\mathbf{C}]} + L_{[[\mathbf{B},\mathbf{C}],\mathbf{A}]} + L_{[[\mathbf{C},\mathbf{A}],\mathbf{B}]} = 0$$

The two flows $A^t$ and $B^s$ commute iff. the Poisson bracket of the corresponding vector fields $\mathbf{A}$, $\mathbf{B}$ is zero (remember, these are the velocity vectors).

$$A^tB^s = B^sA^t \iff [\mathbf{A}, \mathbf{B}] = 0$$

## 8.4 Lie Algebra of Hamiltonian Functions

Let $(M^{2n}, \omega^2)$ be a symplectic manifold. Let $H : M^{2n} \to \mathbb{R}$ be a function on the symplectic manifold. There corresponds to this function a 1-parameter group of canonical transformations $g_H^t : M^{2n} \to M^{2n}$ that leaves the phase volume constant. Let $F : M^{2n} \to \mathbb{R}$ be another function on $M^{2n}$.

The Poisson bracket $(F, H)$ of $F$ on $H$ on a symplectic manifold is the derivative of $F$ in the direction of phase flow with Hamiltonian function $H$.

$$(F, H)(x) = \left.\frac{d}{dt}\right|_{t=0} F(g_H^t(x))$$

---

**Theorem (generalization of Noether's theorem):** If a Hamiltonian function $H$ on a symplectic manifold $(M^{2n}, \omega^2)$ admits the 1-parameter group of canonical transformations given by a Hamiltonian $F$, then $F$ is a first integral of the system with Hamiltonian function $H$.

**Proof:** $H$, as a Hamiltonian function, is a first integral of the flow $g_F^t$, so $(H, F) = 0$. For a Hamiltonian vector space, we have the isomorphism $I$ between 1-forms and vector fields defined by

$$\omega^2(\eta, I\omega^1) = \omega^1(\eta)$$

The velocity vector of the phase flow $g_H^t$ is $I\,dH$, so

$$(F, H) = dF(I\,dH)$$
$$(F, H) = \omega^2(I\,dH, I\,dF)$$

Thus $(H, F) = -(F, H)$, and $(F, H) = 0$. So $F$ is a first integral of the system with Hamiltonian function $H$.

## 8.5 Symplectic Geometry

A **symplectic linear structure** on $\mathbb{R}^{2n}$ is a bilinear skew-symmetric 2-form given in $\mathbb{R}^{2n}$. The form is called the **skew-scalar product**, denoted $[\xi, \eta] = -[\eta, \xi]$. For example, if $(p_1, \ldots, p_n, q_1, \ldots, q_n)$ are coordinate functions on $\mathbb{R}^{2n}$, and $\omega^2$ is given by

$$\omega^2 = p_1 \wedge q_1 + \cdots + p_n \wedge q_n$$

this is a skew-scalar product: $[\xi, \eta] = \omega^2(\xi, \eta)$. $\omega^2$ here is the **standard symplectic structure** for $\mathbb{R}^{2n} = \{(\mathbf{p}, \mathbf{q})\}$. It gives the sum of the oriented area of $(\xi, \eta)$ projected onto the $(p_i, q_i)$-planes.

$\mathbb{R}^{2n}$, along with the symplectic structure $[\ ,\ ]$, is called a **symplectic vector space**.

---

A **symplectic basis** is a set of $2n$ vectors $\mathbf{e}_{p_i}, \mathbf{e}_{q_i}$ which satisfy the following relations:

$$[\mathbf{e}_{p_i}, \mathbf{e}_{p_j}] = [\mathbf{e}_{p_i}, \mathbf{e}_{q_j}] = [\mathbf{e}_{q_i}, \mathbf{e}_{q_j}] = 0$$
$$[\mathbf{e}_{p_i}, \mathbf{e}_{q_i}] = 1$$

This is just like a basis in the Euclidean sense, except each basis vector from $p$ is associated with another from $q$ and vice versa, rather than only to itself.

---

A linear transformation $S : \mathbb{R}^{2n} \to \mathbb{R}^{2n}$ of the symplectic space to itself is a **symplectic transformation** if it preserves the skew-scalar product.

$$[S\xi, S\eta] = [\xi, \eta] \quad , \quad \forall \xi, \eta \in \mathbb{R}^{2n}$$

The set of all symplectic transformations of $\mathbb{R}^{2n}$ is the **symplectic group**, denoted $Sp(2n)$.

---

To impose a Euclidean structure on the symplectic space, fix the coordinates $(\mathbf{p}, \mathbf{q})$. Introduce the Euclidean structure via the dot product

$$\mathbf{x} \cdot \mathbf{x} = \sum p_i^2 + q_i^2 \quad , \quad \mathbf{x} = \sum p_i \mathbf{e}_{p_i} + q_i \mathbf{e}_{q_i}$$

Clearly $\mathbf{e_p}, \mathbf{e_q}$ are orthonormal. Express the skew-scalar product in terms of a dot product:

$$[\xi, \eta] = \omega^2(\xi, \eta) = I\xi \cdot \eta$$

where $I : \mathbb{R}^{2n} \to \mathbb{R}^{2n}$. Since the skew-scalar product is, well, skew-symmetric, $I$ must also be skew-symmetric. In the $(\mathbf{e_p}, \mathbf{e_q})$-basis, it has the following form, where $I_n$ is the $n$-dimensional identity matrix.

$$I = \begin{pmatrix} 0 & -I_n \\ I_n & 0 \end{pmatrix}$$

Note that $I^2 = -I_{2n}$. Thus, we can also introduce a complex structure on top of our existing symplectic structure $[\ ,\ ]$ and Euclidean structure $(\ \cdot\ )$. This is done by defining the action of $I$ to be $i = \sqrt{-1}$. To recap,

1. Transformations of $\mathbb{R}^{2n}$ preserving the Euclidean structure form the **orthonormal group** $O(2n)$.
2. Transformations of $\mathbb{R}^{2n}$ preserving the complex structure form the **complex linear group** $GL(n, \mathbb{C})$.
3. Transformations of $\mathbb{R}^{2n}$ preserving the symplectic structure form the **symplectic group** $Sp(2n)$.

## 8.6 Parametric Resonance

In the Lagrangian section, we studied parametric resonance of systems with periodically varying parameters. The transformation $A$ was stable if $|\text{tr}(A)| < 2$ and unstable if $|\text{tr}(A)| > 2$. Specifically, if all eigenvalues of $A$ had modulus less than 1, the transformation was stable.

Here we analyze the eigenvalues of symplectic transformations. Let $S : \mathbb{R}^{2n} \to \mathbb{R}^{2n}$ be a transformation of symplectic space. Let $(p_1, \ldots, p_n, q_1, \ldots, q_n)$ be a symplectic coordinate system. $S$ is symplectic iff. it satisfies

$$S^T I S = I \quad , \quad I = \begin{pmatrix} 0 & -I_n \\ I_n & 0 \end{pmatrix}$$

**Proof:** The condition for being a symplectic transformation was to *preserve the symplectic structure*, i.e. $[\xi, \eta] = [S\xi, S\eta]$. In the $(\mathbf{e_p}, \mathbf{e_q})$-basis, we have

$$\begin{aligned}
&1.\ [S\xi, S\eta] = IS\xi \cdot S\eta = S^T IS\xi \cdot \eta \\
&2.\ [S\xi, S\eta] = [\xi, \eta] = I\xi \cdot \eta \\
&\quad \rightarrow\ S^T IS = I
\end{aligned}$$

**Theorem:** The characteristic polynomial of a symplectic transformation is reflexive, i.e.

$$\begin{aligned}
p(\lambda) &= \det(S - \lambda I_n) \\
p(\lambda) &= \lambda^{2n} p(1/\lambda)
\end{aligned}$$

**Proof:** Use $\det S = 1$ from above, $I^2 = -I_n$, and $S = -I(S^T)^{-1}I$. Then

$$\begin{aligned}
p(\lambda) &= \det(-I(S^T)^{-1}I - \lambda I_n) \\
&= \det(-(S^T)^{-1} + \lambda S) \\
&= \lambda^{2n} \det\left(S - \frac{1}{\lambda} I_n\right) = \lambda^{2n} p\left(\frac{1}{\lambda}\right)
\end{aligned}$$

Thus, if $\lambda, \bar{\lambda}$ are eigenvalues of the symplectic transformation $S$, then $1/\lambda, 1/\bar{\lambda}$ are also eigenvalues. The transformation $S$ is **stable** if

$$\forall \varepsilon > 0, \exists \delta > 0, \forall N > 0 : |\mathbf{x}| < \delta \implies |S^N \mathbf{x}| < \varepsilon$$

If all eigenvalues lie on the unit circle, all good. Otherwise, for some value of $N$, $S$ will become unstable. This is the same result as from the Lagrangian section.

But there's an interesting case where eigenvalues can *collide* with each other. If, for example, they start to overlap due to a small change in $S$. M. G. Krein found that if eigenvalues with the same sign collide, the roots stay on the unit circle (stable). If roots with opposite signs collide, they tend to leave the unit circle (unstable).

## 8.7 Darboux's Theorem

An atlas of a manifold $M^{2n}$ is a **symplectic atlas** if the standard symplectic structure $\omega^2 = d\mathbf{p} \wedge d\mathbf{q}$ is introduced onto $\mathbb{R}^{2n} = \{(\mathbf{p}, \mathbf{q})\}$, and a transfer from one chart to another is achieved by a canonical transformation $\varphi_i^{-1}\varphi_j$. By canonical, we mean it preserves the symplectic structure $\omega^2$.

**Theorem (Darboux's Theorem):** Let $\omega^2$ be a closed differential 2-form, i.e. $d\omega^2 = 0$, in a neighborhood of $\mathbf{x} \in \mathbb{R}^{2n}$. In some neighborhood of $\mathbf{x}$, we can choose a coordinate system $(p_1, \ldots, p_n, q_1, \ldots, q_n)$ such that the form has the standard form

$$\omega^2 = \sum_{i=1}^{n} dp_i \wedge dq_i$$

This means that on symplectic manifolds, local characteristics are invariant w.r.t canonical transformations.

# 9 Canonical Formalism (p. 233 – 270)

## 9.1 Integral Invariant of Poincaré-Cartan

### 9.1.1 Stokes' Theorem in 3 Dimensions

Let $\mathbf{v}$ be a 3D vector space and $\mathbf{r} = \operatorname{curl} \mathbf{v}$ be the curl. The integral of $\mathbf{r}$ are the **vortex lines**. Let $\gamma_1, \gamma_2$ be two closed curves in $\mathbb{R}^3$, so that $\gamma_1 - \gamma_2 = \partial\sigma$, where $\sigma$ is a vortex tube. Then $\mathbf{v}$ has equal circulation along $\gamma_1$ and $\gamma_2$.

$$\oint_{\gamma_1} \mathbf{v}\, d\mathbf{l} = \oint_{\gamma_2} \mathbf{v}\, d\mathbf{l}$$

**Proof:** Note that $\operatorname{curl} \mathbf{v}$ is tangent to the vortex tube. By Stokes' theorem,

$$\oint_{\gamma_1} \mathbf{v}\, d\mathbf{l} - \oint_{\gamma_2} \mathbf{v}\, d\mathbf{l} = \iint_{\sigma} \operatorname{curl} \mathbf{v}\, d\mathbf{n} = 0$$




Vortex tubes (Arnold 234)

### 9.1.2 Stokes' Theorem in $n$ Dimensions

Stokes' theorem can generalize to any odd dimensional manifold $M^{2n+1}$, not just $\mathbb{R}^3$. To do this, we need to replace the vector field $\mathbf{v}$ with differential forms.

The circulation of $\mathbf{v}$ is replaced with the integral of the 1-form $\omega^1$. The curl of $\mathbf{v}$ is replaced with the 2-form $\omega^2 = d\omega^1$.

**Theorem (multi-dimensional Stokes' theorem):** The integrals of a 1-form $\omega^1$ along the curves $\gamma_1, \gamma_2$ enclosing the same vortex tube are equal.

$$\oint_{\gamma_1} \omega^1 = \oint_{\gamma_2} \omega^1$$

**Proof:** By Stokes' theorem,

$$\oint_{\gamma_1} \omega^1 - \oint_{\gamma_2} \omega^1 = \int_{\partial\sigma} \omega^1 = \int_{\sigma} d\omega^1 = 0$$

### 9.1.3 Hamilton's Equations

Think of Hamiltonian phase space as a fluid, and the canonical transformations as the equations by which the fluid moves.

**Theorem:** Consider the odd-dimensional phase space $\mathbb{R}^{2n+1}$ with coordinates $(p_1, \ldots, p_n, q_1, \ldots, q_n, t)$. Let $H$ be the Hamiltonian function $H(\mathbf{p}, \mathbf{q}, t)$. Construct the 1-form

$$\omega^1 = \mathbf{p}\, d\mathbf{q} - H\, dt$$

Vortex lines of this form are trajectories of the phase flow, and satisfy the canonical equations:

$$\frac{d\mathbf{p}}{dt} = -\frac{\partial H}{\partial \mathbf{q}}\ , \quad \frac{d\mathbf{q}}{dt} = \frac{\partial H}{\partial \mathbf{p}}$$




Hamiltonian phase flow (Arnold 236)

In terms of Stokes' theorem, this is

$$\oint_{\gamma_1} \mathbf{p}\, d\mathbf{q} - H\, dt = \oint_{\gamma_2} \mathbf{p}\, d\mathbf{q} - H\, dt$$

The form $\mathbf{p}\, d\mathbf{q} - H\, dt$ is the **integral invariant of Poincaré-Cartan**. The form $\mathbf{p}\, d\mathbf{q}$ is the **Poincaré's relative integral invariant**. This is invariant under phase flow, i.e. transformations $g^t : \mathbb{R}^{2n} \to \mathbb{R}^{2n}$ that satisfy Hamilton's canonical equations. If we rewrite $\mathbf{p}\, d\mathbf{q}$,

$$\oint_{\gamma} \mathbf{p}\, d\mathbf{q} = \iint_{\sigma} d\mathbf{p} \wedge d\mathbf{q} = \textit{const.}$$

Then it means that the oriented area is preserved under a canonical transformation: Liouville's theorem.

---

Let $\mathbb{R}^{2n} = \{(\mathbf{p}, \mathbf{q})\}$ be an even-dimensional space. Let $g$ be a transformation, $g : \mathbb{R}^{2n} \to \mathbb{R}^{2n}$. From all we have so far, we can see that $g$ is a canonical transformation if any of the following hold:

1. $g$ preserves the 2-form $\omega^2 = d\omega^1 = \sum dp_i \wedge dq_i$.
2. $g$ preserves the area of the projection on a surface: $\iint_\sigma \omega^2 = \iint_{g\sigma} \omega^2$.
3. $\mathbf{p}\, d\mathbf{q}$ is a relative integral invariant of $g$: $\oint_\gamma \mathbf{p}\, d\mathbf{q} = \oint_{g\gamma} \mathbf{p}\, d\mathbf{q}$.

### 9.1.4 Applications

Since the Hamiltonian and Lagrangian are Legendre transforms of each other, we have

$$\int_{t_0}^{t_1} L\, dt = \int_{t_0}^{t_1} (\mathbf{p}\dot{\mathbf{q}} - H)\, dt = \int_{t_0,\mathbf{q}_0}^{t_1,\mathbf{q}_1} \mathbf{p}\, d\mathbf{q} - H\, dt$$

So Lagrange's principle of least action can carry over to the Hamiltonian formalism. Specifically, the integral $\int \mathbf{p}\, d\mathbf{q} - H\, dt$ under a path $\gamma$ has an extremal under variations of $\gamma$: a function $\mathbf{p}\, d\mathbf{q} - H\, dt$ which maximizes/minimizes the integral. Of course, the endpoints $(t_0, \mathbf{q}_0)$ and $(t_1, \mathbf{q}_1)$ must remain the same.

---

If the Hamiltonian doesn't depend on time, then the integral $\int \mathbf{p}\, d\mathbf{q}$ lying on the manifold $M^{2n-1}$ (previously $M^{2n+1}$ for $2n$ momentum/position coordinates and 1 time coordinate) has an extremal for a given path $\gamma$. We've reduced 2 dimensions.

Let $\gamma(\tau)$ be a curve connecting $\mathbf{q}_0$ and $\mathbf{q}_1$ on the $\mathbf{q}$-plane. Let $H$ be the Hamiltonian, parametrized such that it's constant: $H(\partial L/\partial\dot{\mathbf{q}}, \mathbf{q}) = h$. Then the trajectory of the system is an extremal of the integral of **reduced action:**

$$\int_\gamma \mathbf{p}\, d\mathbf{q} = \int_\gamma \mathbf{p}\dot{\mathbf{q}}\, d\tau = \int_\gamma \frac{\partial L(\tau)}{\partial \dot{\mathbf{q}}} \dot{\mathbf{q}}(\tau)\, d\tau$$

Consider a point mass constrained on a smooth Riemannian manifold. According to Hamilton and Lagrange, this will move along the geodesic lines, i.e. extremals of the length $\int ds$. To see this, note that if there's no potential energy,

$$H = L = T = \frac{1}{2}\left(\frac{ds}{d\tau}\right)^2$$
$$\frac{\partial L}{\partial \dot{\mathbf{q}}}\dot{\mathbf{q}} = \frac{ds}{d\tau} \cdot \frac{ds}{d\tau} = \left(\frac{ds}{d\tau}\right)^2$$

To guarantee a fixed value of $H = h$, we parametrize as $d\tau = ds/\sqrt{2h}$. Then the integral of reduced action is

$$\int_\gamma \frac{\partial L}{\partial \dot{\mathbf{q}}}\dot{\mathbf{q}}\, d\tau = \int_\gamma 2h \cdot \frac{ds}{\sqrt{2h}} = \sqrt{2h}\int_\gamma ds$$

which is a geodesic, minimizing the total path traveled.

---

If there *is* potential energy (i.e. multiple interacting particles), the same principle still applies. But the Riemannian metric is different. Let $ds^2$ be the Riemannian metric that gives the kinetic energy, $T = \frac{1}{2}(ds/d\tau)^2$. Let the parametrization be such that the Hamiltonian is constant: $H = h$. Then if $U(\mathbf{q}) < h$, define the Riemannian metric

$$d\rho = \sqrt{h - U(\mathbf{q})}\, ds$$

The geodesic $\int d\rho$ defines the trajectory of the system with kinetic energy $T = \frac{1}{2}(ds/d\tau)^2$, potential energy $U(\mathbf{q})$, and total energy $h$.

**Proof:** Using the fact that $H = T + U$, we see that $T = h - U$, so based on the previous case,

$$\left(\frac{\partial L}{\partial \dot{\mathbf{q}}}\right)\dot{\mathbf{q}} = \left(\frac{ds}{d\tau}\right)^2 = 2(h-U)$$

Then to guarantee a constant $H = h$, parametrize as $d\tau = ds/\sqrt{2(h-U)}$. The reduced integral of action becomes

$$\int_\gamma \frac{\partial L}{\partial \dot{\mathbf{q}}}\dot{\mathbf{q}}\, d\tau = \int_\gamma 2(h-U)\cdot\frac{ds}{\sqrt{2(h-U)}} = \sqrt{2}\int_\gamma d\rho$$

So trajectories are geodesics of Riemannian space with the metric $d\rho$. Distances in the metric $d\rho$ are different from those in $ds$, but angles are the same.

## 9.2 Huygen's Principle

According to Fermat's principle, light travels from $\mathbf{q}_0$ to $\mathbf{q}_1$ in the **shortest possible time**. This could depend on the point $\mathbf{q}$ (inhomogeneous medium) or the direction of the light ray (anisotropic medium). For now, consider a homogeneous, isotropic medium.

Let $\Phi_{\mathbf{q}_0}(t)$ be the set of points that light reaches in time $t$. This is called the wavefront of $\mathbf{q}_0$ after time $t$.

**Theorem (Huygen's principle):** Let $\Phi_{\mathbf{q}_0}(t)$ be the wavefront of $\mathbf{q}_0$ after time $t$. For every point $\mathbf{q} \in \Phi_{\mathbf{q}_0}(t)$, let $\Phi_{\mathbf{q}}(s)$ be the wavefront after time $s$. The wavefront of $\mathbf{q}_0$ after time $s+t$ is the envelope of the fronts $\Phi_{\mathbf{q}}(s)$, for all $\mathbf{q} \in \Phi_{\mathbf{q}_0}(t)$.

Each wavefront acts as the origin of a secondary wavefront. This explains effects like diffraction, interference, etc.




Huygen's principle (Arnold 249)

We can get clever and apply this optical reasoning to mechanics. The trajectories of motion, like wavefronts, are extremals. They're just in higher dimensions. Here's a table from Arnold that shows this comparison:

| Optics | Mechanics |
|---|---|
| Optical medium | Configuration space $\{(\mathbf{q}, t)\}$ |
| Fermat's principle | Hamilton's principle $\delta \int L\, dt = 0$ |
| Rays | Trajectories $\mathbf{q}(t)$ |
| Wavefront normal vector $\mathbf{p}$ | Momentum $\mathbf{p}$ |
| Expressing $\mathbf{p}$ in terms of ray velocity $\dot{\mathbf{q}}$ | Legendre transformation |
| 1-form $\mathbf{p}\, d\mathbf{q}$ | 1-form $\mathbf{p}\, d\mathbf{q} - H\, dt$ |

### 9.2.1 Action Function

**Theorem:** Define the action function as

$$S_{\mathbf{q}_0, t_0}(\mathbf{q}, t) = \int_\gamma L\, dt$$

The differential of the action function is equal to

$$dS = \mathbf{p}\, d\mathbf{q} - H\, dt$$

where $\mathbf{p} = \partial L / \partial \dot{\mathbf{q}}$ and $H = \mathbf{p}\dot{\mathbf{q}} - L$. Here, $\dot{\mathbf{q}}$ is the velocity of the trajectory $\gamma$.

**Proof:** Lift every extremal from $(\mathbf{q}, t)$-space to the phase space $\{(\mathbf{p}, \mathbf{q}, t)\}$. We set $\mathbf{p} = \partial L / \partial \dot{\mathbf{q}}$. Now shift the endpoint $(\mathbf{q}, t)$ slightly by $(\Delta\mathbf{q}, \Delta t)$.




Shifting the endpoint (Arnold 254)

$\sigma$ consists of characteristic curves of the form $\mathbf{p}\, d\mathbf{q} - H\, dt$. Thus,

$$\begin{aligned} 0 = \iint_\sigma d(\mathbf{p}\, d\mathbf{q} - H\, dt) &= \int_{\partial\sigma} \mathbf{p}\, d\mathbf{q} - H\, dt \\ &= \int_{\gamma_1} - \int_{\gamma_2} + \int_\beta - \int_\alpha \mathbf{p}\, d\mathbf{q} - H\, dt \\ &= \int_{\gamma_1} - \int_{\gamma_2} + \int_\beta \mathbf{p}\, d\mathbf{q} - H\, dt \end{aligned}$$

since $d\mathbf{q} = dt = 0$ on $\alpha$. We know that $\gamma_1, \gamma_2$ are phase trajectories, so $\mathbf{p}\, d\mathbf{q} - H\, dt = L\, dt$. Then to satisfy the equation, we must have

$$\begin{aligned} \int_\beta \mathbf{p}\, d\mathbf{q} - H\, dt &= S(\mathbf{q} + \Delta\mathbf{q}, t + \Delta t) - S(\mathbf{q}, t) \\ &\approx \mathbf{p}\Delta\mathbf{q} - H\Delta t \qquad (\Delta\mathbf{q}, \Delta t \to 0) \end{aligned}$$

Thus

$$dS = \mathbf{p}\, d\mathbf{q} - H\, dt$$

### 9.2.2 Hamilton-Jacobi Equation

**Theorem:** The action function satisfies the equation

$$\frac{\partial S}{\partial t} + H\left(\frac{\partial S}{\partial \mathbf{q}}, \mathbf{q}, t\right) = 0$$

**Proof:** Note that from the previous theorem,

$$\begin{aligned} \frac{\partial S}{\partial t} &= -H(\mathbf{p}, \mathbf{q}, t) \\ \frac{\partial S}{\partial \mathbf{q}} &= \mathbf{p} \end{aligned}$$

This equation interprets the motion of a particle as a wave. In that sense, it's closer to modern theories like quantum mechanics than Hamiltonian or Lagrangian mechanics.