

Algorithmic interpretations of fractal dimension

Anastasios Sidiropoulos (The Ohio State University)

Vijay Sridhar (The Ohio State University)

The curse of dimensionality



- ▶ Geometric problems become harder when dimension increases.

The curse of dimensionality

- ▶ Geometric problems become harder when dimension increases.
- ▶ Several notions of dimension in computational geometry:
 - ▶ Euclidean dimension
 - ▶ Doubling dimension
 - ▶ Rate of growth
 - ▶ Highway dimension

How does **fractal dimension** affect algorithmic complexity?

Fractals




Fractal dimension

Several notions of fractal dimension:

- ▶ Hausdorff dimension
- ▶ Minkowski dimension
- ▶ Box-counting dimension
- ▶ ...

Example: Koch curve

length = ∞
area = 0



Fractal dimension and volume

Fractal dimension δ :

Scaling by a factor of $r > 0$ increases the total “volume” by a factor of roughly r^δ .

Fractal dimension and volume


Fractal dimension δ :

Scaling by a factor of $r > 0$ increases the total “volume” by a factor of roughly r^δ .

Example: Sierpinski carpet

Scaling by a factor of 3 increases the volume by a factor of 8

$$\delta = \log_3 8$$



Hausdorff dimension

Let $X \subseteq \mathbb{R}^d$.

δ -dimensional Hausdorff content:

$$C_H^\delta(X) = \inf \left\{ \sum_{i \in I} r_i^\delta : \exists \text{ countable cover of } X \text{ with radii } r_i \right\}$$

Hausdorff dimension:

$$\dim_H(X) = \inf \{ \delta \geq 0 : C_H^\delta(X) = 0 \}$$

What about discrete sets?

- ▶ Most definitions of fractal dimension are *meaningless* for countable sets.
- ▶ E.g.

$$\dim_{\mathrm{H}}(\mathbb{Q} \times \mathbb{Q}) = 0$$

and for all $X \subset \mathbb{R}^2$, $Y \subset \mathbb{Q}^2$,

$$\dim_{\mathrm{H}}(X \cup Y) = \dim_{\mathrm{H}}(X)$$

A definition for discrete spaces

Let $M = (X, \rho)$ be a metric space, $|X| = n$.

We define $\dim_f(X) = \delta$ if δ is the infimum number s.t.

for all $\varepsilon > 0$, $R \geq 2\varepsilon$, for all $x \in \mathbb{R}^2$, for all ε -nets N of X

$$|\text{Ball}(x, R) \cap N| = O((R/\varepsilon)^\delta)$$

A definition for discrete spaces


Let $M = (X, \rho)$ be a metric space, $|X| = n$.

We define $\dim_f(X) = \delta$ if δ is the infimum number s.t.

for all $\varepsilon > 0$, $R \geq 2\varepsilon$, for all $x \in \mathbb{R}^2$, for all ε -nets N of X

$$|\text{Ball}(x, R) \cap N| = O((R/\varepsilon)^\delta)$$

ε -net: maximal $N \subseteq X$ s.t. for all $x \neq y \in N$, $\rho(x, y) > \varepsilon$.



Examples

- ▶ For any $X \subset \mathbb{R}^d$, $\dim_{\text{f}}(X) \leq d$.

Examples

- ▶ For any $X \subset \mathbb{R}^d$, $\dim_{\text{f}}(X) \leq d$.
- ▶ $\dim_{\text{f}}(\{1, \dots, n^{1/d}\}^d) = d$.

Examples

- ▶ For any $X \subset \mathbb{R}^d$, $\dim_{\text{f}}(X) \leq d$.
- ▶ $\dim_{\text{f}}(\{1, \dots, n^{1/d}\}^d) = d$.
- ▶ Discrete Sierpinski carpet:

$$\dim_{\text{f}} \left(\begin{pmatrix} \circ & \circ & \circ & \circ & \circ & \circ & \circ & \circ & \circ \\ \circ & & \circ & \circ & & \circ & \circ & & \circ \\ \circ & \circ & \circ & \circ & \circ & \circ & \circ & \circ & \circ \\ \circ & \circ & \circ & & & & \circ & \circ & \circ \\ \circ & & \circ & & & & \circ & & \circ \\ \circ & \circ & \circ & & & & \circ & \circ & \circ \\ \circ & \circ & \circ & \circ & \circ & \circ & \circ & \circ & \circ \\ \circ & & \circ & \circ & & \circ & \circ & & \circ \\ \circ & \circ & \circ & \circ & \circ & \circ & \circ & \circ & \circ \end{pmatrix} \right) = \log_3 8$$

Relation to other notions of dimension

- ▶ Similar to **Minkowski / box-counting dimension**.

$$\dim_b(X) = \lim_{\varepsilon \rightarrow 0} \log(I_\varepsilon(X)) / \log(1/\varepsilon)$$

Used in numerical estimations of fractal dimension.
Equivalent for “nice” sets.

Relation to other notions of dimension

- ▶ Similar to **Minkowski / box-counting dimension**.

$$\dim_b(X) = \lim_{\varepsilon \rightarrow 0} \log(I_\varepsilon(X)) / \log(1/\varepsilon)$$

Used in numerical estimations of fractal dimension.

Equivalent for “nice” sets.

- ▶ **Doubling dimension:** $\dim_d(M) = 2^k$, if any ball of radius R can be covered by k balls of radius $R/2$.

Fact:

$$\dim_d(M) = \Theta(\dim_f(M)).$$

Relation to other notions of dimension

- ▶ Similar to **Minkowski / box-counting dimension**.

$$\dim_b(X) = \lim_{\varepsilon \rightarrow 0} \log(I_\varepsilon(X)) / \log(1/\varepsilon)$$

Used in numerical estimations of fractal dimension.

Equivalent for “nice” sets.

- ▶ **Doubling dimension:** $\dim_d(M) = 2^k$, if any ball of radius R can be covered by k balls of radius $R/2$.

Fact:

$$\dim_d(M) = \Theta(\dim_f(M)).$$


- ▶ **Fractal dimension in percolation theory:** Percolation in $\{1, \dots, n^{1/d}\}^d$. Largest connected component has size $O(n^\delta)$.

Traveling Salesperson Problem (TSP)

Given set X of n points in \mathbb{R}^d , find minimum length tour visiting all points in X .

Traveling Salesperson Problem (TSP)

Given set X of n points in \mathbb{R}^d , find minimum length tour visiting all points in X .



Traveling Salesperson Problem (TSP)

State of the art:

- ▶ General metric spaces: $2^{O(n)} n^{O(1)}$ time

Traveling Salesperson Problem (TSP)

State of the art:

- ▶ General metric spaces: $2^{O(n)} n^{O(1)}$ time
- ▶ \mathbb{R}^2 : $2^{O(\sqrt{n})} n^{O(1)}$ time (“square-root” phenomenon)

Traveling Salesperson Problem (TSP)

State of the art:

- ▶ General metric spaces: $2^{O(n)} n^{O(1)}$ time
- ▶ \mathbb{R}^2 : $2^{O(\sqrt{n})} n^{O(1)}$ time (“square-root” phenomenon)
- ▶ \mathbb{R}^d : $2^{O(n^{1-1/d})} n^{O(1)}$ time [Smith and Wormald '98]

Traveling Salesperson Problem (TSP)

State of the art:

- ▶ General metric spaces: $2^{O(n)} n^{O(1)}$ time
- ▶ \mathbb{R}^2 : $2^{O(\sqrt{n})} n^{O(1)}$ time (“square-root” phenomenon)
- ▶ \mathbb{R}^d : $2^{O(n^{1-1/d})} n^{O(1)}$ time [Smith and Wormald '98]
- ▶ \mathbb{R}^d : there is no algorithm with running time $2^{O(n^{1-1/d-\varepsilon})}$, assuming ETH [Marx and S. 2014].

Traveling Salesperson Problem (TSP)

State of the art:

- ▶ General metric spaces: $2^{O(n)} n^{O(1)}$ time
- ▶ \mathbb{R}^2 : $2^{O(\sqrt{n})} n^{O(1)}$ time (“square-root” phenomenon)
- ▶ \mathbb{R}^d : $2^{O(n^{1-1/d})} n^{O(1)}$ time [Smith and Wormald '98]
- ▶ \mathbb{R}^d : there is no algorithm with running time $2^{O(n^{1-1/d-\varepsilon})}$, assuming ETH [Marx and S. 2014].
- ▶ $X \subset \mathbb{R}^{O(1)}$, $\dim_f(X) = \delta > 1$: $2^{O(n^{1-1/\delta} \log n)} n^{O(1)}$ time [S. and Sridhar 2016]

Faster algorithms when $\delta < d$

Why does fractal dimension matter?

NP-hardness of TSP in \mathbb{R}^2 [Papadimitriou '77]




Fig. 4. The skeleton, schematically.

Hard instances have $\dim_f = 2$.

The Smith-Wormald approach

Lemma (Smith and Wormald '98)

There exists an optimal tour W and some axis-parallel rectangle balanced separator that crosses at most $O(\sqrt{n})$ edges in W .

The Smith-Wormald approach

Lemma (Smith and Wormald '98)

There exists an optimal tour W and some axis-parallel rectangle balanced separator that crosses at most $O(\sqrt{n})$ edges in W .



The Smith-Wormald approach

Lemma (Smith and Wormald '98)


There exists an optimal tour W and some axis-parallel rectangle balanced separator that crosses at most $O(\sqrt{n})$ edges in W .



$\dim_f(X) = \delta > 1 \Rightarrow$ sphere separator of size $O(n^{1-1/\delta})$.


Applications in parameterized problems

k -Independent Set of Unit Balls



Applications in parameterized problems

k -Independent Set of Unit Balls




State of the art:

- In \mathbb{R}^d : $n^{O(k^{1-1/d})}$ time [Alber, Fiala 2002], [Marx, S. 2014]

Applications in parameterized problems

k -Independent Set of Unit Balls




State of the art:

- ▶ In \mathbb{R}^d : $n^{O(k^{1-1/d})}$ time [Alber, Fiala 2002], [Marx, S. 2014]
- ▶ No $f(k)n^{o(k^{1-1/d})}$ time algorithm exists, assuming ETH [Marx, S. 2014]

Applications in parameterized problems

k -Independent Set of Unit Balls




State of the art:

- ▶ In \mathbb{R}^d : $n^{O(k^{1-1/d})}$ time [Alber, Fiala 2002], [Marx, S. 2014]
- ▶ No $f(k)n^{o(k^{1-1/d})}$ time algorithm exists, assuming ETH [Marx, S. 2014]
- ▶ In $\mathbb{R}^{O(1)}$ if the set of centers has fractal dimension δ [S., Sridhar 2016]:
 - ▶ $\delta > 1$: $n^{O(k^{1-1/\delta}) + \log n}$ time
 - ▶ $\delta \leq 1$: $n^{O(\log n)}$ time


Applications in approximation schemes

R -Cover



Applications in approximation schemes


R -Cover



- ▶ $(1 + d/\ell)$ -approximation in time $\ell^{2d} n^{O((\ell\sqrt{d})^d)}$
[Hochbaum & Maass '85]

Applications in approximation schemes


R -Cover



- ▶ $(1 + d/\ell)$ -approximation in time $\ell^{2d} n^{O((\ell\sqrt{d})^d)}$
[Hochbaum & Maass '85]
- ▶ $(1 + d/\ell)$ -approximation in time $\ell^{d+\delta} n^{O((\ell\sqrt{d})^\delta)}$
[S. & Sridhar 2016]

Applications in approximation schemes

R -Cover



- ▶ $(1 + d/\ell)$ -approximation in time $\ell^{2d} n^{O((\ell\sqrt{d})^d)}$
[Hochbaum & Maass '85]
- ▶ $(1 + d/\ell)$ -approximation in time $\ell^{d+\delta} n^{O((\ell\sqrt{d})^\delta)}$
[S. & Sridhar 2016]
- ▶ Similar result for R -Packing

Spanners

Metric space (X, ρ)

A **c-spanner** is a graph $G = (X, E)$ s.t. for all $x, y \in X$

$$\rho(x, y) \leq d_G(x, y) \leq c \cdot \rho(x, y)$$

Spanners

Metric space (X, ρ)

A **c-spanner** is a graph $G = (X, E)$ s.t. for all $x, y \in X$

$$\rho(x, y) \leq d_G(x, y) \leq c \cdot \rho(x, y)$$

- ▶ Any set of n points in \mathbb{R}^d admits a $(1 + \varepsilon)$ -spanner of size $n(1/\varepsilon)^{O(d)}$ [Salowe '95], [Vaidya '91]

Spanners

Metric space (X, ρ)

A **c-spanner** is a graph $G = (X, E)$ s.t. for all $x, y \in X$

$$\rho(x, y) \leq d_G(x, y) \leq c \cdot \rho(x, y)$$

- ▶ Any set of n points in \mathbb{R}^d admits a $(1 + \varepsilon)$ -spanner of size $n(1/\varepsilon)^{O(d)}$ [Salowe '95], [Vaidya '91]
- ▶ For set of fractal dimension δ : $(1 + \varepsilon)$ -spanner of size $n(1/\varepsilon)^{O(d)}$ and [S. & Sridhar 2016]
 - ▶ $\delta > 1$: treewidth = $O(n^{1-1/\delta} \log n)$
 - ▶ $\delta = 1$: treewidth = $O(\log^2 n)$
 - ▶ $\delta < 1$: treewidth = $O(\log n)$

Spanners

Metric space (X, ρ)

A **c-spanner** is a graph $G = (X, E)$ s.t. for all $x, y \in X$

$$\rho(x, y) \leq d_G(x, y) \leq c \cdot \rho(x, y)$$

- ▶ Any set of n points in \mathbb{R}^d admits a $(1 + \varepsilon)$ -spanner of size $n(1/\varepsilon)^{O(d)}$ [Salowe '95], [Vaidya '91]
- ▶ For set of fractal dimension δ : $(1 + \varepsilon)$ -spanner of size $n(1/\varepsilon)^{O(d)}$ and [S. & Sridhar 2016]
 - ▶ $\delta > 1$: treewidth = $O(n^{1-1/\delta} \log n)$
 - ▶ $\delta = 1$: treewidth = $O(\log^2 n)$
 - ▶ $\delta < 1$: treewidth = $O(\log n)$

Grid minors vs. integer lattices.

Conclusions

- ▶ First step towards understanding complexity of problems as a function of fractal dimension

Conclusions

- ▶ First step towards understanding complexity of problems as a function of fractal dimension
- ▶ Main theme: Faster algorithms when

fractal dimension $<$ ambient dimension

Conclusions

- ▶ First step towards understanding complexity of problems as a function of fractal dimension
- ▶ Main theme: Faster algorithms when

fractal dimension $<$ ambient dimension

- ▶ Many of these results are nearly-tight, assuming ETH
[S. 2016]

Conclusions

- ▶ First step towards understanding complexity of problems as a function of fractal dimension
- ▶ Main theme: Faster algorithms when

fractal dimension $<$ ambient dimension

- ▶ Many of these results are nearly-tight, assuming ETH
[S. 2016]
- ▶ Many other problems to explore

Conclusions

- ▶ First step towards understanding complexity of problems as a function of fractal dimension
- ▶ Main theme: Faster algorithms when

fractal dimension $<$ ambient dimension

- ▶ Many of these results are nearly-tight, assuming ETH
[S. 2016]
- ▶ Many other problems to explore
- ▶ What about fractal sets in higher dimensions (e.g. \mathbb{R}^n)?