

1. A -> C 통신 ping Test

```
PC>ipconfig

FastEthernet0 Connection:(default port)

    Link-local IPv6 Address.....:
FE80::20C:CFFF:FE86:B99E
    IP Address.....:
192.168.100.100
    Subnet Mask.....:
255.255.255.0
    Default Gateway.....:
192.168.100.254

PC>ping 192.168.200.200

Pinging 192.168.200.200 with 32 bytes of data:

Reply from 192.168.200.200: bytes=32 time=2ms
TTL=125
Reply from 192.168.200.200: bytes=32 time=16ms
TTL=125
Reply from 192.168.200.200: bytes=32 time=10ms
TTL=125
Reply from 192.168.200.200: bytes=32 time=2ms
TTL=125
```

2. VLAN간 통신 V10 -> V20 ping test

```
PC>ping 192.168.150.220

Pinging 192.168.150.220 with 32 bytes of data:

Reply from 192.168.150.220: bytes=32 time=0ms TTL=127
Reply from 192.168.150.220: bytes=32 time=14ms TTL=127
Reply from 192.168.150.220: bytes=32 time=0ms TTL=127
Reply from 192.168.150.220: bytes=32 time=0ms TTL=127

Ping statistics for 192.168.150.220:
    Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
    Approximate round trip times in milli-seconds:
        Minimum = 0ms, Maximum = 14ms, Average = 3ms
```

3. Tunnel 경로 확인

```
PC>tracert 192.168.200.200

Tracing route to 192.168.200.200 over a maximum of 30 hops:

  1  0 ms      1 ms      0 ms      192.168.100.254
  2  2 ms      15 ms     2 ms      10.10.10.20
  3  2 ms      15 ms     2 ms      192.168.200.200

Trace complete.

PC>|
```