

1 / RP2040 + FLASH + BOOT + RESET





DECOUPLING: individual IOVDD / USB / ADC / DVDD pins: VREG 1uF input + output







2 / USB DAUGHTERBOARD + 3V3 POWER

DB1: EXTERNAL C5-JSH assumed: CC 5.1k x2 / TPD4E05U06 ESD / PTC / SMF6.0A TVS.


J1: 1=protected USB power 2=D- 3=D+ 4=GND: 1:1 cable. Main-board F1 retained.


Shield joins GND on DB1. No active sustained-overvoltage disconnect. Mechanical fit provisional.





3 / CLOCK + SENSOR MCU-SIDE ONLY






No module connector or 5V sensor connection. Verify revision and level translation before connection.

4 / 5 ROW x 15 COLUMN MATRIX: COL -> switch -> diode ANODE -> CATHODE -> ROW (COL2ROW)

66 keys: stable references from preferred.keys. Central reservation is NOT A HOLE.



C5-JSH ASSUMED — NOT FOR FABRICATION — sensor and mechanical fit provisional

Sheet: /	
File: keycult66.kicad_sch	
Title: Keycult66 / electrical review draft	
Size: A1	Date: 2026-10-30
KiCad E.D.A. 10.0.7	Rev: DRAFT-D
	Id: 1/1