

## Notes part 7

### Professional C++. Ch. 4. Designing Professional C++ Programs

- Proper design saves time in the long run
- Abstraction and reuse (p. 142-150)
- Performance (p. 150-153)

### Exploring C++20. Ch. 12. Conditions and Logic

- `bool` defaults as `int` in `cout`, `string` if with `format` (p.77)
  - use `std::boolalpha` for `bool` as text string in `cout`
  - does not spill over from function to caller code
  - disable with `std::noboolalpha`
  - use `(int)false` to get numerical value with `format`

```
void testBoolNumerisk() {
    std::cout << std::format("***{:9}***{:14}**\n", border1, border2);
    std::cout << std::format("* {:9} * {:14} *\n", "Bool", "Numerical");
    std::cout << std::format("***{:9}***{:14}**\n", border1, border2);
    std::cout << std::format("* {:9} * {:14} *\n", "true", static_cast<int>(true));
    std::cout << std::format("* {:9} * {:14} *\n", "false", static_cast<int>(false));
    std::cout << std::format("***{:9}***{:14}**\n", border1, border2);
}
```

```
void testBoolAlphaNumerisk() {
    std::cout << std::format("***{:9}***{:14}**\n", border1, border2);
    std::cout << std::format("* {:9} * {:14} *\n", "Bool", "Alphanumerical");
    std::cout << std::format("***{:9}***{:14}**\n", border1, border2);
    std::cout << std::format("* {:9} * {:14} *\n", "true", true);
    std::cout << std::format("* {:9} * {:14} *\n", "false", false);
    std::cout << std::format("***{:9}***{:14}**\n", border1, border2);
}
```

```
void testConditional() {
    std::cout << std::format("***{:9}***{:14}**\n", border1, border2);
    std::cout << std::format("* {:9} * {:14} *\n", "If", "Output");
    std::cout << std::format("***{:9}***{:14}**\n", border1, border2);
    std::cout << std::format("* {:9} * {:14} *\n", "true", (true ? "true" : "(no output)"));
    std::cout << std::format("* {:9} * {:14} *\n", "false", (false ? "false" : "(no output)"));
    std::cout << std::format("* {:9} * {:14} *\n", "42", (42 ? "42" : "(no output)"));
    std::cout << std::format("* {:9} * {:14} *\n", "0", (0 ? "0" : "(no output)"));
    std::cout << std::format("* {:9} * {:14} *\n", "42.4242", (42.42 ? "42.42" : "(no output)"));
    std::cout << std::format("* {:9} * {:14} *\n", "0.0", (0.0 ? "0.0" : "(no output)"));
    std::cout << std::format("* {:9} * {:14} *\n", "-0.0", (-0.0 ? "-0.0" : "(no output)"));
    std::cout << std::format("* {:9} * {:14} *\n", "-1", (-1 ? "true" : "(no output)"));
    std::cout << std::format("* {:9} * {:14} *\n", "'\\0'", ('\\0' ? "\\0" : "(no output)"));
    std::cout << std::format("* {:9} * {:14} *\n", "'\\1'", ('\\1' ? "\\1" : "(no output)"));
    std::cout << std::format("* {:9} * {:14} *\n", "\"1\"", ("1" ? "\"1\"" : "(no output)"));
    std::cout << std::format("* {:9} * {:14} *\n", "\"hello\"", ("hello" ? "\"hello\"" : "(no output)"));
    std::cout << std::format("* {:9} * {:14} *\n", "std::cout", (std::cout ? "std::cout" : "(no output)"));
    std::cout << std::format("* {:9} * {:14} *\n", "cin:", (std::cin ? "cin" : "(no output)"));
    std::cout << std::format("***{:9}***{:14}**\n", border1, border2);
}
```

- in conditional statements *zero values*, *empty strings*, and *invalid streams* are *false*