

# Domain-Specific Languages

Advanced Operating Systems (263-3800-00)

Timothy Roscoe
Thursday 9th December 2010

## Outline



- Introduction
- Interface definition languages
- Hardware interface languages
- Filet-of-Fish
- Hamlet
- References

# The problem



- C is a pain to write OS code in.
- 2 classes of problem:
  - 1. Lack of automatic resource mgmt
  - 2. Hard to express high-level semantics

# High-level languages to the rescue?



- Write your OS in Java/Eiffel/C#/etc.
  - Has been tried. Several times.
- Problems:
  - Lose all control over resource management
  - Explicit layout / memory access becomes hard
  - Still can't express high-level semantics
    - (OS code is highly specialized)
  - Sufficiently-expressive languages too slow and too abstract
    - (e.g. Haskell)





### Promising approach:

- NesC: TinyOS's C dialect with support for modules, events [Gay 2003]
- Deputy: extensions to C using type inference for static checks [e.g. Anderson 2009]
- Ivy: evolving C as a language [Brewer 2005]

So far, little uptake (poor toolchain support?)

# Domain specific languages




- Old idea
- Very broad applicability (not just OSes)
- Guy Steele: "design your system as if you were designing a language anyway".
- Build a "little language" tailored for the task at hand
- Generate C which is then compiled with the OS

In Barrelfish, we use DSLs extensively (4 so far, and counting)

# Domain specific language workflow





# Advantages



- Highly specialized: capture the exact semantics you want!
- Can check and enforce useful invariants
- Small, easy to learn
- Can be very fast (faster than a programmer could write)
- Dramatically reduces devel/debug time

#### Of course, there is a downside:

- Lot of effort to write the compiler
- Complicates toolchain management
- May make the code look somewhat alien...

# Examples of DSLs in Operating Systems



- Communication interface definition
- Hardware register access
- Scheduling algorithms (see next week!)
- Protocol stack design (Click, Prolac)
- Capability type system specification
- Error code definitions

• ...

## Outline



- Introduction
- Interface definition languages
- Hardware interface languages
- Filet-of-Fish
- Hamlet
- References

# Interface definition languages



- Perhaps oldest DSLs for OS development
- Original RPC [Birrell and Nelson, 1984]

## Interface definition semantics




### IDLs are NOT like (Java) RMI!

- An IDL typically defines its own type system.
- Concrete types: integers, structs, etc.
- Abstract types: interface references
- IDL compiler maps this to (perhaps many) programming languages












User server code







Network RPC IDLs need to worry about memory management:

• E.g. CORBA defines 3 parameter modes:

in: Argument is passed from client to server (parameter)

out: Argument is passed from server to client (result)

inout: Argument is sent to server, modified, sent back





Network RPC IDLs need to worry about memory management:

• E.g. CORBA defines 3 parameter modes:

in: Argument is passed from client to server (parameter)

out: Argument is passed from server to client (result)

inout: Argument is sent to server, modified, sent back

- This is not enough locally, in an OS with:
  - Shared memory transport
  - No garbage collection
  - Values (like arrays) bigger than a register or machine word

# Memory management in IDLs



#### Basic questions:

- When should memory in the client be freed?
- How can memory in the server be allocated?
- How can memory in the client be allocated?
- When should memory in the server be freed?
- When is it safe to modify client data, if it's been sent to the server?

# Memory management in IDLs



[Hamilton and Kougiouris, 1994]

The IDL for the Spring OS modified CORBA IDL for an OS setting:

copy: Argument is copied to the server.

**consume**: Argument is sent from client to server, and destroyed at client.

produce: Argument is generated at the server and sent back (destroyed at server)

**borrow**: Like **inout**, but can't be modified by client in the meantime.





For network IDLs (CORBA, ANSA, DCE, SunRPC, etc.) stub performance not critical

- Network latency dominates
- Calls are infrequent
- Calls must traverse network stack anyway





# For network IDLs (CORBA, ANSA, DCE, SunRPC, etc.) stub performance not critical

- Network latency dominates
- Calls are infrequent
- Calls must traverse network stack anyway

### It's very different for local OS stubs:

- IPC system highly optimized ⇒ stub performance critical
- Calls are frequent (particularly in a microkernel)

### **Flick**

[Eide et al., 1997]



### Optimizing stub compiler: many techniques, e.g.:


- Marshall all fixed-size data in one go
  - Avoid checking buffer size each time
- Inline most operations
- Use receive buffer space for arguments (e.g. in)
- Aggregate copies into one big memcpy
- Transport-specific marshalling
  - e.g. L4 IPC in registers

# Flick performance

[Eide et al., 1997]



Shows effect of compiler optimizations on marshalling code:







### Consider a domain specific language where:

- You're writing the same boilerplate code again and again (with minor variations)
- It's easy to make mistakes
- Interoperability (common specifications) are useful
- It's clear what the compiler should do
- Compiler optimizations would be useful
- ... or at least some of the above.

## Outline



- Introduction
- Interface definition languages
- Hardware interface languages
- Filet-of-Fish
- Hamlet
- References





Accessing hardware registers is generally fiddly code

- Lots of bit manipulation (registers have many fields)
- Poor C support
  - word size, sign extension, volatile semantics
  - bitfield structs are implementation specific!
- Consequences of errors are bad
  - Very hard to find bugs
  - Frequently hangs entire machine
- C code to manipulate registers is tedious to write

. [Mérillon et al., 2000]



#### • Hand-written macros:

#define	MSE_DATA_PORT	0x23c
#define	MSE_CONTROL_PORT	0x23e
#define	MSE_READ_Y_LOW	0xc0
#define	MSE_READ_Y_HIGH	0xe0

Systems@ETH zürich

[Mérillon et al., 2000]

#### Hand-written macros:

```
#define MSE_DATA_PORT 0x23c

#define MSE_CONTROL_PORT 0x23e
...

#define MSE_READ_Y_LOW 0xc0

#define MSE_READ_Y_HIGH 0xe0
```

### Programmer usage idioms:

```
dy = (inb(MSE_DATA_PORT) & Oxf);
outb(MSE_READ_Y_HIGH, MSE_CONTROL_PORT);
buttons = inb(MSE_DATA_PORT);
dy |= (buttons & Oxf) << 4;
buttons = ((buttons >> 5) & Ox07);
```

[Mérillon et al., 2000]



Device specified in the Devil DSL:

```
device logitech_busmouse (base : bit[8] port @ {0..3})
{
   // Signature register (SR)
   register sig_reg = base @ 1 : bit[8];
   variable signature = sig_reg, volatile, write trigger : int(8);
   // Configuration register (CR)
   register cr = write base @ 3, mask '1001000.' : bit[8];
   variable config = cr[0] : { CONFIGURATION => '1', DEFAULT_MODE => '0' };
   // Interrupt register
   register interrupt_reg = write base @ 2, mask '000.0000' : bit[8];
   variable interrupt = interrupt_reg[4] : { ENABLE => '0', DISABLE => '1' };
   // Index register
   register index_reg = write base @ 2, mask '1..00000' : bit[8];
   private variable index = index_reg[6..5] : int(2);
   register x_low = read base @ 0, pre {index = 0}, mask '****....' : bit[8];
  register x_high = read base @ 0, pre {index = 1}, mask '****...' : bit[8];
   register y_low = read base @ 0, pre {index = 2}, mask '****....' : bit[8];
  register y_high = read base @ 0, pre {index = 3}, mask '...*...' : bit[8];
   structure mouse_state = {
      variable dx = x_high[3..0] # x_low[3..0], volatile : signed int(8);
      variable dy = y_high[3..0] # y_low[3..0], volatile : signed int(8);
      variable buttons = y_high[7..5], volatile : int(3);
  };
}
```

[Mérillon et al., 2000]



#### What's Devil generating?

```
#define bm_get_mouse_state() ( \
   outb(1, bm_cache.__dil_base__+2); bm_cache.cache_mouse_state.cache_get_x_high = inb(bm_cache.__dil_base__); \
   outb(0, bm_cache.__dil_base__+2); bm_cache.cache_mouse_state.cache_get_x_low = inb(bm_cache.__dil_base__); \
   outb(3, bm_cache.__dil_base__+2); bm_cache.cache_mouse_state.cache_get_y_high = inb(bm_cache.__dil_base__); \
   outb(2, bm_cache.__dil_base__+2); bm_cache.cache_mouse_state.cache_get_y_low = inb(bm_cache.__dil_base__))
#define bm_get_dy() ( \
   (bm_cache.cache_mouse_state.cache_get_y_high & Oxfu) << 4 | bm_cache.cache_mouse_state.cache_get_y_low & Oxfu)
#define bm_get_buttons() ((bm_cache.cache_mouse_state.cache_get_y_high & OxeOu) >> 5)
```



[Mérillon et al., 2000]

What the programmer gets to write:

```
bm_get_mouse_state();
dy = bm_get_dy();
buttons = bm_get_buttons();
```

# Other Devil features



- Pre- and post-conditions
  - E.g. index registers used to access other register banks
  - Semaphores which must be held before writing a register
- "Variables"
  - values which combinations (usually concatenations) of register values

# Mackerel Barrelfish's answer to Devil



- Things have changes somewhat in the meantime:
- Lots of address space ⇒ Index registers are less frequent
  - ⇒ pre-conditions less important
    Register address spaces more useful (PCI, memory, IO)
- Registers are wider (32 or 64 bits)
  - ⇒ meaningful values rarely split across hardware fields
- Most complex devices communicate using descriptor rings
  - ⇒ In-memory data structures are just as important as registers

## Mackerel features



- Goal: specifications should be as close to datasheet descriptions as possible.
- Basic constructs specify:
  - Individual registers
  - Register types
  - Register arrays
  - In-memory data types
  - Collections of constant values
- Make extensive of C compiler's type system and inlining
- Comments are incorporated in Cprintf-like code

# Mackerel features



#### Mackerel generates:

- C constant definitions for all constant values
- C Type definitions for all register and data types
- Functions to read/write all registers
- Functions to read/write all register and data type fields
- Functions to **snprintf**:
  - Register values
  - Data type values
  - Entire device state!





- Example: Intel e1000 Ethernet controller
- Fragment showing a register definition:

```
register status rw addr(base, 0x0008) "Device status" {
    fd
             1 "Link full duplex configuration";
             1 "Link up";
    lu
    lan id 2 "LAN ID";
    txoff
             1 "Transmission paused";
    tbimode 1 "TBI mode";
             2 type(linkspeed) "Link speed setting";
    speed
    asdv
             2 type(linkspeed) "Auto speed detection val";
             1 "PHY reset asserted";
    phyra
             8 mbz;
             1 "GIO master enable status";
    gio mes
             12;
};
```



# Systems@ETH zürich

# Mackerel: some figures

Lines of code (using David Wheeler's SLOCCount):

2359 lines of Haskell for the Mackerel compiler

1028 lines of Mackerel for the e1000 specification

23762 lines of C generated from e1000.dev





How come we don't see more of them in OS research?

- Quite hard to design a good one
  - Except Mackerel, all the DSLs in Barrelfish were designed after we had an initial C implementation and understood the functionality.
- Perception: the effort to implement DSL usually outweighs the cost of designing, building, and implementing it
  - With yesterday's tools, there is some truth in this
  - But . . .

# Building a DSL: what does it take?



DSLs are basically simple compilers:

# Building a DSL: what does it take?



DSLs are basically simple compilers:

### 1. Parser

- Used to be tedious to write
- Glorious easy these days
- E.g. combinator-based Monadic parsing in Haskell

# Building a DSL: what does it take?



DSLs are basically simple compilers:

#### 1. Parser

- Used to be tedious to write
- Glorious easy these days
- E.g. combinator-based Monadic parsing in Haskell

## 2. Back-end C code generator

Rather more difficult . . .

# Writing a backend for a DSL



### The backend takes an AST and generates C code

- Basically: concatenate a set of strings into a C file
- Better: encode subset of C syntax into functional combinators easier.

#### **But still:**

- Writing code through a level of indirection
- Only captures syntax of C, not intended semantics.
- Can't automate tests
- Error-prone
- Annoying to debug
- Ultimately, no assurance it works.

## Filet-o-Fish

[Dagand et al., 2009]



Filet-o-Fish is . . .

- Tool for writing C code generators
- Embedding of a subset of C in Haskell
- Notation for expressing DSL semantics
- Library for creating provably-correct C code from semantic specifications

Used in Barrelfish for (to date) 2 DSLs:

Fugu defines error codes and an error stack
Hamlet defines capability type system

# Hamlet: specifying the capability type system



Yes, Hamlet really is a type of fish


### Recall that Barrelfish uses typed, partitioned capabilities

- For each capability, we must specify:
  - Physical layout in memory
  - What it can be retyped to and from
  - Valid invocations on the capability
  - What happens when it is passed between domains
  - etc.
- We capture all this information in a Hamlet specification.

## How Filet-o-Fish compiles Hamlet

[Dagand et al., 2009]






## How Filet-o-Fish compiles Hamlet

Systems@ETH zürich

[Dagand et al., 2009]

Defining semantics instead of syntax:








For the previous example, Haskell resembles:

## Using QuickCheck to test DSLs



[Dagand et al., 2009]

Check randomly-generated ASTs against semantic assertions:







Hamlet makes it easy to add new capability types to Barrelfish

- Led us to encode more functionality into the type system
  - E.g. different cap types for page table levels
     (On all architectures)
  - Type system enforces page table correctness
- Can encode multiple physical address spaces, etc.
- We expect to push further functionality into capability system...





## Used appropriately:

- Reduce code complexity
  - Though rarely, if never, actually evaluated
  - DSLs perhaps seen more as a means to an end...
- Reduce bugs
  - Capture (and check) high-level semantics of the domain
- Facilitate automated testing and/or correctness proofs





- Birrell, A. D. and Nelson, B. J. (1984). **Implementing remote procedure calls.** ACM Trans. Comput. Syst., 2(1):39–59.
- Dagand, P.-E., Baumann, A., and Roscoe, T. (2009). Filet-o-Fish: Practical and Dependable Domain-Specific Languages for OS Development. In Proc. 5th Workshop on Programming Languages and Operating Systems (PLOS 2009).
- Eide, E., Frei, K., Ford, B., Lepreau, J., and Lindstrom, G. (1997). Flick: A flexible, optimizing IDL compiler. In PLDI, pages 44–56.
- Hamilton, G. and Kougiouris, P. (1994). The Spring nucleus: A microkernel for objects. Technical report, Sun Microsystems Laboratories.
- Mérillon, F., Réveillère, L., Consel, C., Marlet, R., and Muller, G. (2000).
   Devil: An IDL for hardware programming. In Proceedings of the 4th USENIX Symposium on Operating Systems Design and Implementation.





- David Gay, Philip Levis, Robert von Behren, Matt Welsh, Eric Brewer, and David Culler. 2003. The nesC language: A holistic approach to networked embedded systems. In Proceedings of the ACM SIGPLAN 2003 conference on Programming language design and implementation (PLDI '03). ACM, New York, NY, USA, 1-11
- Zachary R. Anderson, David Gay, and Mayur Naik. 2009. Lightweight annotations for controlling sharing in concurrent data structures.
   In Proceedings of the 2009 ACM SIGPLAN conference on Programming language design and implementation (PLDI '09)
- Eric Brewer, Jeremy Condit, Bill McCloskey, and Feng Zhou. 2005.
   Thirty years is long enough: getting beyond C. In Proceedings of the 10th conference on Hot Topics in Operating Systems Volume 10 (HOTOS'05), Vol. 10. USENIX Association, Berkeley, CA, USA, 14-14.