

cs805 Assignment 2

Ray Shulang Lei

200253624

Department of Computer Science

University of Regina

October 26, 2012

Abstract

This assignment is written in literate programming style, generated by noweb, rendered by LaTeX, and compiled by clang++ with c++11 standard.

assignment paper is at latex/as2.pdf

c++ programs are at src/*

binary executable for OS X 10.8 is inside bin

1 function implementation

```
<<src/util.cpp>>=
#include "util.h"
#include <cmath>

//pixel iterator for img panel.
ImagePanel foreach_pixel_exec(ImagePanel img, std::function<int(Ray)> ray_func){
    int i = 0;
    for (auto& pixel: img) { //foreach pixel in empty_img
        //using to_2d function to get x,y camera coordinates
        auto cam_xy = to_2d(i);

        //construct Ray
        Ray ray = ray_construction(cam_xy[0], cam_xy[1]);
        pixel = ray_func(ray);
        i++;
    }
    return img;
}

//ray constructor
Ray ray_construction(int x, int y) {
    //calculate x unit
    double x_unit = -(xmax-xmin) / IMG_X;
    double y_unit = (ymax-ymin) / IMG_Y;

    //calculate the point on img panel with world coordinate
    double x_ = xmax + x_unit * x;
    double y_ = ymax - y_unit * y;

    //get vector v0. it is trival that VRP is p0
    Point ori = {0,0,0};
    Point p0 = mul(Mcw, ori);
    Point p1_ = {x_, y_, focal};
    Point p1 = mul(Mcw, p1_);
    Vector v0 = mul(Rcw, p1_);
}
```

```

/*
Vector v0_ = {p1[0] - p0[0],
              p1[1] - p0[1],
              p1[2] - p0[2]};
Vector v0 = normalize(v0_);
*/

if ((x==0 && y==0) || (x==511 && y==511)) {
    std::cout<<"img: x:"<<x<<" y:"<<y<<std::endl;
    std::cout<<"p0: x:"<<VRP[0]<<" y:"<<VRP[1]<<" z:"<<VRP[2]<<std::endl;
    std::cout<<"p0: x:"<<p0[0]<<" y:"<<p0[1]<<" z:"<<p0[2]<<std::endl;
    std::cout<<"p1_: x:"<<p1_[0]<<" y:"<<p1_[1]<<" z:"<<p1_[2]<<std::endl;
    std::cout<<"p1: x:"<<p1[0]<<" y:"<<p1[1]<<" z:"<<p1[2]<<std::endl;
    std::cout<<"v0: x:"<<v0[0]<<" y:"<<v0[1]<<" z:"<<v0[2]<<std::endl;
}

return { VRP[0], VRP[1], VRP[2],
        v0[0], v0[1], v0[2]};
}

//initialize img panel to all 0s
ImagePanel init_img_panel(ImagePanel img) {
    for (auto& pixel: img) { //foreach pixel in empty_img
        pixel = 0;
    }
    return img;
}

//translate ray equation to an 0~255 shading value
int ray_tracing(Ray ray) {
    Intersection p = ray_objects_intersection(ray);
    return shading(p);
}

//calculate the ray object intersection point
Intersection ray_objects_intersection(Ray ray) {
    auto sphere_hit = ray_sphere_intersection(ray);

```

```

    auto polygon_hit = ray_polygon_intersection(ray);
    if (sphere_hit.kd < 0 && polygon_hit.kd < 0) {
        return {-1,-1,-1,
                -1,-1,-1,
                -1.0};
    } else if (polygon_hit.kd < 0) {
        return sphere_hit;
    } else if (sphere_hit.kd < 0) {
        return polygon_hit;
    } else if (closer(sphere_hit.intersection, polygon_hit.intersection, {0,0,0})) {
        return sphere_hit;
    } else {
        return polygon_hit;
    }
}

Intersection ray_sphere_intersection(Ray ray) {
    return {-1,-1,-1,
            -1,-1,-1,
            -1.0};
}

Intersection ray_polygon_intersection(Ray ray) {
    return {-1,-1,-1,
            -1,-1,-1,
            -1.0};
}

//calculate shading value from 0~255 accordingly to intersection info
int shading(Intersection p) {
    if (p.kd < 0) {
        return -1;
    }

    return 255;
}

//=====helpers=====

```

```

//prints a matrix
void pmatrix(std::string str, Matrix m) {
    std::cout<<str<<std::endl;
    for (auto row : m) {
        for (auto num : row) {
            std::cout<<std::setw (10);
            std::cout<<num;
        }
        std::cout<<std::endl;
    }
    std::cout<<std::endl;
}

//get transformation matrix
Matrix get_T(Point vrp) {
    Row r1 = {1, 0, 0, -vrp[0]};
    Row r2 = {0, 1, 0, -vrp[1]};
    Row r3 = {0, 0, 1, -vrp[2]};
    Row r4 = {0, 0, 0, 1};
    return {r1, r2, r3, r4};
}

//get inverse transformation matrix
Matrix get_Ti(Point vrp) {
    Row r1 = {1, 0, 0, vrp[0]};
    Row r2 = {0, 1, 0, vrp[1]};
    Row r3 = {0, 0, 1, vrp[2]};
    Row r4 = {0, 0, 0, 1};
    return {r1, r2, r3, r4};
}

//get rotation matrix
Matrix get_R(Point vrp, Vector vpn, Vector vup) {
    //first get the translation matrix from world to view
    //auto mt = get_T(vrp);

    //we can see vpn_ and vup_ as vectors. such that we can apply them to get_uvn fu

```

```

    auto uvn = get_uvn(vpn, vup);
    //finally construct our rotation matrix using method 2 on class notes
    Row r1 = { uvn[0][0], uvn[0][1], uvn[0][2], 0 };
    Row r2 = { uvn[1][0], uvn[1][1], uvn[1][2], 0 };
    Row r3 = { uvn[2][0], uvn[2][1], uvn[2][2], 0 };
    Row r4 = { 0, 0, 0, 1 };
    return { r1, r2, r3, r4 };
}

//get inverse rotation matrix
Matrix get_Ri(Point vrp, Vector vpn, Vector vup) {
    Matrix m = get_R(vrp, vpn, vup);
    Row r1 = { m[0][0], m[1][0], m[2][0], m[3][0] };
    Row r2 = { m[0][1], m[1][1], m[2][1], m[3][1] };
    Row r3 = { m[0][2], m[1][2], m[2][2], m[3][2] };
    Row r4 = { m[0][3], m[1][3], m[2][3], m[3][3] };
    return {r1,r2,r3,r4};
}

//world to camera
Matrix get_M(Point vrp, Vector vpn, Vector vup) {
    return mul(get_R(vrp, vpn, vup), get_T(vrp));
}

//camera to world
Matrix get_Mi(Point vrp, Vector vpn, Vector vup) {
    return mul(get_Ti(vrp), get_Ri(vrp, vpn, vup));
}

//matrix multiplication
Point mul(Matrix m, Point x) {
    return mul(x, m);
}

Point mul(Point x, Matrix m) {
    double w = m[3][0] * x[0]
               + m[3][1] * x[1]

```

```

        + m[3][2] * x[2]
        + m[3][3];
    return {(x[0]*m[0][0]+x[1]*m[0][1]+x[2]*m[0][2]+m[0][3])/w,
            (x[0]*m[1][0]+x[1]*m[1][1]+x[2]*m[1][2]+m[1][3])/w,
            (x[0]*m[2][0]+x[1]*m[2][1]+x[2]*m[2][2]+m[2][3])/w};
}

Matrix mul(Matrix m, Matrix n) {
    Row r1 = {m[0][0]*n[0][0]+m[0][1]*n[1][0]+m[0][2]*n[2][0]+m[0][3]*n[3][0],
              m[0][0]*n[0][1]+m[0][1]*n[1][1]+m[0][2]*n[2][1]+m[0][3]*n[3][1],
              m[0][0]*n[0][2]+m[0][1]*n[1][2]+m[0][2]*n[2][2]+m[0][3]*n[3][2],
              m[0][0]*n[0][3]+m[0][1]*n[1][3]+m[0][2]*n[2][3]+m[0][3]*n[3][3]};
    Row r2 = {m[1][0]*n[0][0]+m[1][1]*n[1][0]+m[1][2]*n[2][0]+m[1][3]*n[3][0],
              m[1][0]*n[0][1]+m[1][1]*n[1][1]+m[1][2]*n[2][1]+m[1][3]*n[3][1],
              m[1][0]*n[0][2]+m[1][1]*n[1][2]+m[1][2]*n[2][2]+m[1][3]*n[3][2],
              m[1][0]*n[0][3]+m[1][1]*n[1][3]+m[1][2]*n[2][3]+m[1][3]*n[3][3]};
    Row r3 = {m[2][0]*n[0][0]+m[2][1]*n[1][0]+m[2][2]*n[2][0]+m[2][3]*n[3][0],
              m[2][0]*n[0][1]+m[2][1]*n[1][1]+m[2][2]*n[2][1]+m[2][3]*n[3][1],
              m[2][0]*n[0][2]+m[2][1]*n[1][2]+m[2][2]*n[2][2]+m[2][3]*n[3][2],
              m[2][0]*n[0][3]+m[2][1]*n[1][3]+m[2][2]*n[2][3]+m[2][3]*n[3][3]};
    Row r4 = {m[3][0]*n[0][0]+m[3][1]*n[1][0]+m[3][2]*n[2][0]+m[3][3]*n[3][0],
              m[3][0]*n[0][1]+m[3][1]*n[1][1]+m[3][2]*n[2][1]+m[3][3]*n[3][1],
              m[3][0]*n[0][2]+m[3][1]*n[1][2]+m[3][2]*n[2][2]+m[3][3]*n[3][2],
              m[3][0]*n[0][3]+m[3][1]*n[1][3]+m[3][2]*n[2][3]+m[3][3]*n[3][3]};
    return {r1,r2,r3,r4};
}

Row mul(Row x, Matrix m) {
    return {x[0]*m[0][0]+x[1]*m[0][1]+x[2]*m[0][2]+x[3]*m[0][3],
            x[0]*m[1][0]+x[1]*m[1][1]+x[2]*m[1][2]+x[3]*m[1][3],
            x[0]*m[2][0]+x[1]*m[2][1]+x[2]*m[2][2]+x[3]*m[2][3],
            x[0]*m[3][0]+x[1]*m[3][1]+x[2]*m[3][2]+x[3]*m[3][3]};
}

Row mul(Matrix m, Row x) {
    return mul(x, m);
}

```

```

//return if p1 is closer to p0 than p2
bool closer(Point p1, Point p2, Point p0) {
    double d1 = (p1[0] - p0[0])+(p1[1] - p0[1])+(p1[2] - p0[2]);
    double d2 = (p2[0] - p0[0])+(p2[1] - p0[1])+(p2[2] - p0[2]);
    return d1 < d2;
}

//Translate 2D array index of row column to 1D index.
//Notice that x, or column index, starts with 0.
//If return value is -1 then there is an out-of-bounce error.
int to_1d(int x, int y) {
    if (x >= IMG_X || x < 0)
        return -1;
    if (y >= IMG_Y || y < 0)
        return -1;
    return (IMG_Y*y + x);
}

//Translate 1d array index to 2d
std::array<int, 2> to_2d(int x) {
    if (x>=(IMG_X*IMG_Y) || x < 0) {
        return {-1,-1};
    }
    int y_ = x / IMG_X;
    int x_ = x % IMG_X;
    return {x_, y_};
}

//prints the img panel
void print_img_panel(ImagePanel img) {
    std::cout<<std::endl;
    for (auto& pixel : img) {
        std::cout<<pixel<<" ";
    }
    std::cout<<std::endl<<"Array size: "<<img.size()<<std::endl;
}

//get u,v,n from two non-collinear vectors

```



```

UVN get_uvn(Vector V1, Vector V2) {

    //get n, which is just normalized V1
    Vector n = normalize(V1);

    //get u, which is normalized V2 x V1
    Vector u = normalize(cross_product(V2, V1));

    //get v, which is normalized n x u
    Vector v = normalize(cross_product(n, u));

    return {u,v,n};
}

//normalize a Vector
Vector normalize(Vector x) {
    return { x[0]/get_length(x),
            x[1]/get_length(x),
            x[2]/get_length(x) };
}

//calculates cross product of two Vectors
Vector cross_product(Vector x, Vector y) {
    return { x[1]*y[2] - x[2]*y[1],
            x[2]*y[0] - x[0]*y[2],
            x[0]*y[1] - x[1]*y[0] };
}

//calculates length of a Vector
double get_length(Vector x) {
    return sqrt(pow(x[0],2)+pow(x[1],2)+pow(x[2],2));
}

@

```

2 header

Here is an header file for typedefs and function declarations.

```
<<src/util.h>>=
#ifndef UTIL_H
#define UTIL_H

//define preprocessing vars
#define IMG_X 512
#define IMG_Y 512
#define IMG_LEN ( IMG_X * IMG_Y )
/* definition of the image buffer */
#define ROWS IMG_Y
#define COLS IMG_X

#include <array>
#include <functional>
#include <iostream>
#include <iomanip>

//types
typedef std::array<int, IMG_LEN> ImagePanel;
typedef std::array<double, 3> Point;
typedef std::array<double, 3> Vector;
typedef std::array<Vector, 3> UVN;
typedef struct {
    Point intersection; /* intersection point */
    Vector normal; /* intersection polygon normal vector */
    double kd; /* diffuse reflection coefficient of the surface */
} Intersection;
typedef struct {
    Point ref; /* reference point, where the ray is from */
    Vector direction; /* ray direction */
} Ray;
typedef std::array<double, 4> Row;
typedef std::array<Row, 4> Matrix;
typedef struct {
```

```

double x, y, z; /* center of the circle */
double radius; /* radius of the circle */
double kd; /* diffuse reflection coefficient */
} SPHERE;
typedef struct {
double v[4][3]; /* list of vertices */
double N[3]; /* normal of the polygon */
double kd; /* diffuse reflection coefficient */
} POLY4;

//functions
ImagePanel foreach_pixel_exec(ImagePanel, std::function<int(Ray)>);
ImagePanel init_img_panel(ImagePanel);
int ray_tracing(Ray);
Intersection ray_objects_intersection(Ray);
int shading(Intersection);
Intersection ray_sphere_intersection(Ray);
Intersection ray_polygon_intersection(Ray);
Ray ray_construction(int, int);

//helper functions
Point mul(Point, Matrix);
Point mul(Matrix, Point);
Matrix mul(Matrix, Matrix);
Row mul(Row, Matrix);
Row mul(Matrix, Row);
int to_1d(int, int);
std::array<int, 2> to_2d(int);
void print_img_panel(ImagePanel);
void pmatrix(std::string, Matrix);
bool closer(Point, Point, Point);
UVN get_uvn(Vector V1, Vector V2);
Matrix get_T(Point);
Matrix get_Ti(Point);
Matrix get_R(Point, Vector, Vector);
Matrix get_Ri(Point, Vector, Vector);
Matrix get_M(Point, Vector, Vector);
Matrix get_Mi(Point, Vector, Vector);

```

```
double get_length(Vector);
Vector cross_product(Vector, Vector);
Vector normalize(Vector);
```

```
//global vars
extern Matrix Mwc;
extern Matrix Rwc;
extern Matrix Twc;
extern Matrix Mcw;
extern Matrix Rcw;
extern Matrix Tcw;
extern Matrix Mwl;
extern Matrix Mlw;
extern double xmin;
extern double ymin;
extern double xmax;
extern double ymax;
extern Point VRP;
extern Vector VPN;
extern Vector VUP;
extern double focal;
extern Point LRP;
extern double Ip;
#endif
@
```

3 main funciton

```
<<src/main.cpp>>=
#include <iostream>
#include "util.h"

/* create a spherical object */
SPHERE obj1 = {1.0, 1.0, 1.0,/* center of the circle */
1.0,/* radius of the circle */
0.75}; /* diffuse reflection coefficient */
```

```

/* create a polygon object */
POLY4 obj2 = { 0.0, 0.0, 0.0,/* v0 */
0.0, 0.0, 2.0,/* v1 */
2.0, 0.0, 2.0,/* v2 */
2.0, 0.0, 0.0,/* v3 */
0.0, 1.0, 0.0,/* normal of the polygon */
0.8}; /* diffuse reflection coefficient */

//unsigned char img[ROWS][COLS];

/* definition of window on the image plane in the camera coordinates */
/* They are used in mapping (j, i) in the screen coordinates into */
/* (x, y) on the image plane in the camera coordinates */
/* The window size used here simulates the 35 mm film. */
double xmin = 0.0175;
double ymin = -0.0175;
double xmax = -0.0175;
double ymax = 0.0175;

/* definition of the camera parameters */
Point VRP = {1.0, 2.0, 3.5};
Vector VPN = {0.0, -1.0, -2.5};
Vector VUP = {0.0, 1.0, 0.0};

double focal = 0.05; /* focal length simulating 50 mm lens */

/* definition of light source */
Point LRP = {-10.0, 10.0, 2.0}; /* light position */
double Ip = 200.0; /* intensity of the point light source */

/* Transformation from the world to the camera coordinates */
Matrix Mwc = get_M(VRP, VPN, VUP);
Matrix Rwc = get_R(VRP, VPN, VUP);
Matrix Twc = get_T(VRP);
/* Transformation from the camera to the world coordinates */
Matrix Mcw = get_Mi(VRP, VPN, VUP);

```

```

Matrix Rcw = get_Ri(VRP, VPN, VUP);
Matrix Tcw = get_Ti(VRP);
/* Transformation from the world to light coordinates */
Matrix Mwl = get_T(LRP);
/* Transformation from the light to the world coordinates */
Matrix Mlw = get_Ti(LRP);

int main () {
    ImagePanel img;
    img = init_img_panel(img);
    img = foreach_pixel_exec(img, ray_tracing);
    //print_img_panel(img);

    //tests
    Point vrp = {6.0, 10.0, -5.0};
    Vector vpn = {-6.0, -9.0, 5.0};
    Vector vup = {0.0, 1.0, 0.0};
    auto uvn = get_uvn(vpn, vup);
    std::cout<<"get_uvn function:"<<std::endl;
    for (auto vecotr : uvn) { //for each Vecotr in uvn
        for (auto num : vecotr) { //for each number in Vecotr
            std::cout<<num<<',';
        }
        std::cout<<std::endl;
    }

    Matrix mwc = get_M(vrp, vpn, vup);
    Matrix mcw = get_Mi(vrp, vpn, vup);
    Matrix twc = get_T(vrp);
    Matrix tcw = get_Ti(vrp);
    Matrix rwc = get_R(vrp, vpn, vup);
    Matrix rcw = get_Ri(vrp, vpn, vup);
    pmatrix("mwc:", mwc);
    pmatrix("twc:", twc);
    pmatrix("rwc:", rwc);
    pmatrix("mcw:", mcw);
    pmatrix("tcw:", tcw);
    pmatrix("rcw:", rcw);
}

```

```

pmatrix("Mcw:", Mcw);

std::cout<<"to_1d function, expected to be 512:"<<std::endl;
std::cout<<to_1d(0, 1)<<std::endl;

std::cout<<"to_2d function, expected to be 0, 1:"<<std::endl;
std::cout<<to_2d(512) [0]<<std::endl;
std::cout<<to_2d(512) [1]<<std::endl;

std::cout<<"to_1d function, expected to be 513:"<<std::endl;
std::cout<<to_1d(1, 1)<<std::endl;

std::cout<<"to_2d function, expected to be 1,1:"<<std::endl;
std::cout<<to_2d(513) [0]<<std::endl;
std::cout<<to_2d(513) [1]<<std::endl;

std::cout<<"to_1d function, expected to be 1023:"<<std::endl;
std::cout<<to_1d(511, 1)<<std::endl;

std::cout<<"to_2d function, expected to be 511,1:"<<std::endl;
std::cout<<to_2d(1023) [0]<<std::endl;
std::cout<<to_2d(1023) [1]<<std::endl;

std::cout<<"to_1d function, expected to be -1:"<<std::endl;
std::cout<<to_1d(512, 1)<<std::endl;

std::cout<<"to_2d function, expected to be -1,-1:"<<std::endl;
std::cout<<to_2d(512*512) [0]<<std::endl;
std::cout<<to_2d(512*512) [1]<<std::endl;

std::cout<<"closer function, expected to be 1 and 0:"<<std::endl;
std::cout<<closer({1,1,1},{2,2,2},{0,0,0})<<std::endl;
std::cout<<closer({3,3,3},{2,2,2},{0,0,0})<<std::endl;

std::cout<<"mul function: point * matrix"<<std::endl;
Point a = {3,3,3};
std::cout<<mul(a, Mcw) [0]<<std::endl;

```

```

std::cout<<mul(Mcw, a)[1]<<std::endl;
std::cout<<mul(a, Mcw)[2]<<std::endl;

pmatrix("mul funciton: matrix*matrix:", mul(Mwc, Mcw));

std::cout<<"mul function: row * matrix"<<std::endl;
Row b = {3,3,3,3};
std::cout<<mul(b, Mcw)[0]<<std::endl;
std::cout<<mul(Mcw, b)[1]<<std::endl;
std::cout<<mul(b, Mcw)[2]<<std::endl;
std::cout<<mul(b, Mcw)[3]<<std::endl;

return 0;
}
@

```

4 compile script

Furthermore, this is the command to link these files. Notice that I am using `-std=c++11` flag to enable c++ 11 features. The output binary executable is `bin/run`

```

<<compile.sh>>=
clang++ -std=c++11 -stdlib=libc++ -o bin/run src/main.cpp src/util.cpp
@

```