Settings / Developer settings

⊞ GitHub Apps

👤 OAuth Apps

🔑 **Personal access tokens**   ⌃

     Fine-grained tokens   (Beta)

     Tokens (classic)

New personal access token (classic)

Personal access tokens (classic) function like ordinary OAuth access tokens. They can be used instead of a password for Git over HTTPS, or can be used to authenticate to the API over Basic Authentication.

Note

For test

What's this token for?

Expiration *

| 30 days ⇕ | The token will expire on Wed, Jul 12 2023

Select scopes

Scopes define the access for personal tokens. Read more about OAuth scopes.

☑ **repo**	Full control of private repositories
☑ repo:status	Access commit status
☑ repo_deployment	Access deployment status
☑ public_repo	Access public repositories
☑ repo:invite	Access repository invitations
☑ security_events	Read and write security events
☐ **workflow**	Update GitHub Action workflows
☐ **write:packages**	Upload packages to GitHub Package Registry
☐ read:packages	Download packages from GitHub Package Registry
☐ **delete:packages**	Delete packages from GitHub Package Registry
☐ **admin:org**	Full control of orgs and teams, read and write org projects
☐ write:org	Read and write org and team membership, read and write org projects
☐ read:org	Read org and team membership, read org projects
☐ manage_runners:org	Manage org runners and runner groups
☐ **admin:public_key**	Full control of user public keys
☐ write:public_key	Write user public keys
☐ read:public_key	Read user public keys
☐ **admin:repo_hook**	Full control of repository hooks
☐ write:repo_hook	Write repository hooks
☐ read:repo_hook	Read repository hooks
☐ **admin:org_hook**	Full control of organization hooks
☐ **gist**	Create gists

☐ **notifications**	Access notifications
☐ **user**	Update ALL user data
☐ read:user	Read ALL user profile data
☐ user:email	Access user email addresses (read-only)
☐ user:follow	Follow and unfollow users
☐ **delete_repo**	Delete repositories
☐ **write:discussion**	Read and write team discussions
☐ read:discussion	Read team discussions
☐ **admin:enterprise**	Full control of enterprises
☐ manage_runners:enterprise	Manage enterprise runners and runner groups
☐ manage_billing:enterprise	Read and write enterprise billing data
☐ read:enterprise	Read enterprise profile data
☐ **audit_log**	Full control of audit log
☐ read:audit_log	Read access of audit log
☐ **codespace**	Full control of codespaces
☐ codespace:secrets	Ability to create, read, update, and delete codespace secrets
☐ **project**	Full control of projects
☐ read:project	Read access of projects
☐ **admin:gpg_key**	Full control of public user GPG keys
☐ write:gpg_key	Write public user GPG keys
☐ read:gpg_key	Read public user GPG keys
☐ **admin:ssh_signing_key**	Full control of public user SSH signing keys
☐ write:ssh_signing_key	Write public user SSH signing keys
☐ read:ssh_signing_key	Read public user SSH signing keys

Generate token   Cancel