

Gait sequence modelling and estimation

using Hidden Markov Models



Presented by:
Kouame Hermann Kouassi

Prepared for:
Fred Nicolls
Dept. of Electrical and Electronics Engineering
University of Cape Town

Submitted to the Department of Electrical Engineering at the University of Cape Town
in partial fulfilment of the academic requirements for a Bachelor of Science degree in
Electrical and Computer Engineering

November 1, 2017

Declaration

1. I know that plagiarism is wrong. Plagiarism is to use another's work and pretend that it is one's own.
2. I have used the IEEE convention for citation and referencing. Each contribution to, and quotation in, this report from the work(s) of other people has been attributed, and has been cited and referenced.
3. This report is my own work.
4. I have not allowed, and will not allow, anyone to copy my work with the intention of passing it off as their own work or part thereof.

Signature:.....

Kouame H. Kouassi

Date:.....

Acknowledgments

Abstract

- Open the **Project Report Template.tex** file and carefully follow the comments (starting with %).
- Process the file with **pdflatex**, using other processors may need you to change some features such as graphics types.
- Note the files included in the **Project Report Template.tex** (with the .tex extension excluded). You can open these files separately and modify their contents or create new ones.
- Contact the latex manual for more features in your document such as equations, subfigures, footnotes, subscripts & superscripts, special characters etc.
- I recommend using the **kile** latex IDE, as it is simple to use.

Contents

1	Introduction	1
1.1	Background to the study	1
1.2	Objectives of this study	1
1.2.1	Problems to be investigated	2
1.2.2	Purpose of the study	3
1.3	Scope and Limitations	3
1.4	Plan of development	3
2	Literature Review	4
2.1	Gait sequence modelling and estimation	5
2.1.1	Quadrupede gait modelling	5
2.1.2	Quadrupede gait estimation	5
2.2	Case study: Inertia Measurement Unit	5
2.3	Hidden Markov Models	5
2.3.1	HMM parameters specification	6

2.3.2	Three fundamental problems for HMM design	7
2.3.3	Types of HMM	8
2.4	k-Nearest Neighbour	8
2.5	Dimension reduction	8
2.5.1	Feature selection	8
2.6	Sufficiency of Training Data	8
2.7	Techniques to increase Training Data	8
2.7.1	Mirroring	8
3	Hidden Markov Model design	9
3.1	Description of available dataset	9
3.1.1	Quadrupede Gait sequence modelling	10
3.1.2	Data pre-processing	12
3.1.3	Model parameters estimation	12
3.1.4	Dimension reduction	14
3.1.5	Continuous observations/features to Discrete observations/features	14
3.2	HMM implementation	14
4	Results	15
4.1	Experiement 1: The effect of a CHMM' observation dimensionality on its performance	15
4.1.1	Aim of the experiement	15

4.1.2	Apparatus	15
4.1.3	Methods	16
4.2	Results	17
4.3	Analysis	17
4.3.1	Discrete Probability density function duration d in state i	17
4.3.2	Expected number of observations (duration) in a state	17
4.4	Experimental Results	17
5	Discussion	18
6	Conclusions	19
7	Recommendations	20
A	Additional Files and Schematics	23
B	Addenda	24
B.1	Ethics Forms	24

Chapter 1

Introduction

1.1 Background to the study


A very brief background to your area of research. Start off with a general introduction to the area and then narrow it down to your focus area. Used to set the scene [1].

Bio-inspired robotics uses nature to inform real-world engineering systems. Research has been conducted at UCT to investigate the manner in which a cheetah uses its tail for stability during high acceleration, quick turns and sudden braking, with an aim to incorporating identified mechanisms into sophisticated robot designs. One way to acquire useful data is to strap an inertial measurement unit (IMU) to an animal, and log the sensor data while certain actions are being performed. We currently have such a dataset of a dog moving, along with corresponding video data.

1.2 Objectives of this study

The objective of this project is to design, implement, and test Hidden Markov Models (HMM) for estimating gait sequence from Inertia Measurement Unit (IMU) data.

so that specific models can be formulated and their parameters estimated and interrogated. The project can be extended to include any other useful analysis of gait patterns from similar sensor measurements



1 - formulate model 2 - estimate its parameters 3 - Interrogate its parameters 4 - Useful analysis of gait patterns from IMU measurements

1.2.1 Problems to be investigated

Description of the main questions to be investigated in this study.

The main questions to be answered are the following:

1. How well can HMM model gait sequence dynamics using IMU data, in the absence of enough training samples?
2. Can dimensionality reduction cause an increase in performance of HMM models when there is not enough training data?

1.2.2 Purpose of the study

Give the significance of investigating these problems. It must be obvious why you are doing this study and why it is relevant.

1.3 Scope and Limitations

Scope indicates to the reader what has and has not been included in the study. Limitations tell the reader what factors influenced the study such as sample size, time etc. It is not a section for excuses as to why your project may or may not have worked.

1 - Does not include data collection 2 - Focus on design of HMM only 3 - Focus on analysis of the model 4 - Focus on impact of dimensionality reduction

1.4 Plan of development

Here you tell the reader how your report has been organised and what is included in each chapter.

I recommend that you write this section last. You can then tailor it to your report.

Chapter 2

Literature Review

Once upon a time engineers and researchers believed... In this area of research, they used the following methods... [2]

Write this section first as it will take you the longest. I suggest you start writing this as soon as you have done your initial research at the beginning of your project. You can then return to it once you have completed your work to edit and adjust it.

A literature review forms the theoretical basis of your project. You need to read a large number of journal papers, sections in books, technical reports etc. relevant to your work at the start of project. This will give you a good idea of the field of research.

When writing your review start of with the general concepts and move to the more specific aspects explaining the necessary theory as you go. This section is NOT a copy and paste from others work or a rewrite-but-change-one-word section. I suggest you read all your material, and then put it down and write this section, referring back to the work only when you need to check something.

See your PCS textbook for more details on how to write a literature review.

If you include a figure or a table in your text please see the example in Fig. 3.1 as to how to caption it. Please make sure that all text in your figures is readable and that you reference your figures if they are from another source.




Figure 2.1: A block diagram illustrating the connections to the IRQ pin on the MCS08GT16A microcontroller (Please note that your headings should be short descriptions of what is in the diagram not simply the figure title)

2.1 Gait sequence modelling and estimation

2.1.1 Quadrupede gait modelling

Periodicity

2.1.2 Quadrupede gait estimation

2.2 Case study: Inertia Measurement Unit

2.3 Hidden Markov Models

Hidden Markov Models (HMMs) are doubly embedded stochastic processes with a rich underlying statistical structure. Introduced at the end of the 1960s by Baum and colleagues, they have become one of the preferred techniques in speech recognition after the implementation of Baker and Jelinek in 1970s. HMMs have been successfully applied to various other engineering problems in pattern recognition for classification and fraud detection purposes, amongst others.

2.3.1 HMM parameters specification

An HMM is fully specified the following parameters

1. N , the number of distinct states of the model. Together they form the set of individual states $S = \{S_1, S_2, \dots, S_N\}$.
2. T , the number of observations. A sample observation sequence is denoted as $O = \{O_1, O_2, \dots, O_T\}$.
3. $Q = q_t$, the set of states with q_t denoting the current state at time instance, t such that $q_t \in S$ and $t = 1, 2, \dots, T$.
4. K , the number of distinct observation symbols per state.
5. $V = \{v_1, v_2, \dots, v_K\}$, the feature set of K dimensions.
6. $A = \{a_{ij}\}$, the state transition probabilities. It a_{ij} denotes probability of transitioning from state S_i to state S_j .
7. $\Phi = \{\phi_j(k)\}$, the probability distribution of observation symbols in state j .
8. The initial state distribution, $\pi = \pi_i$

For continuous HMM (CHMM), i.e, HMM with continuous-valued observations, Φ consists in a probability distribution function. Many applications have continuous distributions with mixtures of Gaussian distribution. As such, ϕ is approximated by a weighted sum of M multivariate Gaussian distributions η ,

$$\phi(O_t) = \sum_{m=1}^M \beta_{jm} \eta(\mu_{jm}, \Sigma_{jm}, O_t), \quad (2.1)$$

$$\eta(\mu, \Sigma, O) = \frac{1}{\sqrt{(2\pi)^K |\Sigma|}} \exp\left(-\frac{1}{2}(O - \mu)' \Sigma^{-1} (O - \mu)\right) \quad (2.2)$$

$$1 \leq j \leq N; 1 \leq m \leq M; \beta_{jm} \geq 0; \sum_{m=1}^M \beta_{jm} = 1$$

where β_{jm} is the mixture composition coefficient; μ_{jm} , Σ_{jm} , respectively the mean vector and covariance matrix of state j ; M is the number of mixture components and K is the dimensionality of O .

Thus, the compact specification of a continuous valued observation HMM defined in 2.3 and that of a discrete HMM in 2.4.

$$\lambda = (A, \beta_{jm}, \mu_{jm}, \Sigma_{jm}, \pi) \quad (2.3)$$

$$\lambda = (A, b_j(k), \pi) \quad (2.4)$$

Basic assumptions of HMMs theory

HMM theory is built on three basic assumptions listed below. They not only, make it a relatively simple graphic modelling tool but, also simplify its implementation. This naturally comes with some limitations in modelling more complex problems, which however, may be modelled with higher order HMMs.

1. *The Markov assumption:* HMM assumes that the probability of being in the current at any instance of time t , is uniquely dependent on the previous state, at time, $t + 1$. More specifically, $a_{ij} = P[q_t = S_j | q_{t+1} = S_i]$. This assumption makes it unsuitable for long-range correlation capturing applications.
2. *The stationary assumption:* Furthermore, HMM state transition probabilities are assumed to be time-independent. Thus, the transition probabilities of two distinct time, t_1 and t_2 are identical, $P[q_{t_1} = S_j | q_{t_1-1} = S_i] = P[q_{t_2} = S_j | q_{t_2-1} = S_i]$. HMMs can therefore effectively model mechanisms with stationary observations.
3. *The output/observation independence assumption:* The current observation also known as emission symbol is statistically independent of the previous observations. It is "emitted" only by the current state, $P[O | q_1, q_2, \dots, q_T, \lambda] = \prod_{t=1}^T P[O_t | q_t, \lambda]$.

The above three assumptions are similar to those of a Markov chain. This is because the stochastic process of an HMM pertaining to the hidden states can be reduced to a Markov chain. Thus, the essential difference between an HMM and a Markov process is that with the former there is not a one-to-one correspondence between the states and the symbols.

2.3.2 Three fundamental problems for HMM design

In , Lawrence stipulates an HMM design needs to answer three fundamental problems. The three problems and their solutions are discussed in the next sub-sections.

The training problem

The evaluation problem

The decoding problem

First order Markov model - current and predecessor only considered

2.3.3 Types of HMM

Ergodic model

Left-Right model or Bakis model

Evaluation of the probability of a sequence of observations

The determination of a best sequence states

The adjustment of model parameters to account for observed signal

2.4 k-Nearest Neighbour

2.5 Dimension reduction

2.5.1 Feature selection

2.6 Sufficiency of Training Data

2.7 Techniques to increase Training Data

2.7.1 Mirroring

Chapter 3

Hidden Markov Model design

This section focuses on the design of the HMM used to test the hypotheses postulated above.

3.1 Description of available dataset

The available dataset was acquired from a moving dog using Inertia Measurement Units. Two inertial measurements units (IMU) were strapped to the front and back of a dog. Each unit has an accelerometer, a gyroscope and a magnetometer. The dataset contains calibrated measurements of a dog running, walking, and trotting then walking; together with the footfalls. The footfall is represented by a binary value that indicates the state of the dog's leg: if it is on or above the ground, at a particular instant in its gait sequence. More specifically, the value 0 means leg up and the value 1 means leg down. The four variables representing the footfalls effectively constitute the ground truth, informing us about the state in which the dog is, at a given time in its movement.

The dataset can be retrieved from nine different matlab files. Each file contains twenty four matlab variables. The variables of interest are listed in the table 3.1.

The observations are continuous and the statistical property are assumed to be stationary, i.e, they do not vary over time. In this sta

3.1. DESCRIPTION OF AVAILABLE DATASET

Observations			
Body part	Accelerometer	Gyroscope	Magnetometer
Front	accFrontX	FrontPitch	magFront_cal
	accFrontY	FrontRoll	magFront_cal2
	accFrontZ	FrontYaw	magFront_cal3
Back	accBackX	BackPitch	magBack_cal
	accBackY	BackRoll	magBack_cal2
	accBackZ	BackYaw	magBack_cal3

Table 3.1: IMU measurements and footfall variables in dataset

stationary: statistical property do not vary over time or **non-stationary:** properties vary over time

pure or corrupted?

3.1.1 Quadrupede Gait sequence modelling

One of the objectives of this project is to effectively model the gait sequence dynamic of the dog from IMU measurements using HMM. Based on the fact that quadrupedes achieve inverted pendulum-like movements like humans, their gait dynamic can be modelled as a succession of latent states observed by measurements such as IMU data. The states representing the footfalls and the observations, the outputs of the accelerometer, gyroscope and the magnetometer. Similar to human gait mechanism, it is sound to assume that the current state of a quadrupede is conditionally dependent on its previous state. This inference combined with the statistical robustness of HMM makes it the best model candidate when the available dataset is not large enough.

HMM model elements: states and observations properties

The problem at hand requires 16 distinct state that make up the state vector S , shown in equation 3.1

$$S = S_i = \{(LF, RF, LB, RB)\} = \{0000, 0001, 0010, \dots, 1111\}. \quad (3.1)$$

$$|S| = N = 2^4 = 16$$

$$i = 1, 2, \dots, 16$$

3.1. DESCRIPTION OF AVAILABLE DATASET

The 16 distinct states are derived from the combination of the four binary footfalls. In practice, the dataset may not reveal all the 16 states.

The stream of IMU measurement form the observation sequence. An observation instance is a row vector of K dimensions. The initial K value before any dimensionality reduction is 18, from the 18 IMU measurements. Thus, an observation sequence O is a TxK matrix of continuous values as presented in 3.2. T is the total number of the successive measurements.

$$O = \{Ok_t\} = O1_t, O2_t, \dots, O18_t. \quad (3.2)$$

$$k = 1, 2, \dots, 18. \quad (3.3)$$

$$t = 1, 2, \dots, T. \quad (3.4)$$

Splitting the 16-states HMM in two 4-states HHMs

In order to simplify the problem, it was decided to split the the four legs in two sub-parts: two front legs and two back legs. This approach for splitting it was based on the two inverted-like movements for a quadrupede such as a dog has investigated in As a result, the initial 16-states HMM becomes, two distinct 4-states HHMs. These two models may be combined to get back the holistic 16-states model. This design decision was motivated by the fact that it is a simpler task to dsicriminate between 4 distinct classes than 16 classes. From here onward, attention will be given to the 4-states HMM model.

Transition between states

This design assumes that a dog can transition from one state to any other possible state. So, for any transtion from S_i to S_j both S_i and S_j may be any of the element of the state space

$$S = \{S1, S2, S3, S4\}$$

For instance, if a dog has its left leg above ground and its right leg on ground, at time instance t, it may move to any of the 3 other possible positions or remain in the same state, in the next time instance, t + 1. This consideration yielded in an ergodic HMM

where, all the transitions are possible. The graphical model of the simplified HMM is illustrated by figure 3.1




Figure 3.1: Ergodic HMM graphical model showing the hidden states, observation, and transitions between states

3.1.2 Data pre-processing

3.1.3 Model parameters estimation

As a reminder, a continuous HMM model is completely specified by its initial state distribution: π transition matrix: A ; the mean covariance matrices: μ , Σ which can be combined into Φ . If the observations are modelled with gaussian mixture distributions, one addition parameter is required for the initial mixture distribution: β . The next sub-sections discuss how each parameters was estimated in this project.

Transition matrix: A

For each of the front and back 4-state HMM, the state transition matrix A , is a 4-by-4 matrix. Two different approaches were considered in the estimation of A . The two methods make use of the expectation maximisation algorithm but differ in the input arguments considered.

1. Approach 1: Exploiting the available ground truth

This approach takes advantage of the ground truth for a labelled dataset to reduce

3.1. DESCRIPTION OF AVAILABLE DATASET

the HMM model to a Markov Chain. This is done by making the hypothetical observation sequence identical to the state sequence. Then, using approach used in discrete HMM, the transition matrix can be estimated using maximum likelihood algorithm. For each state, the pseudocount was set to the number of occurrences of that state in the training data plus a constant value: $PseudoA = |S_i| + C$. The additional constant C is to avoid having 0 in the transition matrix for states and transitions not reflected in the dataset. It can be chosen empirically. This method is very simple however, it has two limitations. It not only assumes that the number of states is known but also requires the training data to be labelled. Although, the dataset at hand satisfies the two constraints, the second approach which eliminates these possible setbacks, was also considered.

2. Approach 2: This method is the standard approach found in literature using expectation algorithm such as Welch-Baum algorithm. and described in the literature review.

Mean and covariance matrices: μ , Σ and β

The observations were modelled using mixture Gaussian distributions, characterised by a $K \times M \times N$ mean matrix: μ and a $K \times K \times M \times N$ co-variance matrix: Σ . where:

$K = \text{number of features}$, $M = \text{mixture number}$, and $N = \text{number of states}$.

The observations were grouped K classes following based on the ground-truth represented by the state sequence. The each group of observation was used as input to the EM algorithm to estimate the μ and Σ . In general, the optimal number of mixture, M is chosen empirically, in this project, it was estimated using akaike information criterion (AIC). So, gaussian mixture models were built using EM algorithm while varying the M from 1 to K , the feature number. Since AIC is a measure of information loss, the model with the minimum AIC best represents the dataset. The number of mixture M , is therefore set to the mixture number of this model. This algorithm is outlined below.

```
1 function M = best_M(data , K)
2     data = training_set
3     AIC = zeros(1, K);
4     models = cell(1, K);
5     for m = 1:K
6         model = gauss_mixture(data , m);
7         AIC(m) = model.AIC;
8     end
```

```

9  [minAIC, minAIC.Idx] = min(AIC);
10  M = minAIC.Idx;
11  end

```

The mixture components were considered evenly distributed initially. In order to avoid zero values in the covariance matrix, it was regularized with 10^{-10} . The maximum number of iteration of the EM algorithm was empirically set to 1000.

Initial state distribution: π

The initial state distribution was estimated using the probability of occurrence of each state in the training data sample. Thus, $\pi = \{\pi_i\} = \frac{|S_i|}{T}$

3.1.4 Dimension reduction

From 18 to 4 features using classification with knn

3.1.5 Continuous observations/features to Discrete observations/features

3.2 HMM implementation

Chapter 4

Results

4.1 Experiment 1: The effect of a CHMM' observation dimensionality on its performance

4.1.1 Aim of the experiment

The aim of this experiment is to investigate how the number of features impacts the accuracy of a Hidden Markov Model with continuous emission symbols (CHMM), in the absence of enough training data. Thus, the hypothesis under investigation is:

In the absence of enough training data, a CHMM with observations of high dimensionality performs poorly.

4.1.2 Apparatus

To perform this experiment, the following materials are required:

- CHMM, a continuous Hidden Markov Model specified by $\lambda = (A, \beta_{jm}, \mu_{jm}, \Sigma_{jm}, \pi)$.
- At least two sample data sets training the model and testing it.
- A criterion to rank and select subsets of features.
- A measure to evaluate the performance of the CHMM model.

4.1. EXPERIMENT 1: THE EFFECT OF A CHMM' OBSERVATION DIMENSIONALITY ON ITS PERFORMANCE

- Finally, a way to visualise the results of the experiments

4.1.3 Methods

The experiment was performed with the steps listed below:

1. Step 0 - Preliminary data pre-processing: This step consisted in the data pre-processing as described in
2. Step 1 - Partitioning data into training and test sets: Here, the dataset was randomly sampled into training and test sets. The training set was relatively small, it had 510 observations.
3. Step 2 - Feature ranking: The features were sorted in a descending order based on their ability to discriminate the different states of the CHMM. The separability index method described in was used for this purpose.
4. Step 3 - Data subset selection: Select the optimal feature subset, starting with 1 dimension.
5. Step 4 - Model building and training: The CHMM model, λ was built and trained using with training dataset using the optimal feature subset.
6. Step 5 - Model testing and evaluation: The model was tested with the test dataset. The test consisted in decoding the most likely state sequence given a previously unseen sequence of observations. This path prediction was evaluated based on the evaluation criterion presented in
7. Step 6 - Iteration: Step 3 through step 5 were repeated while varying the feature subset size until the maximum size, which is 18 in this case. In each iteration, the prediction accuracy was stored in an array for visualisation.
8. The different accuracies were finally plotted as a function of the observation dimensionality. This data is presented in the results section.

4.2 Results

4.3 Analysis

4.3.1 Discrete Probability density function duration d in state i

4.3.2 Expected number of observations (duration) in a state

4.4 Experimental Results

Chapter 5

Discussion

Here is what the results mean and how they tie to existing literature...

Discuss the relevance of your results and how they fit into the theoretical work you described in your literature review.

Chapter 6

Conclusions

These are the conclusions from the investigation and how the investigation changes things in this field or contributes to current knowledge...

Draw suitable and intelligent conclusions from your results and subsequent discussion.

Chapter 7

Recommendations

Make sensible recommendations for further work.

Use the IEEE numbered reference style for referencing your work as shown in your thesis guidelines. Please remember that the majority of your referenced work should be from journal articles, technical reports and books not online sources such as Wikipedia.

Bibliography

- [1] M. S. Tsoeu and M. Braae, “Control Systems,” *IEEE*, **vol. 34(3)**, pp. 123-129, 2011.
- [2] J. C. Tapson, *Instrumentation*, UCT Press, Cape Town, 2010.

Appendix A

Additional Files and Schematics

Add any information here that you would like to have in your project but is not necessary in the main text. Remember to refer to it in the main text. Separate your appendices based on what they are for example. Equation derivations in Appendix A and code in Appendix B etc.

Appendix B

Addenda

B.1 Ethics Forms