

Lecture 11.23

Exception Handling

SE271 Object-Oriented Programming (2020)

Yeseong Kim

Original slides from Prof. Shin at DGIST

Short Notice


- Team Project – Guideline will be released by this Friday, **but please prepare in advance!**
 - Will have a presentation with a recorded video (4 minutes for each team)
 - Will write a report (3~5 pages)

Today's Topic

- Exception Handling
 - Exception Class

[recap] Types of Errors

- Syntax errors (or syntactic errors)
 - If a program does not follow the syntax
 - Detected by compiler/interpreter before execution
 - Easiest to find and fix
- Runtime errors **How to avoid?**
 - Errors occur as the program executes
 - Errors are not detected until the flow of control reaches the problematic area of codes
 - Typically errors occurs when a certain condition holds (e.g., divide by zero)
- Semantic errors (or logical errors)
 - Usually program runs without any error, but it does not produce correct answers
 - Caused by a wrong design or implementation of the program
 - Most difficult to find and fix



```

#include <iostream>
#include <fstream>
#include <string>
#include <iomanip>
using namespace std;
int main() {
    string name, pn;
    int age;
    ofstream fout("Phonebook.bin", ios::app | ios::binary);
    getline(cin, name);
    cin >> age;
    cin.ignore(100, '\n');
    getline(cin, pn);

    fout << setw(10) << left << name;
    fout << setw(3) << age;
    fout << setw(13) << pn;
}

```

```

Alice Kim
20
010-111-2222
Bob Lee
21
010-1111-2222

```

```

Alice Kim 20 010-111-2222 Bob Lee 21 010-
1111-2222

```

What if Name includes digit?

What if age is set by negative value?

Non-number

What if phone number is strange?

More than 13 words

Input Validation

```
int main() {  
    string name, pn;  
    int age;  
    ofstream fout("Phonebook.bin",  
ios::app | ios::binary);  
    getline(cin, name);  
    cin >> age;  
    cin.ignore(100, '\n');  
    getline(cin, pn);  
  
    fout << setw(10) << left << name;  
    fout << setw(3) << age;  
    fout << setw(13) << pn;  
}
```

```
If (name is valid?) {  
    Processing...Ask age?  
  
    if (age is valid?) {  
        Processing...Ask P/N?  
  
        if (phone number is valid?) {  
  
        } else ...  
  
    } else ...  
  
} else ...
```

Exception Handling

■ Syntax

try

{

if there is an error, a system **throws** exceptions...
or a program **throws** exceptions...

}

catch (exception_parameter)

{

}

...

Example: Exception

```
#include <iostream>

using namespace std;

int main() {
    int age;
    cout << "Your age ? ";
    try{
        cin >> age;
        if (age < 0 || age >= 150)
            throw age;
        cout << "Age: " << age;
    }
    catch(int i) {
        cout << "Age( " << age << " ) is not valid. ";
    }
}
```

Your age ?

STWsourceWreposWexceptionWDebugWexception.exe

? 200

Microsoft Visual C++ Runtime Library



Debug Error!

Program:
C:\Users\WDGIST\source\repos\exception\Debug\exception.exe

abort() has been called

(Press Retry to debug the application)

Microsoft Visual Studio 디버그 콘솔

```
Your age ? 200
Age( 200 ) is not valid.
C:\Users\WDGIST\source\repos\exception\Debug\exception.exe
(33144 프로세스)이(가) 0 코드로 인해 종료되었습니다.
이 창을 닫으려면 아무 키나 누르세요.
```


Multiple catch

■ Syntax

```
try {  
    if there is an error, a system throws exceptions...  
    or a program throws exceptions...  
}  
  
catch (exception_parameter) {  
}  
  
catch (exception_parameter) {  
}  
  
catch (...) {  
    Catch-all handlers  
}  
...
```


Example: multiple catches

```
int main() {  
    string name;  
    int age;  
    try{  
        cout << "Your name ? ";  
        getline(cin, name);  
        if (name.length() > 10) throw name;  
        cout << "Your age ? ";  
        cin >> age;  
        if (age < 0 || age >= 150) throw age;  
        cout << "Age: " << age;  
    }  
    catch (int i) {  
        cout << "Age( " << i << " ) is not valid. ";  
    }  
}
```

```
int main() {  
    string name;  
    int age;  
    try{  
        cout << "Your name ? ";  
        getline(cin, name);  
        if (name.length() > 10) throw name;  
        cout << "Your age ? ";  
        cin >> age;  
        if (age < 0 || age >= 150) throw age;  
        cout << "Age: " << age;  
    }  
    catch (int i) {  
        cout << "Age( " << i << " ) is not valid. ";  
    }  
    catch (string s) {  
        cout << "Name( " << s << " ) is not valid. ";  
    }  
}
```

Nested Try and Catching

```
try{  
    throw 3;  
    try {  
        throw "test";  
  
        throw 3.5;  
    }  
    catch (int i) {  
    }  
    catch (const char* s) {  
    }  
}  
catch (double d) {  
}  
catch (...){  
}
```



stack unwinding

```
void func01() {  
    throw "func01";  
}  
  
int main(){  
    try{  
        func01();  
    }  
    catch (const char* ex) {  
        cout << "Exception at " << ex  
    }  
}
```

```
void func03() {  
    throw "func03";  
}  
  
void func02() { func03(); }  
void func01() { func02(); }  
  
int main(){  
    try{  
        func01();  
    }  
    catch (const char* ex) {  
        cout << "Exception at " << ex << endl;  
    }  
}
```

MyException Class


```
class MyException {
    int errNo;
    string errFunc, errMsg;
public:
    MyException(int n, string f, string m):
        errNo{ n }, errFunc{ f }, errMsg{ m } {}
    virtual ~MyException() {}
    void what(){
        cout << "Error[" << errNo << "] : "
        << errMsg << " at " << errFunc << endl;
    }
};

class MyDivideByZero : public MyException{
public:
    MyDivideByZero(string f) :
        MyException(100, f, "Divide by Zero") {}
};
```

```
int main() {
    int n1{ 10 }, n2{ 0 };
    cin >> n2;

    try {
        if (n2 == 0)
            throw MyException(100, "main()", "Zero");
        MyDivideByZero("main()");
    }
    catch (MyException & e) {
        e.what();
    }
}
```


Exception Class



Example: Exception Class

```
#include<exception>

int main() {
    int nSize;
    char* arr;
    cout << "Enter Array Size: ";
    cin >> nSize;
    try {
        arr = new char[nSize];
        cout << "Array (" << _msize(arr) << ") is
created.";
        delete[] arr;
    }
    catch (bad_alloc & e) {
        cout << e.what() << endl;
    }
}
```



Microsoft Visual Studio 디버그 콘솔

```
Enter Array Size: 10000000000
bad allocation

C:\Users\WDGIST\source\repos\exception\Debug\exception.exe
(27728 프로세스)이(가) 0 코드로 인해 종료되었습니다.
이 창을 닫으려면 아무 키나 누르세요.
```

Inherit from Exception Class & noexcept

```
class exception {  
public:  
    exception() noexcept;  
    exception(const exception &) noexcept;  
    virtual ~exception();  
    virtual const char * what() const noexcept;  
};
```

```
class MyException : public exception {  
public:  
    virtual const char* what() const noexcept {  
        return "my exception";  
    }  
};  
  
try {  
    throw MyException{};  
}  
  
catch (exception & e) {  
    cout << e.what();  
}
```


Uncaught Exception

```
#include <iostream>
#include <exception>
void MyErrorHandler() {
    std::cout << "Error anyway";
    exit(-1);
}
int main() {
    set_terminate(MyErrorHandler);
    try {
        throw 3.14;
    }
    catch (int i) {
    }
}
```

References

- Learn c++
 - <https://www.learncpp.com/>
 - Chapter : 14



ANY QUESTIONS?