


RS80-16NT

REVISION

-

-



NOTICE THIS DRAWING IS THE PROPERTY OF THE WOOSUNG MECHANIC IS SUBMITTED WITH THE UNDERSTANDING THAT IT IS NOT TO BE REPRODUCED,NOR COPIED,NOR LOANED OR OTHERWISE COMMUNICATED TO ANY THIRD PARTY,NOR USED IN ANY MANNER DETRIMENTAL TO THE WOOSUNG MECHANIC.WITHOUT ITS EXPRESS CONSENT.ACCEPTANCE OF THIS DRAWING WILL BE CONSTRUED AS AN AGREEMENT TO THE ABOVE.

TOLERANCE (UNLESS OTHERWISE SPECIFIED)

SIZE	STEEEL WORKS	MACHINING
30~40	±0.10	±0.10
50~70	±0.15	±0.15
70~100	±0.20	±0.20
100~150	±0.30	±0.30
150~200	±0.40	±0.40
200~300	±0.50	±0.50
300~400	±0.60	±0.60
400~500	±0.70	±0.70
500~600	±0.80	±0.80
600~700	±0.90	±0.90
700~800	±1.00	±1.00
800~900	±1.10	±1.10
900~1000	±1.20	±1.20



본 도면은 표준규격을 참고로 제작한 도면이지만 아래의 사항은 제조업체별로 상이한 규격(치수)을 가지고 있을수 있다.
따라서 설계및 적용시에는 반드시 확인하여야 합니다.

- 보스의 길이와 지름
드릴링 치수(최소~최대)

QTY : 1 EA

WEIGHT : - Kg

MATERIAL

QTY

-

PART NAME

RS80-16NT

ASSEMBLED PART No.

-

ASSEMBLED UNIT

-

MACHINE NAME

-

DESIGNED

CHECK

SCALE

DRAWING DATE

1:1

-