URL: String
- Constructed
- encodedURL

Builder: Request.Builder
- Init
- new Builder: Request.Builder()
- Constructed
- url(URL: String)
- hasURL
- post(RequestBody: RequestBody)
- header(ActionParam(propertyName=headerName), ActionParam(propertyName=headerValue))
- build()
- return Request()

Usage in url(URL: String)
Usage in post(RequestBody: RequestBody)

RequestBody: RequestBody
- Init
- create(MediaType: MediaType, Payload: String)
- Constructed

Usage in create(MediaType: MediaType, Payload: String)

Payload: String
- Constructed

Usage in create(MediaType: MediaType, Payload: String)

MediaType: MediaType
- Init
- parse(ContentType: String)
- Constructed

Usage in parse(ContentType: String)

ContentType: String
- Init
- Template
- Constructed

Request: Request
- Constructed

Usage in newCall(Request: Request)

Client: OkHttpClient
- Init
- new Client: OkHttpClient()
- Constructed
- newCall(Request: Request)
- Final
- return Call()

Call: Call
- Constructed
- execute()
- return Response()

Response: Response
- Constructed
- body()
- code()
- return ResponseBody()
- return int()

Entity: ResponseBody
- Constructed
- string()
- byteStream()
- contentLength()
- return String()
- return InputStream()
- return long()

StatusCode: int
- Constructed

Body: String
- Constructed

InputStream: InputStream
- Constructed

ContentLength: long
- Constructed