A-AXIS (0.001deg) NC ROTARY TABLE(OPTION)

AC-AXIS (0.001deg) NC ROTARY TABLE (OPTION)

SUPPORT SIDE DRIVE SIDE

AIR SEAL Ø6

A-AXIS CLAMP

[OPTION] A-AXIS UNCLAMP

SCALE AIR PURGE(OPTION) Ø6

C-AXIS CLAMP

C-AXIS UNCLAMP

[OPTION] A-AXIS CLAMP

LS151 0.38~0.45MPa A-AXIS TABLE CLAMP

LS152 0.38~0.45MPa A-AXIS TABLE UNCLAMP

LS154 0.38~0.45MPa C-AXIS TABLE CLAMP

LS155 0.38~0.45MPa C-AXIS TABLE UNCLAMP

SL150B A-AXIS TABLE CLAMP

SL150 A-AXIS TABLE UNCLAMP

SL151B C-AXIS TABLE CLAMP

SL151 C-AXIS TABLE UNCLAMP

Ø12 Ø6

0.45MPa 0.42MPa

FEEDBACK SCALE (OPTIONAL)

X-AXIS FEEDBACK UNIT

Y-AXIS FEEDBACK UNIT

Z-AXIS FEEDBACK UNIT

0.1 MPa ±5% (1 bar ±5%)

ATLM BARRIER (OPTIONAL) 0.01 µ

WORK WASH GUN

AIR BLOW GUN (OPTIONAL)

ATLM

BTS

CONFIGURATION BASED ON REQUIREMENT

4TH AXIS PNEU (OPTIONAL)

SL304 BLUM ATLM SHUTTER (OPTIONAL)

SL302 BTS/ATLM CLEANING (OPTIONAL)

TSA (OPTIONAL)

SL1782 AIR SEAT CHECK (OPTIONAL)

SL1781 AIR SEAT CHECK (OPTIONAL)

SL18 SPINDLE AIR SEAL (STD)

0.2 MPa ±5% (2 bar ±5%)

Ø4x4

LS1781 LS1782 LS1783 LS1784 LS1785 LS1786 LS1787 LS1788

AIR SEAT CHECK (OPTIONAL)

0.35 MPa ±5% (3.5 bar ±5%)

SL132B DOOR OPEN

AUTO DOOR (OPTIONAL)

DOOR CLOSE SL132A

AUTO DOOR OPEN CLOSE

0.4 MPa ±5% (4 bar ±5%)

SL130B DOOR OPEN

ROBOT DOOR (OPTIONAL)

DOOR CLOSE SL130A

ROBOT DOOR OPEN CLOSE

SPDL AIR SEAL

SPLASH GUARD LEFT FLUSH

SPLASH GUARD RIGHT FLUSH

TSC AIR SEAL (OPTION)

NOZZLE COOLANT

ATC DOOR FLUSH

ATC BOTTOM FLUSH

SPLASH GUARD FRONT BOTTOM FLUSH

FIXTURE COOLANT

AIR FROM PNEUMATIC PANEL

NZSLVLV

SLT0

SLBTF

SLT801

COOLANT MANIFOLD

TSC FLOW SWITCH LS193

PRESSURE GAUGE 0 to 3 MPa (0 to 30 bar)

MANIFOLD 3MPA TSC

PRESSURE RELIEF VALVE 3 MPa (30 bar)

COOLANT CHILLER

EVAPORATOR

INLINE FILTER 25 µ

CLOG SENSOR TSCCG

TEMP SENSOR

PRESSURE GAUGE 0.1 to 0.3 MPa (1 to 3 bar)

CYCLONE FILTER 20 µ (90%)

BAG FILTER 80 µ

M8 3MPa PUMP

STRAINER 1000µ

LS192 LOW LEVEL SENSOR

STRAINER 1mm

LS1319 LOW LEVEL SENSOR

M2 MAIN PUMP

M71 TRF PUMP

DRAIN

TSC CLEAN TANK MAX CAPACITY: 90 L USABLE COOLANT: 60L

MAIN TANK MAX CAPACITY: 520 L USABLE COOLANT: 360 L

DRUM CONVEYOR

DRUM WASH

DRUM MESH SIZE SHENGGONG MAKE: 150 µ

AUTO AIR BLOWER (OPTIONAL)

SL181

AUTO AIR BLOWER(OPTIONAL)

4TH AXIS PNEU(OPTIONAL)

AIR BLOW GUN(OPTIONAL)

AUTO/ROBOT DOOR(OPTIONAL)

FEEDBACK SCALE/ATLM BARRIER(OPTIONAL)

SOLENOID STATION(STD)

CHOKE ID 1.5mm

INLET PORT - ID Ø16 HOSE

AIR DRYER (OPTIONAL)

FRL UNIT 5 µ 0.01 µ

DRAIN

SL905 MASTER VALVE

PRESSURE SWITCH LS905 0.4 ±0.05MPa (4 ±0.05bar)

SL09 SPINDLE TAPER CLEAN

MANIFOLD

RWH

SPINDLE TAPER CLEAN

SUFFIX	REVISION	C.N.	DESCRIPTION OF CHANGE	DATE	ECO.No.	CHANGED BY
--	--	--	--	16DEC24	MV32-xxxx	----

TYPE	MODEL	APPROVED BY	CHECKED BY	DESIGNED BY	DATE
VMC	V32				16/12/24

THIRD ANGLE PROJECTION | SCALE 1 : 1 | SIZE A2

MAKINO ASIA PTE LTD

NAME 名称: PNEUMATIC CIRCUIT, STD

DWG. NUMBER 図面番号: 32VS920A2001=0 | SHEET 1/1

THIS DRAWING MUST NOT BE COPIED OR DISCLOSED TO A THIRD PARTY WITHOUT PERMISSION FROM " MAKINO".
牧野フライスに無断でのコピー・模写・その他の利用は禁止する.