DevSecOps and Cloud Security

"Deliver resilient software capability at the speed of relevance"

Application Security Analyst and DevSecOps expert

- Web and mobile Developer
- +20 Application Security Evaluation
- SANS 540 DevSecOps and Cloud Security automation
- CTF Player/ Organizer
- I love microservices
- Cloud Native Application security advocate

What you will learn

All what you need to secure your CI/CD pipeline !

Agenda

Day 1 :

Attacking and Hardening the DevOps Toolchain

Day 1 :

Attacking and Hardening the DevOps Toolchain

Lab environment overview

Role	Systems(s)
Version Control	GitLab, CodeCommit
CI/CD	Jenkins, CodePipeline
Configuration manager	Ansible, CloudFormation
Container Execution	Docker, K8s
Secret Storage	Vault
Cloud Infrastructure	AWS

Lab setup summary

- Port conflict (GITLAB/JENKINS)
- HTTPS issue in GITLAB/JENKINS integration
- Authorizing local IP addresses in GitLab for WebHooks

Day 1 :Attacking and Hardening the DevOps Toolchain

- DevOps security challenges
- DevOps toolchain

DevOps success factors

CAMS (or CALMS) is a common lens for understanding DevOps and for driving DevOps change. Your organization succeeds when it reaches "CALMS":

- Culture: people come first
- Automation: rely on tools for efficiency and repeatability
- Lean: apply Lean engineering practices to continuously learn and improve
- Measurement: use data to drive decisions and improvements
- Sharing: share ideas, information, and goals across silos

DevOps Unicorns

The DNA of DevOps and DevSecOps comes from a few early leaders or"unicorns":

- Netflix: Undifferentiated heavy lifting in the cloud, Chaos Engineering
- Amazon: You Build It... You Run It, two-pizza teams dogfooding AWS
- Google: Site Reliability Engineering, fearless shared postmortems
- Twitter: Self-service security for developers, immediate feedback
- Etsy: Security in Continuous Deployment, "a Just Culture"

CALMS: Culture

Signs of a culture that supports DevOps:

- Failures are accepted and used as learning opportunities.
  - Accept that failures can and will happen.
  - Utilize blameless postmortems to learn and improve from failures.
- Find ways to minimize impact or "blast radius."
- --Collaboration-- occurs widely across functional lines.
- Problem-solving: the problem is the enemy.
- Empower teams to take action on their own.
- Staff have a shared sense of ownership and accountability.
- --High levels of trust-- allow people to feel safe with each other.

CALMS: Automation

DevOps teams use programmable tools and cloud service APIs to:

- Take care of "undifferentiated heavy lifting" and repetitive work
- Continuously iterate and experiment in production
- Increase transparency
- Ensure consistency
- Prevent common mistakes
- Enable measurement and sharing
- Control operations at scale



CALMS: Automation "Everything as Code"

Get everything into code and check it into version control:

- Application source code/package dependencies
- Operations scripts
- Application configuration
- Tests and test scripts
- Build, deployment scripts, and runbooks
- Infrastructure provisioning and configuration
- Documentation
- Database definitions and change scripts
- Security/compliance policies
- Security tool configuration

CALMS: Lean engineering

Lean engineering improves efficiency, reduces friction, eliminates hand-offs and delays:

- Confront bureaucracy.
- Use Value Stream Mapping to identify waste, bottlenecks, and delays.
- Leverage Automation for routine work.
- Measurement: Use data to drive continuous improvements.
- Prioritize just in time-always work on what's important.

CALMS: Measurements

Measurements can help you to understand-and improve-how your teams work and where to automate:

1. Change frequency
2. Change failure/success rate
3. Correlation between change frequency and failure rate
4. MTTR recovery window instead of MTTF (time to failure)
5. Change lead time to deliver a change or fix, from check-in to deployment

CALMS: Measurements for DevSecOps

Collect security metrics along your delivery pipelines to assess how healthy your code is and how healthy your security program is.

- Measure automated test coverage for high-risk code
- Track # of vulnerabilities found… and where they were found in the pipeline
- Track # of vulnerabilities fixed
- How long vulnerabilities remain open (window of exposure)
- Type of vulnerability (OWASP Top 10) for Root Cause Analysis
- Elapsed time for security testing-make feedback loops as short as possible
- False positives versus true positives-improve quality of feedback
- Vulnerability escape rate to production

CALMS: Sharing

Information should be shared freely across the organization.

- Everyone has access to all information that they need to do their job.
- Eliminate hand-offs where information/knowledge is often lost.
  Open up communications channels across teams/functional lines.
- Chat and ChatOps, shared code repos, backlog tools, dashboards, etc.
  Share goals and accountability across Dev, Ops, and Security.
- Everyone has a stake in success and preventing failures.
  Evangelism through conferences, blogs, articles, podcasts, etc.
- DevOps has an active, open community (DevOpsDays, open-source tools...).
- Vendors have latched on to this hyperactivity.

CALMS: US DOD case study



Security culture vs DevOps

DevOps culture conflicts with traditional security culture:

- Top-down risk management instead of team-based decision-making
- Need to know restrictions versus extended information sharing
- Zero failure versus fail fast and fail forward
- Limiting change: Security is always ready to say "No!"

Security Challenges in DevOps

Powerful new technologies create opportunities for attackers-and new risks for organizations:

- Weaknesses in the DevOps toolchain can compromise the entire stack.
- Cloud platform misconfigurations can easily allow unauthorized access to data.
- Containers and orchestrators introduce a new attack surface, often not supported by traditional security scanners.
- Microservice-based architectures, new languages, and frameworks compound security guidelines.
- Delivery at the speed of DevOps requires enhanced detection and automated remediation.

Day 1 :Attacking and Hardening the DevOps Toolchain

DevOps toolchain

DevOps toolchain



Version control

- The DevOps toolchain starts with pushing code to a version control system.
- The most common version control systems include:

GitFlow

Understanding GitFlow is important for security teams to:

- Contribute to development and operations workflows
- Prevent attackers from compromising the workflow



Continuous Integration

Approving and completing a merge request creates a commit on the "main" branch and automatically triggers a pipeline:

- Ensure that changes integrate successfully with the rest of the codebase
- Executes automated unit tests and other automated checks
  - Red: no other check-ins are allowed until the build is fixed
  - Green: creates build artifacts for next steps in CD pipeline
- Fast feedback - build and test steps need to run in a few minutes to encourage iterative development (small, frequent changes)

Continuous Delivery

Pipeline model and control framework extending Continuous Integration:

- It uses the latest good build from CI, packages for deployment, and release.
- Changes are automatically pushed to test/staging environments to conduct more realistic/comprehensive tests.
- It can insert manual reviews/testing/approvals between pipeline stages.
- Log steps and results to provide audit trail from check-in to deploy.
- Any failures will "stop the line."
- No additional changes can be accepted until the failure is corrected.
- This ensures that code is always ready to be deployed.
- Changes may be batched up before production release.

Continuous Delivery vs Continuous Deployement



Continuous Deployment

Continuous Deployment is how organizations like Netflix, Etsy, and Amazon push out changes n times per day/hour/minute:

- Changes are deployed directly and automatically to production using the CD pipeline once all tests/checks pass.
- Self-service - Changes are pushed to production by developers.
- Blue/Green Deployment - Deploy changes and switch between production environments using load balancing
- Canaries - Incremental deployment that stops and rolls back if errors occur
- A/B testing - Measuring the effect/acceptance of a change or new feature in production
- Dark Launching - Protect changes behind "feature switches"

CI/CD Systems

Version control push events on the develop/main branches trigger workflow pipelines for building, testing, and deploying the changes.

Jenkins pipeline as code declarative syntax

Jenkins pipeline building a docker image

```
pipeline {
    agent { dockerfile true }
    stages {
        stage('Test') {
            steps {
                sh 'node --version'
                sh 'svn --version'
            }
        }
    }
}
```

Jenkins credential manager




```
AWS_ACCESS_ID = ${env.AWS_ACCESS_ID}
AWS_SECRET = ${env.AWS_SECRET}
```

CI/CD Attacks

SOLARWINDS

CODECOV

CI/CD Security Risks

Top 10 **CI/CD Security** Risks

CICD-SEC-1	Insufficient Flow Control Mechanisms
CICD-SEC-2	Inadequate Identity and Access Management
CICD-SEC-3	Dependency Chain Abuse
CICD-SEC-4	Poisoned Pipeline Execution (PPE)
CICD-SEC-5	Insufficient PBAC (Pipeline-Based Access Controls)
CICD-SEC-6	Insufficient Credential Hygiene
CICD-SEC-7	Insecure System Configuration
CICD-SEC-8	Ungoverned Usage of 3rd Party Services
CICD-SEC-9	Improper Artifact Integrity Validation
CICD-SEC-10	Insufficient Logging and Visibility

OWASP

DevOps toolchain summary:

Security teams must understand how the CI/CD pipeline works, the tools involved, and how the teams use them before they start looking how and where to add security checks

Day 1 :Attacking and Hardening the DevOps Toolchain

Securing DevOps toolchain

DevOps / DevSecOps

Incremental, iterative development and rapid delivery in DevOps can significantly reduce this window of exposure:

- DevOps teams follow "just-in-time prioritization"
- Automated testing cheap and safe to push out changes quickly.
- DevOps teams follow Lean techniques.
- Automated security checks in the CI/CD pipeline will catch many vulnerabilities.
- Security fixes are "standard changes".
- DevOps encourages developers and ops and security specialists to work together.

Security Champions: Breaking Down DevOps Silos

- Security experts embedded into the development organization
- Break down barriers between the central Security and DevOps teams
- Requires funding and support from upper management
- Provides several ancillary benefits:
  - The reputation of the company
  - Teaches valuable leadership skills
  - Increased employee retention

DevOps workflow

The DevOps workflow is based on five key phases:
-Manual work done before merging code into a delivery branch
-Automated Continuous Integration (CI) & Continuous Delivery (CD) process



DevOps workflow



DevOps workflow

RRA

- **Quick!** The RRA takes 30 to 60 minutes maximum.
- **Very high-level**. Details are for complete threat models. The RRA can become a complete threat model over time though!
- **Concise, readable**. Short and with clear risk levels.
- **Easy to update**. Can be run during any phase of the project development and continuously updated.
- **Informative**. Collects risk impact and a data dictionary. Also, collections information about how the service functions.
- **Let you know what to do**. The RRA includes the list of recommendations from the security team with a priority for each item.

Threat Modeling

Ask a few basic questions:

1. Are you changing the attack surface of the system in a material way? Are you adding a new API or opening a new port, adding a new user type/role, adding or changing a data store/sink, calling out to a new service or system?
2. Are you changing the technology stack? Are you adding or significantly upgrading a framework or important library or language or runtime component?
3. Are you changing security controls: authentication or session management code, cryptologic, access control code or rules, auditing logic...?
4. Are you adding confidential/sensitive data or changing data classifications?
5. Are you modifying high-risk code?

Store Markdown RRA and Threat Modeling in the repository /docs directory

Code Inventory

```
$ scc path/to/your/code
```

Language	Files	Lines	Code	Comments	Blanks
Go	112	50145	38876	5449	5838
Markdown	8	2228	1710	163	355
Shell	11	799	598	97	104
YAML	6	515	408	10	97
Total	137	53687	41670	5719	6394

Code Analysis: IDE Security Extensions

The VS Code Marketplace contains thousands of security-focused plugins:

- Semgrep
- Checkov/CFN Nag
- SonarLint/ ESLint
- Hadolint
- InSpec

Version Control Security

Version control systems and git provide workflow capabilities for locking down the remainder of the pre-commit security controls:

- Git Hooks
- Mandatory peer reviews
- Mandatory security reviews
- High risk code approvals

Git Commit Hooks

Run script automatically, checking for embedded secrets, code correctness at different point in the workflow :

- Local repository : pre-commit, commit, post-commit ...
- Remote repository: pre-receive, post-receive
- Implement team-wide workflow policies before CI

Manual Code Reviews

Take advantage of code review workflows for security reviews

- Security team sets policies and train developers on how to de security code reviews. Create a checklist for them.
- Look for problems that static analysis tools don't find.
- Tag High-risk code

Branch Protection

All version control providers provides a branch protection capability:

- Require merge requests to commit to the branch
- It defines the role that can complete a merge request.
- It prevents users to directly push to the main branch
- it enables the CodeOwners approval workflow

Code Owners

Inventory high risk code and identify groups and individuals responsible for approvals :

- Create CODEOWNERS file in the repository root directory
- Define directories or individual files in the CODEOWNERS file
- Require one or many approvers during the pull request to review changes
- The security team can participate in the GitFlow workflow

Code Owners

```
# This is a comment.
# Each line is a file pattern followed by one or more owners.
# Specify the owners for the entire repository
*       @all-developers
# Specify the owners for security-related files
/security/ @security
# Specify the owners for user experience-related files
/frontend/ @user-experience
# Example for specific files
README.md @all-developers
# Example for a specific directory
docs/ @all-developers
# Example for specific file types
*.js @all-developers
CODEOWNERS @security @admin
```

Detecting High Risk Code

Using unit tests to check if a high-risk code file changed.

```
describe('HighRiskCode Checksum Test', () => {
    const testCases = [
        { file: 'path/to/Jenkinsfile', checksum: '2bf33b66ddb07616f882ceed0718826af298a7' },
        { file: 'path/to/Dockerfile', checksum: 'fe83bf6f453698c5f78cab167bca14c72daf32c0' },
    ];
    testCases.forEach(({ file, checksum }) => {
        it(`should verify the checksum of ${file}`, () => {
            const alertSpy = sinon.spy(requestCodeReview);
            const actualChecksum = getChecksum(file);
            const match = checksum === actualChecksum;
            if (!match) {
                requestCodeReview(file);
            }
        });
    });
});
```

Security Checklist: Pull Request Templates

Markdown based templates for starting a pull request can include checklists, including security tasks



Summary

Secure your Version Control System

DevOps workflow - Security Controls



Static Analysis :

Provide fast and clear feedback on code commit:

- Run code scans in parallel with unit testing for speed.
- Run high-risk checks early in the pipeline to "fail fast."
- Do incremental scanning, if possible, as deep scanning takes too long for CI/CD, especially on large codebases,
- Set a max time limit with the dev team, alert them if the limit is breached and fix it.
- Return results directly to developers using their IDE or backlog list/tool.
- Run full/long-running scans out-of-band (nightly) or in the scanning

Minimize False Positives

Developers will tune out results if you don't tune out false positives.

- Carefully review rules to identify which checkers provide high-confidence results.
- Fail the pipeline if these checks fail.
- Turn off noisy, low-confidence checks in the pipeline-run them separately and review/qualify them manually. Feed real positive findings back to the development team's backlog.
- Periodically review and re-tune rules and configurations.
  Track and document tool configurations and decisions on which checkers or rules you disable (for compliance/governance).

SAST : Configuration management

IaC Technology	Static Code Analysis Tools
Ansible	KICS
CloudFormation	cfn_nag, Cfripper, Checkov, KICS
Terraform	Terrascan, Checkov, TFSec, KICS, ShiftLeft

SAST : Language Support

Type	Java	Node.js	Python	PHP
Code Quality	SonarQube, PMD	ESLint	Pylint, SonarQube	SonarQube, PHPStan, Psalm, Phan
Security Checker	Fortify, Checkmarx,	npm-audit, NSP	Bandit	RIPS
Bug Corrector	FindBugs	Flow	Pyflakes	Phan

SAST : Semgrep

Semgrep provides a lightweight, multi-language, extensible static analysis solution.

- Open-source
- Community driven rules
- Language support : Go, Java, JavaScript, Python ...
- Support automation !!!!!!!

SAST : Semgrep

```
semgrep --config "p/expressjs" --config custom_rules.yml /path/to/your/express/app

/path/to/your/express/app/index.js
  5:14  error  jwt-hardcoded-secret  Avoid hardcoding JWT secrets
  10:5  error  security-audit-rule   Some other security issue

2 issues
```

Semgrep : Custom rules

Custom rules can be added using the Semgrep playground to test the rule syntax :

```
rules:
- id: public-s3-policy-statement
  pattern: |
    {
      "Effect": "Allow",
      "Principal": "*",
      "Resource": [
        ..., "=~/arn:aws:s3.*/
        ", ...
      ],
      ...
    }
  message: Detected public S3
  bucket policy. This policy
  allows anyone to access
  severity: WARNING
  languages:
  - json
```

```
{
    "Version": "2012-10-17",
    "Statement": [
        {
            "Sid": "PublicReadGetObject",
            "Effect": "Allow",
            "Principal": "*",
            "Action": [
                "s3:GetObject"
            ],
            "Resource": [
                "arn:aws:s3:::example.com/*"
            ]
        },
        {
            "Sid": "CloudFront Origin Access Identity",
            "Effect": "Allow",
            "Principal": {
                "AWS": "arn:aws:iam::cloudfront:user/CloudF
                ECLOUDFRONTOAI"
```

Dependencies : Component Analysis

Dependency Checker	Supported Languages
OWASP Dependency-Check	Java, JavaScript, .NET, Python, Ruby, PHP, Node.js
retire.js	JavaScript, Node.js
safety	Python
PHP Dependency Checker	PHP

Machine Readable report

Running security tools in CI/CD requires a supported machine-readable output format.

- xUnit/JUnit
  - Standard XML schema for reporting pass/fail unit test results
- Checkstyle
  - Standard XML schema for reporting static analysis results
- SARIF (Static Analysis Results Interchange Format)
  - JSON based schema primarily used for displaying results in GitHub
- JSON
  - Custom schemas are machine-readable, but you have work to do!

Containers Security

NIST SP 800-190

Containers will force you to use different security tools and practices:

- Adopt new technologies for writing secure Dockerfiles and scanning images.
- Understand how to sign and store images securely in a registry.
- Leverage container-optimized host operating systems (e.g., Google COS) to reduce attack surface.
- Obtain container-specific runtime security appliances that manage dynamic and ephemeral containerized environments. Perimeter-based runtime defenses like IDS/IPS/WAF do not have visibility inside container networks.

Container Security life cycle

Security must shift left and consistent policies are implemented along each step of the container life cycle:

1- Pre-commit
2- Version Control
3- CI/CD
4- Container Registry
5- Container Orchestrator

Dockerfile Commands

Command	Description
`FROM`	Specifies the base image to use for the Docker image.
`LABEL`	Adds metadata to the image, such as a maintainer or version.
`RUN`	Executes a command in a new layer on top of the current image and commits the results.
`CMD`	Provides the default command to run when the container starts. Can be overridden with `docker run`.
`ENTRYPOINT`	Configures a container to run as an executable. Unlike `CMD`, it is not overridden by the `docker run` command.
`WORKDIR`	Sets the working directory for any `RUN`, `CMD`, `ENTRYPOINT`, `COPY`, and `ADD` instructions that follow it.
`COPY`	Copies new files or directories from `<src>` and adds them to the file system of the container at the path `<dest>`.
`ADD`	Similar to `COPY` but can also extract local tar archives and download remote files.
`ENV`	Sets an environment variable.
`EXPOSE`	Informs Docker that the container listens on the specified network ports at runtime.
`USER`	Sets the username or UID to use when running the image and for any `RUN`, `CMD`, and `ENTRYPOINT` instructions that follow it.
`VOLUME`	Creates a mount point with the specified path and marks it as holding externally mounted volumes from native host or other containers.
`ARG`	Defines a variable that users can pass at build-time to the builder with the `docker build` command.

Hunt The Bug

```
FROM mcr.rnicrosoft.com/dotnet/core/sdk:2.2
ARG ENVIRONMENT=prod
ENV ASPNETCORE ENVIRONMENT=$(ENVIRONMENT}
ENV CERTIFICATE_PASSPHRASE-mycertpassphrase
RUN apt-get update && apt-get install -y libss1-dev=1.1*
COPL cert.conf -/cert.conf
RUN openssl reg -x509 -nodes -days 3650 -newkey rsa:4096 -keyout app.key
-out app.ert -config cert.cont -passin pass:$(CERTIFICATE_PASSPHRASE)
RUN openssl pkcsl2 -export -out app.pfx -inkey app.key -in app.crt
-passout pass: $(CERTIFICATE_PASSPHRASE]
USER root
WORKDIR /WWW
ENTRYPOINT ["dotnet", "Sans. CreditUnion API.dil"1]
```

Container Security : Pre-commit

Container security starts upfront the pre-commit phase with policies:

- SAST for Dockerfile misconfiguration
- Locking down the base image supply chain
- Installing approved binaries inside a base image
- Using multi-stage builds to create minimalistic images
- Passing build time secrets to image build commands

SAST for Dockerfiles

Tool	Description
Hadolint	A linter for Dockerfiles that helps you build best practice Docker images by providing tips.
KICS	An open-source tool that finds security vulnerabilities, compliance issues, and misconfigurations in IaC.
Dockerfilelint	A linter for Dockerfiles to ensure adherence to best practices.
dockerfile-lint	Another linter for Dockerfiles focusing on best practices and potential issues.

Hadolint

Hadolint parses Dockerfiles into Abstract Syntax Trees (AST) and runs rules:

- Supports an approved list of trusted registries
- Suppress false positives via inline comments or a configuration file
- Export formats include checkstyle, sarif, and json

```
$ hadolint --trusted-regestry gcr.io ./Dockerfile
Dockerfile:4 DL3008 warning: Pin versions in apt-get install. Instead of `apt-get install -y python3` use `apt-get install -y python3=<version>`
Dockerfile:7 DL3018 info: Pin versions in pip. Instead of `pip install -r requirements.txt` use `pip install -r requirements.txt && pip freeze > requirements.txt`
Dockerfile:9 DL4000 warning: MAINTAINER is deprecated
Dockerfile:10 DL3020 error: Use COPY instead of ADD for files and folders
Dockerfile:14 DL3025 info: Use arguments JSON notation for CMD and ENTRYPOINT commands
```

Supply chain hardening

MITRE ATT&CK Containers T1525: Implant Internal Image

- Images from public registries may contain vulnerabilities or malware, easy and common attack vector
- Mitigations:
  - Building inventory of approved base images
  - Downloading base images from trusted suppliers
  - Scanning base images for vulnerabilities
  - Creating a private container registry
  - Signing custom images and storing in a private registry

Container image trusted suppliers

- Docker hub (Verified Publisher)
- Platform One Iron Bank
- MCR
- ECR Gallery

Conftest - Trusted supplier policy

The big difference between Contest and a static analysis engine like hadolunt is the ability to wnte custom tests using the Open Policy Agent (OPA - pronounced oh-pa) Rego query language. The example above shows how to create a trusted images Rego policy.

```
package main
trusted_suppliers = ["ubuntu:20.04", "alpine:3.13", "node:14-alpine"]
deny[msg] {
    input[i].Cmd == "from"
    image := input[i].Value
    not image in trusted_suppliers
    msg = sprintf("The image '%s' is not from a trusted supplier.", [image])
}
```

Conftest - Trusted supplier policy

Pre-commit hooks can validate conftest policies for trusted base images and package install commands:

```
$ conftest test --namespace image, install Dockerfile
```

- Failing policies are shown in the console output
- Optional output formats for table, junit and json

```
FAIL - Dockerfile - image - [untrusted_supplier] Untrusted supplier identified: mer.rnicrosoft.com/dotnet/core/sdk:2.2
FAIL - Dockerfile - install - [install_command] Disallowed command found: ["apt-get update &s apt-get install -y libss1-dev=1.1**]
2 tests, 0 passed, 0 warnings, 2 failures, 0 exceptions
```

Minimal image with multi-stage Builds

Multi-stage builds use multiple FROM statements to differentiate "development" from "runtime" base images.

- Stage 1 uses a base image with an SDK to build the application (1.5GB)
- Stage 2 copies the binaries into an Alpine runtime image (120MB)

```
FROM mcr.microsoft.com/dotnet/nightly/sdk:6.0 AS build
COPY ./Web/  ./Web/
RUN dotnet publish "./Web/Website.csproj" -c Release -o /app/bin
FROM mcr.microsoft.com/dotnet/nightly/runtine:6.0.2-alpine3.15
WORKDIR /www
COPY --fron-build /app/bin ./ ENTRYPOINI ["dotnet", "Website.dll"]
```

Configure Build Time Secrets

Docker BuildKit supports build secrets (--secrets) to help developers avoid hard-coding secrets in Dockerfiles and environment variables:

```
COPY cert.conf /cert.conf
RUN --mount-type-secret, id-passphrase openssl req -x509 -nodes -days 3650 - newkey rsa: 4096 -keyout app.key -out app.ert -config cert.conf
-passin file: ///run/secrets/passphrase
RUN --mount-type-secret, id-passphrase openssl pkes12 -export -out app.pfx - inkey app.key -in app.ert -passout file: ///run/secrets/passphrase
```

Running the docker build command, setting the tag, and configuring a build time secret:

```
echo $ (CERTIFICATE_PASSPHRASE) > passphrase
docker build --tag dntools/base: insecure --secret id-passphrase, sro-passphrase --file Dockertile
```

Docker scan

- Scan images and Dockerfiles with docker scan CLI (Snyk) before committing Dockerfile
- Requires Docker Hub account to run scan locally

```
$ docker scan --file./Dockerfile
X Critical severity vuinerability found in Curl/1ibcur13
Description: Double Free
Into: https: //snyk.10/vuln/SNYK-DEBIAN9-CURI-466508
```

Container Security - CI/CD

Merge requests triggering CI/CD workflows responsible for building and releasing container images must certify the image:

- Enforce pre-commit controls and validate results.
- Build a release candidate image and perform in-depth scanning for vulnerabilities.
- Sign the release candidate image, tagging for production, and pushing to the container registry.

Open Source Container Scanning Tools

- Anchore
- Docker Bench
- OpenSCAP plugin
- Trivy

Trivy Image Scanning

- Scannning the container image in CI/CD
- Output format : table, json, sarif ...

Cosign Container Image Scanning

- Cosign support artifact signings
- Signing key storage in AWS, Azure, GCP, VAULT, and on premise

```
$ docker push 123456789012.dkr.ecr.us-west-2.amazonaws.com/api-image:1.4
$ cosign sign --key awskms:///alias/dm/cosign 123456789012.dr.ecr.us-west-2.amazonaws.com/api-image:1.4

1.4: digest: sha256:b30e9b9aße0e29d1852c07825dcca52d51ad58920849851747c64a5379bb1a95 size: 1793
Pushing signature to: 123456789012.dkr.ecr.us-west-2.amazonaws.com/api-image
```

Container Security - Registry

Private container registries storing production images are the bridge between development and operations:

- They store image signature metadata for validation.
- They enforce strict access control on registry read and write operations.
- They are continuously scanning registries for new vulnerabilities and sending notifications.

AWS ECR - Best practices

AWS Elastic Container Registry (ECR) security best practices:

- Isolate container registries in a dedicated DevOps account
- Restrict access using resource-based and identity-based IAM policies for cross-account access
- Protect production images from corruption or deletion with immutable tagging
- Enable basic container image scanning

Container Security - Runtime

Container runtimes and orchestrators are responsible for pulling registry images and managing the workloads:

- Review security hardening guides for the selected runtime
- Admission controllers validate image signatures and security
- requirements
- Runtime security appliances inspect network traffic, monitor lateral communications, quarantine containers, and run vulnerability scans