

FaceForge Core

This folder contains the **Core API service** (planned: FastAPI + Uvicorn).

Repo structure (Core)

If you're trying to find things quickly:

```
core/
  src/faceforge_core/
    __main__.py      # `python -m faceforge_core` entrypoint
    app.py           # FastAPI app wiring
    api/v1/          # versioned HTTP routes
    auth.py          # install-token auth helpers
    config.py         # config loading + path resolution
    home.py          # FACEFORGE_HOME + layout contract
    db/              # SQLite schema + migrations + queries
    internal/        # internal CLIs (dev/admin helpers)
  tests/             # pytest tests
  pyproject.toml     # packaging/dependencies
```

Sprint 1: home/config/runtime contract

Core is **local-first** and writes all persistent/runtime files under FACEFORGE_HOME.

FACEFORGE_HOME

- If FACEFORGE_HOME is set, Core uses that directory.
- If it is not set, Core defaults to a per-user OS data directory (never relative to the working directory):
 - Windows: %LOCALAPPDATA%\FaceForge
 - macOS: ~/Library/Application Support/FaceForge
 - Linux: \$XDG_DATA_HOME/faceforge (or ~/.local/share/faceforge)

Required subfolders

On startup, Core ensures these directories exist:

- \${FACEFORGE_HOME}/db

- `${FACEFORGE_HOME}/s3`
- `${FACEFORGE_HOME}/assets`
- `${FACEFORGE_HOME}/logs`
- `${FACEFORGE_HOME}/tmp`
- `${FACEFORGE_HOME}/config`
- `${FACEFORGE_HOME}/tools`
- `${FACEFORGE_HOME}/plugins`

Core config file

Core loads JSON config from:

- `${FACEFORGE_HOME}/config/core.json`

If the file does not exist, defaults are used.

Current config shape (v1, subject to change):

```
{
  "version": "1",
  "auth": {
    "install_token": "...",
  },
  "network": {
    "bind_host": "127.0.0.1",
    "core_port": 8787,
    "seaweed_s3_port": null
  },
  "paths": {
    "db_dir": null,
    "s3_dir": null,
    "logs_dir": null,
    "plugins_dir": null
  },
  "tools": {
    "exiftool_enabled": true,
    "exiftool_path": null
  },
  "storage": {
    "routing": {
      "default_provider": "fs",
      "kind_map": {},
      "s3_min_size_bytes": null
    },
    "s3": {
```

```

        "enabled": false,
        "endpoint_url": null,
        "access_key": null,
        "secret_key": null,
        "bucket": "faceforge",
        "region": "us-east-1",
        "use_ssl": false
    },
    "seaweed": {
        "enabled": false,
        "weed_path": null,
        "data_dir": null,
        "ip": "127.0.0.1",
        "master_port": 9333,
        "volume_port": 8080,
        "filer_port": 8888,
        "s3_port": null
    }
}

```

Notes:

- paths.* may be absolute paths or paths relative to FACEFORGE_HOME.
- tmp/ and config/ are intentionally **not configurable**.

Runtime ports file

Desktop (or other launcher) may write the selected ports to:

- \${FACEFORGE_HOME}/config/ports.json

Format:

```

{
    "core": 43210,
    "seaweed_s3": 43211
}

```

Core also supports a legacy location for compatibility with the design spec:

- \${FACEFORGE_HOME}/runtime/ports.json

Desktop integration (Sprint 12)

FaceForge Desktop (Tauri) is responsible for the first-run wizard and process orchestration.

Desktop writes (or updates):

- `${FACEFORGE_HOME}/config/ports.json` (selected ports)
- `${FACEFORGE_HOME}/config/core.json` (network + auth token; optional S3 config)

Desktop then starts Core with:

- `FACEFORGE_HOME` set to the chosen directory
- `FACEFORGE_BIND=127.0.0.1` (localhost-only by default)

For browser usage, the Core UI requires logging in once at `/ui/login` (pastes the install token and stores it in an `HttpOnly` cookie).

Dev run

From the repo root (Windows PowerShell):

- `./scripts/dev-core.ps1`
- `./scripts/check-core.ps1` (format + lint + tests)
- `./scripts/build-core.ps1` (builds a local `core/dist/faceforge-core.exe`)

Build outputs note:

- `./scripts/build-core.ps1` will automatically prune old timestamped `core/build-*` and `core/dist-*` folders left behind by prior locked builds.
- If you want to keep build history for debugging, run: `./scripts/build-core.ps1 - KeepBuildHistory`
- If `core/build` or `core/dist` cannot be deleted (e.g. you have a terminal opened inside those folders), the build now fails with a clear message instead of creating timestamped folders. To opt into the old fallback behavior, run: `./scripts/build-core.ps1 - AllowTimestampFallback`

This repo is set up to avoid relying on a global Python for running commands. The scripts create/use the repo-local `.venv` and always run via `.venv\Scripts\python.exe`.

Prereq: Python 3.12+ installed (used only to bootstrap the repo-local `.venv`).

The service should come up on `http://127.0.0.1:8787` and expose:

- `GET /healthz`

- GET /docs (public)
- GET / (redirects to Web UI)

Sprint 11: Core Web UI MVP

Core serves a small, server-rendered Web UI (no runtime Node) intended for basic, non-technical workflows.

Routes:

- GET /ui/login (public): paste the install token and sign in
- POST /ui/login: sets an HttpOnly cookie
- POST /ui/logout: clears the cookie
- GET /ui/entities: browse/create entities (table/gallery)
- GET /ui/entities/{entity_id}: entity detail
(overview/descriptors/attachments/relationships)
- GET /ui/jobs: job list + start bulk-import
- GET /ui/jobs/{job_id}: job details + logs
- GET /ui/plugins: list discovered plugins, enable/disable, edit config

API endpoints (v1):

- GET /v1/ping (requires token)
- GET /v1/system/info (requires token)
- GET /v1/entities (requires token)
- POST /v1/entities (requires token)
- GET/PATCH/DELETE /v1/entities/{entity_id} (requires token)
- POST /v1/assets/upload (requires token; multipart)
- GET /v1/assets/{asset_id} (requires token)
- GET /v1/assets/{asset_id}/download (requires token; streaming + Range)
- POST /v1/assets/bulk-import (requires token; starts a job)
- POST /v1/entities/{entity_id}/assets/{asset_id} (requires token; link)
- DELETE /v1/entities/{entity_id}/assets/{asset_id} (requires token; unlink)
- POST /v1/jobs (requires token)
- GET /v1/jobs (requires token)
- GET /v1/jobs/{job_id} (requires token)

- GET /v1/jobs/{job_id}/log (requires token; pollable)
- POST /v1/jobs/{job_id}/cancel (requires token)
- GET /v1/admin/field-defs (requires token)
- POST /v1/admin/field-defs (requires token)
- GET /v1/admin/field-defs/{field_def_id} (requires token)
- PATCH /v1/admin/field-defs/{field_def_id} (requires token)
- DELETE /v1/admin/field-defs/{field_def_id} (requires token)
- GET /v1/entities/{entity_id}/descriptors (requires token)
- POST /v1/entities/{entity_id}/descriptors (requires token)
- PATCH /v1/descriptors/{descriptor_id} (requires token)
- DELETE /v1/descriptors/{descriptor_id} (requires token)
- POST /v1/relationships (requires token)
- GET /v1/relationships?entity_id=... (requires token)
- DELETE /v1/relationships/{relationship_id} (requires token)
- GET /v1/relation-types?query=... (requires token)
- GET /v1/plugins (requires token)
- POST /v1/plugins/{plugin_id}/enable (requires token)
- POST /v1/plugins/{plugin_id}/disable (requires token)
- GET /v1/plugins/{plugin_id}/config (requires token)
- PUT /v1/plugins/{plugin_id}/config (requires token)

Auth (Sprint 3)

Core requires a per-install token for non-health endpoints.

- The token is stored in `${FACEFORGE_HOME}/config/core.json` under `auth.install_token`.
- Requests may provide the token via:
 - Authorization: Bearer <token>
 - X-FaceForge-Token: <token>

Browser UI support:

- The Web UI can store the token in an HttpOnly cookie named `ff_token` (set by POST `/ui/login`).
- This makes browser downloads (e.g. GET `/v1/assets/{asset_id}/download`) work without manually setting headers.

Sprint 10: Plugins (discovery + registry)

Core discovers plugin manifests under `${FACEFORGE_HOME}/plugins/*/plugin.json` and stores metadata/config in the `plugin_registry` table.

The v1 endpoints under `/v1/plugins` expose discovery results, enable/disable state, and a JSON Schema-validated config document.

Manifest format (plugin.json)

Minimal example:

```
{
  "id": "demo.plugin",
  "name": "Demo Plugin",
  "version": "0.1.0",
  "capabilities": ["ui"],
  "config_schema": {
    "type": "object",
    "properties": {
      "example_flag": {"type": "boolean", "description": "Example option"}
    }
  }
}
```

Supported fields today (best-effort discovery):

- `id` (required): stable plugin identifier.
- `name` (required)
- `version` (optional)
- `capabilities` (optional list)
- `config_schema` (optional object): JSON Schema used to validate PUT `/v1/plugins/{plugin_id}/config`.

Notes:

- Discovery is best-effort: invalid manifests are ignored.

- `/v1/plugins/{plugin_id}/...` is reserved for future plugin routes (plugin compute is not implemented in Core).

Sprint 2: SQLite schema + migrations (internal)

Core stores metadata in a SQLite DB under:

- `${FACEFORGE_HOME}/db/core.sqlite3`

On Core startup, schema migrations are applied automatically (idempotent).

Apply migrations and create sample records without using the API:

1) Run `./scripts/dev-core.ps1` once (it installs Core editable into `.venv`). 2) Then invoke internal modules using the venv Python:

- `.\.venv\Scripts\python.exe -m faceforge_core.internal.bootstrap_db --home <PATH> --migrate`
- `.\.venv\Scripts\python.exe -m faceforge_core.internal.bootstrap_db --home <PATH> --create-entity "Ada Lovelace"`
- `.\.venv\Scripts\python.exe -m faceforge_core.internal.bootstrap_db --home <PATH> --create-asset <FILEPATH>`

Sprint 4: Entities CRUD (v1)

Endpoints:

- GET `/v1/entities`
- POST `/v1/entities`
- GET `/v1/entities/{entity_id}`
- PATCH `/v1/entities/{entity_id}`
- DELETE `/v1/entities/{entity_id}` (soft delete)

List query params (minimal primitives):

- `limit` (default 50, max 200)
- `offset` (default 0)
- `sort_by`: `created_at` | `updated_at` | `display_name`
- `sort_order`: `asc` | `desc`
- `q`: substring match (basic)
- `tag`: filter by exact tag string

Sprint 5: Assets v1 (filesystem provider)

Upload

- POST /v1/assets/upload
 - Multipart field file (required)
 - Multipart field meta (optional): companion JSON sidecar (commonly _meta.json)

Example (PowerShell):

- Invoke-WebRequest -Headers @{ Authorization = "Bearer <token>" } -Form @{ file = Get-Item .\myfile.bin; meta = Get-Item ._meta.json } http://127.0.0.1:8787/v1/assets/upload

Metadata

- GET /v1/assets/{asset_id}

Download (streaming + resume)

- GET /v1/assets/{asset_id}/download
- Supports Range: bytes=... (single range)

Example (curl):

- curl -H "Authorization: Bearer <token>" -H "Range: bytes=0-1048575" -o first-1mb.bin http://127.0.0.1:8787/v1/assets/<asset_id>/download

Sprint 9: Jobs + structured logs + bulk import

Core exposes a minimal durable job model backed by SQLite:

- Jobs are created with status queued and executed in-process.
- Logs are append-only and stored in job_logs with timestamps and levels.
- Cancellation is cooperative: POST /v1/jobs/{job_id}/cancel requests cancellation and the worker stops at a safe point.

Create a bulk import job

- POST /v1/assets/bulk-import
 - Body: { "path": "...", "recursive": true, "kind": "file" }

- Response: { job_id, job_type, status, created_at }

Then poll:

- GET /v1/jobs/{job_id} (status + progress)
- GET /v1/jobs/{job_id}/log?after_id=0 (logs; use next_after_id for incremental polling)

Link/unlink to entities

- POST /v1/entities/{entity_id}/assets/{asset_id} (optional JSON body: { "role": "..."})
- DELETE /v1/entities/{entity_id}/assets/{asset_id}

ExifTool metadata extraction (best-effort)

On upload, Core will attempt to run ExifTool in the background (if available) and store extracted JSON under the asset meta.metadata[] list.

Configuration:

- \${FACEFORGE_HOME}/config/core.json → tools.exiftool_enabled (default true)
- \${FACEFORGE_HOME}/config/core.json → tools.exiftool_path (optional override)

Sprint 7: Descriptors + Field Definitions (admin)

FaceForge Core supports a small “flexible schema without migrations” layer:

- Admin creates **field definitions** (scope + key + type + validation rules)
- API accepts **descriptors** immediately once a field definition exists
- Invalid descriptor values are rejected with a clear validation_error response

Field definitions

- GET /v1/admin/field-defs (optional query: scope=...)
- POST /v1/admin/field-defs
- GET /v1/admin/field-defs/{field_def_id}
- PATCH /v1/admin/field-defs/{field_def_id}
- DELETE /v1/admin/field-defs/{field_def_id} (soft delete)

Field definition fields:

- scope (string; default descriptor)
- field_key (string)
- field_type (string; supports string, int, float, bool, enum, json)
- required (bool)
- regex (string; string only)
- options (object; for enum, use { "options": ["a", "b"] })

Descriptors

- GET /v1/entities/{entity_id}/descriptors
- POST /v1/entities/{entity_id}/descriptors
- PATCH /v1/descriptors/{descriptor_id}
- DELETE /v1/descriptors/{descriptor_id} (soft delete)

Descriptors are validated against the matching field definition (scope + field_key).

Bundling/embedding requirement:

- Core does **not** search your system PATH for exiftool.
- If tools.exiftool_path is not set, Core only checks bundled locations under \${FACEFORGE_HOME}/tools, using these candidate paths:
 - Windows: \${FACEFORGE_HOME}/tools/exiftool.exe or
\${FACEFORGE_HOME}/tools/exiftool/exiftool.exe
 - macOS/Linux: \${FACEFORGE_HOME}/tools/exiftool or
\${FACEFORGE_HOME}/tools/exiftool/exiftool

Sprint 6: SeaweedFS provider + “default local S3” wiring

Core can optionally store asset bytes in an **S3-compatible backend** (intended: SeaweedFS S3 endpoint), while still supporting filesystem-only mode.

Storage routing (upload-time)

Uploads are routed based on:

- storage.routing.kind_map (highest priority)
- storage.routing.s3_min_size_bytes (optional)
- storage.routing.default_provider

If routing selects s3 but the endpoint is not reachable, Core **falls back to filesystem** automatically.

S3 configuration

Set these in `${FACEFORGE_HOME}/config/core.json`:

- `storage.s3.enabled`: enable S3 provider
- `storage.s3.endpoint_url`: optional; if omitted, Core derives from `network.bind_host` + `network.seaweed_s3_port`
- `storage.s3.access_key` / `storage.s3.secret_key`: credentials for the endpoint
- `storage.s3.bucket`: default bucket name (Core will create it best-effort)

SeaweedFS “managed binary” contract (optional)

Desktop will orchestrate SeaweedFS later, but Core can optionally start it for dev/testing if you set `seaweed.enabled=true` and provide the weed binary under `${FACEFORGE_HOME}/tools`.

Binary resolution order:

- `seaweed.weed_path` (absolute or relative to `${FACEFORGE_HOME}/tools`)
- Otherwise, Core checks:
 - Windows: `${FACEFORGE_HOME}/tools/weed.exe`,
`${FACEFORGE_HOME}/tools/seaweedfs/weed.exe`,
`${FACEFORGE_HOME}/tools/seaweed/weed.exe`
 - Non-Windows: analogous paths without `.exe`

Core-managed runner:

- `weed server -s3 ...` with ports from `seaweed.*` (and/or `network.seaweed_s3_port`)
- Data dir defaults to `${FACEFORGE_HOME}/s3/seaweedfs` (override via `seaweed.data_dir`)

Dev helper CLI:

- `.\.venv\Scripts\python.exe -m faceforge_core.internal.seaweedfs_cli --home <FACEFORGE_HOME> --health`
- `.\.venv\Scripts\python.exe -m faceforge_core.internal.seaweedfs_cli --home <FACEFORGE_HOME> --run`
- If `tools.exiftool_path` is a relative path, it is resolved relative to `${FACEFORGE_HOME}/tools`.

Core skips ExifTool processing for filenames matching the exclusions defined in `core/src/faceforge_core/ingest/exiftool.py`.