

PYTHON - SE - BACKEND

SOFTWARE ENGINEERING – MODULE 4

Database Management – SQL & PL/SQL

SESSION / ASSIGNMENT – 2

TASKS :

1. Open MySQL Workbench or CLI and write a CREATE TABLE statement to create a table called 'restaurants' with columns: id (INT, primary key, auto-increment), name (VARCHAR(100)), location (VARCHAR(100)), and rating (DECIMAL(2,1)).

→ CODE:

```
CREATE TABLE restaurants (  
    id INT PRIMARY KEY AUTO_INCREMENT,  
    name VARCHAR(100),  
    location VARCHAR(100),  
    rating DECIMAL(2,1)  
);
```

```
SELECT * FROM restaurants;
```

OUTPUT:

✓ MySQL returned an empty result set (i.e. zero rows). (Query took 0.0014 seconds.)

```
SELECT * FROM restaurants;
```

☐ Profiling [[Edit inline](#)] [[Edit](#)] [[Explain SQL](#)] [[Create PHP code](#)] [[Refresh](#)]

id	name	location	rating
----	------	----------	--------

2. Use the ALTER TABLE command in MySQL to add a new column 'average_cost' (INT) to your 'restaurants' table.

Hint: Remember to specify the data type when adding a new column.

➔ CODE:

```
ALTER TABLE restaurants
ADD COLUMN average_cost INT;

SELECT * FROM restaurants;
```

OUTPUT:

✓ MySQL returned an empty result set (i.e. zero rows). (Query took 0.0005 seconds.)

```
ALTER TABLE restaurants ADD COLUMN average_cost INT;
```

[Edit inline] [Edit] [Create PHP code]

✓ MySQL returned an empty result set (i.e. zero rows). (Query took 0.0004 seconds.)

```
SELECT * FROM restaurants;
```

☐ Profiling [Edit inline] [Edit] [Explain SQL] [Create PHP code] [Refresh]

id	name	location	rating	average_cost
----	------	----------	--------	--------------

3. Write a SQL statement to DROP the 'restaurants' table you created earlier. Double-check your command before running it to avoid accidental data loss.

➔ CODE:

```
DROP TABLE restaurants;
```

OUTPUT:

Show query box

✓ MySQL returned an empty result set (i.e. zero rows). (Query took 0.0060 seconds.)

```
DROP TABLE restaurants;
```

[Edit inline] [Edit] [Create PHP code]

4. Create a new table called 'playlists' for a music app like Spotify, with columns: playlist_id (INT, primary key, auto-increment), title (VARCHAR(50)), created_by (VARCHAR(50)), and created_at (DATE).

➔ **CODE:**

```
CREATE TABLE playlists (  
    playlist_id INT PRIMARY KEY AUTO_INCREMENT,  
    title VARCHAR(50),  
    created_by VARCHAR(50),  
    created_at DATE  
);  
SELECT * FROM playlists;
```

OUTPUT:

✔ MySQL returned an empty result set (i.e. zero rows). (Query took 0.0004 seconds.)

```
CREATE TABLE playlists ( playlist_id INT PRIMARY KEY AUTO_INCREMENT, title VARCHAR(50), created_by VARCHAR(50), created_at DATE );
```

[[Edit inline](#)] [[Edit](#)] [[Create PHP code](#)]

✔ MySQL returned an empty result set (i.e. zero rows). (Query took 0.0012 seconds.)

```
SELECT * FROM playlists;
```

☐ Profiling [[Edit inline](#)] [[Edit](#)] [[Explain SQL](#)] [[Create PHP code](#)] [[Refresh](#)]

playlist_id	title	created_by	created_at
-------------	-------	------------	------------