



Digital Design Verification

FYP/Internship Program

Lab 06- Link List

Name: Abdul Hadi Afzal

Date: 9 April 2025

Contents

Task1:.....2

Task2:.....5

Task3:.....8

CONCLUSION:14

Task1:

SS:

```
HP@haadi MSYS /c/Users/HP/Desktop/LCDC/LAB6/LAB6
# ./decode
inserted symbol: a
inserted symbol: b
inserted symbol: c
inserted symbol: d
inserted symbol: e
inserted symbol: f
inserted symbol: g
Decoding completed. Output saved in decoded.txt
```



decoded.txt - Notepad

File Edit Format View Help

abbacafabad

CODE:

Decode.c

```
/**
 * Author: Abdul Hadi Afzal
 * Task: Lab 6 - Huffman Decoder (Task 1: Decompress encoded file)
 */

#include <stdio.h>
#include <stdlib.h>
#include <string.h>

#define MAX_SYMBOLS 255
#define MAX_LEN 10

// Huffman tree node structure
struct tnode {
    struct tnode* left;
    struct tnode* right;
```

```

        int isleaf;
        char symbol;
    };

    // Global root of the Huffman tree
    struct tnode* root = NULL;

    /**
     * @function talloc
     * @desc Allocates a new tree node
     */
    struct tnode* talloc() {
struct tnode* p = (struct tnode*)malloc(sizeof(struct tnode));
        if (p != NULL) {
            p->left = p->right = NULL;
            p->symbol = 0;
            p->isleaf = 0;
        }
        return p;
    }

    /**
     * @function build_tree
     * @desc Builds the Huffman tree from symbol-code mapping in code.txt
     */
    void build_tree(FILE* fp) {
        char symbol;
        char strcode[MAX_LEN];
        int items_read, i, len;
        struct tnode* curr = NULL;

        while (!feof(fp)) {
            items_read = fscanf(fp, " %c %s\n", &symbol, strcode);
            if (items_read != 2) break;

            curr = root;
            len = strlen(strcode);

            for (i = 0; i < len; i++) {
                if (strcode[i] == '0') {
                    if (curr->left == NULL)
                        curr->left = talloc();
                    curr = curr->left;
                } else if (strcode[i] == '1') {
                    if (curr->right == NULL)
                        curr->right = talloc();
                    curr = curr->right;
                }
            }

            curr->isleaf = 1;
            curr->symbol = symbol;
            printf("inserted symbol: %c\n", symbol);
        }
    }

    /**

```

```

        * @function decode
* @desc Decodes binary input using the Huffman tree and writes to output
        */
        void decode(FILE* fin, FILE* fout) {
            char c;
            struct tnode* curr = root;

            while ((c = getc(fin)) != EOF) {
                if (c == '0')
                    curr = curr->left;
                else if (c == '1')
                    curr = curr->right;
                else
                    continue; // ignore unexpected characters like newline, space

                if (curr->isleaf) {
                    fputc(curr->symbol, fout);
                    curr = root;
                }
            }

            /**
        * @function freetree
* @desc Recursively frees memory for Huffman tree
        */
        void freetree(struct tnode* root) {
            if (root == NULL)
                return;
            freetree(root->left);
            freetree(root->right);
            free(root);
        }

        /**
        * @function main
* @desc Entry point: builds tree from code.txt, decodes encoded.txt to
        decoded.txt
        */
        int main() {
            const char* IN_FILE = "encoded.txt";
            const char* CODE_FILE = "code.txt";
            const char* OUT_FILE = "decoded.txt";

            FILE* fout;
            FILE* fin;

            root = malloc(); // allocate root node

            // Build tree from code.txt
            fin = fopen(CODE_FILE, "r");
            if (!fin) {
                perror("Error opening code.txt");
                return 1;
            }
            build_tree(fin);
            fclose(fin);

```

```

        // Decode encoded.txt
        fin = fopen(IN_FILE, "r");
        fout = fopen(OUT_FILE, "w");
        if (!fin || !fout) {
            perror("Error opening input/output files");
            return 1;
        }

        decode(fin, fout);
        fclose(fin);
        fclose(fout);

        // Free memory
        freetree(root);

    printf("Decoding completed. Output saved in decoded.txt\n");
    getchar(); // pause the program
    return 0;
}

```


Task2:

SS:

```


# ./encode.exe
built code: g -> 0
built code: a -> 10000
built code: b -> 10001
built code: c -> 1001
built code: d -> 101
built code: e -> 110
built code: f -> 111
original: abba cafe bad
encoded: 100001000110001100001001100001111101000110000101

```

 encoded.txt - Notepad

File Edit Format View Help

100001000110001100001001100001111101000110000101

 code.txt - Notepad

File Edit Format View Help

a 10000

b 10001

c 1001

d 101

e 110

f 111

g 0

CODE:

Encoded.c

/**

* Author: Abdul Hadi Afzal

```

* Task: Lab 6 - Huffman Encoder (Task 2: Encode sample string using fixed
    frequencies)
    */

#include <stdio.h>
#include <stdlib.h>
#include <string.h>

#define MAX_SYMBOLS 255
#define MAX_LEN 10

struct tnode {
    struct tnode* left;
    struct tnode* right;
    struct tnode* parent;
    struct tnode* next;
    float freq;
    int isleaf;
    char symbol;
};

// Global variables
char code[MAX_SYMBOLS][MAX_LEN];
struct tnode* root = NULL;
struct tnode* qhead = NULL;

// Allocate new node
struct tnode* talloc(int symbol, float freq) {
    struct tnode* p = (struct tnode*)malloc(sizeof(struct tnode));
    if (p) {
        p->left = p->right = p->parent = p->next = NULL;
        p->symbol = symbol;
        p->freq = freq;
        p->isleaf = 1;
    }
    return p;
}

// Insert into priority queue
void pq_insert(struct tnode* p) {
    struct tnode *curr = qhead, *prev = NULL;

    if (qhead == NULL || p->freq < qhead->freq) {
        p->next = qhead;
        qhead = p;
        return;
    }

    while (curr && p->freq >= curr->freq) {
        prev = curr;
        curr = curr->next;
    }

    prev->next = p;
    p->next = curr;
}

```

```

// Pop from priority queue
struct tnode* pq_pop() {
    if (qhead == NULL)
        return NULL;
    struct tnode* p = qhead;
    qhead = qhead->next;
    p->next = NULL;
    return p;
}

// Generate code using parent pointer
void generate_code(struct tnode* node, int depth) {
    if (node->isleaf) {
        int symbol = node->symbol;
        code[symbol][depth] = '\0';

        struct tnode* p = node;
        int i = depth - 1;
        while (p->parent) {
            code[symbol][i--] = (p == p->parent->left) ? '0' : '1';
            p = p->parent;
        }

        printf("built code: %c -> %s\n", symbol, code[symbol]);
    } else {
        if (node->left) generate_code(node->left, depth + 1);
        if (node->right) generate_code(node->right, depth + 1);
    }
}

// Write code table to file
void dump_code(FILE* fp) {
    for (int i = 0; i < MAX_SYMBOLS; i++) {
        if (code[i][0]) {
            fprintf(fp, "%c %s\n", i, code[i]);
        }
    }
}

// Encode string using generated code
void encode(const char* str, FILE* fout) {
    while (*str) {
        if (*str != ' ') {
            fprintf(fout, "%s", code[*str]);
        }
        str++;
    }
}

// Free Huffman tree
void freetree(struct tnode* node) {
    if (!node) return;
    freetree(node->left);
    freetree(node->right);
    free(node);
}

```



```

// Main function
int main() {
float freq[] = {0.01, 0.04, 0.05, 0.11, 0.19, 0.20, 0.4}; // For a-g
int NCHAR = 7;
const char* test_string = "abba cafe bad";
const char* CODE_FILE = "code.txt";
const char* OUT_FILE = "encoded.txt";
FILE* fout = NULL;

memset(code, 0, sizeof(code));

// Step 1: Insert characters into queue
for (int i = 0; i < NCHAR; i++) {
pq_insert(talloc('a' + i, freq[i]));
}

// Step 2: Build Huffman tree
while (qhead && qhead->next) {
struct tnode* lc = pq_pop();
struct tnode* rc = pq_pop();
struct tnode* parent = talloc(0, lc->freq + rc->freq);
parent->isleaf = 0;
parent->left = lc;
parent->right = rc;
lc->parent = rc->parent = parent;
pq_insert(parent);
}
root = pq_pop();

// Step 3: Generate codes
generate_code(root, 0);

// Step 4: Write code.txt
fout = fopen(CODE_FILE, "w");
dump_code(fout);
fclose(fout);

// Step 5: Write encoded.txt
fout = fopen

```

Task3:

CODE:

```

* Author: Abdul Hadi Afzal
* Task: Lab 6 - Huffman Encoder (Task 3)
*/

#include <stdio.h>
#include <stdlib.h>
#include <string.h>

#define MAX_SYMBOLS 256
#define MAX_LEN 64

struct tnode {
struct tnode* left;
struct tnode* right;

```

```

        struct tnode* parent;
        struct tnode* next;
        float freq;
        int isleaf;
        char symbol;
    };

    char code[MAX_SYMBOLS][MAX_LEN];
    struct tnode* root = NULL;
    struct tnode* qhead = NULL;
    int char_freq[MAX_SYMBOLS] = {0};

    // Allocate a tree node
    struct tnode* talloc(int symbol, float freq) {
    struct tnode* p = (struct tnode*)malloc(sizeof(struct tnode));
        if (p) {
            p->left = p->right = p->parent = p->next = NULL;
            p->symbol = symbol;
            p->freq = freq;
            p->isleaf = 1;
        }
        return p;
    }

    // Insert into priority queue
    void pq_insert(struct tnode* p) {
    struct tnode *curr = qhead, *prev = NULL;

    while (curr && p->freq >= curr->freq) {
        prev = curr;
        curr = curr->next;
    }

    p->next = curr;
    if (prev) prev->next = p;
    else qhead = p;
    }

    // Pop from priority queue
    struct tnode* pq_pop() {
    if (!qhead) return NULL;
    struct tnode* p = qhead;
    qhead = qhead->next;
    p->next = NULL;
    return p;
    }

    // Generate code strings using parent pointers
    void generate_code(struct tnode* node, int depth) {
    if (node->isleaf) {
        int symbol = (unsigned char)node->symbol;
        code[symbol][depth] = '\0';
        struct tnode* p = node;
        int i = depth - 1;
        while (p->parent) {
            if (p == p->parent->left)
                code[symbol][i--] = '0';

```

```

        else
            code[symbol][i--] = '1';
            p = p->parent;
        }
    printf("built code: %c (%d) -> %s\n", symbol, symbol,
        code[symbol]);
    } else {
        if (node->left) generate_code(node->left, depth + 1);
        if (node->right) generate_code(node->right, depth + 1);
    }
}

// Output codes to file
void dump_code(FILE* fp) {
    for (int i = 0; i < MAX_SYMBOLS; i++) {
        if (code[i][0]) {
            fprintf(fp, "%c %s\n", i, code[i]);
        }
    }
}

// Encode input file into binary codes
void encode(FILE* fin, FILE* fout) {
    int c;
    while ((c = fgetc(fin)) != EOF) {
        if (code[c][0]) {
            fputs(code[c], fout);
        }
    }
}

// Free the Huffman tree
void freetree(struct tnode* node) {
    if (!node) return;
    freetree(node->left);
    freetree(node->right);
    free(node);
}

int main() {
    FILE *fin, *fout;
    const char* IN_FILE = "book.txt";
    const char* CODE_FILE = "code.txt";
    const char* OUT_FILE = "encoded.txt";

    memset(code, 0, sizeof(code));
    memset(char_freq, 0, sizeof(char_freq));

    // Step 1: Read file and count frequencies
    fin = fopen(IN_FILE, "r");
    if (!fin) {
        perror("Error opening book.txt");
        return 1;
    }

    int total = 0, c;
    while ((c = fgetc(fin)) != EOF) {

```

```

        char_freq[c]++;
        total++;
    }
    fclose(fin);

    // Step 2: Build priority queue
    for (int i = 0; i < MAX_SYMBOLS; i++) {
        if (char_freq[i] > 0) {
            pq_insert(talloc(i, (float)char_freq[i] / total));
        }
    }

    // Step 3: Build Huffman tree
    while (qhead && qhead->next) {
        struct tnode* lc = pq_pop();
        struct tnode* rc = pq_pop();
        struct tnode* parent = talloc(0, lc->freq + rc->freq);
        parent->isleaf = 0;
        parent->left = lc;
        parent->right = rc;
        lc->parent = rc->parent = parent;
        pq_insert(parent);
    }
    root = pq_pop();

    // Step 4: Generate codes
    generate_code(root, 0);

    // Step 5: Save code.txt
    fout = fopen(CODE_FILE, "w");
    if (!fout) {
        perror("Error writing code.txt");
        return 1;
    }
    dump_code(fout);
    fclose(fout);

    // Step 6: Encode book.txt to encoded.txt
    fin = fopen(IN_FILE, "r");
    fout = fopen(OUT_FILE, "w");
    if (!fin || !fout) {
        perror("Error during encoding");
        return 1;
    }
    encode(fin, fout);
    fclose(fin);
    fclose(fout);

    printf("✅ book.txt compressed successfully.\n");
    printf("→ Output files: encoded.txt and code.txt\n");

    freetree(root);
    getchar();
    return 0;
}

```

SS:

```
built code: i (105) -> 0000
built code: s (115) -> 0001
built code: e (101) -> 001
built code: h (104) -> 0100
built code: n (110) -> 0101
built code: k (107) -> 0110000
built code: I (73) -> 0110001
built code: , (44) -> 011001
built code: g (103) -> 011010
built code: q (113) -> 0110110000
built code: R (82) -> 01101100010
built code: D (68) -> 01101100011
built code: Y (89) -> 0110110010
built code: E (69) -> 01101100110
built code: J (74) -> 011011001110
built code: l (49) -> 0110110011110
built code: 3 (51) -> 011011001111100
built code: 5 (53) -> 011011001111101
built code: 2 (50) -> 01101100111111
built code: B (66) -> 0110110100
built code: x (120) -> 0110110101
built code: T (84) -> 011011011
built code: v (118) -> 0110111
built code: o (111) -> 0111
built code: a (97) -> 1000
built code: l (108) -> 10010
built code: f (102) -> 100110
built code: y (121) -> 100111
built code: t (116) -> 1010
built code: d (100) -> 10110
built code: - (45) -> 101110000
built code: L (76) -> 10111000100
built code: z (122) -> 101110001010
built code: 7 (55) -> 101110001011000
built code: X (88) -> 1011100010110010
built code: & (38) -> 10111000101100110
built code: ( (40) -> 10111000101100111
built code: 8 (56) -> 10111000101101
built code: K (75) -> 1011100010111
built code: N (78) -> 10111000110
built code: O (79) -> 10111000111
built code: H (72) -> 101110010
built code: G (71) -> 101110011000
built code: O (48) -> 1011100110010
built code: V (86) -> 1011100110011
built code: C (67) -> 10111001101
built code: j (106) -> 10111001110
built code: ! (33) -> 10111001111
built code: " (34) -> 1011101
built code: c (99) -> 101111
built code: (32) -> 110
built code: w (119) -> 111000
built code: m (109) -> 111001
built code: r (114) -> 11101
built code: b (98) -> 1111000
built code: M (77) -> 1111001000
built code: ? (63) -> 1111001001
built code: ' (39) -> 111100101
```

```

built code: w (87) -> 1111001100
built code: A (65) -> 1111001101
built code: S (83) -> 1111001110
built code: P (80) -> 111100111100
built code: F (70) -> 111100111101
built code: Q (81) -> 111100111110000
built code: 4 (52) -> 111100111110001
built code: U (85) -> 11110011111001
built code: ) (41) -> 11110011111010000
built code: Γ (226) -> 1111001111101000100
built code: ϕ (232) -> 1111001111101000101
built code: Z (90) -> 1111001111101000110
built code: / (47) -> 11110011111010001110
built code: α (224) -> 11110011111010001111
built code: ø (233) -> 1111001111101001
built code: 9 (57) -> 1111001111101010
built code: 6 (54) -> 1111001111101011
built code: : (58) -> 11110011111011
built code: ; (59) -> 111100111111
built code:
(10) -> 111101
built code: . (46) -> 1111100
built code: p (112) -> 1111101
built code: u (117) -> 111111
rfa book.txt compressed successfully.
rfa output files: encoded.txt and code.txt

```

encoded.txt - Notepad

File Edit Format View Help

```

01101101110111001001101100110110111100110101101100011101110011001101101100
0110110100001110011011010001110001101111011111001111100000111010111001100
01101101010010000111001101100110010101101000000101001001111011111001010001
00111101110010011011001101111001000011000111110011011111011111010110001111
11101001100111111011100110001111010010101001110111100110110110100100011110
1111011100100001110111000011111111100101011011001001000011011100111011111
011111110101101001100111111011101001000011101010111011000000001010011011
11010111111101100010111101100001100000010111001110101001110011110011011001
00111111110011110111110101100011100100100010110110000100100101011101001000
01110111000001111010011100001111111100110100110000010111100000010101101011
011100000100101011101011110111110000000010100111010000101101101101000
0001010000001110101110000001011110110011001111001010010011111100000000101
11011111010011111101011110011010011011011100111111111101101100011110101100
10101001000010001001110000100000110100101000111001111001101100100000000011
110101111110011101000110101110011100111111111111101010100110011111010100111
01101000111010110000110000001011011110000101100010101101000011100111100110
0011101001110100110000001101011111111101001110111101100000010001110101011
01110101001111001010110110101001000010000111011111010111111000010111000011
11100110000101010100111101110111000100000011100101011110101100011001101001
11101010010000111010111101111110101010011110111111001100110110110100001010

```

Ln 1, Col 1 100% Windows (CRLF) UTF-8

CONCLUSION:

In this lab, we successfully implemented Huffman encoding and decoding algorithms in C. The process began with building a Huffman tree from either a fixed set of frequencies (Task 2) or real character frequencies extracted from a large input file (Task 3). Using this tree, we generated optimal prefix codes for each character and encoded strings or entire files into binary form.