

INTEGRATING SENTIMENT ANALYSIS WITH MACHINE LEARNING FOR CYBERBULLYING DETECTION ON SOCIAL MEDIA

A Seminar Report

*Submitted to the APJ Abdul Kalam Technological University
in partial fulfillment of requirements for the award of degree of*

Bachelor of Technology

in

ARTIFICIAL INTELLIGENCE AND DATA SCIENCE

by

KHADEEJA HANNA P (MES22AD033)



DEPARTMENT OF ARTIFICIAL INTELLIGENCE AND DATA SCIENCE

MES COLLEGE OF ENGINEERING KUTTIPURAM

KERALA

2025-2026

DEPT. OF ARTIFICIAL INTELLIGENCE AND DATA SCIENCE
MES COLLEGE OF ENGINEERING KUTTIPURAM
2025-26



CERTIFICATE

This is to certify that the report entitled **Integrating Sentiment Analysis With Machine Learning for Cyberbullying Detection on Social Media** submitted by **Khadeeja Hanna P** (MES22AD033), to the APJ Abdul Kalam Technological University in partial fulfillment of the B.Tech. degree in Artificial Intelligence and Data Science is a bonafide record of the seminar work carried out by her under our guidance and supervision. This report in any form has not been submitted to any other University or Institute for any purpose.

Seminar Guide

Mr. Sherikh KK
Assistant Professor
Dept. of ADS

Seminar Coordinator

Mr. Abin C Jose
Assistant Professor
Dept. of ADS

Head of Dept

Dr. Govindaraj E
Associate Professor
Dept. of ADS

DECLARATION

I hereby declare that the seminar report **Integrating Sentiment Analysis With Machine Learning for Cyberbullying Detection on Social Media**, submitted in partial fulfillment of the requirements for the Bachelor of Technology degree at APJ Abdul Kalam Technological University, Kerala, is my original work completed under the supervision of **Mr. Sherikh KK**. I affirm that this submission adheres to academic integrity, with proper citations wherever applicable. I understand that any violation may result in disciplinary action by the institute or university. This report has not been submitted previously for any other degree or title.

I sincerely thank **Dr. Govindaraj E**, Head of the Department, Artificial Intelligence and Data Science, MES College of Engineering, for his constant support and for providing the necessary facilities.

My heartfelt gratitude goes to our seminar coordinator, **Mr. Abin C Jose**, Assistant Professor, Dept. of ADS, for his continuous guidance and encouragement throughout the project.

Finally, I extend my thanks to all our faculty members for their support, motivation, and guidance, which contributed to the successful completion of my seminar.

KUTTIPURAM

KHADEEJA HANNA P

22-10-2025

Abstract

Social media has become a powerful communication tool, allowing people to connect and share information easily. However, this rapid growth has also increased harmful activities such as cyberbullying. Cyberbullying involves repeated online actions like spreading rumors, threats, or harassment. It causes serious emotional and mental harm, especially among young people. Manual monitoring of huge online content is not practical, which creates the need for intelligent automated solutions.

This seminar presents a smart and efficient framework that combines Sentiment Analysis (SA) with Machine Learning (ML) to accurately detect cyberbullying on social media platforms. The system first collects and cleans tweets by removing noise such as URLs, emojis, and special characters, ensuring that the text is properly processed for analysis. Using SA, it examines the emotional tone of each message to identify harmful or offensive language, even when direct bullying keywords are not used. This helps the model understand hidden negativity and sarcasm more effectively. To address the problem of uneven data distribution, the SMOTE technique is applied to balance the dataset. This ensures fair and accurate detection of different categories of cyberbullying such as age, gender, religion, and ethnicity, improving overall model performance and reliability.

The proposed framework was tested using several ML algorithms. Among them, the Extra Trees classifier achieved the highest accuracy of 95.38% and an F1 score of 0.95. The approach is fast, accurate, and scalable for large social media platforms. It can be used to alert parents, teachers, and authorities, helping to create safer online spaces. In the future, the system can be improved to support multiple languages and handle complex cases like sarcasm and hidden abuse.

Acknowledgement

I take this opportunity to express my deepest sense of gratitude and sincere thanks to everyone who helped me to complete this work successfully. I express my sincere thanks to **Dr. Govindaraj E** , Head of Department, Artificial Intelligence and Data Science, MES College of Engineering for providing me with all the necessary facilities and support.

I would like to express my sincere gratitude to the **Mr. Abin C Jose**, department of Artificial Intelligence and Data Science, MES College of Engineering, Kuttipuram for the support and co-operation.

I would like to place on record my sincere gratitude to my seminar guide **Mr. Sherikh KK**, Artificial Intelligence and Data Science, MES College of Engineering, for the guidance and mentorship throughout this work.

Finally I thank my family, and friends who contributed to the succesful fulfilment of this seminar work.

KHADEEJA HANNA P

Contents

Abstract	i
Acknowledgement	ii
List of Figures	v
List of Tables	vi
List of Symbols	vii
1 Introduction	1
2 Literature Review	5
2.1 Cyberbullying Detection Using Conventional Machine Learning and DistilBERT [1]	5
2.2 Evaluation of Machine Learning Models for Cyberbullying Sentiment [2]	6
2.3 VADSentence Miner for Cyber-Trolling Detection [3]	6
2.4 Detecting Cyberbullying on Twitter Using Sentiment Analysis and N-Gram-Based Machine Learning Techniques [4]	7
3 System Development	8
3.1 Problem Statement	8
3.2 Proposed Solution	9
3.3 Technologies Used	10
3.4 System Architecture Overview	10
3.4.1 Core Components of the Architecture	11

4	Results and Discussion	13
5	Conclusion and Future Scope	15
5.1	Summary of Findings	15
5.2	Final Thoughts	16
5.3	Future Scope	17
	References	18

List of Figures

3.1	Framework for enhanced cyberbullying detection through sentiment analysis and machine learning.	11
4.1	Data boxplot	14

List of Tables

4.1 Performance Comparison of Machine Learning Models 13

Abbreviations

- **SA** – Sentiment Analysis
- **NLP** – Natural Language Processing
- **SMOTE** – Synthetic Minority Oversampling Technique
- **TF-IDF** – Term Frequency–Inverse Document Frequency
- **SVM** – Support Vector Machine
- **LR** – Logistic Regression
- **RF** – Random Forest
- **ET** – Extra Trees Classifier

Chapter 1

Introduction

1.1 Background

The rise of social media has revolutionized communication by allowing billions of users to share opinions, ideas, and emotions across platforms such as Twitter, Instagram, and Facebook. However, this digital freedom has also given rise to harmful behaviors such as cyberbullying, which refers to the deliberate and repeated use of technology to harass, humiliate, or threaten individuals online. Cyberbullying can take various forms such as spreading false rumors, posting offensive content, impersonating others, or sharing private information without consent.

According to a 2022 survey by the Pew Research Center, nearly 46% of U.S. teens reported experiencing cyberbullying, with girls being more frequently targeted than boys. Furthermore, about 19% of bullying incidents occurred through social media platforms. This growing trend has raised serious concerns due to its lasting emotional and psychological effects, including anxiety, depression, low self-esteem, and suicidal thoughts.

The large amount of social media content makes manual monitoring impossible. Intelligent automated systems are needed to detect and prevent cyberbullying in real time. Artificial Intelligence (AI), including Machine Learning (ML) and Natural Language Processing (NLP), can help with this. These systems can quickly analyze messages and learn new abusive patterns. By understanding the tone and context, AI can detect harmful content more accurately than traditional methods.

One such technique is Sentiment Analysis (SA), which identifies the emotional tone—positive, negative, or neutral—of online messages. By integrating SA with ML algorithms, systems can learn to detect abusive or harmful communication patterns automatically, even when offensive language is hidden or indirect [9]. This approach enables scalable, accurate, and early detection of cyberbullying, fostering a safer online environment for users.

1.2 Need for Cyberbullying Detection Using Sentiment Analysis and Machine Learning

Traditional keyword-based or rule-based detection systems are limited in their ability to understand the context, tone, and subtle nuances of online messages. Cyberbullying often includes sarcasm, coded expressions, or humor that simple filtering systems fail to recognize. Moreover, the vast and continuously evolving nature of online communication demands adaptive systems that can learn from emerging patterns over time.

By incorporating Sentiment Analysis, machines can evaluate the underlying emotions in text and classify them as supportive, neutral, or harmful. When combined with ML algorithms, this approach enables the model to learn from past examples, detect hidden abusive behavior, and improve its predictive accuracy. It also allows the system to differentiate between harmless teasing and harmful harassment, reducing false positives and improving reliability.

Furthermore, the automated system can be scaled to process large volumes of data in real time, providing early warnings and actionable insights for parents, educators, and online moderators [10]. Integration with cloud and edge computing ensures low-latency processing, while advanced techniques like transfer learning and federated learning can enhance adaptability and maintain user privacy. By leveraging these AI-based methods, the system can continuously evolve, making it a robust, efficient, and proactive solution for combating cyberbullying. This need for a scalable, intelligent, and context-aware detection framework forms the foundation of this seminar work.

1.3 Objectives of the Study

The main goal of this seminar is to develop a smart and efficient framework that integrates Sentiment Analysis with Machine Learning for the detection of cyberbullying on social media. The specific objectives include:

1. To analyze and preprocess social media text data for accurate classification.
2. To apply sentiment analysis for extracting emotional tone and context from online posts.
3. To handle data imbalance using the SMOTE (Synthetic Minority Oversampling Technique) for fair and unbiased results.
4. To train and compare various ML classifiers to identify the most effective model for cyberbullying detection.
5. To create a scalable system capable of real-time detection across large datasets.

These objectives ensure the framework not only achieves high accuracy but also adapts to different categories of bullying such as age, gender, religion, and ethnicity.

1.4 Challenges in Cyberbullying Detection

Despite advances in AI, cyberbullying detection presents numerous challenges that affect model performance and reliability:

- **Sarcasm and Hidden Abuse:** Bullying is often expressed through subtle humor or sarcasm that lacks explicit negative words, making detection difficult.
- **Imbalanced Data Distribution:** Some bullying types (like religion or age-based) are underrepresented, leading to biased classification results.
- **Dynamic Language Patterns:** Social media language evolves quickly, requiring frequent dataset updates and retraining of models.
- **Multilingual Issues:** Most detection systems are limited to English and fail to process non-English or mixed-language content.

- **Privacy and Ethical Concerns:** Handling user-generated content demands strict measures to protect privacy and prevent misuse.

Overcoming these challenges is essential for developing a reliable, ethical, and effective detection framework.

1.5 Significance of the Study

The integration of Sentiment Analysis with Machine Learning offers a significant step toward building safer digital spaces. This study contributes to this goal through the following key aspects:

- **Improved Accuracy:** The proposed framework detects harmful language with high precision, achieving an accuracy of 95.38% using the Extra Trees Classifier.
- **Scalability and Automation:** The system efficiently processes large volumes of data without human intervention, enabling real-time moderation.
- **Fairness and Balance:** Using SMOTE ensures equal learning for all categories of bullying, reducing bias in detection results.
- **Social Impact:** The system can help educators, parents, and organizations detect early signs of harassment and protect individuals from online abuse.
- **Future Advancement:** The study lays the foundation for future improvements, such as multilingual detection, image-text analysis, and sarcasm recognition.

Overall, this research emphasizes how combining NLP and ML can transform cyberbullying detection from a manual, reactive process into an automated, intelligent, and proactive system—paving the way toward a more respectful and secure online world.

Chapter 2

Literature Review

2.1 Cyberbullying Detection Using Conventional Machine Learning and DistilBERT [1]

A hybrid framework was proposed that combines conventional Machine Learning (ML) algorithms with DistilBERT, a transformer-based language model derived from BERT. The main objective of this approach was to improve the efficiency and accuracy of cyberbullying detection while reducing computational complexity. The framework utilized multiple ML classifiers such as Support Vector Machine (SVM), Logistic Regression (LR), and Random Forest (RF) alongside DistilBERT's text embeddings to analyze online text data. The method emphasized preprocessing as a key step, which included tokenization, stop-word removal, and text normalization. DistilBERT was used to extract deep contextual features from sentences, allowing the system to capture the meaning and tone of words in bullying contexts. These features were then passed into conventional ML classifiers for the final prediction. The experimental results showed that integrating DistilBERT with traditional ML models led to a notable improvement, achieving an F-measure of 72.42%, outperforming standard ML-based techniques. The framework proved effective at detecting implicit and emotionally charged bullying content, though it was also noted that high computational cost and longer training times limited its real-time deployment.

2.2 Evaluation of Machine Learning Models for Cyberbullying Sentiment [2]

A detailed comparative analysis was conducted to evaluate the performance of different Machine Learning (ML) algorithms for cyberbullying detection using sentiment-based features. The approach employed a Bag-of-Words (BoW) model combined with Chi-Square feature selection to extract relevant terms from large-scale social media datasets. Multiple classifiers, including Support Vector Machine (SVM), Logistic Regression (LR), and Naïve Bayes (NB), were implemented to assess their effectiveness in identifying offensive and bullying content. The dataset included diverse categories of online aggression such as gender, religion, and age-based bullying. The results showed that SVM and LR achieved an accuracy of 83%, outperforming other models in recognizing negative sentiment and abusive language. However, the Naïve Bayes classifier performed less effectively with complex or sarcastic expressions, with only 62% accuracy, due to its inability to capture contextual dependencies between words. The analysis highlighted that balanced datasets and strong preprocessing methods are crucial for reliable sentiment-based detection. The study concluded that SVM and LR serve as strong baseline algorithms for cyberbullying sentiment analysis when supported by effective feature selection and normalization. It also emphasized the importance of advanced preprocessing and hybrid feature extraction techniques to better handle noisy real-world data.

2.3 VADSentence Miner for Cyber-Trolling Detection [3]

A novel sentiment-based model called VADSentence Miner was introduced to detect cyber-trolling and harassment using emotional intensity metrics — Valence, Arousal, and Dominance (VAD). Unlike conventional sentiment analysis methods that classify text as simply positive or negative, this approach measures the emotional strength and psychological impact behind online messages. The framework employed the VAD lexicon to map words to their emotional dimensions, enabling the system

to evaluate both polarity and intensity. These VAD scores were then combined with SVM, Decision Tree, and Random Forest classifiers to predict whether a message carried trolling or bullying intent. The model achieved an accuracy of 90%, outperforming traditional sentiment tools like TextBlob. By incorporating emotional strength (Arousal) and control (Dominance), the system provided deeper insight into user behavior, helping distinguish between harmless jokes and aggressive trolling. However, it was observed that the framework performed best on Twitter data and required further testing across different platforms and languages. Despite these challenges, the VADSentence Miner approach showed strong potential for enhancing cyberbullying detection. By integrating psychological emotion modeling with ML algorithms, it made the system more context-aware and sensitive to emotional variation, offering a more accurate way to identify harmful online interactions.

2.4 Detecting Cyberbullying on Twitter Using Sentiment Analysis and N-Gram-Based Machine Learning Techniques [4]

A study was conducted to detect cyberbullying from Twitter data by integrating Sentiment Analysis (SA) with N-gram-based ML models, emphasizing emotional tone and word-level context in identifying hidden abusive content. The framework followed a structured pipeline of data collection, text preprocessing, sentiment scoring, and N-gram-based feature extraction. Multiple ML algorithms, including Naïve Bayes (NB), Logistic Regression (LR), and Convolutional Neural Network (CNN), were trained and evaluated for effectiveness. Among these, the CNN-based classifier achieved the best performance due to its ability to capture local word dependencies and contextual semantics. The integration of sentiment polarity features improved classification accuracy and precision, though it required higher computational resources and longer training time. The findings showed that combining Sentiment Analysis with N-gram features enhances the system's ability to detect subtle forms of online harassment and provides a strong foundation for future emotion-aware text classification research.

Chapter 3

System Development

3.1 Problem Statement

The widespread use of social media platforms has led to a dramatic rise in online communication, but it has also resulted in a growing issue of cyberbullying. Millions of users experience online harassment through offensive posts, abusive language, and targeted comments. Identifying such harmful content manually is nearly impossible due to the massive volume of daily posts and the subtle ways in which abuse is expressed.

Traditional methods that rely solely on keyword filtering fail to recognize implicit or sarcastic bullying, where negative intent is hidden beneath polite or humorous wording. Moreover, linguistic diversity, slang, and emojis further complicate detection.

Hence, there is a need for an automated and intelligent system capable of detecting cyberbullying from social media text by understanding both the emotional tone and context behind words. The proposed study aims to address this challenge by integrating Sentiment Analysis (SA) with Machine Learning (ML) to improve detection accuracy and scalability.

In existing cyberbullying detection systems, rule-based or keyword-matching approaches are commonly used. These systems maintain a predefined list of offensive or negative words and classify any message containing them as bullying.

3.2 Proposed Solution

The proposed system aims to build an intelligent and automated model that can detect cyberbullying on social media platforms by combining Sentiment Analysis (SA) and Machine Learning (ML). Unlike older systems that only look for specific abusive keywords, this approach tries to understand the emotional tone, meaning, and context of online messages [7]. Its main goal is to identify not just direct insults but also hidden or sarcastic forms of harassment that simple filters often miss. By studying both the words used and the emotions behind them, the system can better understand how people communicate online.

The process starts by collecting data from platforms like Twitter and Facebook using public APIs. The dataset includes both bullying and non-bullying messages. After collection, the text is cleaned through preprocessing — this includes changing all text to lowercase, removing special characters, links, emojis, and unnecessary words, and then splitting and simplifying the text (tokenization and lemmatization). This cleaning step helps make the data more uniform and easier for the system to analyze accurately.

Next, Sentiment Analysis is performed to find out whether each message expresses a positive, negative, or neutral emotion. This helps detect negative or aggressive tones that might indicate bullying. Then, the text is converted into numerical features using TF-IDF and N-gram methods [4]. The processed data is then used to train different ML algorithms such as Logistic Regression (LR), Support Vector Machine (SVM), Random Forest (RF), and Extra Trees (ET).

Since bullying messages are fewer compared to normal ones, the system uses SMOTE (Synthetic Minority Oversampling Technique) to create balanced training data by generating extra samples of the bullying category. The models are then tested and evaluated based on accuracy, precision, recall, and F1-score. Among all the models, the Extra Trees Classifier performed the best with a 95.38% accuracy. This shows that combining sentiment information with ML methods makes cyberbullying detection more accurate and effective. Overall, the proposed system provides a smart and reliable way to identify harmful online behavior and promote safer social media spaces.

3.3 Technologies Used

Python (v3.9.0)	Easy-to-learn, cross-platform language with libraries like Pandas, TensorFlow, OpenCV.
Scikit-learn (v1.3.0)	ML library used to train and evaluate various machine learning models including Extra Trees Classifier, SVM, and Logistic Regression.
NLTK (v3.8.1)	Natural Language Toolkit used for text preprocessing tasks like tokenization, stopwords removal, and lemmatization.
Imbalanced-learn (v0.11.0)	Library used to apply SMOTE resampling technique for handling class imbalance in the dataset.
VADER Sentiment (v3.3.2)	Sentiment analysis tool used to detect emotional tone (positive, negative, neutral) in tweets for early detection of cyberbullying.
GPT	Generates human-like, context-aware text from retrieved information.
IR Models (TF-IDF, VSM, ColBERT)	Locate and rank relevant data efficiently; ColBERT uses BERT for fast, accurate search.

3.4 System Architecture Overview

The proposed system architecture offers a structured workflow to detect cyberbullying content on social media using Sentiment Analysis (SA) and Machine Learning (ML). The architecture begins with the collection of social media data, followed by preprocessing to clean and normalize the text. After that, sentiment analysis identifies the emotional polarity of messages, which helps in recognizing hidden or indirect abuse. The cleaned and sentiment-tagged data are then converted into numerical features and used to train machine learning models for classification, as illustrated in Figure 3.1. The performance of each model is evaluated using key metrics such as accuracy, precision, recall, and F1-score.




Figure 3.1: Framework for enhanced cyberbullying detection through sentiment analysis and machine learning.

Furthermore, the architecture integrates various functional layers to ensure accurate, scalable, and real-time detection. It includes a data acquisition layer for collecting user-generated content, a processing layer for cleaning and analyzing text, and a classification layer where trained machine learning algorithms categorize the messages. A feedback layer can also be included to continuously refine the model based on new patterns of online behavior. By combining both linguistic (sentiment-based) and statistical (feature-based) analysis, the system can capture not only explicit offensive words but also subtle emotional cues often missed by traditional keyword-based filters. This complete workflow ensures that the system can detect cyberbullying effectively, adapt to evolving language trends, and maintain high performance across large social media datasets.

3.4.1 Core Components of the Architecture

The proposed architecture consists of several key components, each playing a specific role in the detection process:

- 1. Data Collection:** Social media posts are collected from platforms such as Twitter and Facebook using public APIs. The data contains both bullying and non-bullying messages that serve as the foundation for model training and testing.

- 2. Data Preprocessing:** The text is cleaned by removing emojis, URLs, punctuation, and stopwords, converted to lowercase, and tokenized and lemmatized for uniformity. This step reduces noise, highlights relevant features, and improves model performance.
- 3. Sentiment Analysis:** Each post's emotional tone—positive, negative, or neutral—is analyzed using tools like VADER. Identifying negative sentiment helps the system detect subtle or indirect cyberbullying beyond explicit offensive words.
- 4. Feature Extraction:** The cleaned and sentiment-labeled text is transformed into numerical features using techniques such as TF-IDF and N-gram models. This captures semantic and contextual information, enabling more accurate classification.
- 5. SMOTE:** Since bullying messages are fewer than normal posts, SMOTE is applied to generate synthetic examples of the minority class, ensuring the model is balanced and unbiased.
- 6. Model Training and Prediction:** Machine learning models like Logistic Regression, SVM, Random Forest, and Extra Trees Classifier are trained to classify messages. Among them, Extra Trees achieved the highest performance, with 95.38% accuracy and an F1-score of 0.95.
- 7. Evaluation:** Trained models are tested on unseen data, and performance is measured using Accuracy, Precision, Recall, and F1-Score. This ensures the system is reliable, scalable, and capable of handling real-world social media data efficiently.

Chapter 4

Results and Discussion

The proposed system for detecting cyberbullying was developed and tested using several Machine Learning (ML) algorithms to evaluate their ability to identify abusive messages on social media platforms. The dataset used in this study consisted of a large number of posts collected from sources like Twitter and Facebook, containing both bullying and non-bullying texts. Before training the models, the data underwent multiple preprocessing steps, including the removal of stopwords, punctuation, emojis, and links, followed by tokenization and lemmatization. These steps helped remove noise from the data and made the text cleaner and more suitable for analysis.

After preprocessing, Sentiment Analysis (SA) was applied to determine the emotional tone of each post — positive, negative, or neutral. These sentiment values were then combined with text features extracted using TF-IDF and N-gram techniques, forming the input for the ML classifiers. To address class imbalance, SMOTE (Synthetic Minority Oversampling Technique) was used to balance the dataset and reduce bias. The performance of multiple ML models — Logistic Regression, SVM, Random Forest, and Extra Trees — was then evaluated using standard metrics such as Accuracy, Precision, Recall, and F1-Score, as summarized in Table 4.1.

Model	Accuracy(%)	Precision	Recall	F1-Score
Logistic Regression	92.14	0.90	0.89	0.90
Support Vector Machine	93.68	0.92	0.91	0.91
Random Forest	94.10	0.93	0.92	0.93
Extra Trees Classifier	95.38	0.95	0.95	0.95

Table 4.1: Performance Comparison of Machine Learning Models




Figure 4.1: Data boxplot

Detailed Discussion

The results show that combining Sentiment Analysis (SA) with Machine Learning (ML) greatly improves cyberbullying detection accuracy. Figure 4.1 shows the data boxplot, which illustrates the dataset distribution and highlights outliers. After applying SMOTE, the data became more balanced between bullying and non-bullying classes. This improved fairness and reduced model bias. By combining emotional tone with text features, the system could detect hidden or sarcastic bullying effectively. Among all models, the Extra Trees Classifier achieved the highest accuracy of 95.38%, followed by Random Forest, SVM, and Logistic Regression.

A key reason for this strong performance is the preprocessing and feature extraction process. Tokenization, stopwords removal, and lemmatization improved data quality, while TF-IDF and N-grams helped the model understand word context. Sentiment polarity added emotional weight to each post, enabling the system to detect hidden bullying patterns more effectively.

The use of SMOTE balanced the dataset, reducing model bias and improving classification fairness. Evaluation metrics like Accuracy, Precision, Recall, and F1-Score showed consistent results, with higher recall values meaning fewer bullying cases were missed. Overall, the system offers a reliable, scalable, and intelligent solution for cyberbullying detection on social media.

Chapter 5

Conclusion and Future Scope

5.1 Summary of Findings

The **key findings** from this study include:

- **Need for Cyberbullying Detection:** Social media platforms face increasing issues of online harassment and abusive language. Manual moderation is slow and ineffective. Automated detection using Machine Learning (ML) and Sentiment Analysis (SA) provides a scalable and intelligent solution.
- **Working of the Proposed System:** Combines Sentiment Analysis and Machine Learning to detect harmful messages.
 - **Sentiment Analysis:** Identifies emotional tone (positive, negative, neutral).
 - **Feature Extraction:** Uses TF-IDF and N-gram techniques.
 - **Classification:** ML algorithms categorize messages as bullying or non-bullying.

- **Advantages of the System:**

- Detects both explicit and implicit bullying (like sarcasm or hidden aggression).
- Handles data imbalance using the SMOTE technique.
- Provides high accuracy (95.38%), precision, and reliability.

- **Model Performance:** Among the tested models—Logistic Regression, SVM, Random Forest, and Extra Trees—the Extra Trees Classifier performed best with 95.38% accuracy and an F1-score of 0.95.

- **Significance of Findings:**

- Sentiment Analysis improves emotion understanding and context recognition.
- Preprocessing (tokenization, stopwords removal, lemmatization) enhances text clarity.
- Balancing data ensures fair detection across bullying categories.

5.2 Final Thoughts

Cyberbullying has become one of the most serious issues on social media platforms. With the increasing use of online communication, harmful activities such as harassment, threats, and abusive language are rising. Manual monitoring is not effective due to the massive amount of data generated daily, highlighting the need for intelligent systems that can automatically detect and prevent online abuse in real time.

By integrating Sentiment Analysis with Machine Learning, this seminar presents an effective approach to identifying and classifying harmful content. The use of tools like VADER Sentiment, NLTK, and ML algorithms such as Extra Trees Classifier has shown strong results in accuracy and speed. Applying SMOTE resampling has further improved the system's ability to detect different bullying categories fairly and reliably.

In the future, this system can be expanded to support multiple languages, multimedia inputs, and advanced deep learning models for even better performance. Implementing such technologies on social media platforms can help reduce online harassment, create safer digital spaces, and protect individuals from psychological harm. This work proves that technology can play a strong role in promoting kindness, safety, and responsible communication online.

5.3 Future Scope

The proposed framework for cyberbullying detection can be expanded in several advanced directions to make it more powerful and practical for real-world applications. One important step is to integrate deep learning models such as LSTM, GRU, or Transformers, which can better understand complex patterns, sarcasm, and context in abusive messages. This would allow the system to detect subtle or indirect forms of bullying that traditional ML models may miss [6]. Additionally, expanding the model to analyze multiple languages and regional dialects would help cover a broader range of online communities. Another key area is incorporating multimodal analysis, where the system can detect bullying not just from text but also from images, audio, and video content, making it more effective across different social media platforms.

In the future, this system can be implemented as a real-time monitoring tool that operates directly on social media platforms and messaging applications. It can automatically send alerts, block harmful content, or provide early warnings to moderators, parents, or educators. By integrating with cloud and edge computing technologies, the model can efficiently scale to handle millions of posts with minimal delay. Incorporating advanced AI techniques such as deep learning and transfer learning can further enhance detection accuracy and adaptability to new forms of online abuse. Privacy-preserving methods like federated learning can also be used to maintain user data confidentiality while continuously improving system performance. With multilingual capabilities, continuous updates, and ethical deployment, this system has the potential to play a crucial role in building safer, more inclusive digital spaces and protecting individuals from online harassment worldwide.

References

- [1] E. Sosa, C. Chang, and T. Miller, “Cyberbullying detection using conventional machine learning and distilbert,” pp. 112–119, 2022.
- [2] P. Sharma, R. Kumar, and A. Patel, “Evaluation of machine learning models for cyberbullying sentiment,” pp. 201–208, 2023.
- [3] J. Lee, R. Tan, and M. Gupta, “Vadsentence miner for cyber-trolling detection,” pp. 85–92, 2021.
- [4] S. Kumar, R. Singh, and P. Mehta, “Detecting cyberbullying on twitter using sentiment analysis and n-gram-based machine learning techniques,” pp. 145–152, 2020.
- [5] A. Alakrot, L. Murray, and N. S. Nikolov, “Dataset construction for the detection of anti-social behaviour in online communication in arabic,” *Proceedings of the 2018 International Conference on Language and Social Media Analysis*, pp. 36–41, 2018.
- [6] Z. Zhang, D. Robinson, and J. Tepper, “Detecting hate speech on twitter using machine learning,” *Proceedings of the International Workshop on Social Media Mining*, pp. 10–15, 2020.
- [7] P. Pawar, R. Patil, and A. Jadhav, “Sentiment analysis based cyberbullying detection on twitter,” *International Journal of Advanced Computer Science and Applications (IJACSA)*, pp. 180–185, 2022.
- [8] S. Rajput, M. Choudhary, and D. Patel, “Cyberbullying detection using natural language processing and machine learning,” *International Journal of Computer Applications*, pp. 23–30, 2021.

- [9] P. Fortuna and S. Nunes, “Hate speech detection: A systematic review,” *Journal of Information Processing and Management*, vol. 51, no. 4, pp. 1–30, 2018.
- [10] J. Salminen, H. Almerikhi, M. Milenković, S. Jung, and B. J. Jansen, “Online hate detection: A critical review and perspectives,” *ACM Transactions on the Web*, pp. 1–8, 2020.