



deeplearning.ai

Learning from
multiple tasks

Multi-task
learning

Simplified autonomous driving example



$x^{(i)}$

Pedestrians

Cars

Stop signs

Traffic lights

\vdots

$y^{(i)}$


$(4, 1)$

0
1
1
0
 \vdots

$$Y = \begin{bmatrix} y^{(1)} & y^{(2)} & y^{(3)} & \dots & y^{(m)} \\ 1 & 1 & 1 & \dots & 1 \end{bmatrix}$$

$(4, m)$

Neural network architecture



Loss: $\hat{y}^{(i)}$
(4,1)

$$\rightarrow \frac{1}{m} \sum_{i=1}^m \sum_{j=1}^4 \mathcal{L}(\hat{y}_j^{(i)}, y_j^{(i)})$$

Sum only over
value of j with
0/1 label.

Unlike softmax regression:

One image can have multiple labels

Usual logistic loss
 $-y_j^{(i)} \log \hat{y}_j^{(i)} - (1 - y_j^{(i)}) \log (1 - \hat{y}_j^{(i)})$


Multi-task learning \leftarrow

$$Y = \begin{bmatrix} 1 & 1 & 0 & ? \\ 0 & 1 & 1 & 1 \\ ? & ? & 1 & 2 \\ ? & ? & 0 & ? \end{bmatrix} \leftarrow$$

When multi-task learning makes sense

- Training on a set of tasks that could benefit from having shared lower-level features.
- Usually: Amount of data you have for each task is quite similar.

A 1,000,000
↓ ↓
B 1,000



- Can train a big enough neural network to do well on all the tasks.