




SF1518/19 Mästarprov 13: Strömkretsen

Fun version

Hassan Al Noori
hassanan@kth.se




LC-circuit



LC-circuit

- What is an LC-circuit?







Electronic article surveillance





Project statement



Project statement

- ▶ What is the current in the circuit?



Project statement

- ▶ What is the current in the circuit?
- ▶ How is the current affected by the voltage?



Project statement

- ▶ What is the current in the circuit?
- ▶ How is the current affected by the voltage?
- ▶ Prove $E(t)$ is constant



Project statement

- ▶ What is the current in the circuit?
- ▶ How is the current affected by the voltage?
- ▶ Prove $E(t)$ is constant
- ▶ How big is the error?



Project statement

- ▶ What is the current in the circuit?
- ▶ How is the current affected by the voltage?
- ▶ Prove $E(t)$ is constant
- ▶ How big is the error?
- ▶ Fourier transform



Project statement

- ▶ What is the current in the circuit?
- ▶ How is the current affected by the voltage?
- ▶ Prove $E(t)$ is constant
- ▶ How big is the error?
- ▶ Fourier transform
- ▶ Voluntary part

Mathematical formulation

$$L = \frac{L_0}{1 + I^2}$$

$$U = L \frac{dI}{dt}$$

$$I = -C \frac{dU}{dt} \quad t = 0, \quad I = 0, \quad \frac{dI}{dt} = \frac{U_0}{L_0}$$

Mathematical formulation

$$\frac{d^2 I}{dt^2} = \frac{2I}{1 + I^2} \left(\frac{dI}{dt} \right)^2 - \frac{I (1 + I^2)}{L_0 C}$$

$$\tilde{y}'(t) = \begin{bmatrix} y_1'(t) \\ y_2'(t) \end{bmatrix} = \begin{bmatrix} y_2(t) \\ \frac{2y_1(t)y_2^2(t)}{1+y_1(t)^2} - \frac{y_1(t)(1+y_1(t)^2)}{L_0C} \end{bmatrix}$$

Numerical Methods - Runge Kutta 4

$$K_1 = hf(x_n, y_n)$$

$$K_2 = hf(x_n + \frac{h}{2}, y_n + \frac{k_1}{2})$$

$$K_3 = hf(x_n + \frac{h}{2}, y_n + \frac{k_2}{2})$$

$$K_4 = hf(x_n + h, y_n + k_3)$$

$$y_{n+1} = y_n + \frac{1}{6} (K_1 + 2K_2 + 2K_3 + K_4) + O(h^5)$$



Mathematical formulation

$$E(t) = U(t)^2 - \log(1 + I(t)^2)$$

Mathematical formulation

$$\frac{dE}{dt} = \frac{d}{dt} (U(t)^2 - \log(1 + I(t)^2))$$

Mathematical formulation

$$= \frac{d}{dt} \left(\left(\frac{L_0 \frac{dI}{dt}}{1 + I(t)^2} \right)^2 - \log (1 + I(t)^2) \right)$$

Mathematical formulation

$$= \frac{d}{dt} \left(\frac{L_0 \frac{dI}{dt}}{1 + I(t)^2} \right)^2 - \frac{d}{dt} (\log (1 + I(t)^2))$$



Mathematical formulation

$= \dots$

Mathematical formulation

$$= 2 \left(\frac{\frac{dI}{dt} \left(1 + I(t)^2 \right) \left(\frac{d^2 I}{dt^2} \right) - 2I(t) \left(\frac{dI}{dt} \right)^2}{(1 + I(t)^2)^3} - \frac{I(t) \left(\frac{dI}{dt} \right)}{(1 + I(t)^2)} \right)$$

$$= 2 \left(\frac{\frac{dI}{dt}}{1 + I(t)^2} \right) \left(\frac{1 + I(t)^2 \left(\frac{d^2 I}{dt^2} \right) - 2I(t) \left(\frac{dI}{dt} \right)^2}{(1 + I(t)^2)^2} - \frac{I(t)}{1} \right)$$

Mathematical formulation

$$\frac{dE}{dt} = 0 \quad \forall \quad t \in \mathbb{R} \quad \Longleftrightarrow \quad \frac{d}{dt}I(0) = 0 \quad \text{or} \quad I(0) = 0 \quad \therefore$$



$$\frac{dE}{dt} = 0 \implies \frac{d^2 I}{dt^2} = \left(\frac{2I(t) \frac{dI}{dt}}{1 + I(t)^2} + \frac{4 \left(\frac{dI}{dt} \right)^3 I(t)}{(1 + I(t)^2)^3} \right) \frac{(1 + I(t)^2)^2}{2 \left(\frac{dI}{dt} \right)}$$

Which by definition is a second order autonomous ODE. Thus, If $I = c$ is a specific solution, then its phase line is independent of the time at which initial conditions are applied. Hence

$$\frac{d^2 I}{dt^2} = 0, \quad I_0 = 0 \quad \therefore \quad \frac{dE}{dt} = 0$$



□

$$U_0 = 240V$$





| Iteration | Period [seconds] | Error |
|-----------|-----------------------|-----------------------|
| 1 | 6.280000000000000e-03 | 2.000000000000000e-05 |
| 2 | 6.260000000000000e-03 | 1.000000000000000e-05 |
| 3 | 6.250000000000000e-03 | 5.000000000000000e-06 |
| 4 | 6.245000000000000e-03 | 5.000000000000000e-06 |
| 5 | 6.240000000000000e-03 | 1.250000000000000e-06 |
| 6 | 6.238750000000000e-03 | 0 |
| 7 | 6.238750000000000e-03 | 3.125000000000000e-07 |
| 8 | 6.238437500000000e-03 | 3.125000000000000e-07 |
| 9 | 6.238125000000000e-03 | 0 |
| 10 | 6.238125000000000e-03 | 3.906200000000000e-08 |
| 11 | 6.238085937500000e-03 | 3.906300000000000e-08 |
| 12 | 6.238046875000000e-03 | 9.765599999999999e-09 |
| 13 | 6.238037109375000e-03 | 4.882800000000000e-09 |
| 14 | 6.238032226562000e-03 | 0 |
| 15 | 6.238032226562000e-03 | 2.441400000000000e-09 |
| 16 | 6.238029785156000e-03 | 6.103500000000000e-10 |
| 17 | 6.238029174805000e-03 | NaN |

$$U_0 = 1200V$$



| Iteration | Period [seconds] | Error |
|-----------|-----------------------|--------------------------|
| 1 | 5.240000000000000e-03 | 0 |
| 2 | 5.240000000000000e-03 | 2.000000000000005e-05 |
| 3 | 5.230000000000000e-03 | 0 |
| 4 | 5.220000000000000e-03 | 2.499999999999898e-06 |
| 5 | 5.220000000000000e-03 | 2.499999999999898e-06 |
| 6 | 5.218750000000000e-03 | 0 |
| 7 | 5.218125000000000e-03 | 6.250000000000191e-07 |
| 8 | 5.217500000000000e-03 | 0 |
| 9 | 5.217343750000000e-03 | 7.812500000000781e-08 |
| 10 | 5.217265625000000e-03 | 7.812499999996444e-08 |
| 11 | 5.217226562500000e-03 | 1.9531250000001279e-08 |
| 12 | 5.217207031250000e-03 | 0 |
| 13 | 5.217207031250000e-03 | 9.7656250000063977e-09 |
| 14 | 5.217197265625000e-03 | 2.441406000000107393e-09 |
| 15 | 5.217194824219000e-03 | 1.22070300000053697e-09 |
| 16 | 5.217193603516000e-03 | 0 |
| 17 | 5.217193603516000e-03 | NaN |

$$U_0 = 2400V$$



| Iteration | Period [seconds] | Error |
|-----------|-----------------------|------------------------|
| 1 | 3.120000000000000e-03 | 0 |
| 2 | 3.120000000000000e-03 | 2.000000000000005e-05 |
| 3 | 3.100000000000000e-03 | 0 |
| 4 | 3.100000000000000e-03 | 2.499999999999898e-06 |
| 5 | 3.097500000000000e-03 | 2.499999999999898e-06 |
| 6 | 3.095000000000000e-03 | 0 |
| 7 | 3.095000000000000e-03 | 6.2500000000001914e-07 |
| 8 | 3.094375000000000e-03 | 0 |
| 9 | 3.094375000000000e-03 | 7.8125000000007813e-08 |
| 1 | 3.094296875000000e-03 | 7.81249999964445e-08 |
| 1 | 3.094218750000000e-03 | 1.953125000012795e-08 |
| 1 | 3.094199218750000e-03 | 0 |
| 1 | 3.094199218750000e-03 | 9.765625000063977e-09 |
| 1 | 3.094189453125000e-03 | 2.441406000107393e-09 |
| 1 | 3.094187011719000e-03 | 1.220703000053697e-09 |
| 1 | 3.094185791016000e-03 | 0 |
| 1 | 3.094185791016000e-03 | NaN |



Fourier analysis

$$I(t) = a_1 \sin(\omega t) + a_2 \sin(2\omega t) + a_3 \sin(3\omega t) + \cdots, \quad \omega = 2\pi/T$$



$$a_k = \frac{2}{T} \int_0^T I(t) \sin(k\omega t) dt, \quad k = 1, 2, 3, \dots$$

- Trapezoidal integration for periodic functions



$$T(h) = \frac{h}{2} \left(f_0 + f_m + 2 \sum_{i=1}^{m-1} y_i \right)$$

$$I = T(h) - \frac{f'(b) - f'(a)}{12} h^2 + \frac{f'''(b) - f'''(a)}{720} h^4 - \frac{f^{(5)}(b) - f^{(5)}(a)}{30240} h^6 + O(h^8)$$



$$U_0 = 240V$$



$$U_0 = 1200V$$



$$U_0 = 2400V$$





Voluntary part 1

$$I_{max} := 10$$



Voluntary part 1

$$I_{max} := 10$$

$$I_{\alpha} = \max \{ \quad I(U_0^*, L_0) : U_0 \in]240, 2400[, L_0 \in \mathbb{R} \quad \}$$

Voluntary part 1

$$I_{max} := 10$$

$$I_{\alpha} = \max \{ I(U_0^*, L_0) : U_0 \in]240, 2400[, L_0 \in \mathbb{R} \}$$

$$g(U_0^*, L_0) = 0 = I_{max} - I_{\alpha}$$

Voluntary part 1

$$I_{max} := 10$$


$$I_{\alpha} = \max \{ \quad I(U_0^*, L_0) : U_0 \in]240, 2400[, L_0 \in \mathbb{R} \quad \}$$

$$g(U_0^*, L_0) = 0 = I_{max} - I_{\alpha}$$


- Bisection method

Voluntary part 1

Current at $U_0 = 2148 \text{ V}$




Relationship between U_0^* and L_0




$$U = L \frac{dI}{dt} \quad I = -C \frac{dU}{dt} \quad L = \frac{L_0}{1 + I^2}$$

$$\tilde{y}' = \begin{bmatrix} \frac{dI}{dt} \\ \frac{dU}{dt} \end{bmatrix} = \begin{bmatrix} \frac{1+I^2}{L_0} U \\ \left(\frac{dI}{dt} \right) \frac{1}{-C} \end{bmatrix}$$


Voluntary part 2



Voluntary part 2



Voluntary part 2





Thanks

github - haaln

mail - hassanan@kth.se