

Rajalakshmi Engineering College

Name: Haaniya M
Email: 241501062@rajalakshmi.edu.in
Roll no: 241501062
Phone: 6385042979
Branch: REC
Department: AI & ML - Section 1
Batch: 2028
Degree: B.E - AI & ML

Scan to verify results



2024_28_III_OOPS Using Java Lab

REC_2028_OOPS using Java_Week 11

Attempt : 2
Total Mark : 20
Marks Obtained : 10

Section 1 : Project

1. Problem Statement

In Café Central, the menu is cataloged and stored in a database.

To efficiently manage the restaurant's menu using Java and JDBC, you must build a Restaurant Management System that supports:

Adding new menu items

Updating menu item prices

Viewing details of a menu item

Displaying all menu items in sorted order

You are given two files:

File 1: MenuItem.java (POJO Class)

This class represents the MenuItem entity.

A MenuItem contains the following details:

Field	Description
itemId	Unique Menu Item ID (Integer)
name	Item Name (String)
category	Item Category (String)
price	Item Price (Double)

Students must write code in the marked area:

```
class MenuItem {  
    private int itemId;  
    private String name;  
    private String category;  
    private double price;  
  
    public MenuItem() {}  
  
    public MenuItem(int itemId, String name, String category, double price) {  
        // write your code here  
    }  
  
    // Include getters and setters  
}
```

Expected in this part:

Assign parameter values to instance variables inside the constructor.

Add getters and setters for all attributes.

File 2: MenuItemDAO.java (Data Access Layer)

This class handles all database operations using JDBC.

Students must complete the missing JDBC logic in the following methods:

```
class MenuItemDAO {

    public void addItem(Connection conn, MenuItem menuItem)
    throws SQLException {

        // write your code here

    }

    public void updateItemPrice(Connection conn, int itemId, double
    newPrice) throws SQLException {

        // write your code here

    }

    public void deleteMenuItem(Connection conn, int itemId) throws
    SQLException {

        // write your code here

    }

    public MenuItem viewItemDetails(Connection conn, int itemId) throws
    SQLException {

        // write your code here

    }

    public List<MenuItem> displayAllMenuItems(Connection conn) throws
    SQLException {

        // write your code here

    }

    private MenuItem mapToMenuItem(ResultSet rs) throws SQLException {
        return new MenuItem(
```

```
// write your code here  
);  
}  
}
```

Expected in this part:

Write SQL queries for INSERT, UPDATE, DELETE, SELECT.

Execute queries using PreparedStatement or Statement.

Map ResultSet rows to MenuItem objects using mapToMenuItem().

Return a List<MenuItem> where required.

The system should connect to a MySQL database using the following default credentials:

DB URL: jdbc:mysql://localhost/ri_db

USER: test

PWD: test123

The menu table has already been created with the following structure:

Table Name: menu

Input Format

The first line of input consists of an integer choice, representing the operation to be performed (1 for Add Item, 2 for Restock item, 3 for reduce item, 4 for Display, 5 for Exit).

For choice 1 (Add Menu Item):

- The second line consists of an integer item_id.
- The third line consists of a string name.
- The fourth line consists of a string category.
- The fifth line consists of a double price.

For choice 2 (Update Item Price):

- The second line consists of an integer item_id.
- The third line consists of a double new_price.

For choice 3 (View Item Details):

- The second line consists of an integer item_id.

For choice 4 (Display All Menu Items):

- No additional inputs are required.

For choice 5 (Exit):

- No additional inputs are required.

Output Format

For choice 1 (Add Menu Item):

- Print "Menu item added successfully" if the item was added.
- Print "Failed to add item." if the insertion failed.

For choice 2 (Update Item Price):

- Print "Item price updated successfully" if the price update was successful.
- Print "Item not found." if the specified item ID does not exist.

For choice 3 (View Item Details):

- Display the item details in the format:
- ID: [item_id] | Name: [name] | Category: [category] | Price: [price]
- Print "Item not found." if the specified item ID does not exist.

For choice 4 (Display All Menu Items):

- Display each item on a new line in the format:
- ID | Name | Category | Price
- If no items are available, print nothing (or handle with an appropriate message if desired).

For choice 5 (Exit):

- Print "Exiting Restaurant Management System."

For invalid input:

- Print "Invalid choice. Please try again."

Sample Test Case

Input: 1

11

Margherita Pizza

Main Course

12.99

4

5

Output: Menu item added successfully

ID | Name | Category | Price

11 | Margherita Pizza | Main Course | 12.99

Exiting Restaurant Management System.

Answer

```
import java.sql.*;
```

```
import java.util.Scanner;
```

```
class RestaurantManagementSystem {
```

```
    public static void main(String[] args) {
```

```
        try (Connection conn = DriverManager.getConnection("jdbc:mysql://localhost/ri_db", "test", "test123"));
```

```
            Scanner scanner = new Scanner(System.in)) {
```

```
                boolean running = true;
```

```
                while (running) {
```

```
                    int choice = scanner.nextInt();
```

```
                    switch (choice) {
```

```
                        case 1:
```

```
                            addMenuItem(conn, scanner);
```

```
                            break;
```

```
                        case 2:
```

```
                            updateItemPrice(conn, scanner);
```

```
                            break;
```

```

        case 3:
            viewItemDetails(conn, scanner);
            break;
        case 4:
            displayAllMenuItems(conn);
            break;
        case 5:
            System.out.println("Exiting Restaurant Management System.");
            running = false;
            break;
        default:
            System.out.println("Invalid choice. Please try again.");
    }
}
} catch (SQLException e) {
    e.printStackTrace();
}
}

public static void addMenuItem(Connection conn, Scanner scanner) {
    int id = scanner.nextInt();
    scanner.nextLine();
    String name = scanner.nextLine();
    String category = scanner.nextLine();
    double price = scanner.nextDouble();

    try {
        String sql = "INSERT INTO menu (itemId, name, category, price) VALUES"
            "(?, ?, ?, ?)";
        PreparedStatement ps = conn.prepareStatement(sql);

        ps.setInt(1, id);
        ps.setString(2, name);
        ps.setString(3, category);
        ps.setDouble(4, price);

        int rows = ps.executeUpdate();

        if (rows > 0)
            System.out.println("Menu item added successfully");
        else
            System.out.println("Failed to add item.");
    }
}

```

```

    } catch (Exception e) {
        System.out.println("Failed to add item.");
    }
}

// =====
// METHOD 2 – Update Item Price
// =====
public static void updateItemPrice(Connection conn, Scanner scanner) {
    int id = scanner.nextInt();
    double newPrice = scanner.nextDouble();

    try {
        String check = "SELECT * FROM menu WHERE itemId = ?";
        PreparedStatement ps1 = conn.prepareStatement(check);
        ps1.setInt(1, id);
        ResultSet rs = ps1.executeQuery();

        if (!rs.next()) {
            System.out.println("Item not found.");
            return;
        }

        String sql = "UPDATE menu SET price = ? WHERE itemId = ?";
        PreparedStatement ps = conn.prepareStatement(sql);
        ps.setDouble(1, newPrice);
        ps.setInt(2, id);
        ps.executeUpdate();

        System.out.println("Item price updated successfully");

    } catch (Exception e) {
        System.out.println("Item not found.");
    }
}

// =====
// METHOD 3 – View Item Details
// =====
public static void viewItemDetails(Connection conn, Scanner scanner) {
    int id = scanner.nextInt();

```



```

try {
    String sql = "SELECT * FROM menu WHERE itemId = ?";
    PreparedStatement ps = conn.prepareStatement(sql);
    ps.setInt(1, id);

    ResultSet rs = ps.executeQuery();

    if (rs.next()) {
        System.out.println(
            "ID: " + rs.getInt("itemId") +
            " | Name: " + rs.getString("name") +
            " | Category: " + rs.getString("category") +
            " | Price: " + rs.getDouble("price"));
    } else {
        System.out.println("Item not found.");
    }

} catch (Exception e) {
    System.out.println("Item not found.");
}

}

// =====
// METHOD 4 – Display All Menu Items
// =====
public static void displayAllMenuItems(Connection conn) {
    try {
        String sql = "SELECT * FROM menu ORDER BY itemId";
        Statement st = conn.createStatement();
        ResultSet rs = st.executeQuery(sql);

        System.out.println("ID | Name | Category    | Price");
        while (rs.next()) {
            System.out.println(
                rs.getInt("itemId") + " | " +
                rs.getString("name") + " | " +
                rs.getString("category") + " | " +
                String.format("%.2f", rs.getDouble("price")));
        }

    } catch (Exception e) {
        // No output needed
    }
}

```

```

}
}
}

// =====
// MENU ITEM CLASS
// =====

class MenuItem {
    private int itemId;
    private String name;
    private String category;
    private double price;

    public MenuItem(int itemId, String name, String category, double price) {
        this.itemId = itemId;
        this.name = name;
        this.category = category;
        this.price = price;
    }

    public int getItemId() { return itemId; }
    public void setItemId(int itemId) { this.itemId = itemId; }

    public String getName() { return name; }
    public void setName(String name) { this.name = name; }

    public String getCategory() { return category; }
    public void setCategory(String category) { this.category = category; }

    public double getPrice() { return price; }
    public void setPrice(double price) { this.price = price; }
}

//

```

Status : Wrong

Marks : 0/10

2. Problem Statement

Create a JDBC-based Inventory Management System that handles runtime

input to manage items in an inventory. The system should allow users to:

Add a new item (item ID, name, quantity, price).

Restock an item by increasing its quantity.

Reduce the stock of an item, ensuring sufficient quantity.

Display all items in the inventory in a sorted order by item ID.

Exit the application.

Half of the code is given here; Only the remaining part should be completed.

The system should connect to a MySQL database using the following default credentials:

DB URL: jdbc:mysql://localhost/ri_db

USER: test

PWD: test123

The items table has already been created with the following structure:

Table Name: items

Input Format

The first line of input consists of an integer choice, representing the operation to be performed (1 for Add Item, 2 for Restock item, 3 for reduce item, 4 for Display, 5 for Exit).

For choice 1 (Add Item):

- The second line consists of an integer item_id.
- The third line consists of a string name.
- The fourth line consists of an integer quantity.
- The fifth line consists of a double price.

For choice 2 (Restock Item):

- The second line consists of an integer `item_id`.
- The third line consists of an integer `quantity_to_add` (must be positive).

For choice 3 (Reduce Stock):

- The second line consists of an integer `item_id`.
- The third line consists of an integer `quantity_to_remove` (must be positive).

For choice 4 (Display Inventory):

- No additional inputs are required.

For choice 5 (Exit):

- No additional inputs are required.

Output Format

For choice 1 (Add Item):

- Print "Item added successfully" if the item was added.
- Print "Failed to add item." if the insertion failed.

For choice 2 (Restock Item):

- Print "Item restocked successfully" if the restock was successful.
- Print "Item not found." if the specified item ID does not exist.

For choice 3 (Reduce Stock):

- Print "Stock reduced successfully" if the stock reduction was successful.
- Print "Not enough stock to remove." if there is insufficient quantity.
- Print "Item not found." if the specified item ID does not exist.

For choice 4 (Display Inventory):

- Display each item on a new line in the format:
- ID | Name | Quantity | Price
- If no items are available, print nothing (or handle with an appropriate message if desired).

For choice 5 (Exit):

- Print "Exiting Inventory Management System."

For invalid input:

- Print "Invalid choice. Please try again."

Sample Test Case

Input: 1

101

Laptop

50

1200.00

4

5

Output: Item added successfully

ID | Name | Quantity | Price

101 | Laptop | 50 | 1200.00

Exiting Inventory Management System.

Answer

```
import java.sql.*;
```

```
import java.util.Scanner;
```

```
class InventoryManagementSystem {
```

```
    public static void main(String[] args) {
```

```
        try (Connection conn = DriverManager.getConnection("jdbc:mysql://localhost/ri_db", "test", "test123"));
```

```
            Scanner scanner = new Scanner(System.in)) {
```

```
                boolean running = true;
```

```
                while (running) {
```

```
                    int choice = scanner.nextInt();
```

```
                    switch (choice) {
```

```
                        case 1:
```

```
                            addItem(conn, scanner);
```

```
                            break;
```

```

        case 2:
            restockItem(conn, scanner);
            break;
        case 3:
            reduceStock(conn, scanner);
            break;
        case 4:
            displayInventory(conn);
            break;
        case 5:
            System.out.println("Exiting Inventory Management System.");
            running = false;
            break;
        default:
            System.out.println("Invalid choice. Please try again.");
    }
}
} catch (SQLException e) {
    e.printStackTrace();
}
}

```

public static void addItem(Connection conn, Scanner scanner) throws
SQLException {

```

    int id = scanner.nextInt();
    String name = scanner.next();
    int qty = scanner.nextInt();
    double price = scanner.nextDouble();

```

```

    PreparedStatement ps = conn.prepareStatement(
        "INSERT INTO items(item_id, name, quantity, price) VALUES (?, ?, ?, ?)");
    ps.setInt(1, id);
    ps.setString(2, name);
    ps.setInt(3, qty);
    ps.setDouble(4, price);

```

```

    if (ps.executeUpdate() > 0)
        System.out.println("Item added successfully");
    else
        System.out.println("Failed to add item.");
}

```

public static void restockItem(Connection conn, Scanner scanner) throws

```
SQLException {
    int id = scanner.nextInt();
    int qtyAdd = scanner.nextInt();

    PreparedStatement ps = conn.prepareStatement(
        "SELECT quantity FROM items WHERE item_id=?");
    ps.setInt(1, id);
    ResultSet rs = ps.executeQuery();

    if (!rs.next()) {
        System.out.println("Item not found.");
        return;
    }

    PreparedStatement upd = conn.prepareStatement(
        "UPDATE items SET quantity = quantity + ? WHERE item_id=?");
    upd.setInt(1, qtyAdd);
    upd.setInt(2, id);
    upd.executeUpdate();

    System.out.println("Item restocked successfully");
}
```

public static void reduceStock(Connection conn, Scanner scanner) throws
SQLException {

```
    int id = scanner.nextInt();
    int qtyRemove = scanner.nextInt();

    PreparedStatement ps = conn.prepareStatement(
        "SELECT quantity FROM items WHERE item_id=?");
    ps.setInt(1, id);
    ResultSet rs = ps.executeQuery();

    if (!rs.next()) {
        System.out.println("Item not found.");
        return;
    }

    int currentQty = rs.getInt(1);
    if (currentQty < qtyRemove) {
        System.out.println("Not enough stock to remove.");
    }
}
```

```

        return;
    }

    PreparedStatement upd = conn.prepareStatement(
        "UPDATE items SET quantity = quantity - ? WHERE item_id=?");
    upd.setInt(1, qtyRemove);
    upd.setInt(2, id);
    upd.executeUpdate();

    System.out.println("Stock reduced successfully");
}

public static void displayInventory(Connection conn) throws SQLException {
    Statement st = conn.createStatement();
    ResultSet rs = st.executeQuery("SELECT * FROM items ORDER BY item_id");

    // REQUIRED HEADER
    System.out.println("ID | Name | Quantity | Price");

    while (rs.next()) {
        System.out.println(
            rs.getInt("item_id") + " | " +
            rs.getString("name") + " | " +
            rs.getInt("quantity") + " | " +
            String.format("%.2f", rs.getDouble("price"))
        );
    }
}
}

```

Status : Correct

Marks : 10/10