

# Lab Quiz 4

## Q1

**Q1** (40 points; 10 points per part): Study the following code to answer the question below

```
class BinaryTreeNode[A](var value: A, var left: BinaryTreeNode[A], var right: BinaryTreeNode[A]) {}
```

```
def preOrderTraversal[A](node: BinaryTreeNode[A], f: A => Unit): Unit = {  
  if (node != null) {  
    f(node.value)  
    preOrderTraversal(node.left, f)  
    preOrderTraversal(node.right, f)  
  }  
}
```

```
def inOrderTraversal[A](node: BinaryTreeNode[A], f: A => Unit): Unit = {  
  if (node != null) {  
    inOrderTraversal(node.left, f)  
    f(node.value)  
    inOrderTraversal(node.right, f)  
  }  
}
```

```
def postOrderTraversal[A](node: BinaryTreeNode[A], f: A => Unit): Unit = {  
  if (node != null) {  
    postOrderTraversal(node.left, f)  
    postOrderTraversal(node.right, f)  
    f(node.value)  
  }  
}
```

```
def q1(): Unit = {  
  val root = new BinaryTreeNode[Int](17, null, null)  
  root.left = new BinaryTreeNode[Int](-30, null, null)  
  root.right = new BinaryTreeNode[Int](4, null, null)  
  root.left.right = new BinaryTreeNode[Int](6, null, null)  
  root.right.left = new BinaryTreeNode[Int](81, null, null)  
  root.right.right = new BinaryTreeNode[Int](-4, null, null)  
  root.right.right.right = new BinaryTreeNode[Int](3, null, null)  
  
  preOrderTraversal(root, println)  
  inOrderTraversal(root, println)  
  postOrderTraversal(root, println)  
}
```

a) Draw the tree created by running `q1()`

b) Write the pre-order traversal of the tree (`preOrderTraversal(root, println)`)

c) Write the in-order traversal of the tree (`inOrderTraversal(root, println)`)

d) Write the post-order traversal of the tree (`postOrderTraversal(root, println)`)

## Q2

**Q2** (20 points): Study the following code to answer the question below

```
class BinarySearchTree[A](comparator: (A, A) => Boolean) {

  var root: BinaryTreeNode[A] = null

  def insert(a: A): Unit = {
    if(this.root == null){
      this.root = new BinaryTreeNode(a, null, null)
    }else{
      insertHelper(a, this.root)
    }
  }

  def insertHelper(a: A, node: BinaryTreeNode[A]): Unit = {
    if(comparator(node.value, a)){
      if(node.right == null){
        node.right = new BinaryTreeNode[A](a, null, null)
      }else{
        insertHelper(a, node.right)
      }
    }else{
      if(node.left == null){
        node.left = new BinaryTreeNode[A](a, null, null)
      }else{
        insertHelper(a, node.left)
      }
    }
  }
}

def q2(): Unit = {

  val comp = (a: Int, b: Int) => a < b

  val bst = new BinarySearchTree[Int](comp)

  bst.insert(-10)
  bst.insert(9)
  bst.insert(-9)
  bst.insert(6)
  bst.insert(-8)
  bst.insert(-1)
  bst.insert(10)
  bst.insert(-12)
```

}

Draw the Binary Search Tree created when q2() is called

Q3

**Q3** (20 points):

Write the following infix expression using postfix notation

$$4 + 5 * (3 + 1 - 2) - 20 / 2$$

## Q4

**Q4** (20 points): Study the following code to answer the question below

```
class BinaryTreeNode[A](var value: A, var left: BinaryTreeNode[A], var right: BinaryTreeNode[A]) {

  def compute(func: (Int, A, Int) => Int): Int = {
    val leftResult = if (this.left != null) this.left.compute(func) else 1
    val rightResult = if (this.right != null) this.right.compute(func) else 1
    func(leftResult, this.value, rightResult)
  }
}

def q4(): Unit = {
  val root = new BinaryTreeNode[Int](9, null, null)
  root.left = new BinaryTreeNode[Int](4, null, null)
  root.right = new BinaryTreeNode[Int](18, null, null)
  root.left.right = new BinaryTreeNode[Int](-6, null, null)
  root.right.left = new BinaryTreeNode[Int](12, null, null)
  root.right.right = new BinaryTreeNode[Int](8, null, null)

  val customFunction = (a: Int, b: Int, c: Int) => a + 4 * b - c

  println(root.compute(customFunction))
}
```

What is printed by the last line of q4()?