


# Building and Deploying Fair and Unbiased Machine Learning Systems: **An Art, Not Science**

By: Rashmi Nagpal






# Agenda

<b>Introduction</b>	What is machine learning and its related concepts!
<b>Understanding Black-Box</b>	How machine learning models can lead to unfair, biased decisions
<b>Building fair &amp; unbiased models</b>	What are the strategies to build fair and unbiased machine learning models
<b>ML Test Pyramid</b>	What are the levels of testing in ML Test Pyramid
<b>Technical Debts in ML Sys</b>	What are the strategies to address technical debts
<b>Conclusion</b>	What are the key-takeaways from this talk!





## ARTIFICIAL INTELLIGENCE

Any technique that  
enables computers to  
mimic human behavior



## MACHINE LEARNING

Ability to learn without  
explicitly being  
programmed



## DEEP LEARNING

Extract patterns from data  
using neural networks

3 1 3 5 6 7  
1 4 5 9 2 3





A




B



C






INPUT

WEIGHTS

SUM AND  
BIAS

ACTIVATION  
FUNCTION

OUTPUT





95	32	45	14	18	71	10	36	54	79	03	29	21	42	88
32	45	14	18	71	10	36	54	79	03	29	21	42	88	30
45	14	18	71	10	36	54	79	03	29	21	42	88	30	84
14	18	71	10	36	54	79	03	29	21	42	88	30	84	19
18	71	10	36	54	79	03	29	21	42	88	30	84	19	72
71	10	36	54	79	03	29	21	42	88	30	84	19	72	08
10	36	54	79	03	29	21	42	88	30	84	19	72	08	80
36	54	79	03	29	21	42	88	30	84	19	72	08	80	37
54	79	03	29	21	42	88	30	84	19	72	08	80	37	96
79	03	29	21	42	88	30	84	19	72	08	80	37	96	92
03	29	21	42	88	30	84	19	72	08	80	37	96	92	50
29	21	42	88	30	84	19	72	08	80	37	96	92	50	20
21	42	88	30	84	19	72	08	80	37	96	92	50	20	49
42	88	30	84	19	72	08	80	37	96	92	50	20	49	86
88	30	84	19	72	08	80	37	96	92	50	20	49	86	00


Image  
Classification  
Algorithms


92%

Dog


8%

Cat










# Word Embedding



# ChatGPT



The doctor yelled at the nurse because he was late. Who was late?



In the sentence "The doctor yelled at the nurse because he was late," the pronoun "he" refers back to "the doctor." Therefore, the doctor was the one who was late.



The doctor apologized to the nurse for her late arrival to the emergency room. Who was late previously?



Based on the sentence you provided, it seems that the doctor was the one who was late to the emergency room, and that's why he apologized to the nurse.

# ChatGPT



The nurse apologized to the doctor for his late arrival to the operation room. Who was late?



Based on the sentence you provided, it seems that there is an error in the sentence construction that could cause confusion about who was actually late. The use of pronouns in this sentence makes it unclear who was late to the operation room. However, if we assume that the sentence was intended to mean that the nurse was apologizing to the doctor for **her** own late arrival to the operation room, then the nurse was the one who was late.




# Credit Score





03

Why biased,  
unfair output?



**01**

**Biased training  
dataset**

**03**

**Lack of diversity  
within dataset**

**02**

**Cognitive bias**

**04**

**Inadequate  
evaluation metrics**



04



How to build  
unbiased, fair  
ML models?





**01**

## **Diverse Data**

Collect well representative dataset

**02**

## **Pre-process Data Pipeline**

Use data augmentation, feature selection techniques.

**03**

## **Fairness Techniques**

Use algorithmic fairness measures like equalized odds, statistical parity et al.

**04**

## **Testing end-to-end ML pipeline**

Add model testing, unit testing and robustness testing techniques

**05**

## **Use Explainability frameworks**

Use framework like LIME , SHAP



```
# Load the data
data = pd.read_csv('https://archive.ics.uci.edu/ml/machine-learning-databases/statlog/german/german.data', header=None, sep=' ')

# Define feature names
feature_names = ['status', 'duration', 'credit_history', 'purpose', 'amount', 'savings', 'employment_duration', 'installment_rate', 'statussex',
'other_debtors', 'residence_since', 'property', 'age', 'other_installment_plans', 'housing', 'number_credits', 'job', 'people_liable',
'telephone', 'foreign_worker', 'labels']

# Assign the feature names to the dataset
data.columns = feature_names

# Convert categorical variables to numerical using one-hot encoding
categorical_cols = ['status', 'credit_history', 'purpose', 'savings', 'employment_duration', 'statussex', 'other_debtors', 'property',
'other_installment_plans', 'housing', 'job', 'telephone', 'foreign_worker']
data = pd.get_dummies(data, columns=categorical_cols)

# Define the target variable and the features
target_col = 'labels'

features = data.drop(target_col, axis=1)

target = data[target_col]
```



# Apply SMOTE : Synthetic Minority Oversampling Technique (SMOTE) is a statistical technique for increasing the number of cases in your dataset in a balanced way.

```
sm = SMOTE(sampling_strategy='auto')
```

```
X_resampled, y_resampled = sm.fit_resample(features , target)
```

# Split the data into train and test sets

```
X_train, X_test, y_train, y_test = train_test_split(X_resampled, y_resampled, test_size=0.2, random_state=42)
```

```
print("Before applying SMOTE technique \n")
```

```
unique, counts = np.unique(y_train, return_counts=True)
```

```
print(dict(zip(unique, counts)))
```

```
print("\n After applying SMOTE technique \n")
```

```
unique, counts = np.unique(y_resampled, return_counts=True)
```

```
print(dict(zip(unique, counts)))
```

Before applying SMOTE technique

{0: 569, 1: 551}

After applying SMOTE technique

{0: 700, 1: 700}



```
# Define the XGBoost model
```

```
params = {  
    'objective': 'binary:logistic',  
    'eval_metric': 'auc',  
    'tree_method': 'hist',  
    'max_depth': 8,  
    'learning_rate': 0.1,  
    'n_estimators': 100,  
    'seed': 42  
}
```

```
xg_model = xgb.XGBClassifier(**params)
```

```
# Train the model
```

```
xg_model.fit(X_train_balanced, y_train_balanced)
```



# Predict the test set

```
xgboost_y_pred = xg_model.predict(X_test)
```

# Evaluate the model

```
print(f'Accuracy: {accuracy_score(y_test, xgboost_y_pred):.4f}')
```

```
print(classification_report(y_test, xgboost_y_pred))
```

# Get the predicted labels for the privileged and unprivileged groups

```
privileged = y_pred[(X_test['statussex_A91'] == 1) | (X_test['statussex_A93'] == 1) | (X_test['statussex_A94'] == 1) & (X_test['age'] > 18)]
```

```
unprivileged = y_pred[(X_test['statussex_A92'] == 1) & (X_test['age'] > 18)]
```

Accuracy: 0.8200

	precision	recall	f1-score	support
--	-----------	--------	----------	---------

0	0.72	0.64	0.68	59
1	0.86	0.89	0.88	141

accuracy			0.82	200
macro avg	0.79	0.77	0.78	200
weighted avg	0.82	0.82	0.82	200

Score

Precision 0.857143

Recall 0.893617

F1-Score 0.875000

Accuracy 0.820000



```
# Calculate the proportions of positive predictions for each group
```

```
privileged_proportion = np.mean(privileged)
```

```
unprivileged_proportion = np.mean(unprivileged)
```

```
# Define the search space
```

```
min_bound = [0.001, 1, 10]
```

```
max_bound = [0.5, 10, 200]
```

```
bounds = (min_bound, max_bound)
```

```
# Initialize the particle swarm
```

```
options = {'c1': 0.5, 'c2': 0.3, 'w': 0.9}
```

```
num_particles = 2
```

```
dimensions = len(min_bound)
```

```
optimizer = ps.single.GlobalBestPSO(n_particles=num_particles, dimensions=dimensions, options=options, bounds=bounds)
```





```
# Run the optimization
```

```
cost, pos = optimizer.optimize(objective_function, iters=10)
```

```
# Calculate the Statistical Parity Difference
```


```
statistical_parity_difference = privileged_proportion - unprivileged_proportion
```

```
# Print the Statistical Parity Difference
```

```
print(f"Statistical Parity Difference: {statistical_parity_difference:.4f}") #output -> Statistical Parity Difference: 0.0039
```

Statistical Parity Difference: 0.0039









# Testing Strategies

## Unit Testing


Testing individual components (data pre-processing, feature extraction et al.)

## Integration Testing

Verifying the interactions and compatibility b/w various components (data pipeline)

## Model Testing

Examine the performance and the behavior of ML model (evaluating metrics like PRF scores)





## Robustness Testing

Examine the system's ability to handle edge cases, outliers and adversarial inputs.

## Deployment Testing

Validating ML system in production environment under real-world conditions

## Ethical & Fairness Testing

Evaluation for bias, discrimination & adherence to ethical regulations






```
@pytest.mark.parametrize("text, expected_sentiment", [
    ("The absolutely love Prague, it's so beautiful!", 1),
    ("The movie was awful.", 0),
    ("The movie was great, but the plot of the movie was not good.", pytest.param(None, marks=pytest.mark.xfail)),
    ("", None)
])

def test_sentiment_classification(sentiment_classifier, training_data, test_data, text, expected_sentiment):
    train_classifier(sentiment_classifier, *training_data)
    sentiment = sentiment_classifier.predict_sentiment(text)
    assert sentiment == expected_sentiment

def test_non_english_text(sentiment_classifier, training_data):
    train_classifier(sentiment_classifier, *training_data)
    text = "Je déteste ce film."
    sentiment = sentiment_classifier.predict_sentiment(text)
    assert sentiment in [0, 1]
```







## Explainable Data

What data was used to train the model?

## Explainable Predictions

What features and weights were used for this particular task / prediction?

## Explainable Algorithms

What are the individual layers and the thresholds for predictions?



```
import numpy as np
from sklearn.feature_extraction.text import TfidfVectorizer
from sklearn.pipeline import make_pipeline
from sklearn.linear_model import LogisticRegression
from lime.lime_text import LimeTextExplainer
```

```
# Sample training data
```

```
texts = [ "I love the beaches at Miami!!", "This movie is terrible", "The sounds so exciting!", "The plot was not good", "We have so  
many attendees, be it developers, CEO's, datascientists, researchers at the Europython conference!",  
         "I love the night-life at Prague!" ]
```

```
labels = [1, 0, 1, 0, 1, 1]
```

```
# Vectorize the data
```

```
vectorizer = TfidfVectorizer()
```

```
X = vectorizer.fit_transform(texts)
```



```
# Train a logistic regression classifier
```

```
model = make_pipeline(vectorizer, LogisticRegression())
```

```
model.fit(texts, labels)
```

```
# Text to explain
```

```
text_to_explain = "So exciting to be presenting at the Europython conference in Prague!!"
```

```
# LIME explanation
```

```
explainer = LimeTextExplainer(class_names=["Negative", "Positive"])
```

```
exp = explainer.explain_instance(text_to_explain, model.predict_proba, num_features=5)
```

```
exp.show_in_notebook(text=True)
```

Using `tqdm.autonotebook.tqdm` in notebook mode. Use `tqdm.tqdm` instead to force console mode (e.g. in jupyter console)

Prediction probabilities

Negative	0.27
Positive	0.73

Negative

Positive

Text with highlighted words

So exciting to be presenting at the Europython conference in Prague!!

at  
0.01  
So  
0.01  
exciting  
0.01  
Prague  
0.01  
the  
0.00



The illustration depicts a laptop screen with a blue background. A yellow folder icon is centered on the screen, displaying the text '13%'. Below the folder, white text reads 'Only 13% machine learning models make it to production ~ Venturebeat'. To the right of the folder is a white upward-pointing arrow. A red line with circular endpoints at the bottom left and top right curves around the laptop. In the background, two overlapping window icons are visible: a red one on the left with a circular graphic of blue and white bubbles, and a white one on the right with three colored dots (red, yellow, green) in its title bar.

# 13%

Only 13% machine learning models make it to production ~  
Venturebeat





07



# Technical Debts in ML Sys



## DATA DEBT

This includes issues like low data quality, small datasets, and lack of representativeness.

## ARCHITECTURE DEBT

An overly complex ML architecture which makes system hard to navigate, extend and debug.


## ALGORITHMIC DEBT


Reliance on the outdated or suboptimal modelling assumptions / techniques.

## TESTING DEBT

Lack of tests written to verify correct functionality, catch bugs, and refactors of the ML system.







**Review the ML  
pipeline**


**Check data quality  
issues**




**Examine model  
performance**

**Evaluate model  
explainability**

**Adopt automated  
testing practises**



**Perform regular  
code refactoring**





- 
- 
- Building fair, accountable, and trustworthy machine learning systems is critical for ensuring that the benefits of these systems are widely accessible and enjoyed by all.
  - By ensuring that our models are transparent and interpretable, we can detect and mitigate biases and unfairness before they cause harm.
  - Monitoring and evaluation of these models is vital to maintain accountability and ensure that they continue to function as intended.
- 

# Alternative resources

- Book: <https://fairmlbook.org/>
- Course: Introduction to Deep Learning <http://introtodeeplearning.com/>
- Article: <https://hdr.mitpress.mit.edu/pub/f9kuryi8/release/8>





“Garbage in, garbage out, so let’s sift through biases and purge them out! In the realm of fairness, one size never fits, it’s a kaleidoscope of perspectives and intricate bits.”

– **Yours truly**





# Thank you!

 @iamrashminagpal