

FRONTEND API CONTRACT

LEX Chat History

New chat, sidebar history, open thread, delete, and persisted POST /chat/. History lives on the Main API (Postgres). REST only — no sockets.

Document ID NL-FE-LEX-HIST-001

Version 1.0 · Date 11 August 2026

LEX BASE

<https://nexus-lexis-backend-ql8w.vercel.app/api/v1/lex>

1. Changelog

Added

Method	Path	Purpose
POST	/sessions/	New chat — empty thread + session_key
GET	/sessions/	History sidebar — this owner's threads
GET	/sessions/:session_key/	Open one thread (user + LEX turns)
DELETE	/sessions/:session_key/	Delete a thread

Updated

Method	Path	Change
POST	/chat/	Saves every turn. Returns session_key, owner_key, title. Last 5 turns → LLM.

Deleted

None. GET /sessions/ is no longer an empty stub.

2. Product flow

```
Open LEX
  mint owner_key = guest_ + uuid    (localStorage)
  GET /sessions/?owner_key=...      → sidebar

New chat
  POST /sessions/ { owner_key }
  → session_key, title "New chat"
  POST /chat/ { message, session_key, owner_key }
  → response; server stores both turns; title = first message

Open old thread
  GET /sessions/:session_key/?owner_key=...
  → messages[] sender user | lex
```

AUTH Logged-in: send Authorization: Bearer. Owner becomes user:<id>. Do not mix guest and user owners.

3. Owner (required for history)

Who	How
Guest	JSON owner_key or header X-Lex-Owner
Logged in	JWT only — backend sets user:<id>

No owner → GET /sessions/ is []. Chat still works; if the server returns owner_key, save it.

4. New chat

```
POST /api/v1/lex/sessions/
X-Lex-Owner: guest_8f3a...
{ "owner_key": "guest_8f3a...", "title": "New chat" }

201 { session_key, owner_key, title: "New chat", messages: [] }
```

5. Send a message (saved)

```
POST /api/v1/lex/chat/
{
  "message": "What is an FIR?",
  "session_key": "session_1786457021479_0678f44a",
  "owner_key": "guest_8f3a..."
}

200 adds: session_key, owner_key, title
Omit session_key → server creates one and returns it.
```

6. List / open / delete

Call	Use
GET /sessions/?owner_key=	Sidebar. messages always []. turnCount on each row.
GET /sessions/:key/	Bubbles: sender user lex, text, showReferral, referralLabel
DELETE /sessions/:key/	Remove thread. Wrong owner → 404.

List item title = first user message (max 50 chars). Urdu bubble: language === "UR" → RTL. showReferral / chat show_lawyer → Find a Lawyer.

7. Checklist

#	Check
1	Persist owner_key (guest uuid) or send JWT
2	New chat = POST /sessions/
3	Sidebar = GET /sessions/
4	Open = GET /sessions/:key/
5	Send = POST /chat/ with same session_key
6	No WebSocket in production

LIVE Live: <https://nexus-lexis-backend-ql8w.vercel.app/api/v1/lex>