

PMSCS 694

Information Security

Crypto: Part IV

Lecture 6

Md. Rafsan Jani
Associate Professor
Department of Computer Science and Engineering
Jahangirnagar University

AES: Executive Summary

- ❑ **Block size:** 128 bits (others in Rijndael)
- ❑ **Key length:** 128, 192 or 256 bits
(independent of block size in Rijndael)
- ❑ 10 to 14 rounds (depends on key length)
- ❑ Each round uses 4 functions (3 "layers")
 - ByteSub (nonlinear layer)
 - ShiftRow (linear mixing layer)
 - MixColumn (nonlinear layer)
 - AddRoundKey (key addition layer)

AES ByteSub

- Treat 128 bit block as 4x4 byte array

$$\begin{bmatrix} a_{00} & a_{01} & a_{02} & a_{03} \\ a_{10} & a_{11} & a_{12} & a_{13} \\ a_{20} & a_{21} & a_{22} & a_{23} \\ a_{30} & a_{31} & a_{32} & a_{33} \end{bmatrix} \longrightarrow \text{ByteSub} \longrightarrow \begin{bmatrix} b_{00} & b_{01} & b_{02} & b_{03} \\ b_{10} & b_{11} & b_{12} & b_{13} \\ b_{20} & b_{21} & b_{22} & b_{23} \\ b_{30} & b_{31} & b_{32} & b_{33} \end{bmatrix}.$$

- ByteSub is AES's "S-box"
- Can be viewed as nonlinear (but invertible) composition of two math operations

AES "S-box"

Last 4 bits of input

First 4
bits of
input

	0	1	2	3	4	5	6	7	8	9	a	b	c	d	e	f
0	63	7c	77	7b	f2	6b	6f	c5	30	01	67	2b	fe	d7	ab	76
1	ca	82	c9	7d	fa	59	47	f0	ad	d4	a2	af	9c	a4	72	c0
2	b7	fd	93	26	36	3f	f7	cc	34	a5	e5	f1	71	d8	31	15
3	04	c7	23	c3	18	96	05	9a	07	12	80	e2	eb	27	b2	75
4	09	83	2c	1a	1b	6e	5a	a0	52	3b	d6	b3	29	e3	2f	84
5	53	d1	00	ed	20	fc	b1	5b	6a	cb	be	39	4a	4c	58	cf
6	d0	ef	aa	fb	43	4d	33	85	45	f9	02	7f	50	3c	9f	a8
7	51	a3	40	8f	92	9d	38	f5	bc	b6	da	21	10	ff	f3	d2
8	cd	0c	13	ec	5f	97	44	17	c4	a7	7e	3d	64	5d	19	73
9	60	81	4f	dc	22	2a	90	88	46	ee	b8	14	de	5e	0b	db
a	e0	32	3a	0a	49	06	24	5c	c2	d3	ac	62	91	95	e4	79
b	e7	c8	37	6d	8d	d5	4e	a9	6c	56	f4	ea	65	7a	ae	08
c	ba	78	25	2e	1c	a6	b4	c6	e8	dd	74	1f	4b	bd	8b	8a
d	70	3e	b5	66	48	03	f6	0e	61	35	57	b9	86	c1	1d	9e
e	e1	f8	98	11	69	d9	8e	94	9b	1e	87	e9	ce	55	28	df
f	8c	a1	89	0d	bf	e6	42	68	41	99	2d	0f	b0	54	bb	16

AES ShiftRow

□ Cyclic shift rows

$$\begin{bmatrix} a_{00} & a_{01} & a_{02} & a_{03} \\ a_{10} & a_{11} & a_{12} & a_{13} \\ a_{20} & a_{21} & a_{22} & a_{23} \\ a_{30} & a_{31} & a_{32} & a_{33} \end{bmatrix} \xrightarrow{\text{ShiftRow}} \begin{bmatrix} a_{00} & a_{01} & a_{02} & a_{03} \\ a_{11} & a_{12} & a_{13} & a_{10} \\ a_{22} & a_{23} & a_{20} & a_{21} \\ a_{33} & a_{30} & a_{31} & a_{32} \end{bmatrix}$$

- the first row doesn't shift,
- the second row circular left-shifts by one byte,
- the third row left-shifts by two bytes, and the last row left-shifts three bytes.
- Note that ShiftRow is inverted by simply shifting in the opposite direction.

AES MixColumn

- Invertible, linear operation applied to each column

$$\begin{bmatrix} a_{0i} \\ a_{1i} \\ a_{2i} \\ a_{3i} \end{bmatrix} \longrightarrow \text{MixColumn} \longrightarrow \begin{bmatrix} b_{0i} \\ b_{1i} \\ b_{2i} \\ b_{3i} \end{bmatrix} \quad \text{for } i = 0, 1, 2, 3$$

- Implemented as a (big) lookup table

AES AddRoundKey

- XOR subkey with block

$$\begin{bmatrix} a_{00} & a_{01} & a_{02} & a_{03} \\ a_{10} & a_{11} & a_{12} & a_{13} \\ a_{20} & a_{21} & a_{22} & a_{23} \\ a_{30} & a_{31} & a_{32} & a_{33} \end{bmatrix} \oplus \begin{bmatrix} k_{00} & k_{01} & k_{02} & k_{03} \\ k_{10} & k_{11} & k_{12} & k_{13} \\ k_{20} & k_{21} & k_{22} & k_{23} \\ k_{30} & k_{31} & k_{32} & k_{33} \end{bmatrix} = \begin{bmatrix} b_{00} & b_{01} & b_{02} & b_{03} \\ b_{10} & b_{11} & b_{12} & b_{13} \\ b_{20} & b_{21} & b_{22} & b_{23} \\ b_{30} & b_{31} & b_{32} & b_{33} \end{bmatrix}$$

Block

Subkey

- RoundKey (subkey) determined by **key schedule** algorithm

AES Decryption

- ❑ To decrypt, process must be invertible
- ❑ Inverse of MixAddRoundKey is easy, since " $\oplus$ " is its own inverse
- ❑ MixColumn is invertible (inverse is also implemented as a lookup table)
- ❑ Inverse of ShiftRow is easy (cyclic shift the other direction)
- ❑ ByteSub is invertible (inverse is also implemented as a lookup table)

Time for TEA...

- ❑ Tiny Encryption Algorithm (TEA)
- ❑ 64 bit block, 128 bit key
- ❑ Assumes 32-bit arithmetic
- ❑ Number of rounds is variable (32 is considered secure)
- ❑ Uses "weak" round function, so large number of rounds required

TEA Encryption

Assuming 32 rounds:

$(K[0], K[1], K[2], K[3]) = 128 \text{ bit key}$

$(L, R) = \text{plaintext (64-bit block)}$

$\text{delta} = 0x9e3779b9 \text{ //magic number or seeds}$

$\text{sum} = 0$

for $i = 1$ to 32

$\text{sum} += \text{delta}$

$L += ((R \ll 4) + K[0]) \wedge (R + \text{sum}) \wedge ((R \gg 5) + K[1])$

$R += ((L \ll 4) + K[2]) \wedge (L + \text{sum}) \wedge ((L \gg 5) + K[3])$

next i

$\text{ciphertext} = (L, R)$

TEA Decryption

Assuming 32 rounds:

$(K[0], K[1], K[2], K[3]) = 128 \text{ bit key}$

$(L, R) = \text{ciphertext (64-bit block)}$

$\text{delta} = 0x9e3779b9$

$\text{sum} = \text{delta} \ll 5$

for $i = 1$ to 32

$R \leftarrow ((L \ll 4) + K[2]) \wedge (L + \text{sum}) \wedge ((L \gg 5) + K[3])$

$L \leftarrow ((R \ll 4) + K[0]) \wedge (R + \text{sum}) \wedge ((R \gg 5) + K[1])$

$\text{sum} \leftarrow \text{sum} + \text{delta}$

next i

$\text{plaintext} = (L, R)$

TEA Comments

- ❑ **"Almost"** a Feistel cipher
 - Uses + and − (mod 2^{32}) instead of $\oplus$ (XOR)
- ❑ Simple, easy to implement, fast, low memory requirement, etc.
- ❑ Possibly a "related key" attack
- ❑ eXtended TEA (XTEA) eliminates related key attack (slightly more complex)
- ❑ Simplified TEA (STEAs) —insecure version used as an example for cryptanalysis

Block Cipher Modes


Multiple Blocks

- ❑ How to encrypt multiple blocks?
- ❑ Do we need a new key for each block?
 - If so, as impractical as a one-time pad!
- ❑ Encrypt each block independently?
- ❑ Is there any analog of codebook “additive”?
- ❑ How to handle partial blocks?
 - We won't discuss this issue

Modes of Operation

- ❑ Many modes —we discuss 3 most popular
- ❑ Electronic Codebook (**ECB**) mode
 - Encrypt each block independently
 - Most obvious approach, but a **bad** idea
- ❑ Cipher Block Chaining (**CBC**) mode
 - “Chain” the blocks together
 - More secure than ECB, virtually no extra work
- ❑ Counter Mode (**CTR**) mode
 - Block ciphers acts like a stream cipher
 - Popular for random access

ECB



Same plaintext will be encrypted to the same ciphertext

ECB Mode

- Notation: $C = E(P, K)$
- Given plaintext $P_0, P_1, \dots, P_m, \dots$
- Most obvious way to use a block cipher:

Encrypt

$$C_0 = E(P_0, K)$$

$$C_1 = E(P_1, K)$$

$$C_2 = E(P_2, K) \dots$$

Decrypt

$$P_0 = D(C_0, K)$$

$$P_1 = D(C_1, K)$$

$$P_2 = D(C_2, K) \dots$$

- For fixed key K , this is “electronic” version of a codebook cipher (***without additive***)
 - With a different codebook for each key

ECB Cut and Paste


- Suppose plaintext is
Alice digs Bob. Trudy digs Tom.
- Assuming 64-bit blocks and 8-bit ASCII:
 $P_0 = \text{"Alice di"}, P_1 = \text{"gs Bob. "},$
 $P_2 = \text{"Trudy di"}, P_3 = \text{"gs Tom. "}$
- Ciphertext: C_0, C_1, C_2, C_3
- Trudy cuts and pastes: C_0, C_3, C_2, C_1
- Decrypts as
Alice digs Tom. Trudy digs Bob.

ECB Weakness

- Suppose $P_i = P_j$
- Then $C_i = C_j$ and Trudy knows $P_i = P_j$
- This gives Trudy some information, even if she does not know P_i or P_j
- Trudy might know P_i
- Is this a serious issue?


Alice Hates ECB Mode

- Alice's uncompressed image, and ECB encrypted (TEA)



- Why does this happen?
- Same plaintext yields same ciphertext!

Cipher Block Chaining (CBC)



What if IV is predictable?

CBC Mode

- ❑ Blocks are “chained” together
- ❑ A random initialization vector, or IV, is required to initialize CBC mode
- ❑ IV is random, but not secret

Encryption

$$C_0 = E(IV \oplus P_0, K),$$

$$C_1 = E(C_0 \oplus P_1, K),$$

$$C_2 = E(C_1 \oplus P_2, K), \dots$$

Decryption

$$P_0 = IV \oplus D(C_0, K),$$

$$P_1 = C_0 \oplus D(C_1, K),$$

$$P_2 = C_1 \oplus D(C_2, K), \dots$$


- ❑ Analogous to classic codebook *with additive*

CBC Mode

- ❑ Identical plaintext blocks yield different ciphertext blocks —this is very good!
- ❑ But what about errors in transmission?
 - If C_1 is garbled to, say, G then
$$P_1 \neq C_0 \oplus D(G, K), P_2 \neq G \oplus D(C_2, K)$$
 - But $P_3 = C_2 \oplus D(C_3, K), P_4 = C_3 \oplus D(C_4, K), \dots$
 - Automatically recovers from errors!
- ❑ Cut and paste is still possible, but more complex (and will cause garbles)

Alice Likes CBC Mode

- Alice's uncompressed image, Alice CBC encrypted (TEA)



- Why does this happen?
- Same plaintext yields different ciphertext!

Counter Mode (CTR)

- CTR is popular for random access
- Use block cipher like a stream cipher

Encryption

$$C_0 = P_0 \oplus E(\text{IV}, K),$$

$$C_1 = P_1 \oplus E(\text{IV}+1, K),$$

$$C_2 = P_2 \oplus E(\text{IV}+2, K), \dots$$

Decryption

$$P_0 = C_0 \oplus D(\text{IV}, K),$$

$$P_1 = C_1 \oplus D(\text{IV}+1, K),$$

$$P_2 = C_2 \oplus D(\text{IV}+2, K), \dots$$

- Note: CBC also works for random access
 - But there is a significant limitation in that case

Integrity

Data Integrity

- ❑ **Integrity** —detect unauthorized writing (i.e., detect unauthorized mod of data)
- ❑ Example: Inter-bank fund transfers
 - Confidentiality may be nice, integrity is *critical*
- ❑ Encryption provides **confidentiality** (prevents unauthorized disclosure)
- ❑ Encryption alone does **not** provide integrity
 - One-time pad, ECB cut-and-paste, etc., etc.

MAC

- ❑ Message Authentication Code (MAC)
 - Used for data **integrity**
 - Integrity **not** the same as confidentiality
- ❑ MAC is computed as **CBC residue**
 - That is, compute CBC encryption, saving only final ciphertext block, the MAC
 - The MAC serves as a cryptographic checksum for data

MAC Computation

- MAC computation (assuming N blocks)

$$C_0 = E(IV \oplus P_0, K),$$

$$C_1 = E(C_0 \oplus P_1, K),$$

$$C_2 = E(C_1 \oplus P_2, K), \dots$$

$$C_{N-1} = E(C_{N-2} \oplus P_{N-1}, K) = \text{MAC}$$

- Send $IV, P_0, P_1, \dots, P_{N-1}$ and MAC
- Receiver does same computation and verifies that result agrees with MAC
- Both sender and receiver must know K

Does a MAC work?

- Suppose Alice has 4 plaintext blocks
- Alice computes
$$C_0 = E(IV \oplus P_0, K), C_1 = E(C_0 \oplus P_1, K),$$
$$C_2 = E(C_1 \oplus P_2, K), C_3 = E(C_2 \oplus P_3, K) = \text{MAC}$$
- Alice sends IV, P_0, P_1, P_2, P_3 and **MAC** to Bob
- Suppose Trudy changes P_1 to X
- Bob computes
$$C_0 = E(IV \oplus P_0, K), C_1 = E(C_0 \oplus X, K),$$
$$C_2 = E(C_1 \oplus P_2, K), C_3 = E(C_2 \oplus P_3, K) = \text{MAC} \neq \text{MAC}$$
- It works since error propagates into **MAC**
- Cannot make **MAC** == **MAC** without key K

Confidentiality and Integrity

- ❑ Encrypt with one key, MAC with another key
- ❑ Why not use the same key?
 - Send last encrypted block (MAC) twice?
 - This cannot add any security!
- ❑ Using different keys to encrypt and compute MAC works, even if keys are related
 - But, twice as much work as encryption alone
 - Can do a little better —about 1.5 “encryptions”
- ❑ Confidentiality and integrity with same work as one encryption is a research topic

Sample Questions

- ❑ What improvements does AES offer over DES? List its key features and block size.
- ❑ Describe the four functions used in an AES encryption round.
- ❑ AES consists of four functions in three layers.
 - a. Which of the four functions are primarily for confusion and which are primarily for diffusion? Justify your answer
- ❑ Compare ECB (Electronic Codebook) and CBC (Cipher Block Chaining) modes of operation. Highlight their advantages and disadvantages.
- ❑ What is the purpose of an initialization vector (IV) in CBC mode?
- ❑ Explain the concept of a Message Authentication Code (MAC). How does it ensure data integrity?