

PMSCS 670

Software Testing

Graph Coverage-Part2

Lecture 8-9

Mohammad Ashraful Islam

Overview

- A common application of graph criteria is to program **source**
- **Graph** : Usually the control flow graph (CFG)
- **Node coverage** : Execute every statement
- **Edge coverage** : Execute every branch
- **Loops** : Looping structures such as for loops, while loops, etc.
- **Data flow coverage** : Augment the CFG
 - **defs** are statements that assign values to variables
 - **uses** are statements that use variables

Example Control Flow – Stats

```
public static void computeStats (int [ ] numbers)
{
    int length = numbers.length;
    double med, var, sd, mean, sum, varsum;

    sum = 0;
    for (int i = 0; i < length; i++)
    {
        sum += numbers [ i ];
    }
    med  = numbers [ length / 2];
    mean = sum / (double) length;

    varsum = 0;
    for (int i = 0; i < length; i++)
    {
        varsum = varsum + ((numbers [ i ] - mean) * (numbers [ i ] - mean));
    }
    var = varsum / ( length - 1.0 );
    sd  = Math.sqrt ( var );

    System.out.println ("length:          " + length);
    System.out.println ("mean:          " + mean);
    System.out.println ("median:        " + med);
    System.out.println ("variance:      " + var);
    System.out.println ("standard deviation: " + sd);
}
```

*Draw the
graph and
label the
edges.*

Control Flow Graph for Stats

```
public static void computeStats (int [ ] numbers)
```

```
{  
    int length = numbers.length;  
    double med, var, sd, mean, sum, varsum;
```

```
    sum = 0;
```

```
    for (int i = 0; i < length; i++)
```

```
    {  
        sum += numbers [ i ];
```

```
    }  
    med = numbers [ length / 2];  
    mean = sum / (double) length;
```

```
    varsum = 0;
```

```
    for (int i = 0; i < length; i++)
```

```
    {  
        varsum = varsum + ((numbers [ i ] - mean) * (numbers [ i ] - mean));
```

```
    }  
    var = varsum / ( length - 1.0 );  
    sd = Math.sqrt ( var );
```

```
    System.out.println ("length: " + length);
```



```
    System.out.println ("mean: " + mean);
```

```
    System.out.println ("median: " + med);
```

```
    System.out.println ("variance: " + var);
```

```
    System.out.println ("standard deviation: " + sd);
```

```
}
```




i = 0




i >= length



i++



i = 0



i < length


i >= length



i++




Control Flow TRs and Test Paths—EC



Edge Coverage		
TR	Test Path	
A. [1, 2] Write down the TRs for	[1, 2, 8]	Write down test paths that tour all edges.
B. [3, 5]		
C. [4, 3]		
D. [5, 6]		
E. [6, 7]		
F. [6, 8]		
G. [7, 6]		
H. [6, 8]		
I. [7, 6]		

Control Flow TRs and Test Paths—EPC



Edge-Pair Coverage

TR

A. [1, 2, 3]

Write down
TRs for EPC.

D. [3, 4, 3]

E. [3, 5, 6]

F. [4, 3, 5]

G. [5, 6, 7]

H. [5, 6, 8]

I. [6, 7, 6]

J. [7, 6, 8]

K. [4, 3, 4]

L. [7, 6, 7]

Test Paths

i. [1, 2, 3, 4, 3, 5, 6, 7, 6, 8]
Write down test

ii. [1 paths that tour all
edge pairs.

iii. [1, 2, 3, 4, 3, 5, 6, 7, 6, 8]

TP	TRs toured	sidetrips
i	A, B, D, E, F, G, I, J	C, H
ii	A, C, E, H	
iii	A, B, D, E, F, G, I, J, K, L	C, H

TP iii makes TP i
redundant. A minimal
set of TPs is cheaper.

Control Flow TRs and Test Paths—PPC

```
graph TD; 1((1)) --> 2((2)); 2 --> 3((3)); 3 --> 4((4)); 4 --> 3; 3 --> 5((5)); 5 --> 6((6)); 6 --> 7((7)); 7 --> 6; 6 --> 8((8));
```

Prime Path Coverage

TR
A. [3, 4, 3]
B. [4 Write down
C. [TRs for PPC.
D. [7, 6, 8]
E. [6, 7, 6]
F. [1, 2, 3, 4]
G. [4, 3, 5, 6, 7]
H. [4, 3, 5, 6, 8]
I. [1, 2, 3, 5, 6, 7]
J. [1, 2, 3, 5, 6, 8]

Test Paths
i. [1, 2, 3, 4, 3, 5, 6, 7, 6, 8]
ii. [Write down test
paths that tour all
prime paths.
iii. [1, 2, 3, 4, 3, 5, 6, 8]
iv. [1, 2, 3, 5, 6, 7, 6, 8]
v. [1, 2, 3, 5, 6, 8]


TP	TRs toured	sidetrips
i	A, D, E, F, G	H, I, J
ii	A, B, C, D, E, F,	H, I, J
iii	A, F, H	J
iv	D, E, F, I	J
v	J	

TP ii makes
TP i redundant.

Data Flow Criteria

Goal : Ensure that values are computed and used correctly

- **Definition (def)** : A location where a value for a variable is stored into memory
- **Use** : A location where a variable's value is accessed



Defs: def (1) = { **X** }

def (5) = { **Z** }

def (6) = { **Z** }

*Fill in
these
sets*

Uses: use (5) = { **X** }

use (6) = { **X** }

The values given in **defs** should **reach** at least **one, some, or all possible uses**

DU Pairs and DU Paths

- **def (n) or def (e)** : The set of variables that are defined by node n or edge e
- **use (n) or use (e)** : The set of variables that are used by node n or edge e
- **DU pair** : A pair of locations (l_i, l_j) such that a variable v is **defined at l_i** and **used at l_j**
- **Def-clear** : A path from l_i to l_j is **def-clear with respect to variable v** if v is not given another value on any of the nodes or edges in the path
- **Reach** : If there is a def-clear path from l_i to l_j with respect to v , the def of v at l_i reaches the use at l_j
- **du-path** : A simple subpath that is def-clear with respect to v from a def of v to a use of v
- **du (n_i, n_j, v)** – the set of du-paths from n_i to n_j
- **du (n_i, v)** – the set of du-paths that start at n_i

Touring DU-Paths

- A test path p *du-tours* subpath d with respect to v if p tours d and the subpath taken is def-clear with respect to v
- *Sidetrips* can be used, just as with previous touring
- Three criteria
 - Use every **def**
 - Get to every **use**
 - Follow all **du-paths**

Data Flow Test Criteria

- First, we make sure **every def** reaches **a use**

All-defs coverage (ADC) : For each set of du-paths $S = du(n, v)$, TR contains at least one path d in S .


- Then we make sure that **every def** reaches **all** possible uses

All-uses coverage (AUC) : For each set of du-paths to uses $S = du(n_d, n_u, v)$, TR contains at least one path d in S .

- Finally, we cover **all the paths** between defs and uses

All-du-paths coverage (ADUPC) : For each set $S = du(n_i, n_j, v)$, TR contains every path d in S .

Data Flow Testing Example



All-defs for X

*Write down
paths to
satisfy ADC*

All-uses for X

[1, 2, 4, 5]

*Write down
paths to
satisfy AUC*

All-du-paths for X

[1, 2, 4, 5]

*Write down
paths to
satisfy
ADUPC*
[1, 3, 4, 6]

Data Flow Coverage for Source

- **def** : a location where a value is stored into **memory**
 - x appears on the **left side** of an assignment (x = 44;)
 - x is a **formal parameter** of a method (implicit def when method starts)
 - x is an **input** to a program
- **use** : a location where variable's value is **accessed**
 - x appears on the **right side** of an assignment
 - x appears in a conditional **test**
 - x is an **actual parameter** to a method
 - x is an **output** of the program
 - x is an output of a method in a **return** statement
- If a def and a use appear on the **same node**, then **it is only a DU-pair if the def occurs after** the use and the node is in a loop

Example Data Flow – Stats


```
public static void computeStats (int [ ] numbers)
{
    int length = numbers.length;
    double med, var, sd, mean, sum, varsum;

    sum = 0.0;
    for (int i = 0; i < length; i++)
    {
        sum += numbers [ i ];
    }
    med  = numbers [ length / 2 ];
    mean = sum / (double) length;


    varsum = 0.0;
    for (int i = 0; i < length; i++)
    {
        varsum = varsum + ((numbers [ i ] - mean) * (numbers [ i ] - mean));
    }
    var = varsum / ( length - 1 );
    sd  = Math.sqrt ( var );

    System.out.println ("length:          " + length);
    System.out.println ("mean:          " + mean);
    System.out.println ("median:        " + med);
    System.out.println ("variance:      " + var);
    System.out.println ("standard deviation: " + sd);
}
```

Control Flow Graph for Stats



CFG for Stats – With Defs & Uses



Defs and Uses Tables for Stats

Node	Def	Use
1	{ numbers, sum, length }	{ numbers }
2	{ i }	
3		
4	{ sum, i }	{ numbers, i, sum }
5	{ med, mean, varsum, i }	{ numbers, length, sum }
6		
7	{ varsum, i }	{ varsum, numbers, i, mean }
8	{ var, sd }	{ varsum, length, var, mean, med, var, sd }

Edge	Use
(1, 2)	
(2, 3)	
(3, 4)	{ i, length }
(4, 3)	
(3, 5)	{ i, length }
(5, 6)	
(6, 7)	{ i, length }
(7, 6)	
(6, 8)	{ i, length }

DU Pairs for Stats

variable	DU Pairs
numbers	(1,1) (1, 4) (1, 5) (1, 7)
length	(1, 5) (1, 8) (1, (3,4)) (1, (3,5)) (1, (6,7)) (1, (6,8))
med	(5, 8)
var	(8, 8)
sd	(8, 8)
mean	(5, 7) (5, 8)
sum	(1, 4) (1, 5) (4, 4) (4, 5)
varsum	(5, 7) (5, 8) (7, 7) (7, 8)
i	(2, 4) (2, (3,4)) (2, (3,5)) (2, 7) (2, (6,7)) (2, (6,8)) (4, 4) (4, (3,4)) (4, (3,5)) (4, 7) (4, (6,7)) (4, (6,8)) (5, 7) (5, (6,7)) (5, (6,8)) (7, 7) (7, (6,7)) (7, (6,8))

defs come before uses,
do not count as DU pairs

defs after use in loop,
these are valid DU pairs

No def-clear path ...
different scope for i

No path through graph
from nodes 5 and 7 to 4 or 3

DU Paths for Stats

variable	DU Pairs	DU Paths
numbers	(1, 4) (1, 5) (1, 7)	[1, 2, 3, 4] [1, 2, 3, 5] [1, 2, 3, 5, 6, 7]
length	(1, 5) (1, 8) (1, (3,4)) (1, (3,5)) (1, (6,7)) (1, (6,8))	[1, 2, 3, 5] [1, 2, 3, 5, 6, 8] [1, 2, 3, 4] [1, 2, 3, 5] [1, 2, 3, 5, 6, 7] [1, 2, 3, 5, 6, 8]
med	(5, 8)	[5, 6, 8]
var	(8, 8)	No path needed
sd	(8, 8)	No path needed
sum	(1, 4) (1, 5) (4, 4) (4, 5)	[1, 2, 3, 4] [1, 2, 3, 5] [4, 3, 4] [4, 3, 5]

variable	DU Pairs	DU Paths
mean	(5, 7) (5, 8)	[5, 6, 7] [5, 6, 8]
varsum	(5, 7) (5, 8) (7, 7) (7, 8)	[5, 6, 7] [5, 6, 8] [7, 6, 7] [7, 6, 8]
i	(2, 4) (2, (3,4)) (2, (3,5)) (4, 4) (4, (3,4)) (4, (3,5)) (5, 7) (5, (6,7)) (5, (6,8)) (7, 7) (7, (6,7)) (7, (6,8))	[2, 3, 4] [2, 3, 4] [2, 3, 5] [4, 3, 4] [4, 3, 4] [4, 3, 5] [5, 6, 7] [5, 6, 7] [5, 6, 8] [7, 6, 7] [7, 6, 7] [7, 6, 8]

DU Paths for Stats—No Duplicates

There are 34 DU paths for Stats, but only 12 unique

★ [1, 2, 3, 4]	[4, 3, 4] ★
★ [1, 2, 3, 5]	[4, 3, 5] ★
★ [1, 2, 3, 5, 6, 7]	[5, 6, 7] ★
★ [1, 2, 3, 5, 6, 8]	[5, 6, 8] ★
★ [2, 3, 4]	[7, 6, 7] ★
★ [2, 3, 5]	[7, 6, 8] ★

★ 4 expect a loop not to be “entered”

★ 6 require at least one iteration of a loop

★ 2 require at least two iterations of a loop

Test Cases and Test Paths

Test Case : numbers = (44) ; length = 1

Test Path : [1, 2, 3, 4, 3, 5, 6, 7, 6, 8]

Additional DU Paths covered (no sidetrips)

[1, 2, 3, 4] [2, 3, 4] [4, 3, 5] [5, 6, 7] [7, 6, 8]

The five stars ★ that require at least one iteration of a loop

Test Case : numbers = (2, 10, 15) ; length = 3

Test Path : [1, 2, 3, 4, 3, 4, 3, 4, 3, 5, 6, 7, 6, 7, 6, 7, 6, 8]

DU Paths covered (no sidetrips)

[4, 3, 4] [7, 6, 7]

The two stars ★ that require at least two iterations of a loop

Other DU paths ★ require arrays with length 0 to skip loops

But the method fails with index out of bounds exception...

med = numbers [length / 2];



Summary

- Applying the graph test criteria to **control flow graphs** is relatively straightforward
 - Most of the developmental **research** work was done with CFGs
- A few **subtle decisions** must be made to translate control structures into the graph
- Some tools will assign each statement to a **unique node**
 - These slides and the book uses **basic blocks**
 - Coverage is the same, although the **bookkeeping** will differ