

The GNU Privacy Handbook

Copyright © 1999 by The Free Software Foundation

Permission is granted to copy, distribute and/or modify this document under the terms of the GNU Free Documentation License, Version 1.1 or any later version published by the Free Software Foundation; with no Invariant Sections, no Front-Cover Texts, and no Back-Cover Texts. A copy of the license is included in the section entitled "GNU Free Documentation License".

Please direct questions, bug reports, or suggestions concerning this manual to the maintainer, Mike Ashley (<jashley@acm.org>). When referring to the manual please specify which version of the manual you have by using this version string: \$Name: v1_1 \$.

Contributors to this manual include Matthew Copeland, Joergen Grahn, and David A. Wheeler. J Horacio MG has translated the manual to Spanish.

Table of Contents

1. [Getting Started](#)

[Generating a new keypair](#)

[Generating a revocation certificate](#)

[Exchanging keys](#)

[Exporting a public key](#)

[Importing a public key](#)

[Encrypting and decrypting documents](#)

[Making and verifying signatures](#)

[Clearsigned documents](#)

[Detached signatures](#)

2. [Concepts](#)

[Symmetric ciphers](#)

[Public-key ciphers](#)

[Hybrid ciphers](#)

[Digital signatures](#)

3. [Key Management](#)

[Managing your own keypair](#)

[Key integrity](#)

[Adding and deleting key components](#)

[Revoking key components](#)

[Updating a key's expiration time](#)

[Validating other keys on your public keyring](#)

[Trust in a key's owner](#)

[Using trust to validate keys](#)

[Distributing keys](#)

4. [Daily use of GnuPG](#)

[Defining your security needs](#)

[Choosing a key size](#)

[Protecting your private key](#)

[Selecting expiration dates and using subkeys](#)

[Managing your web of trust](#)

[Building your web of trust](#)

[Using GnuPG legally](#)

5. [Topics](#)

[Writing user interfaces](#)

A. [GNU Free Documentation License](#)

0. [PREAMBLE](#)

1. [APPLICABILITY AND DEFINITIONS](#)

2. [VERBATIM COPYING](#)

3. [COPYING IN QUANTITY](#)

4. [MODIFICATIONS](#)

5. [COMBINING DOCUMENTS](#)

6. [COLLECTIONS OF DOCUMENTS](#)

7. [AGGREGATION WITH INDEPENDENT WORKS](#)

8. [TRANSLATION](#)

9. [TERMINATION](#)

10. [FUTURE REVISIONS OF THIS LICENSE](#)

[How to use this License for your documents](#)

List of Figures

3-1. [A hypothetical web of trust](#)

Chapter 1. Getting Started

GnuPG is a tool for secure communication. This chapter is a quick-start guide that covers the core functionality of GnuPG. This includes keypair creation, exchanging and verifying keys, encrypting and decrypting documents, and authenticating documents with digital signatures. It does not explain in detail the concepts behind public-key cryptography, encryption, and digital signatures. This is covered in Chapter [2](#). It also does not explain how to use GnuPG wisely. This is covered in Chapters [3](#) and [4](#).

GnuPG uses public-key cryptography so that users may communicate securely. In a public-key system, each user has a pair of keys consisting of a *private key* and a *public key*. A user's private key is kept secret; it need never be revealed. The public key may be given to anyone with whom the user wants to communicate. GnuPG uses a somewhat more sophisticated scheme in which a user has a primary keypair and then zero or more additional subordinate keypairs. The primary and subordinate keypairs are bundled to facilitate key management and the bundle can often be considered simply as one keypair.

Generating a new keypair

The command-line option `--gen-key` is used to create a new primary keypair.

```
alice% gpg --gen-key
gpg (GnuPG) 0.9.4; Copyright (C) 1999 Free Software Foundation, Inc.
This program comes with ABSOLUTELY NO WARRANTY.
This is free software, and you are welcome to redistribute it
under certain conditions. See the file COPYING for details.
```

```
Please select what kind of key you want:
```

```
(1) DSA and ElGamal (default)
```

```
(2) DSA (sign only)
```

```
(4) ElGamal (sign and encrypt)
Your selection?
```

GnuPG is able to create several different types of keypairs, but a primary key must be capable of making signatures. There are therefore only three options. Option 1 actually creates two keypairs. A DSA keypair is the primary keypair usable only for making signatures. An ElGamal subordinate keypair is also created for encryption. Option 2 is similar but creates only a DSA keypair. Option 4[1] creates a single ElGamal keypair usable for both making signatures and performing encryption. In all cases it is possible to later add additional subkeys for encryption and signing. For most users the default option is fine.

You must also choose a key size. The size of a DSA key must be between 512 and 1024 bits, and an ElGamal key may be of any size. GnuPG, however, requires that keys be no smaller than 768 bits. Therefore, if Option 1 was chosen and you choose a keysize larger than 1024 bits, the ElGamal key will have the requested size, but the DSA key will be 1024 bits.

```
About to generate a new ELG-E keypair.
      minimum keysize is 768 bits
      default keysize is 1024 bits
      highest suggested keysize is 2048 bits
What keysize do you want? (1024)
```

The longer the key the more secure it is against brute-force attacks, but for almost all purposes the default keysize is adequate since it would be cheaper to circumvent the encryption than try to break it. Also, encryption and decryption will be slower as the key size is increased, and a larger keysize may affect signature length. Once selected, the keysize can never be changed.

Finally, you must choose an expiration date. If Option 1 was chosen, the expiration date will be used for both the ElGamal and DSA keypairs.

```
Please specify how long the key should be valid.
      0 = key does not expire
      <n> = key expires in n days
      <n>w = key expires in n weeks
      <n>m = key expires in n months
      <n>y = key expires in n years
Key is valid for? (0)
```

For most users a key that does not expire is adequate. The expiration time should be chosen with care, however, since although it is possible to change the expiration date after the key is created, it may be difficult to communicate a change to users who have your public key.

You must provide a user ID in addition to the key parameters. The user ID is used to associate the key being created with a real person.

```
You need a User-ID to identify your key; the software constructs the user id
from Real Name, Comment and Email Address in this form:
      "Heinrich Heine (Der Dichter) <heinrichh@duesseldorf.de>"
```

```
Real name:
```

Only one user ID is created when a key is created, but it is possible to create additional user IDs if you want to use the key in two or more contexts, e.g., as an employee at work and a political activist on the side. A user ID should be created carefully since it cannot be edited after it is created.

GnuPG needs a passphrase to protect the primary and subordinate private keys that you keep in your possession.

```
You need a Passphrase to protect your private key.
```

Enter passphrase:

There is no limit on the length of a passphrase, and it should be carefully chosen. From the perspective of security, the passphrase to unlock the private key is one of the weakest points in GnuPG (and other public-key encryption systems as well) since it is the only protection you have if another individual gets your private key. Ideally, the passphrase should not use words from a dictionary and should mix the case of alphabetic characters as well as use non-alphabetic characters. A good passphrase is crucial to the secure use of GnuPG.

Generating a revocation certificate

After your keypair is created you should immediately generate a revocation certificate for the primary public key using the option `--gen-revoke`. If you forget your passphrase or if your private key is compromised or lost, this revocation certificate may be published to notify others that the public key should no longer be used. A revoked public key can still be used to verify signatures made by you in the past, but it cannot be used to encrypt future messages to you. It also does not affect your ability to decrypt messages sent to you in the past if you still do have access to the private key.

```
alice% gpg --output revoke.asc --gen-revoke mykey
[...]
```

The argument `mykey` must be a *key specifier*, either the key ID of your primary keypair or any part of a user ID that identifies your keypair. The generated certificate will be left in the file `revoke.asc`. If the `--output` option is omitted, the result will be placed on standard output. Since the certificate is short, you may wish to print a hardcopy of the certificate to store somewhere safe such as your safe deposit box. The certificate should not be stored where others can access it since anybody can publish the revocation certificate and render the corresponding public key useless.

Exchanging keys

To communicate with others you must exchange public keys. To list the keys on your public keyring use the command-line option `--list-keys`.

```
alice% gpg --list-keys
/users/alice/.gnupg/pubring.gpg
-----
pub  1024D/BB7576AC 1999-06-04 Alice (Judge) <alice@cyb.org>
sub  1024g/78E9A8FA 1999-06-04
```

Exporting a public key

To send your public key to a correspondent you must first export it. The command-line option `--export` is used to do this. It takes an additional argument identifying the public key to export. As with the `--gen-revoke` option, either the key ID or any part of the user ID may be used to identify the key to export.

```
alice% gpg --output alice.gpg --export alice@cyb.org
```

The key is exported in a binary format, but this can be inconvenient when the key is to be sent though email or published on a web page. GnuPG therefore supports a command-line option `--armor` [\[2\]](#) that causes output

to be generated in an ASCII-armored format similar to uuencoded documents. In general, any output from GnuPG, e.g., keys, encrypted documents, and signatures, can be ASCII-armored by adding the `--armor` option.

```
alice% gpg --armor --export alice@cyb.org
-----BEGIN PGP PUBLIC KEY BLOCK-----
Version: GnuPG v0.9.7 (GNU/Linux)
Comment: For info see http://www.gnupg.org
```

```
[...]
-----END PGP PUBLIC KEY BLOCK-----
```

Importing a public key

A public key may be added to your public keyring with the `--import` option.

```
alice% gpg --import blake.gpg
gpg: key 9E98BC16: public key imported
gpg: Total number processed: 1
gpg:      imported: 1
alice% gpg --list-keys
/users/alice/.gnupg/pubring.gpg
-----
pub  1024D/BB7576AC 1999-06-04 Alice (Judge) <alice@cyb.org>
sub  1024g/78E9A8FA 1999-06-04

pub  1024D/9E98BC16 1999-06-04 Blake (Executioner) <blake@cyb.org>
sub  1024g/5C8CBD41 1999-06-04
```

Once a key is imported it should be validated. GnuPG uses a powerful and flexible trust model that does not require you to personally validate each key you import. Some keys may need to be personally validated, however. A key is validated by verifying the key's fingerprint and then signing the key to certify it as a valid key. A key's fingerprint can be quickly viewed with the `--fingerprint` command-line option, but in order to certify the key you must edit it.

```
alice% gpg --edit-key blake@cyb.org

pub  1024D/9E98BC16  created: 1999-06-04 expires: never      trust: -/q
sub  1024g/5C8CBD41  created: 1999-06-04 expires: never
(1)  Blake (Executioner) <blake@cyb.org>

Command> fpr
pub  1024D/9E98BC16 1999-06-04 Blake (Executioner) <blake@cyb.org>
      Fingerprint: 268F 448F CCD7 AF34 183E 52D8 9BDE 1A08 9E98 BC16
```

A key's fingerprint is verified with the key's owner. This may be done in person or over the phone or through any other means as long as you can guarantee that you are communicating with the key's true owner. If the fingerprint you get is the same as the fingerprint the key's owner gets, then you can be sure that you have a correct copy of the key.

After checking the fingerprint, you may sign the key to validate it. Since key verification is a weak point in public-key cryptography, you should be extremely careful and *always* check a key's fingerprint with the owner before signing the key.

```
Command> sign

pub  1024D/9E98BC16  created: 1999-06-04 expires: never      trust: -/q
      Fingerprint: 268F 448F CCD7 AF34 183E 52D8 9BDE 1A08 9E98 BC16
```

```
Blake (Executioner) <blake@cyb.org>
```

```
Are you really sure that you want to sign this key
with your key: "Alice (Judge) <alice@cyb.org>"
```

```
Really sign?
```

Once signed you can check the key to list the signatures on it and see the signature that you have added. Every user ID on the key will have one or more self-signatures as well as a signature for each user that has validated the key.

```
Command> check
uid  Blake (Executioner) <blake@cyb.org>
sig!      9E98BC16 1999-06-04    [self-signature]
sig!      BB7576AC 1999-06-04    Alice (Judge) <alice@cyb.org>
```

Encrypting and decrypting documents

A public and private key each have a specific role when encrypting and decrypting documents. A public key may be thought of as an open safe. When a correspondent encrypts a document using a public key, that document is put in the safe, the safe shut, and the combination lock spun several times. The corresponding private key is the combination that can reopen the safe and retrieve the document. In other words, only the person who holds the private key can recover a document encrypted using the associated public key.

The procedure for encrypting and decrypting documents is straightforward with this mental model. If you want to encrypt a message to Alice, you encrypt it using Alice's public key, and she decrypts it with her private key. If Alice wants to send you a message, she encrypts it using your public key, and you decrypt it with your private key.

To encrypt a document the option `--encrypt` is used. You must have the public keys of the intended recipients. The software expects the name of the document to encrypt as input; if omitted, it reads standard input. The encrypted result is placed on standard output or as specified using the option `--output`. The document is compressed for additional security in addition to encrypting it.

```
alice% gpg --output doc.gpg --encrypt --recipient blake@cyb.org doc
```

The `--recipient` option is used once for each recipient and takes an extra argument specifying the public key to which the document should be encrypted. The encrypted document can only be decrypted by someone with a private key that complements one of the recipients' public keys. In particular, you cannot decrypt a document encrypted by you unless you included your own public key in the recipient list.

To decrypt a message the option `--decrypt` is used. You need the private key to which the message was encrypted. Similar to the encryption process, the document to decrypt is input, and the decrypted result is output.

```
blake% gpg --output doc --decrypt doc.gpg
```

```
You need a passphrase to unlock the secret key for
user: "Blake (Executioner) <blake@cyb.org>"
1024-bit ELG-E key, ID 5C8CBD41, created 1999-06-04 (main key ID 9E98BC16)
```

```
Enter passphrase:
```

Documents may also be encrypted without using public-key cryptography. Instead, you use a symmetric cipher to encrypt the document. The key used to drive the symmetric cipher is derived from a passphrase supplied when the document is encrypted, and for good security, it should not be the same passphrase that you use to protect your private key. Symmetric encryption is useful for securing documents when the passphrase does not need to be communicated to others. A document can be encrypted with a symmetric cipher by using the `--symmetric` option.

```
alice% gpg --output doc.gpg --symmetric doc
Enter passphrase:
```

Making and verifying signatures

A digital signature certifies and timestamps a document. If the document is subsequently modified in any way, a verification of the signature will fail. A digital signature can serve the same purpose as a hand-written signature with the additional benefit of being tamper-resistant. The GnuPG source distribution, for example, is signed so that users can verify that the source code has not been modified since it was packaged.

Creating and verifying signatures uses the public/private keypair in an operation different from encryption and decryption. A signature is created using the private key of the signer. The signature is verified using the corresponding public key. For example, Alice would use her own private key to digitally sign her latest submission to the Journal of Inorganic Chemistry. The associate editor handling her submission would use Alice's public key to check the signature to verify that the submission indeed came from Alice and that it had not been modified since Alice sent it. A consequence of using digital signatures is that it is difficult to deny that you made a digital signature since that would imply your private key had been compromised.

The command-line option `--sign` is used to make a digital signature. The document to sign is input, and the signed document is output.

```
alice% gpg --output doc.sig --sign doc
```

```
You need a passphrase to unlock the private key for
user: "Alice (Judge) <alice@cyb.org>"
1024-bit DSA key, ID BB7576AC, created 1999-06-04
```

```
Enter passphrase:
```

The document is compressed before being signed, and the output is in binary format.

Given a signed document, you can either check the signature or check the signature and recover the original document. To check the signature use the `--verify` option. To verify the signature and extract the document use the `--decrypt` option. The signed document to verify and recover is input and the recovered document is output.

```
blake% gpg --output doc --decrypt doc.sig
gpg: Signature made Fri Jun  4 12:02:38 1999 CDT using DSA key ID BB7576AC
gpg: Good signature from "Alice (Judge) <alice@cyb.org>"
```

Clearsigned documents

A common use of digital signatures is to sign usenet postings or email messages. In such situations it is undesirable to compress the document while signing it. The option `--clearsign` causes the document to be

wrapped in an ASCII-armored signature but otherwise does not modify the document.

```
alice% gpg --clearsign doc
```

```
You need a passphrase to unlock the secret key for
user: "Alice (Judge) <alice@cyb.org>"
1024-bit DSA key, ID BB7576AC, created 1999-06-04
```

```
-----BEGIN PGP SIGNED MESSAGE-----
Hash: SHA1
```

```
[...]
```

```
-----BEGIN PGP SIGNATURE-----
```

```
Version: GnuPG v0.9.7 (GNU/Linux)
```

```
Comment: For info see http://www.gnupg.org
```

```
iEYEARECAAYFAjdYCQoACgkQJ9S6ULtldqz6IwCfQ7wP6i/i8HhbcOSKF4ELyQB1
oCoAoOuqpRqEzr4kOkQqHRLE/b8/Rw2k
=y6kj
```

```
-----END PGP SIGNATURE-----
```

Detached signatures

A signed document has limited usefulness. Other users must recover the original document from the signed version, and even with clearsigned documents, the signed document must be edited to recover the original. Therefore, there is a third method for signing a document that creates a detached signature, which is a separate file. A detached signature is created using the `--detach-sig` option.

```
alice% gpg --output doc.sig --detach-sig doc
```

```
You need a passphrase to unlock the secret key for
user: "Alice (Judge) <alice@cyb.org>"
1024-bit DSA key, ID BB7576AC, created 1999-06-04
```

```
Enter passphrase:
```

Both the document and detached signature are needed to verify the signature. The `--verify` option can be to check the signature.

```
blake% gpg --verify doc.sig doc
```

```
gpg: Signature made Fri Jun  4 12:38:46 1999 CDT using DSA key ID BB7576AC
```

```
gpg: Good signature from "Alice (Judge) <alice@cyb.org>"
```

Chapter 2. Concepts

GnuPG makes uses of several cryptographic concepts including *symmetric ciphers*, *public-key ciphers*, and *one-way hashing*. You can make basic use GnuPG without fully understanding these concepts, but in order to use it wisely some understanding of them is necessary.

This chapter introduces the basic cryptographic concepts used in GnuPG. Other books cover these topics in much more detail. A good book with which to pursue further study is [Bruce Schneier's "Applied Cryptography"](#).

Symmetric ciphers

A symmetric cipher is a cipher that uses the same key for both encryption and decryption. Two parties communicating using a symmetric cipher must agree on the key beforehand. Once they agree, the sender encrypts a message using the key, sends it to the receiver, and the receiver decrypts the message using the key. As an example, the German Enigma is a symmetric cipher, and daily keys were distributed as code books. Each day, a sending or receiving radio operator would consult his copy of the code book to find the day's key. Radio traffic for that day was then encrypted and decrypted using the day's key. Modern examples of symmetric ciphers include 3DES, Blowfish, and IDEA.

A good cipher puts all the security in the key and none in the algorithm. In other words, it should be no help to an attacker if he knows which cipher is being used. Only if he obtains the key would knowledge of the algorithm be needed. The ciphers used in GnuPG have this property.

Since all the security is in the key, then it is important that it be very difficult to guess the key. In other words, the set of possible keys, i.e., the *key space*, needs to be large. While at Los Alamos, Richard Feynman was famous for his ability to crack safes. To encourage the mystique he even carried around a set of tools including an old stethoscope. In reality, he used a variety of tricks to reduce the number of combinations he had to try to a small number and then simply guessed until he found the right combination. In other words, he reduced the size of the key space.

Britain used machines to guess keys during World War 2. The German Enigma had a very large key space, but the British built specialized computing engines, the Bombes, to mechanically try keys until the day's key was found. This meant that sometimes they found the day's key within hours of the new key's use, but it also meant that on some days they never did find the right key. The Bombes were not general-purpose computers but were precursors to modern-day computers.

Today, computers can guess keys very quickly, and this is why key size is important in modern cryptosystems. The cipher DES uses a 56-bit key, which means that there are 2^{56} possible keys. 2^{56} is 72,057,594,037,927,936 keys. This is a lot of keys, but a general-purpose computer can check the entire key space in a matter of days. A specialized computer can check it in hours. On the other hand, more recently designed ciphers such as 3DES, Blowfish, and IDEA all use 128-bit keys, which means there are 2^{128} possible keys. This is many, many more keys, and even if all the computers on the planet cooperated, it could still take more time than the age of the universe to find the key.

Public-key ciphers

The primary problem with symmetric ciphers is not their security but with key exchange. Once the sender and receiver have exchanged keys, that key can be used to securely communicate, but what secure communication channel was used to communicate the key itself? In particular, it would probably be much easier for an attacker to work to intercept the key than it is to try all the keys in the key space. Another problem is the number of keys needed. If there are n people who need to communicate, then $n(n-1)/2$ keys are needed for each pair of people to communicate privately. This may be OK for a small number of people but quickly becomes unwieldy for large groups of people.

Public-key ciphers were invented to avoid the key-exchange problem entirely. A public-key cipher uses a pair of keys for sending messages. The two keys belong to the person receiving the message. One key is a *public key* and may be given to anybody. The other key is a *private key* and is kept secret by the owner. A sender