Copyright Notice

deeplearning.ai

Deep Neural Networks

Deep L-layer Neural network

What is a deep neural network?



logistic regression



1 hidden layer



2 hidden layers



5 hidden layers

Andrew

Deep neural network notation



$L = 4$ (#layers)

$n^{[l]}$ = #units in layer l

$n^{[1]} = 5$, $n^{[2]} = 5$, $n^{[3]} = 3$, $n^{[4]} = n^{[L]} = 1$

$n^{[0]} = n_x = 3$

$a^{[l]}$ = activations in layer l

$a^{[l]} = g^{[l]}(z^{[l]})$, $w^{[l]}$, $b^{[l]}$ = weights for $z^{[l]}$

Andrew

deeplearning.ai

Deep Neural Networks

Forward Propagation in a Deep Network

Forward propagation in a deep network



$$z^{[1]} = W^{[1]} a^{[0]} + b^{[1]}$$

$$a^{[1]} = g^{[1]}(z^{[1]})$$

$$z^{[2]} = W^{[2]} a^{[1]} + b^{[2]}$$

$$a^{[2]} = g^{[2]}(z^{[2]})$$

$$z^{[4]} = W^{[4]} a^{[3]} + b^{[4]}, \quad a^{[4]} = g^{[4]}(z^{[4]}) = \hat{y}$$

$$\begin{bmatrix} z^{[1](1)} & z^{[1](2)} & \cdots & z^{[1](m)} \\ | & | & & | \end{bmatrix}$$

$A^{[0]} = X$

$$z^{[l]} = W^{[l]} A^{[l-1]} + b^{[l]}$$

$$A^{[l]} = g^{[l]}(z^{[l]})$$

Vectorized:

$$Z^{[1]} = W^{[1]} A^{[0]} + b^{[1]}$$

$$A^{[1]} = g^{[1]}(Z^{[1]})$$

$$Z^{[2]} = W^{[2]} A^{[1]} + b^{[2]}$$

$$A^{[2]} = g^{[2]}(Z^{[2]})$$

$$\hat{Y} = g(Z^{[4]}) = A^{[4]}$$

$X = A^{[0]}$

for $l = 1 \ldots 4$

deeplearning.ai

Deep Neural Networks

Getting your matrix dimensions right

Parameters $W^{[l]}$ and $b^{[l]}$



$L = 5$

$z^{[l]} = g^{[l]}(a^{[l]})$

$a^{[l]}$

$W^{[l]} : (n^{[l]}, n^{[l-1]})$

$b^{[l]} : (n^{[l]}, 1)$

$dW^{[l]} : (n^{[l]}, n^{[l-1]})$

$db^{[l]} : (n^{[l]}, 1)$

$z^{[1]} = W^{[1]} \cdot x + b^{[1]}$

$(3,1) \leftarrow (3,2) \quad (2,1) \quad (3,1)$

$(n^{[1]}, 1) \quad (n^{[1]}, n^{[0]}) \quad (n^{[0]}, 1) \quad (n^{[1]}, 1)$

$W^{[1]} : (n^{[1]}, n^{[0]})$

$W^{[2]} : (5, 3) \quad (n^{[2]}, n^{[1]})$

$z^{[2]} = W^{[2]} \cdot a^{[1]} + b^{[2]}$

$\rightarrow (5,1) \quad (5,3) \quad (3,1) \quad (5,1)$

$(n^{[2]}, 1)$

$W^{[3]} : (4, 5)$

$W^{[4]} : (2, 4) \quad , \quad W^{[5]} : (1, 2)$

$\begin{bmatrix} \cdot \\ \cdot \\ \cdot \end{bmatrix} = \begin{bmatrix} \cdot & \cdot \\ \cdot & \cdot \\ \cdot & \cdot \end{bmatrix} \begin{bmatrix} \cdot \\ \cdot \end{bmatrix}$

Andrew Ng

Vectorized implementation



$$z^{[1]} = W^{[1]} \cdot x + b^{[1]}$$

$(n^{[1]}, 1) \quad (n^{[1]}, n^{[0]}) \quad (n^{[0]}, 1) \quad (n^{[1]}, 1)$

$$\begin{bmatrix} z^{[1](1)} & z^{[1](2)} & \cdots & z^{[1](m)} \end{bmatrix}$$

$$Z^{[1]} = W^{[1]} \cdot X + b^{[1]}$$

$(n^{[1]}, m) \quad (n^{[1]}, n^{[0]}) \quad (n^{[0]}, m) \quad (n^{[1]}, 1) \rightarrow (n^{[1]}, m)$

$z^{[l]}, a^{[l]} : (n^{[l]}, 1)$

$Z^{[l]}, A^{[l]} : (n^{[l]}, m)$

$l = 0 \quad A^{[0]} = X = (n^{[0]}, m)$

$dZ^{[l]}, dA^{[l]} : (n^{[l]}, m)$

deeplearning.ai

Deep Neural Networks

Why deep representations?

Intuition about deep representation



Andrew Ng

Circuit theory and deep learning

Informally: There are functions you can compute with a "small" L-layer deep neural network that shallower networks require exponentially more hidden units to compute.





Deep Neural Networks

Building blocks of deep neural networks



deeplearning.ai

Forward and backward functions



Forward and backward functions



Andrew

deeplearning.ai

Deep Neural Networks

Forward and backward propagation

Backward propagation for layer l

→ Input $da^{[l]}$

→ Output $da^{[l-1]}, dW^{[l]}, db^{[l]}$

$$dz^{[l]} = da^{[l]} * g^{[l]\prime}(z^{[l]})$$

$$dW^{[l]} = dz^{[l]} \cdot a^{[l-1]}$$

$$db^{[l]} = dz^{[l]}$$

$$da^{[l-1]} = W^{[l]T} \cdot dz^{[l]}$$

$$dz^{[l]} = W^{[l+1]T} dz^{[l+1]} * g^{[l]\prime}(z^{[l]})$$

$$dz^{[l]} = dA^{[l]} * g^{[l]\prime}(Z^{[l]})$$

$$dW^{[l]} = \frac{1}{m} dz^{[l]} \cdot A^{[l-1]T}$$

$$db^{[l]} = \frac{1}{m} np.sum(dz^{[l]}, axis=1, keepdims=True)$$

$$dA^{[l-1]} = W^{[l]T} \cdot dz^{[l]}$$

Summary


X
ReLU
ReLU
Sigmoid
$\hat{y}$
$z^{[1]}$
$z^{[2]}$
$z^{[3]}$
$da^{[0]}$
$da^{[1]}$
$da^{[2]}$
$da^{[3]}$
$\mathcal{L}(\hat{y}, y)$
$da^{[3]} = -\frac{y}{a} + \frac{(1-y)}{(1-a)}$
$dA^{[3]} = \left(-\frac{y^{(1)}}{a^{(1)}} + \frac{(1-y^{(1)})}{(1-a^{(1)})} \cdots \right.$
$\cdots \left. \frac{y^{(m)}}{a^{(m)}} + \frac{(1-y^{(m)})}{(1-a^{(m)})} \right)$
$dW^{[1]}$ $db^{[1]}$
$dW^{[2]}$ $db^{[2]}$
$dW^{[3]}$ $db^{[3]}$

deeplearning.ai

Deep Neural Networks

Parameters vs Hyperparameters

What are hyperparameters?

Parameters: $W^{[1]}, b^{[1]}, W^{[2]}, b^{[2]}, W^{[3]}, b^{[3]}$ ...

Hyperparameters: learning rate α

#iterations

#hidden layers L

#hidden units $n^{[1]}, n^{[2]}, \ldots$

choice of activation function

Later: Momentum, mini-batch size, regularizations, ...

Applied deep learning is a very empirical process

Idea

$\alpha = 0.04$
0.05



Experiment

Code



Vision, Speech, NLP, Ad, Search, Recommendation.

deeplearning.ai

Deep Neural Networks

What does this have to do with the brain?

Forward and backward propagation

$$
\begin{aligned}
Z^{[1]} &= W^{[1]}X + b^{[1]} \\
A^{[1]} &= g^{[1]}(Z^{[1]}) \\
Z^{[2]} &= W^{[2]}A^{[1]} + b^{[2]} \\
A^{[2]} &= g^{[2]}(Z^{[2]}) \\
&\vdots \\
A^{[L]} &= g^{[L]}(Z^{[L]}) = \hat{Y}
\end{aligned}
$$

"It's like the brain."

$$
\begin{aligned}
dZ^{[L]} &= A^{[L]} - Y \\
dW^{[L]} &= \frac{1}{m} dZ^{[L]} A^{[L]T} \\
db^{[L]} &= \frac{1}{m} np.\mathrm{sum}(\mathrm{d}Z^{[L]}, axis = 1, keepdims = True) \\
dZ^{[L-1]} &= dW^{[L]T} dZ^{[L]} g'^{[L]}(Z^{[L-1]}) \\
&\vdots \\
dZ^{[1]} &= dW^{[L]T} dZ^{[2]} g'^{[1]}(Z^{[1]}) \\
dW^{[1]} &= \frac{1}{m} dZ^{[1]} A^{[1]T} \\
db^{[1]} &= \frac{1}{m} np.\mathrm{sum}(\mathrm{d}Z^{[1]}, axis = 1, keepdims = True)
\end{aligned}
$$





Andrew Ng