



HTML

CSS

JAVASCRIPT

SQL

PYTHON

PHP

BOOTSTRAP

HOW TO

W3.CSS

JAVA



Python Tutorial

[Python HOME](#)[Python Intro](#)[Python Get Started](#)[Python Syntax](#)[Python Comments](#)[Python Variables](#)[Python Data Types](#)[Python Numbers](#)[Python Casting](#)[Python Strings](#)[Python Booleans](#)[Python Operators](#)[Python Lists](#)[Python Tuples](#)[Python Sets](#)[Python Dictionaries](#)[Python If...Else](#)[Python While Loops](#)[Python For Loops](#)[Python Functions](#)[Python Lambda](#)[Python Arrays](#)[Python Classes/Objects](#)

Python Functions

[< Previous](#)[Next >](#)

A function is a block of code which only runs when it is called.

You can pass data, known as parameters, into a function.

A function can return data as a result.

Creating a Function

In Python a function is defined using the `def` keyword:

Example

```
def my_function():  
    print("Hello from a function")
```

[Python Inheritance](#)[Python Iterators](#)[Python Scope](#)[Python Modules](#)[Python Dates](#)

Calling a Function

To call a function, use the function name followed by parenthesis:

Example

```
def my_function():  
    print("Hello from a function")  
  
my_function()
```

[Try it Yourself »](#)

Arguments

Information can be passed into functions as arguments.

Arguments are specified after the function name, inside the parentheses. You can add as many arguments as you want, just separate them with a comma.

The following example has a function with one argument (fname). When the function is called, we pass along a first name, which is used inside the function to print the full name:

Example

```
def my_function(fname):  
    print(fname + " Refsnes")
```

COLOR
PICKER



LIKE US



Get certified
by completing
a course today!



Get started

CODE GAME

```
my_function("Emil")  
my_function("Tobias")  
my_function("Linus")
```

[Try it Yourself »](#)

Arguments are often shortened to *args* in Python documentations.

Parameters or Arguments?

The terms *parameter* and *argument* can be used for the same thing: information that are passed into a function.

From a function's perspective:



[Play Game](#)

A parameter is the variable listed inside the parentheses in the function definition.

An argument is the value that is sent to the function when it is called.

Number of Arguments

By default, a function must be called with the correct number of arguments. Meaning that if your function expects 2 arguments, you have to call the function with 2 arguments, not more, and not less.

Example

This function expects 2 arguments, and gets 2 arguments:

```
def my_function(fname, lname):  
    print(fname + " " + lname)  
  
my_function("Emil", "Refsnes")
```

[Try it Yourself »](#)

If you try to call the function with 1 or 3 arguments, you will get an error:

Example

This function expects 2 arguments, but gets only 1:

```
def my_function(fname, lname):  
    print(fname + " " + lname)
```

```
my_function("Emil")
```

[Try it Yourself »](#)

Arbitrary Arguments, *args

If you do not know how many arguments that will be passed into your function, add a `*` before the parameter name in the function definition.

This way the function will receive a *tuple* of arguments, and can access the items accordingly:

Example

If the number of arguments is unknown, add a `*` before the parameter name:

```
def my_function(*kids):  
    print("The youngest child is " + kids[2])  
  
my_function("Emil", "Tobias", "Linus")
```

[Try it Yourself »](#)

Arbitrary Arguments are often shortened to **args* in Python documentations.

Keyword Arguments

You can also send arguments with the *key = value* syntax.

This way the order of the arguments does not matter.

Example

```
def my_function(child3, child2, child1):  
    print("The youngest child is " + child3)  
  
my_function(child1 = "Emil", child2 = "Tobias", child3 = "Linus")
```

Try it Yourself »

The phrase *Keyword Arguments* are often shortened to *kwargs* in Python documentations.

Arbitrary Keyword Arguments, **kwargs

If you do not know how many keyword arguments that will be passed into your function, add two asterisk: `**` before the parameter name in the function definition.

This way the function will receive a *dictionary* of arguments, and can access the items accordingly:

Example

If the number of keyword arguments is unknown, add a double `**` before the parameter name:

```
def my_function(**kid):  
    print("His last name is " + kid["lname"])  
  
my_function(fname = "Tobias", lname = "Refsnes")
```

Try it Yourself »

Arbitrary Kword Arguments are often shortened to ***kwargs* in Python documentations.

Default Parameter Value

The following example shows how to use a default parameter value.

If we call the function without argument, it uses the default value:

Example

```
def my_function(country = "Norway"):  
    print("I am from " + country)  
  
my_function("Sweden")  
my_function("India")  
my_function()  
my_function("Brazil")
```

Try it Yourself »

Passing a List as an Argument

You can send any data types of argument to a function (string, number, list, dictionary etc.), and it will be treated as the same data type inside the function.

E.g. if you send a List as an argument, it will still be a List when it reaches the function:

Example

```
def my_function(food):  
    for x in food:  
        print(x)  
  
fruits = ["apple", "banana", "cherry"]  
  
my_function(fruits)
```

Try it Yourself »

Return Values

To let a function return a value, use the `return` statement:

Example

```
def my_function(x):  
    return 5 * x  
  
print(my_function(3))
```



```
print(my_function(5))  
print(my_function(9))
```

[Try it Yourself »](#)

The pass Statement

`function` definitions cannot be empty, but if you for some reason have a `function` definition with no content, put in the `pass` statement to avoid getting an error.

Example

```
def myfunction():  
    pass
```

[Try it Yourself »](#)

Recursion

Python also accepts function recursion, which means a defined function can call itself.

Recursion is a common mathematical and programming concept. It means that a function calls itself. This has the benefit of meaning that you can loop through data to reach a result.

The developer should be very careful with recursion as it can be quite easy to slip into writing a function which never terminates, or one that uses excess amounts of memory or processor power. However, when written correctly recursion can be a very efficient and mathematically-elegant approach to programming.

In this example, `tri_recursion()` is a function that we have defined to call itself ("recurse"). We use the `k` variable as the data, which decrements (`-1`) every time we recurse. The recursion ends when the condition is not greater than 0 (i.e. when it is 0).

To a new developer it can take some time to work out how exactly this works, best way to find out is by testing and modifying it.

Example

Recursion Example

```
def tri_recursion(k):  
    if(k > 0):  
        result = k + tri_recursion(k - 1)  
        print(result)  
    else:  
        result = 0  
    return result  
  
print("\n\nRecursion Example Results")  
tri_recursion(6)
```

[Try it Yourself »](#)

Test Yourself With Exercises

Exercise:

Create a function named `my_function`.

```
def my_function():  
    print("Hello from a function")
```

[Submit Answer »](#)

[Start the Exercise](#)

[◀ Previous](#)

[Next ▶](#)

[REPORT ERROR](#)

[FORUM](#)

[ABOUT](#)

[SHOP](#)

Top Tutorials

[HTML Tutorial](#)
[CSS Tutorial](#)
[JavaScript Tutorial](#)
[How To Tutorial](#)
[SQL Tutorial](#)
[Python Tutorial](#)
[W3.CSS Tutorial](#)

Top References

[HTML Reference](#)
[CSS Reference](#)
[JavaScript Reference](#)
[SQL Reference](#)
[Python Reference](#)
[W3.CSS Reference](#)
[Bootstrap Reference](#)

Top Examples

[HTML Examples](#)
[CSS Examples](#)
[JavaScript Examples](#)
[How To Examples](#)
[SQL Examples](#)
[Python Examples](#)
[W3.CSS Examples](#)

Web Courses

[HTML Course](#)
[CSS Course](#)
[JavaScript Course](#)
[Front End Course](#)
[SQL Course](#)
[Python Course](#)
[PHP Course](#)

[Bootstrap Tutorial](#)
[PHP Tutorial](#)
[Java Tutorial](#)
[C++ Tutorial](#)
[jQuery Tutorial](#)

[PHP Reference](#)
[HTML Colors](#)
[Java Reference](#)
[Angular Reference](#)
[jQuery Reference](#)

[Bootstrap Examples](#)
[PHP Examples](#)
[Java Examples](#)
[XML Examples](#)
[jQuery Examples](#)

[jQuery Course](#)
[Java Course](#)
[C++ Course](#)
[C# Course](#)
[XML Course](#)

[Get Certified »](#)

W3Schools is optimized for learning and training. Examples might be simplified to improve reading and learning. Tutorials, references, and examples are constantly reviewed to avoid errors, but we cannot warrant full correctness of all content. While using W3Schools, you agree to have read and accepted our terms of use, cookie and privacy policy.

Copyright 1999-2021 by Refsnes Data. All Rights Reserved.
W3Schools is Powered by W3.CSS.

