Technician Safety Handbook

Document SAF-2026 · Version 2.0 · Effective 1 January 2026 · Owner: Head of Field Operations

1. Purpose

This handbook sets the minimum safety rules for every Contoso DIY service pro working in customer homes. Service pros must read it before their first job and confirm each year that they have reread it.

2. Restricted trades and certified skills

Some jobs may only be carried out by a service pro whose profile lists the matching certified skill. Managers must not assign these jobs to anyone else, even when the backlog is high.

Restricted trade	Required skill on profile	Typical jobs	Rule ID
Electrical	electrical	Replace hallway light fixture; install under-cabinet task lighting; install smart doorbell (wired)	SAF-01
Plumbing	plumbing	Repair leaking kitchen sink trap; replace bathroom faucet cartridge	SAF-02
HVAC	hvac	Replace HVAC return filter and inspect vent flow; clean and test mini-split filters	SAF-03

3. Before starting any job

- Confirm the customer identity and the work-order number on arrival.
- Walk the work area with the customer and agree what will be done.
- Check for children and pets and ask the customer to keep them out of the work area.
- Photograph the area before starting; attach photos to the work order.

4. Electrical work (SAF-01)

- Isolate the circuit at the consumer unit and lock or tag the breaker before touching any wiring.
- Test for dead with an approved voltage tester on a known live source before and after testing the circuit.
- Never work on a live circuit. If the circuit cannot be isolated, stop and mark the job needs_followup.
- Fixtures heavier than 5 kg must be fixed to a joist or an approved ceiling anchor.

5. Plumbing work (SAF-02)

- Shut off the local isolation valve, or the main stopcock if none exists, and drain the line.
- Lay protective sheeting and keep a bucket and absorbent mat under any joint being opened.
- After the repair, run water for at least two minutes and check joints for leaks before leaving.

6. Working at height and drilling

- Use a ladder only up to the second-highest step; above 2 metres a second person must hold the ladder.
- Scan walls with a cable and pipe detector before drilling. Do not drill within 15 cm vertically above or below a socket or switch.
- Furniture taller than 1.2 metres (for example wardrobes and shelving) must be anchored to wall studs with the anti-tip kit.

7. Stop-work and incident reporting

Every service pro has the right and the duty to stop work if conditions are unsafe: asbestos is suspected, gas is smelt, wiring is damaged, or the customer interferes with the work area. Mark the work order needs_followup with a short note explaining why, and inform the city manager the same day. Injuries, near misses and restricted-trade breaches must be reported within 24 hours (see ESC-04 in POL-OPS-2026).

8. Personal protective equipment

Task type	Minimum PPE
Drilling, sanding, grouting	Safety glasses, dust mask (FFP2)
Painting and sealing	Gloves, ventilation; respirator for solvent-based products
Electrical	Insulated tools, voltage tester
Outdoor fencing and gates	Work gloves, safety boots