

服务器准备

服务器 IP	配置	软件
172.16.5.30	4C4G	nodejs, npm, nginx

环境准备

安装Nodejs, npm工具

```
$ dnf -y install nodejs npm

# 检查安装版本
$ node -v
$ npm -v

# 设置npm源
$ npm config set registry https://registry.npmmirror.com
```

创建 `/etc/yum.repos.d/nginx.repo` 文件并添加以下内容

```
# 使用官方 yum 源安装 nginx
cat > /etc/yum.repos.d/nginx.repo <<EOF
[nginx-stable]
name=nginx stable repo
baseurl=http://nginx.org/packages/centos/$releasever/$basearch/
gpgcheck=1
enabled=1
gpgkey=https://nginx.org/keys/nginx_signing.key
module_hotfixes=true

[nginx-mainline]
name=nginx mainline repo
baseurl=http://nginx.org/packages/mainline/centos/$releasever/$basearch/
gpgcheck=1
enabled=0
```

```
gpgkey=https://nginx.org/keys/nginx_signing.key  
module_hotfixes=true  
EOF
```

安装nginx

```
# 重建缓存  
$ dnf makecache  
  
# 安装nginx  
$ dnf install nginx -y  
  
# 开机启动  
$ systemctl enable --now nginx
```

获取源代码

https://gitee.com/y_project/RuoYi-Vue

```
# 使用wget下载到服务器上  
wget https://gitee.com/y_project/RuoYi-Vue/repository/archive/v3.8.9.zip  
  
# 解压zip包  
$ unzip v3.8.9.zip
```

编译代码

```
$ cd RuoYi-Vue-v3.8.9/ruoyi-ui

# 设置临时变量
$ export NODE_OPTIONS=--openssl-legacy-provider
$ npm install
$ npm run build:prod

$ cp -r dist /home/www/dist
```

部署HTTP服务

```
# 添加 Nginx 站点
# /etc/nginx/conf.d/ruoyi.conf
server {
    listen      80;
    server_name 172.16.5.50;
    charset utf-8;

    location / {
        root    /home/www/dist;
        try_files $uri $uri/ /index.html;
        index   index.html index.htm;
    }
}
```

重载配置

```
$ nginx -t

$ systemctl reload nginx
```