

Peer Chat

A Simple Chat Application implemented in Java Swing
IIT2013075 | Vishnu Ks

How to run the software

- Download PeerChatServer.java and PeerChatClient.java
- enter `javac PeerChatServer.java` in terminal
- enter `javac PeerChatClient.java` in terminal
- enter `java PeerChatServer` in terminal (Started Server)
- enter `java PeerChatClient` in terminal (Started Client)
- enter `java PeerChatClient` again so that there are now two clients connected to server

Precuations

- Make sure that PeerChatServer is already started before running the Clients
- The software is tested only in Ubuntu/Linux.
- If port **8888** is used by some other application please change it.

How it works?

The PeerChatServer acts only as the server. Start atleast two peerChatClient files to start communication with each other along with the Server file running.


How to connect to server?



When this screen pops up enter localhost.

Optional: If you are using two diffrent computers enter the ip address of the server.


How to login?



The following login credentials can be used to login to the system

Username	Password
snape	iiita
potter	malfoy
jonsnow	iiita
hulk	iiita
ironman	tonystark
batman	darkknight

Once logged in the clients can send messages to each other.



Awesome Features

- Secure communication with JCE(DES/ECB/PKCS5)
- Group chat
- Validation of sign in details in Server side
- Simple to use GUI
- Cross Platform (Windows, MAC, Linux)

Wireshark Traces

1)


Connecting to the server

0000	00 00 00 00 00 00 00 00 00 00	00 00 00 00 08 00 45 00E.
0010	00 3e 23 e0 40 00 40 06	18 d8 7f 00 00 01 7f 00	.>#.@.@.
0020	00 01 22 b8 99 82 b0 80	e7 7b 4d eb e3 e1 80 18	..". {M.
0030	01 56 fe 32 00 00 01 01	08 0a 00 b1 d7 df 00 b1	.V.2....
0040	d7 df 48 41 4e 44 53 48	41 4b 45 0a	..HANDSHAKE.

Sending and receiving (Eg: JonSnow sending “How are r you”)

```
0000 00 00 00 00 00 00 00 00 00 00 00 00 08 00 45 00 .....E.
0010 00 4f 23 e1 40 00 40 06 18 c6 7f 00 00 01 7f 00 .0#.@.@. ....
0020 00 01 22 b8 99 82 b0 80 e7 85 4d eb e3 ec 80 18 ..".....M....
0030 01 56 fe 43 00 00 01 01 08 0a 00 b2 bc a0 00 b2 .V.C.... ....
0040 bc 9f 53 54 52 45 41 4d 20 6a 6f 6e 73 6e 6f 77 ..STREAM jonsnow
0050 3a 20 68 6f 77 20 72 20 79 6f 75 27 0a : how r you'.
```

2) Multiple Clients



Sending Login Credentials

```
0000 00 00 00 00 00 00 00 00 00 00 00 00 08 00 45 00 .....E.
0010 00 3e b1 7a 40 00 40 06 8b 3d 7f 00 00 01 7f 00 .>.z@.@. .=. ....
0020 00 01 99 f4 22 b8 79 09 5c f6 f9 08 60 34 80 18 ....".y. \...`4..
0030 01 56 fe 32 00 00 01 01 08 0a 00 bd f9 53 00 bd .V.2....S..
0040 f0 7c 68 75 6c 6b 69 69 69 74 61 0a .|hulkii ita.
```

Correct login, handshake completed

```
0000 00 00 00 00 00 00 00 00 00 00 00 00 08 00 45 00 .....E.
0010 00 3e 8d ac 40 00 40 06 af 0b 7f 00 00 01 7f 00 .>..@.@. ....
0020 00 01 22 b8 99 f4 f9 08 60 34 79 09 5d 00 80 18 ..".....`4y.]...
0030 01 56 fe 32 00 00 01 01 08 0a 00 bd f9 53 00 bd .V.2....S..
0040 f9 53 48 41 4e 44 53 48 41 4b 45 0a .SHANDSH AKE.
```

Sending message

```
259 3248,597048( 127.0.0.1 127.0.0.1 TCP 88 ddi-tcp-1 > 39412 [PSH, ACK] Seq=91 Ack=50 Win=43776 Len=22 TSval=12462375 TSecr=124623
260 3248,597196( 127.0.0.1 127.0.0.1 TCP 66 39412 > ddi-tcp-1 [ACK] Seq=50 Ack=113 Win=43776 Len=0 TSval=12462375 TSecr=12462375
Source port: ddi-tcp-1 (8888)
0000 00 00 00 00 00 00 00 00 00 00 00 00 08 00 45 00 .....E.
0010 00 4a 8d b0 40 00 40 06 ae fb 7f 00 00 01 7f 00 .J..@.@. ....
0020 00 01 22 b8 99 f4 f9 08 60 82 79 09 5d 26 80 18 ..".....".y.]6..
0030 01 56 fe 3e 00 00 01 01 08 0a 00 be 29 27 00 be .V.>....)'...
0040 29 27 53 54 52 45 41 4d 20 68 75 6c 6b 3a 20 68 )'STREAM hulk: h
0050 65 79 20 67 75 79 73 0a ey guys.
```

3) Messages are not encrypted as they are visible through wireshark. The message from hulk “**hey guys**” is visible in the packet.

259	3248.597048	127.0.0.1	127.0.0.1	TCP	88 ddi-tcp-1 > 39412 [PSH, ACK] Seq=91 Ack=50 Win=43776 Len=22 TSval=12462375 TSecr=12462375
260	3248.597196	127.0.0.1	127.0.0.1	TCP	66 39412 > ddi-tcp-1 [ACK] Seq=50 Ack=113 Win=43776 Len=0 TSval=12462375 TSecr=12462375
Source port: ddi-tcp-1 (8888)					
0000	00 00 00 00 00 00 00 00	00 00 00 00 08 00 45 00	E.	
0010	00 4a 8d b0 40 00 40 06	ae fb 7f 00 00 01 7f 00	.J..@.@.		
0020	00 01 22 b8 99 f4 f9 08	60 82 79 09 5d 26 80 18	.."...n..1		
0030	01 56 fe 3e 00 00 01 01	08 0a 00 be 29 27 00 be	.V.>....		
0040	29 27 53 54 52 45 41 4d	20 68 75 6c 6b 3a 20 68)'STREAM	hulk: h	
0050	65 79 20 67 75 79 73 0a		ey guys.		

4)
After implementing JCE for encrypting the messages. The messages are not visible as they are encrypted.

276	3611.174170	127.0.0.1	127.0.0.1	TCP	91 39418 >
277	3611.183107	127.0.0.1	127.0.0.1	TCP	113 ddi-tcp-1 >
278	3611.183193	127.0.0.1	127.0.0.1	TCP	66 39418 >
Source port: ddi-tcp-1 (8888)					
0000	00 00 00 00 00 00 00 00	00 00 00 00 08 00 45 00	E.	
0010	00 63 dd 24 40 00 40 06	5f 6e 7f 00 00 01 7f 00	.c.\$@.@.	n.....	
0020	00 01 22 b8 99 fa 6e 96	a7 31 bc d8 07 c2 80 18	.."...n..1		
0030	01 56 fe 57 00 00 01 01	08 0a 00 bf 8b 3e 00 bf	.V.W....	>..	
0040	8b 3b c2 8b 70 c2 a8 c2	a1 74 14 c3 82 54 07 c3	.;..p...	t...T..	
0050	b3 c2 81 2b c2 ab c2 90	c3 98 2f 43 c3 b1 68 52	...+....	/C..hR	
0060	c2 81 6a 70 79 c2 b0 c3	8a 13 77 5e 4e c2 bb 77	..jpy...	w^N..w	
0070	0a		.		

276	3611.174170	127.0.0.1	127.0.0.1	TCP	91 39418 >
277	3611.183107	127.0.0.1	127.0.0.1	TCP	113 ddi-tcp-1 >
278	3611.183193	127.0.0.1	127.0.0.1	TCP	66 39418 >
Source port: 39418 (39418)					
0000	00 00 00 00 00 00 00 00	00 00 00 00 08 00 45 00	E.	
0010	00 4d 7c 54 40 00 40 06	c0 54 7f 00 00 01 7f 00	.M T@.@.	T.....	
0020	00 01 99 fa 22 b8 bc d8	07 a9 6e 96 a7 31 80 18"...	n..1..	
0030	01 56 fe 41 00 00 01 01	08 0a 00 bf 8b 3b 00 bf	.V.A....;	
0040	88 48 c3 a5 4e 51 56 c2	8c 15 c3 9e c3 95 c2 85	.H..NQV.	
0050	c2 ab 11 c3 9a 76 76 20	c3 9b 0avv	...	