



OWASP ZAP Scan Report

Target: https://listenzenify.vercel.app/

All scanned sites: https://listenzenify.vercel.app

Javascript included from: https://listenzenifybackend.up.railway.app https://listenzenify.vercel.app

Generated on Mon, 23 Feb 2026 02:14:54

ZAP Version: 2.17.0

Summary of Alerts

Risk Level	Number of Alerts
High	0
Medium	3
Low	2
Informational	2

Alerts

Name	Risk Level	Number of Instances
Content Security Policy (CSP) Header Not Set	Medium	3
Cross-Domain Misconfiguration	Medium	5
Missing Anti-clickjacking Header	Medium	1
Strict-Transport-Security Header Not Set	Low	1
X-Content-Type-Options Header Missing	Low	5
Re-examine Cache-control Directives	Informational	5
Retrieved from Cache	Informational	5

Passing Rules

Name	Rule Type	Threshold	Strength
Session Management Response Identified	Passive	MEDIUM	-
Verification Request Identified	Passive	MEDIUM	-
Private IP Disclosure	Passive	MEDIUM	-
Session ID in URL Rewrite	Passive	MEDIUM	-
Script Served From Malicious Domain (polyfill)	Passive	MEDIUM	-
ZAP is Out of Date	Passive	MEDIUM	-
Insecure JSF ViewState	Passive	MEDIUM	-
Sub Resource Integrity Attribute Missing	Passive	MEDIUM	-

Vulnerable JS Library (Powered by Retire.js)	Passive	MEDIUM	-
Java Serialization Object	Passive	MEDIUM	-
In Page Banner Information Leak	Passive	MEDIUM	-
Charset Mismatch	Passive	MEDIUM	-
Cookie No HttpOnly Flag	Passive	MEDIUM	-
Cookie Without Secure Flag	Passive	MEDIUM	-
Cross-Domain JavaScript Source File Inclusion	Passive	MEDIUM	-
Content-Type Header Missing	Passive	MEDIUM	-
Application Error Disclosure	Passive	MEDIUM	-
Information Disclosure - Debug Error Messages	Passive	MEDIUM	-
Information Disclosure - Sensitive Information in URL	Passive	MEDIUM	-
Information Disclosure - Sensitive Information in HTTP Referrer Header	Passive	MEDIUM	-
Information Disclosure - Suspicious Comments	Passive	MEDIUM	-
Off-site Redirect	Passive	MEDIUM	-
Cookie Poisoning	Passive	MEDIUM	-
User Controllable Charset	Passive	MEDIUM	-
WSDL File Detection	Passive	MEDIUM	-
User Controllable HTML Element Attribute (Potential XSS)	Passive	MEDIUM	-
Loosely Scoped Cookie	Passive	MEDIUM	-
Viewstate	Passive	MEDIUM	-
Directory Browsing	Passive	MEDIUM	-
Heartbleed OpenSSL Vulnerability (Indicative)	Passive	MEDIUM	-
HTTP Server Response Header	Passive	MEDIUM	-
Server Leaks Information via "X-Powered-By" HTTP Response Header Field(s)	Passive	MEDIUM	-
X-Backend-Server Header Information Leak	Passive	MEDIUM	-
Secure Pages Include Mixed Content	Passive	MEDIUM	-
HTTP to HTTPS Insecure Transition in Form Post	Passive	MEDIUM	-
HTTPS to HTTP Insecure Transition in Form Post	Passive	MEDIUM	-
User Controllable JavaScript Event (XSS)	Passive	MEDIUM	-
Big Redirect Detected (Potential Sensitive Information Leak)	Passive	MEDIUM	-
X-ChromeLogger-Data (XCOLD) Header Information Leak	Passive	MEDIUM	-
Cookie without SameSite Attribute	Passive	MEDIUM	-
CSP	Passive	MEDIUM	-
X-Debug-Token Information Leak	Passive	MEDIUM	-
Username Hash Found	Passive	MEDIUM	-
X-AspNet-Version Response Header	Passive	MEDIUM	-
PII Disclosure	Passive	MEDIUM	-
Script Passive Scan Rules	Passive	MEDIUM	-
Stats Passive Scan Rule	Passive	MEDIUM	-
Absence of Anti-CSRF Tokens	Passive	MEDIUM	-
Timestamp Disclosure	Passive	MEDIUM	-
Hash Disclosure	Passive	MEDIUM	-
Weak Authentication Method	Passive	MEDIUM	-

Reverse Tabnabbing	Passive	MEDIUM	-
Modern Web Application	Passive	MEDIUM	-
Authentication Request Identified	Passive	MEDIUM	-

Alert Detail

Medium	Content Security Policy (CSP) Header Not Set
Description	Content Security Policy (CSP) is an added layer of security that helps to detect and mitigate certain types of attacks, including Cross Site Scripting (XSS) and data injection attacks. These attacks are used for everything from data theft to site defacement or distribution of malware. CSP provides a set of standard HTTP headers that allow website owners to declare approved sources of content that browsers should be allowed to load on that page — covered types are JavaScript, CSS, HTML frames, fonts, images and embeddable objects such as Java applets, ActiveX, audio and video files.
URL	https://listenzenify.vercel.app/
Method	GET
Parameter	
Attack	
Evidence	
Other Info	
Request Header	GET https://listenzenify.vercel.app/ HTTP/1.1 host: listenzenify.vercel.app user-agent: Mozilla/5.0 (Windows NT 10.0; Win64; x64) AppleWebKit/537.36 (KHTML, like Gecko) Chrome/141.0.0.0 Safari/537.36 pragma: no-cache cache-control: no-cache
Request Body	
Response Header	HTTP/1.1 200 OK Accept-Ranges: bytes Access-Control-Allow-Origin: * Age: 27111 Cache-Control: public, max-age=0, must-revalidate Content-Disposition: inline Content-Length: 12764 Content-Type: text/html; charset=utf-8 Cross-Origin-Opener-Policy: same-origin-allow-popups Date: Mon, 23 Feb 2026 02:14:32 GMT Etag: "b438d6765ef820441c4fa90cb0229f09" Referrer-Policy: no-referrer-when-downgrade Server: Vercel Strict-Transport-Security: max-age=63072000; includeSubDomains; preload Vary: rsc, next-router-state-tree, next-router-prefetch, next-router-segment-prefetch X-Matched-Path: / X-Nextjs-Prerender: 1 X-Nextjs-Stale-Time: 300 X-Vercel-Cache: HIT X-Vercel-Id: iad1::b9r76-1771812872048-8ecfe16b9560
Response Body (truncated)	<!DOCTYPE html><!--hBVSfDU6ZJUImH61CQqY9--><html lang="en"><head><meta charSet="utf-8"/><meta name="viewport" content="width=device-width, initial-scale=1"/><link rel="preload" href="/_next/static/media/01e4147cff8141ee-s.p.7787e134.woff2" as="font" crossorigin="" type="font/woff2"/><link rel="preload" href="/_next/static/media/1b99372b3eaef0c8-s.p.758e15a8.woff2" as="font" crossorigin="" type="font/woff2"/><link rel="preload" href="/_next/static/media/83afe278b6a6bb3c-s.p.3a6ba036.woff2" as="fo...(truncated)

URL	https://listenzenify.vercel.app/robots.txt
Method	GET
Parameter	
Attack	
Evidence	
Other Info	
URL	https://listenzenify.vercel.app/sitemap.xml
Method	GET
Parameter	
Attack	
Evidence	
Other Info	
Instances	3
Solution	Ensure that your web server, application server, load balancer, etc. is configured to set the Content-Security-Policy header.
Reference	https://developer.mozilla.org/en-US/docs/Web/HTTP/Guides/CSP https://cheatsheetseries.owasp.org/cheatsheets/Content_Security_Policy_Cheat_Sheet.html https://www.w3.org/TR/CSP/ https://w3c.github.io/webappsec-csp/ https://web.dev/articles/csp https://caniuse.com/#feat=contentsecuritypolicy https://content-security-policy.com/
CWE Id	693
WASC Id	15
Plugin Id	10038
Medium	Cross-Domain Misconfiguration
Description	Web browser data loading may be possible, due to a Cross Origin Resource Sharing (CORS) misconfiguration on the web server.
URL	https://listenzenify.vercel.app/
Method	GET
Parameter	
Attack	
Evidence	Access-Control-Allow-Origin: *
Other Info	The CORS misconfiguration on the web server permits cross-domain read requests from arbitrary third party domains, using unauthenticated APIs on this domain. Web browser implementations do not permit arbitrary third parties to read the response from authenticated APIs, however. This reduces the risk somewhat. This misconfiguration could be used by an attacker to access data that is available in an unauthenticated manner, but which uses some other form of security, such as IP address white-listing.
Request Header	GET https://listenzenify.vercel.app/ HTTP/1.1 host: listenzenify.vercel.app user-agent: Mozilla/5.0 (Windows NT 10.0; Win64; x64) AppleWebKit/537.36 (KHTML, like Gecko) Chrome/141.0.0.0 Safari/537.36 pragma: no-cache cache-control: no-cache
Request Body	
Response Header	HTTP/1.1 200 OK Accept-Ranges: bytes Access-Control-Allow-Origin: *

	Age: 27111 Cache-Control: public, max-age=0, must-revalidate Content-Disposition: inline Content-Length: 12764 Content-Type: text/html; charset=utf-8 Cross-Origin-Opener-Policy: same-origin-allow-popups Date: Mon, 23 Feb 2026 02:14:32 GMT Etag: "b438d6765ef820441c4fa90cb0229f09" Referrer-Policy: no-referrer-when-downgrade Server: Vercel Strict-Transport-Security: max-age=63072000; includeSubDomains; preload Vary: rsc, next-router-state-tree, next-router-prefetch, next-router-segment-prefetch X-Matched-Path: / X-Nextjs-Prerender: 1 X-Nextjs-Stale-Time: 300 X-Vercel-Cache: HIT X-Vercel-Id: iad1::b9r76-1771812872048-8ecfe16b9560
Response Body (truncated)	<!DOCTYPE html><!--hBVSfDU6ZJUImH61CQqY9--><html lang="en"><head><meta charSet="utf-8"/><meta name="viewport" content="width=device-width, initial-scale=1"/><link rel="preload" href="/_next/static/media/01e4147cff8141ee-s.p.7787e134.woff2" as="font" crossorigin="" type="font/woff2"/><link rel="preload" href="/_next/static/media/1b99372b3eaef0c8-s.p.758e15a8.woff2" as="font" crossorigin="" type="font/woff2"/><link rel="preload" href="/_next/static/media/83afe278b6a6bb3c-s.p.3a6ba036.woff2" as="fo...(truncated)>
URL	https://listenzenify.vercel.app/_next/static/chunks/9e9e9efd420e4a6d.css
Method	GET
Parameter	
Attack	
Evidence	Access-Control-Allow-Origin: *
Other Info	The CORS misconfiguration on the web server permits cross-domain read requests from arbitrary third party domains, using unauthenticated APIs on this domain. Web browser implementations do not permit arbitrary third parties to read the response from authenticated APIs, however. This reduces the risk somewhat. This misconfiguration could be used by an attacker to access data that is available in an unauthenticated manner, but which uses some other form of security, such as IP address white-listing.
URL	https://listenzenify.vercel.app/_next/static/media/01e4147cff8141ee-s.p.7787e134.woff2
Method	GET
Parameter	
Attack	
Evidence	Access-Control-Allow-Origin: *
Other Info	The CORS misconfiguration on the web server permits cross-domain read requests from arbitrary third party domains, using unauthenticated APIs on this domain. Web browser implementations do not permit arbitrary third parties to read the response from authenticated APIs, however. This reduces the risk somewhat. This misconfiguration could be used by an attacker to access data that is available in an unauthenticated manner, but which uses some other form of security, such as IP address white-listing.
URL	https://listenzenify.vercel.app/robots.txt
Method	GET
Parameter	
Attack	
Evidence	Access-Control-Allow-Origin: *
Other Info	The CORS misconfiguration on the web server permits cross-domain read requests from arbitrary third party domains, using unauthenticated APIs on this domain. Web browser implementations do not permit arbitrary third parties to read the response from authenticated APIs, however. This reduces the risk somewhat. This misconfiguration could be used by an attacker to access data that is available in an unauthenticated manner, but which uses some other form of security, such as IP address white-listing.
URL	https://listenzenify.vercel.app/sitemap.xml
Method	GET

Parameter	
Attack	
Evidence	Access-Control-Allow-Origin: *
Other Info	The CORS misconfiguration on the web server permits cross-domain read requests from arbitrary third party domains, using unauthenticated APIs on this domain. Web browser implementations do not permit arbitrary third parties to read the response from authenticated APIs, however. This reduces the risk somewhat. This misconfiguration could be used by an attacker to access data that is available in an unauthenticated manner, but which uses some other form of security, such as IP address white-listing.
Instances	5
Solution	Ensure that sensitive data is not available in an unauthenticated manner (using IP address white-listing, for instance). Configure the "Access-Control-Allow-Origin" HTTP header to a more restrictive set of domains, or remove all CORS headers entirely, to allow the web browser to enforce the Same Origin Policy (SOP) in a more restrictive manner.
Reference	https://vulncat.fortify.com/en/detail?category=HTML5&subcategory=Overly%20Permissive%20CORS%20Policy
CWE Id	264
WASC Id	14
Plugin Id	10098

Medium	Missing Anti-clickjacking Header
Description	The response does not protect against 'ClickJacking' attacks. It should include either Content-Security-Policy with 'frame-ancestors' directive or X-Frame-Options.
URL	https://listenzenify.vercel.app/
Method	GET
Parameter	x-frame-options
Attack	
Evidence	
Other Info	
Request Header	GET https://listenzenify.vercel.app/ HTTP/1.1 host: listenzenify.vercel.app user-agent: Mozilla/5.0 (Windows NT 10.0; Win64; x64) AppleWebKit/537.36 (KHTML, like Gecko) Chrome/141.0.0.0 Safari/537.36 pragma: no-cache cache-control: no-cache
Request Body	
Response Header	HTTP/1.1 200 OK Accept-Ranges: bytes Access-Control-Allow-Origin: * Age: 27111 Cache-Control: public, max-age=0, must-revalidate Content-Disposition: inline Content-Length: 12764 Content-Type: text/html; charset=utf-8 Cross-Origin-Opener-Policy: same-origin-allow-popups Date: Mon, 23 Feb 2026 02:14:32 GMT Etag: "b438d6765ef820441c4fa90cb0229f09" Referrer-Policy: no-referrer-when-downgrade Server: Vercel Strict-Transport-Security: max-age=63072000; includeSubDomains; preload Vary: rsc, next-router-state-tree, next-router-prefetch, next-router-segment-prefetch X-Matched-Path: / X-Nextjs-Prerender: 1 X-Nextjs-Stale-Time: 300

	X-Vercel-Cache: HIT X-Vercel-Id: iad1::b9r76-1771812872048-8ecfe16b9560
Response Body (truncated)	<!DOCTYPE html><!--hBVSfDU6ZJUImH61CQqY9--><html lang="en"><head><meta charSet="utf-8"/><meta name="viewport" content="width=device-width, initial-scale=1"/><link rel="preload" href="/_next/static/media/01e4147cff8141ee-s.p.7787e134.woff2" as="font" crossorigin="" type="font/woff2"/><link rel="preload" href="/_next/static/media/1b99372b3eaef0c8-s.p.758e15a8.woff2" as="font" crossorigin="" type="font/woff2"/><link rel="preload" href="/_next/static/media/83afe278b6a6bb3c-s.p.3a6ba036.woff2" as="fo...(truncated)
Instances	1
Solution	Modern Web browsers support the Content-Security-Policy and X-Frame-Options HTTP headers. Ensure one of them is set on all web pages returned by your site/app. If you expect the page to be framed only by pages on your server (e.g. it's part of a FRAMESET) then you'll want to use SAMEORIGIN, otherwise if you never expect the page to be framed, you should use DENY. Alternatively consider implementing Content Security Policy's "frame-ancestors" directive.
Reference	https://developer.mozilla.org/en-US/docs/Web/HTTP/Reference/Headers/X-Frame-Options
CWE Id	1021
WASC Id	15
Plugin Id	10020

Low	Strict-Transport-Security Header Not Set
Description	HTTP Strict Transport Security (HSTS) is a web security policy mechanism whereby a web server declares that complying user agents (such as a web browser) are to interact with it using only secure HTTPS connections (i.e. HTTP layered over TLS/SSL). HSTS is an IETF standards track protocol and is specified in RFC 6797.
URL	https://listenzenify.vercel.app/
Method	GET
Parameter	
Attack	
Evidence	
Other Info	
Request Header	GET https://listenzenify.vercel.app/ HTTP/1.1 host: listenzenify.vercel.app User-Agent: Mozilla/5.0 (X11; Linux x86_64; rv:140.0) Gecko/20100101 Firefox/140.0 Accept: text/html,application/xhtml+xml,application/xml;q=0.9,*/*;q=0.8 Accept-Language: en-US,en;q=0.5 Connection: keep-alive Upgrade-Insecure-Requests: 1 Sec-Fetch-Dest: document Sec-Fetch-Mode: navigate Sec-Fetch-Site: none Sec-Fetch-User: ?1 If-None-Match: "b438d6765ef820441c4fa90cb0229f09" Priority: u=0, i
Request Body	
Response Header	HTTP/1.1 304 Not Modified Cache-Control: public, max-age=0, must-revalidate Date: Mon, 23 Feb 2026 02:14:38 GMT Server: Vercel X-Vercel-Cache: HIT X-Vercel-Id: iad1::wdf4m-1771812878871-ae657091e937
Response Body	

Instances	1
Solution	Ensure that your web server, application server, load balancer, etc. is configured to enforce Strict-Transport-Security.
Reference	https://cheatsheetseries.owasp.org/cheatsheets/HTTP_Strict_Transport_Security_Cheat_Sheet.html https://owasp.org/www-community/Security-Headers https://en.wikipedia.org/wiki/HTTP_Strict_Transport_Security https://caniuse.com/stricttransportsecurity https://datatracker.ietf.org/doc/html/rfc6797
CWE Id	319
WASC Id	15
Plugin Id	10035

Low	X-Content-Type-Options Header Missing
Description	The Anti-MIME-Sniffing header X-Content-Type-Options was not set to 'nosniff'. This allows older versions of Internet Explorer and Chrome to perform MIME-sniffing on the response body, potentially causing the response body to be interpreted and displayed as a content type other than the declared content type. Current (early 2014) and legacy versions of Firefox will use the declared content type (if one is set), rather than performing MIME-sniffing.
URL	https://listenzenify.vercel.app/
Method	GET
Parameter	x-content-type-options
Attack	
Evidence	
Other Info	This issue still applies to error type pages (401, 403, 500, etc.) as those pages are often still affected by injection issues, in which case there is still concern for browsers sniffing pages away from their actual content type. At "High" threshold this scan rule will not alert on client or server error responses.
Request Header	GET https://listenzenify.vercel.app/ HTTP/1.1 host: listenzenify.vercel.app user-agent: Mozilla/5.0 (Windows NT 10.0; Win64; x64) AppleWebKit/537.36 (KHTML, like Gecko) Chrome/141.0.0.0 Safari/537.36 pragma: no-cache cache-control: no-cache
Request Body	
Response Header	HTTP/1.1 200 OK Accept-Ranges: bytes Access-Control-Allow-Origin: * Age: 27111 Cache-Control: public, max-age=0, must-revalidate Content-Disposition: inline Content-Length: 12764 Content-Type: text/html; charset=utf-8 Cross-Origin-Opener-Policy: same-origin-allow-popups Date: Mon, 23 Feb 2026 02:14:32 GMT Etag: "b438d6765ef820441c4fa90cb0229f09" Referrer-Policy: no-referrer-when-downgrade Server: Vercel Strict-Transport-Security: max-age=63072000; includeSubDomains; preload Vary: rsc, next-router-state-tree, next-router-prefetch, next-router-segment-prefetch X-Matched-Path: / X-Nextjs-Prerender: 1 X-Nextjs-Stale-Time: 300 X-Vercel-Cache: HIT X-Vercel-Id: iad1::b9r76-1771812872048-8ecfe16b9560
Response Body (truncated)	<!DOCTYPE html><!--hBVSfDU6ZJUImH61CQqY9--><html lang="en"><head><meta charSet="utf-8"/><meta name="viewport" content="width=device-width, initial-scale=1"/><link rel="preload" href="/_next/static/media/01e4147cff8141ee-s.p.7787e134.woff2" as="font" crossorigin="" type="font/woff2"/><link rel="preload" href="/_next/static/media/1b99372b3eaef0c8-s.p.75

	8e15a8.woff2" as="font" crossorigin="" type="font/woff2"/><link rel="preload" href="/_next/static/media/83afe278b6a6bb3c-s.p.3a6ba036.woff2" as="fo...(truncated)
URL	https://listenzenify.vercel.app/_next/static/chunks/528a3613526e0334.css
Method	GET
Parameter	x-content-type-options
Attack	
Evidence	
Other Info	This issue still applies to error type pages (401, 403, 500, etc.) as those pages are often still affected by injection issues, in which case there is still concern for browsers sniffing pages away from their actual content type. At "High" threshold this scan rule will not alert on client or server error responses.
URL	https://listenzenify.vercel.app/_next/static/chunks/9e9e9efd420e4a6d.css
Method	GET
Parameter	x-content-type-options
Attack	
Evidence	
Other Info	This issue still applies to error type pages (401, 403, 500, etc.) as those pages are often still affected by injection issues, in which case there is still concern for browsers sniffing pages away from their actual content type. At "High" threshold this scan rule will not alert on client or server error responses.
URL	https://listenzenify.vercel.app/_next/static/chunks/turbopack-3800110d96aa62c2.js
Method	GET
Parameter	x-content-type-options
Attack	
Evidence	
Other Info	This issue still applies to error type pages (401, 403, 500, etc.) as those pages are often still affected by injection issues, in which case there is still concern for browsers sniffing pages away from their actual content type. At "High" threshold this scan rule will not alert on client or server error responses.
URL	https://listenzenify.vercel.app/_next/static/media/01e4147cff8141ee-s.p.7787e134.woff2
Method	GET
Parameter	x-content-type-options
Attack	
Evidence	
Other Info	This issue still applies to error type pages (401, 403, 500, etc.) as those pages are often still affected by injection issues, in which case there is still concern for browsers sniffing pages away from their actual content type. At "High" threshold this scan rule will not alert on client or server error responses.
Instances	5
Solution	Ensure that the application/web server sets the Content-Type header appropriately, and that it sets the X-Content-Type-Options header to 'nosniff' for all web pages. If possible, ensure that the end user uses a standards-compliant and modern web browser that does not perform MIME-sniffing at all, or that can be directed by the web application/web server to not perform MIME-sniffing.
Reference	https://learn.microsoft.com/en-us/previous-versions/windows/internet-explorer/ie-developer/compatibility/gg622941(v=vs.85) https://owasp.org/www-community/Security-Headers
CWE Id	693
WASC Id	15
Plugin Id	10021
Informational	Re-examine Cache-control Directives
Description	The cache-control header has not been set properly or is missing, allowing the browser and proxies to cache content. For static assets like css, js, or image files this might be intended, however, the resources should be reviewed to ensure that no sensitive content will be cached.

URL	https://listenzenify.vercel.app/
Method	GET
Parameter	cache-control
Attack	
Evidence	public, max-age=0, must-revalidate
Other Info	
Request Header	GET https://listenzenify.vercel.app/ HTTP/1.1 host: listenzenify.vercel.app user-agent: Mozilla/5.0 (Windows NT 10.0; Win64; x64) AppleWebKit/537.36 (KHTML, like Gecko) Chrome/141.0.0.0 Safari/537.36 pragma: no-cache cache-control: no-cache
Request Body	
Response Header	HTTP/1.1 200 OK Accept-Ranges: bytes Access-Control-Allow-Origin: * Age: 27111 Cache-Control: public, max-age=0, must-revalidate Content-Disposition: inline Content-Length: 12764 Content-Type: text/html; charset=utf-8 Cross-Origin-Opener-Policy: same-origin-allow-popups Date: Mon, 23 Feb 2026 02:14:32 GMT Etag: "b438d6765ef820441c4fa90cb0229f09" Referrer-Policy: no-referrer-when-downgrade Server: Vercel Strict-Transport-Security: max-age=63072000; includeSubDomains; preload Vary: rsc, next-router-state-tree, next-router-prefetch, next-router-segment-prefetch X-Matched-Path: / X-Nextjs-Prerender: 1 X-Nextjs-Stale-Time: 300 X-Vercel-Cache: HIT X-Vercel-Id: iad1::b9r76-1771812872048-8ecfe16b9560
Response Body (truncated)	<!DOCTYPE html><!--hBVSfDU6ZJUImH61CQqY9--><html lang="en"><head><meta charSet="utf-8"/><meta name="viewport" content="width=device-width, initial-scale=1"/><link rel="preload" href="/_next/static/media/01e4147cff8141ee-s.p.7787e134.woff2" as="font" crossorigin="" type="font/woff2"/><link rel="preload" href="/_next/static/media/1b99372b3eaef0c8-s.p.758e15a8.woff2" as="font" crossorigin="" type="font/woff2"/><link rel="preload" href="/_next/static/media/83afe278b6a6bb3c-s.p.3a6ba036.woff2" as="fo...(truncated)
URL	https://listenzenify.vercel.app/about?_rsc=vusbg
Method	GET
Parameter	cache-control
Attack	
Evidence	public, max-age=0, must-revalidate
Other Info	
URL	https://listenzenify.vercel.app/pricing?_rsc=vusbg
Method	GET
Parameter	cache-control
Attack	

Evidence	public, max-age=0, must-revalidate
Other Info	
URL	https://listenzenify.vercel.app/profile?_rsc=vusbg
Method	GET
Parameter	cache-control
Attack	
Evidence	public, max-age=0, must-revalidate
Other Info	
URL	https://listenzenify.vercel.app/search?q=UqujZxRJ&_rsc=1uu52
Method	GET
Parameter	cache-control
Attack	
Evidence	public, max-age=0, must-revalidate
Other Info	
Instances	5
Solution	For secure content, ensure the cache-control HTTP header is set with "no-cache, no-store, must-revalidate". If an asset should be cached consider setting the directives "public, max-age, immutable".
Reference	https://cheatsheetseries.owasp.org/cheatsheets/Session_Management_Cheat_Sheet.html#web-content-caching https://developer.mozilla.org/en-US/docs/Web/HTTP/Reference/Headers/Cache-Control https://grayduck.mn/2021/09/13/cache-control-recommendations/
CWE Id	525
WASC Id	13
Plugin Id	10015

Informational	Retrieved from Cache
Description	The content was retrieved from a shared cache. If the response data is sensitive, personal or user-specific, this may result in sensitive information being leaked. In some cases, this may even result in a user gaining complete control of the session of another user, depending on the configuration of the caching components in use in their environment. This is primarily an issue where caching servers such as "proxy" caches are configured on the local network. This configuration is typically found in corporate or educational environments, for instance.
URL	https://listenzenify.vercel.app/
Method	GET
Parameter	
Attack	
Evidence	Age: 27111
Other Info	The presence of the 'Age' header indicates that a HTTP/1.1 compliant caching server is in use.
Request Header	GET https://listenzenify.vercel.app/ HTTP/1.1 host: listenzenify.vercel.app user-agent: Mozilla/5.0 (Windows NT 10.0; Win64; x64) AppleWebKit/537.36 (KHTML, like Gecko) Chrome/141.0.0.0 Safari/537.36 pragma: no-cache cache-control: no-cache
Request Body	
Response Header	HTTP/1.1 200 OK Accept-Ranges: bytes Access-Control-Allow-Origin: *

	Age: 27111 Cache-Control: public, max-age=0, must-revalidate Content-Disposition: inline Content-Length: 12764 Content-Type: text/html; charset=utf-8 Cross-Origin-Opener-Policy: same-origin-allow-popups Date: Mon, 23 Feb 2026 02:14:32 GMT Etag: "b438d6765ef820441c4fa90cb0229f09" Referrer-Policy: no-referrer-when-downgrade Server: Vercel Strict-Transport-Security: max-age=63072000; includeSubDomains; preload Vary: rsc, next-router-state-tree, next-router-prefetch, next-router-segment-prefetch X-Matched-Path: / X-Nextjs-Prerender: 1 X-Nextjs-Stale-Time: 300 X-Vercel-Cache: HIT X-Vercel-Id: iad1::b9r76-1771812872048-8ecfe16b9560
Response Body (truncated)	<!DOCTYPE html><!--hBVSfDU6ZJUImH61CQqY9--><html lang="en"><head><meta charSet="utf-8"/><meta name="viewport" content="width=device-width, initial-scale=1"/><link rel="preload" href="/_next/static/media/01e4147cff8141ee-s.p.7787e134.woff2" as="font" crossorigin="" type="font/woff2"/><link rel="preload" href="/_next/static/media/1b99372b3eaef0c8-s.p.758e15a8.woff2" as="font" crossorigin="" type="font/woff2"/><link rel="preload" href="/_next/static/media/83afe278b6a6bb3c-s.p.3a6ba036.woff2" as="fo...(truncated)
URL	https://listenzenify.vercel.app/_next/static/chunks/9e9e9efd420e4a6d.css
Method	GET
Parameter	
Attack	
Evidence	Age: 0
Other Info	The presence of the 'Age' header indicates that a HTTP/1.1 compliant caching server is in use.
URL	https://listenzenify.vercel.app/_next/static/media/01e4147cff8141ee-s.p.7787e134.woff2
Method	GET
Parameter	
Attack	
Evidence	Age: 0
Other Info	The presence of the 'Age' header indicates that a HTTP/1.1 compliant caching server is in use.
URL	https://listenzenify.vercel.app/robots.txt
Method	GET
Parameter	
Attack	
Evidence	Age: 467
Other Info	The presence of the 'Age' header indicates that a HTTP/1.1 compliant caching server is in use.
URL	https://listenzenify.vercel.app/sitemap.xml
Method	GET
Parameter	
Attack	
Evidence	Age: 467
Other Info	The presence of the 'Age' header indicates that a HTTP/1.1 compliant caching server is in use.
Instances	5

Solution	Validate that the response does not contain sensitive, personal or user-specific information. If it does, consider the use of the following HTTP response headers, to limit, or prevent the content being stored and retrieved from the cache by another user:
	Cache-Control: no-cache, no-store, must-revalidate, private
	Pragma: no-cache
	Expires: 0
This configuration directs both HTTP 1.0 and HTTP 1.1 compliant caching servers to not store the response, and to not retrieve the response (without validation) from the cache, in response to a similar request.	
Reference	https://datatracker.ietf.org/doc/html/rfc7234 https://datatracker.ietf.org/doc/html/rfc7231 https://www.rfc-editor.org/rfc/rfc9110.html
CWE Id	525
WASC Id	
Plugin Id	10050