

C++ Introduction

Michael C. Hackett

Computer Science Department

Community
College
of Philadelphia


A little background on C++

- Released in 1985 by Bjarne Stroustrup.
 - Started in 1979 as “C with Classes”
 - Renamed “C++” in 1983
- Added classes/object-oriented programming (among other things) to the C programming language.
- General-purpose, high-level, compiled language.

A little background on C++

- C++ is standardized by an ISO (International Standards Organization) group.
 - <https://isocpp.org/>
- Standards (kind of like “versions”):
 - C++98: 1998-2013
 - C++03: 2003-2011
 - C++11: 2011-2014
 - C++14: 2014-2017
 - C++17: 2017-2020 (Current standard)
 - C++20: 2020-? (Expected sometime in early 2020)

A little background on C++



<https://isocpp.org/std/status>

Creating a C++ Program

- C++ source code is written in a plaintext file.
 - Compiled to an executable program (.exe file on Windows, for example)
- The main function is the starting point for a C++ application.
 - The main function must be written as shown below.
 - It is similar to the main method in a Java program.

```
int main() {  
  
}
```

Creating a C++ Program

- Unlike the main method in a Java program (return type is void), the return type of the C++ main function is int.
- The main function typically returns 0 when finished.

```
int main() {  
    //Statements to execute  
  
    return 0;  
}
```

Creating a C++ Program

- Java shares a similar syntax to C++.
- Most of the basics require no “re-education”.
- The point of these slides is to highlight the key differences.

Preprocessor Directives

- A **preprocessor directive** is a statement at the beginning of the source code that includes the functions/objects of other source code.
 - Similar to an import statement in Python or Java.
- The include statements allow the program to use the code of header files and libraries.
 - Explained later.

Preprocessor Directives

- Syntax:

#include <*header*>

- *header* is replaced with the actual name of the header file.

Preprocessor Directives

- The first header we will see is the **iostream** header.
 - Part of the standard input/output library.
- Will allow the program to print output and get keyboard input.

```
#include <iostream>
```

Preprocessor Directives

```
#include <iostream>
```

```
int main() {  
    //Statements to execute  
  
    return 0;  
}
```

Console Output

- The statement below prints the string literal “Hello World!” as the program’s output.
 - `iostream` header must be included.

```
std::cout << "Hello World!";
```

Console Output

```
std::cout << "Hello World!";
```

- **std::cout** indicates the standard output stream, which is usually printing to the console/screen.
- **<<** in this context is the *insertion operator*.
 - In other contexts, it is the left-shift bitwise operator.
 - Indicates what is being inserted into the standard output stream.

Console Output

```
#include <iostream>

int main() {
    std::cout << "Hello World!";

    return 0;
}
```

Output:
Hello World!

Console Output

```
std::cout << "Hello World!";
```

Is equivalent to the following Java statement:

```
System.out.print("Hello World!");
```

Console Output

```
#include <iostream>

int main() {
    std::cout << "Hello World 1";
    std::cout << "Hello World 2";

    return 0;
}
```

Output:

Hello World 1Hello World 2

Console Output

- To end a line (insert a line break), use the following:

```
std::cout << "Hello World!" << std::endl;
```

Console Output

```
std::cout << "Hello World!" << std::endl;
```

Is equivalent to the following Java statement:

```
System.out.println("Hello World!");
```

Console Output

```
#include <iostream>
```

```
int main() {  
    std::cout << "Hello World 1" << std::endl;  
    std::cout << "Hello World 2";  
  
    return 0;  
}
```

Output:

Hello World 1

Hello World 2

Console Output

- You can use the insertion operator multiple times in a single output statement:

```
std::cout << "Hello" << " " << "World!" << std::endl;
```

Output:

```
Hello World!
```

Namespaces

- A **using declaration** allows us to specify a namespace (which are used to prevent name conflicts) that we want to include in our program.
- For example:

using std::cout;

would allow us to simply use **cout** instead of **std::cout** in our program.

Namespaces

- Using declarations typically appear after any preprocessor directives.

```
#include <iostream>
```

```
using std::cout;
```

```
int main() {  
    cout << "Hello World 1" << std::endl;  
    cout << "Hello World 2";  
  
    return 0;  
}
```

Namespaces

- We can use a using declaration to use an entire namespace.
- For example:

using namespace std;

would allow us to no longer need to use the **std::** prefix in our program.

Namespaces

See Example1_ConsoleOutput.cpp
See Example2_ConsoleOutput.cpp
See Example3_ConsoleOutput.cpp

- No need to use **std::** before cout or endl

```
#include <iostream>
```

```
using namespace std;
```

```
int main() {  
    cout << "Hello World 1" << endl;  
    cout << "Hello World 2";  
  
    return 0;  
}
```


Fundamental Data Types

- Similar concept to the eight Java primitives, which are simplified versions of C++'s fundamental types.
- Boolean type
- Integer type
- Floating Point type
- Character type

Boolean Type

- **bool** (1 byte/8 bits; Only one bit is used though)
 - Can be **true** or **false**.

Integer Types

- **int** (4 bytes/32 bits)
 - Can represent any integer between -2,147,483,648 and 2,147,483,647
 - C++ standard says a minimum of 16 bits for an int, but it will be 32 bits on modern computers.
- Modifiers
 - **signed** and **unsigned**
 - **short** and **long**

Integer Types

Specifier	Equivalent to	Range	Size
short	short int	-32768 through 32767	16 bits (2 bytes)
short int			
signed short			
signed short int			
unsigned short	unsigned short int	0 through 65535	
unsigned short int			

`short int` is equivalent to Java's `short` type

Integer Types

Specifier	Equivalent to	Range	Size
int	int	-2,147,483,648 through 2,147,483,647	32 bits* (4 bytes)
signed			
signed int			
unsigned	unsigned int	0 through 4,294,967,295	
unsigned int			

*The C++ standard specifies *at least* 16 bits for the `int` type. It's generally going to be 32 bits on modern systems.

Technically, `int` is also equivalent to Java's `short` type; on modern systems it is like Java's `int` type.

Integer Types

Specifier	Equivalent to	Range	Size
<code>long</code>	<code>long int</code>	$\pm 9.22 \times 10^{18}$ (Approx)	64 bits* (8 bytes)
<code>long int</code>			
<code>signed long</code>			
<code>signed long int</code>			
<code>unsigned long</code>	<code>unsigned long int</code>	0 through 1.84×10^{19}	
<code>unsigned long int</code>			

*The C++ standard specifies *at least* 32 bits for the `long int` type. It's generally going to be 64 bits on modern systems.

Technically, `long int` is the equivalent to Java's `int` type; on modern systems it is like Java's `long` type.

Integer Types

Specifier	Equivalent to	Range	Size
long long	long long int	+/- 9.22 * 10 ¹⁸ (Approx)	64 bits (8 bytes)
long long int			
signed long long			
signed long long int			
unsigned long long	unsigned long long int	0 through 1.84 * 10 ¹⁹	
unsigned long long int			

*The C++ standard specifies *at least* 64 bits for the `long long int` type.
`long long int` is equivalent to the `long` type in Java

Integer Primitives

- It's a lot to remember, but I only expect you to use:
 - **short int** (will act like Java's short)
 - **int** (will act like Java's int)
 - **long int** (will act like Java's long)

Floating Point Types

- **float** (usually 4 bytes/32 bits) (Same as Java)
- **double** (usually 8 bytes/64 bits) (Same as Java)
- **long double** (usually 12 bytes/96 bits on modern systems)
 - Extended precision
 - Doesn't always map to the IEEE-754 floating point standard

Character Type

- **char** (1 byte/8 bits)
 - Can represent a single, 8-bit Unicode character.
 - Can represent an 8-bit number
- This is sort of a mix between Java's byte and char primitive types.

Character Types

Specifier	Range (Numeric)	Size
char	-128 through 127	8 bits (1 byte)
signed char		
unsigned char	0 through 255	

char is equivalent to Java's **byte** type with regard to integer data

char is like Java's **char** type with regard to character data, but is only 8 bits (Java's char is 16 bits)

Variables

See Example4_VariablesAndTypes.cpp

- Variables are declared and used in an identical fashion to Java:

```
int age;  
age = 22;
```

```
double temp = 98.6;
```

- Like Java, variables in C++ are ***statically typed***.
 - It cannot reference values of a different data type after it has been declared.

Literals

- Similar rules as found in Java for long literals (needs an l or L) and float literals (needs an f or F)

```
long int exampleLongLiteral = 255L;  
float myExampleFloat = 15.5F;
```

Literals (Char)

- char literals can be expressed as a character literal or a number.
- **Use single quotes for characters.**

```
char exampleCharLiteral = 'A';  
char example8BitNumber = 65;
```

Naming Rules for Variables

- Same rules as Java.
- A variable's data type cannot be changed after declaration.
- Keywords cannot be the name of a variable.
- “Camel-case” is the convention used for variable names in C++, as it was in Java.

Naming Rules for Variables

- Names must start with a letter, dollar sign, or underscore.
- Names may contain numbers, but **cannot** start with numbers.
- Aside from letters, dollar signs, underscores, and numbers, no other characters may be used.
- Names cannot contain spaces. Use underscores, if necessary.

`int someName;` **Valid.**

`int _someName;` **Valid. Can start with underscore.**
`int some_Name;` **Valid. Can contain any underscores.**

`int $someName;` **Valid. Can start with dollar sign.**
`int some$Name;` **Valid. Can contain any dollar signs.**

`int 0someName;` **INVALID. Can't start with a number.**
`int some0Name;` **Valid. Can contain any numbers.**

`int some Name;` **INVALID.**
`int some_Name;` **Valid.**

Constants

See Example6_Constants.cpp

- Constants (variables that can't be changed) are declared by using the **const** keyword.
 - By convention, the name of a constant is in uppercase with underscores between words.

```
const int FREEZING_POINT = 32;
```

Comments

- Same as Java
- `//` - Inline Comments
- `/* */` - Multiline Comments

Strings

See `Example7_Strings.cpp`

- The string object is provided through the `iostream` header.
- Without `std` namespace, must specify `std::string`

Declaring/Initializing Strings

- Lowercase s in string.

```
string hello = "Hello There!";
```

- Without using the std namespace:

```
std::string hello = "Hello There!";
```

String Concatenation/Appending

- Same as Java
- Concatentation: +
- Appending: +=

See `Example8_ConcatenationAndApending.cpp`

Keyboard Input

```
std::cin >> someVariable;
```

- **std::cin** indicates the standard input stream, which is usually keyboard entries.
- **>>** in this context is the *extraction operator*.
 - In other contexts, it is the right-shift bitwise operator.
 - Indicates data is extracted from the standard input stream and stored into the provided variable.

Keyboard Input

```
#include <iostream>

using namespace std;

int main() {
    string name;
    cout << "Enter your name: ";
    cin >> name;
    cout << "Hello, " + name + "!" << endl;

    return 0;
}
```

Output:

Enter your name: **John**
Hello, John!


Arithmetic Operators

- Same as Java
- Addition: +
- Subtraction: -
- Multiplication: *
- Division: /
- Remainder: %
- Operator precedence is the same as Java.
- Augmented Assignment (+=, -=, etc) is the same as Java.

Typecasting

- The process is identical to Java.

```
double myDouble = 453.87;  
int myInt;  
myInt = (int)myDouble;
```



Put the desired data type, in parenthesis, before the variable name to ***typecast*** the value as that type.

In the example above, the value stored at the memory location referenced by myInt is 453 not 453.87

Typecasting Numbers to Strings

- Use the `std::to_string()` function.
 - Or simply call `to_string()` when `std` namespace is used.

```
double myDouble = 453.87;  
string doubleString = to_string(myDouble);
```

Typecasting Numbers to Strings

- Numeric data must be converted to strings before you can concatenate/append.

```
int myInt = 123;  
string output = "Your number is: " + to_string(myInt);
```

Typecasting Integers from Strings

- Use the `std::stoi()` function.
 - Or simply call `stoi()` when `std` namespace is used.
 - `stoi` = “string to int”

```
string numString = "123";  
int myInt = stoi(numString);
```

Typecasting Doubles from Strings

- Use the `std::stod()` function.
 - Or simply call `stod()` when `std` namespace is used.
 - `stod` = “string to double”

```
string numString = "456.78";  
double myDouble = stod(numString);
```

Math Header

See Example12_MathHeader.cpp

- Provides access to mathematical functions like rounding, exponents, and square roots.
 - Similar to Java's Math object

#include <cmath>

- Provides a number of familiar functions like:
 - sqrt, pow, round, ceil, and floor

Relational Operators

- Same Operators as Java
- ==, !=, <, >, <=, >=

Logical Operators

- Same Operators as Java
- &&, ||, !

If Statements

- Same syntax as Java
- See `Example1_IfStatements.cpp`

Loops

- For, while, and do-while loops have same syntax as Java.
- See Example2_ForLoops.cpp
- See Example3_WhileLoops.cpp
- See Example4_DoWhileLoops.cpp

Subroutines and Functions

See Example1_BasicSubroutine.cpp

- Generally, the syntax for a subroutine/function/method is the same as Java.
- However, the subroutine must be defined before it can be called.

Prototypes

See Example2_SubroutinePrototypes.cpp
See Example3_Arguments.cpp

- Placing a prototype at the beginning of the program declares the subroutine, its return type and parameter list types.
- This allows the subroutine to be defined anywhere in the source code.

Arrays

See Example1_ArrayBasics.cpp

- The basic usage of an array is the same as it was in Java.
- The declaration is a little different.
 - The [] comes after the variable name.
- With data: `int numArray[] = {4, 7, 9, 10};`
- Without data: `int numArray[5];`
 - The number specifies the length.

Arrays

See Example3_ArrayLength.cpp

- To find the length of an array, you need to use the sizeof function to determine the total byte size.
- Then, divide by the byte size of each element

```
int numArray[] = {4, 7, 9, 10};  
int byteSize = sizeof(numArray);  
int length = byteSize / 4;
```

ints are 4 bytes in size



Arrays

- Alternatively...

```
int numArray[] = {4, 7, 9, 10};  
int length = sizeof(numArray) / 4;
```