


DATE	16-Jun-23
QUOTE #	099/Q/VI/2023
VALID UNTIL	17-Jul-23
Currency	IDR
REV.	#00



CUSTOMER

Kepada : Yth.
Ibu Ismi
PT. UBC Medical Indonesia

Prepared by:

Putri Fadillah Sari
putri.f.s@dgscientific.com
088263244837/081112014888

No	Description	Unit Price	Qty	Amount
1	Dry Bath / Heating Block Model : SH-DB1  <p>Spesification</p> <ol style="list-style-type: none"> Temp Range : Ambient +5 to 150°C Temp Accuracy : $\pm 0.1^{\circ}\text{C}$ at 37°C, $\pm 0.2^{\circ}\text{C}$ at 90°C, $\pm 0.4^{\circ}\text{C}$ at 135°C Temp Resolution : 0.1°C-Display, 0.1°C-Contro Heat up Speed : Approx. $5^{\circ}\text{C}/\text{min}$ Controller : Digital Fuzzy Controller with Touch Button & Jog Dia Timer : 99hr 59min., $\pm 0.1\text{min.}$ Increments Display : Full Digital LCD Display with Back-Light Function Permissible Temp. & Humidity : $5^{\circ}\text{C}\sim 40^{\circ}\text{C}$, $<80\%$ Heater : Molded Heater Power Consumption : 300W Material Unit Case : ABS Material Block Case : PPS Material Blok : Anodized Aluminum Others : Incl. PC Cover for sample Safety Devices : Over Temp Protection, Over Current Protector, Sensor Error Detector Dimensions (WxDxH)&Net Weight : 165 X 250X 145mm/6.50x9.84x5.71", 1.6Kg Packing Size (WxDxH)&Gross Weight : 230 x 310 x 260mm/9.06x12.02x10.24", 2.2Kg Power Supply : 1 Phase, AC 120V, 60Hz or AC 230V, 50/60 HZ 	18,616,800	1	18,616,800
2	Dry Bath / Heating Block Model : SH-DB1 - Set <p>Spesification</p> <ol style="list-style-type: none"> Temp Range : Ambient +5 to 150°C Temp Accuracy : $\pm 0.1^{\circ}\text{C}$ at 37°C, $\pm 0.2^{\circ}\text{C}$ at 90°C, $\pm 0.4^{\circ}\text{C}$ at 135°C Temp Resolution : 0.1°C-Display, 0.1°C-Contro Heat up Speed : Approx. $5^{\circ}\text{C}/\text{min}$ Controller : Digital Fuzzy Controller with Touch Button & Jog Dia Timer : 99hr 59min., $\pm 0.1\text{min.}$ Increments Display : Full Digital LCD Display with Back-Light Function 	23,080,800	1	23,080,800

	8.Permissible Temp. & Humidity : 5°C~40°C, <80%			
	9.Heater : Molded Heater			
	10.Power Consumption : 300W			
	11.Material Unit Case : ABS			
	12.Material Block Case : PPS			
	13.Material Blok : Anodized Aluminum			
	14.Others : Incl. PC Cover for sample			
	15.Safety Devices : Over Temp Protection, Over Current Protector, Sensor Error Detector			
	16.Dimensions (WxDxH)&Net Weight : 165 X 250X 145mm/6.50x9.84x5.71", 2.4Kg			
	17.Packing Size (WxDxH)&Gross Weight : 230 x 310 x 260mm/9.06x12.02x10.24", 3.0Kg			
	18.Power Supply : 1 Phase, AC 120V, 60Hz or AC 230V, 50/60 HZ			
3	Centrifuges	48,037,500	1	48,037,500
	Model : CD-3024			
				
	Spesification			
	1.Speed : 500-15000 rpm in 10 rpm steps			
	2.Max RCF : 21380 g			
	3.Time : 0,5-99 min., continous			
	4.Dimensions : 34 x 68 x 33 cm			
	5.Weight : CD-3024 12 kg without Rotor			
	6.Rotor Capacity : 18 x 5 ml, 24 x 2 ml, 36 x 0,5 ml			
4	Centrifuges	28,192,500	1	28,192,500
	Model : CD-0412-50			
				
	Spesification			
	1.Speed : 300 - 4.000 rpm			
	2.Max RCF : 1800 g			
	3.Timer : 0,5-99 minutes, impulse			
	4.Dimensions : 30 x 35 x 20 cm			
	5.Weight : 6 kg			
	6.Max.Rotor Capacity : 6 x 15 ml or 6 x 50 ml 54° fix angle			
	7.Increament : 100 rpm			
	8.Delivery : Incl Rotor			
	9.Noise : < 54 dB (A)			
		Subtotal		117,927,600

PPN (11%)	12,972,036
-----------	------------

TERMS AND CONDITIONS

TOTAL	130,899,636
--------------	--------------------

1. Price is include Tax (PPN). FRANCO JABODETABEK
2. Payment : DP 50%, full payment before delivery
3. Delivery : Indent 4 - 12 weeks after PO received
4. Warranty : - 1 year for main unit and part except consumable part
 - Including Installation and training
 - Available Additional Contract Services 1 year after

If you have any questions about this price quote, please don't hesitate to contact us

Thank You For Your Business!

GBC Scientific Equipment Authorized Distributor



Manufacturer of world class scientific equipment and accessories: AAS, HPLC, ICP-OES, ICP- α TOFMS, Rheometry, UV-Vis and XRD - since 1978.

