

Exercise 5 – Canalyzer/Cluster

1. For each of the following steps copy and paste a screenshot to view the result.
 - Create one TRACE block for each CAN channel (Trace BH and Trace C1)
 - In the trace BH create a filter that shows only the messages transmitted and received related to IPC
 - In the trace C1 create a filter that stop the messages transmitted by BSM
 - Using the IG block simulate the following signals:
 - AIRBAG1.AirBagFailSts = 1 (Fail_not_Present_Lamp_Flashing)
 - BRAKE1.VehicleSpeedVSOSignal = 40Km/h
 - BCM_COMMAND.CmdlgnSts = RUN
 - ENGINE1.PowertrainPrplsnActv =1
2. With a GRAPHIC window verify that all previous signals are set accordingly with IG block.
3. With IG Block simulate AIRBAG1.AirBagFailSts = 0 and verify with a graphic that IPC send the signal CLUSTER2.AirBagLamp_FailSts = 0
4. With IG Block simulate AIRBAG1.AirBagFailSts = 1 and verify with a graphic that IPC send the signal CLUSTER2.AirBagLamp_FailSts = 3
5. With IG Block simulate BRAKE8. ABSFailSts = 1 and verify with a graphic that IPC send the signal CLUSTER2.ABSLamp_FailSts = 2
6. Choose 10 signals to change from the IG block (every signal from a different message) create a log with only the signals that you chose and change them while you are logging
7. Use the previous log in offline mode to analyze the time in which you change every signal verify what is the delta-time between the moment in which you changed the first signal and the moment in which you change the third one $dt = 4.35$
8. verify what is the delta-time between the moment in which you changed the first signal and the moment in which you change the last on $dt = 9.16$
9. Create a general report containing all the answers for the previous questions;