

Q 

Categories

A->Z

System Core >

Analog >

Timers v

RTC

TIM1

TIM2

☒ TIM3☐ TIM4

Connectivity >

Computing >

Middleware and Soft... >

TIM3 Mode and Configuration

Mode

Slave Mode Trigger Source ☒ Internal ClockChannel1 Channel2 Channel3 Channel4 Combined Channels ☐ XOR activation☐ One Pulse Mode

Configuration

Reset Configuration

☒ Parameter Settings☒ User Constants☒ NVIC Settings☒ DMA Settings

NVIC Interrupt Table	Enabled	Preemption Priority	Sub Priority
TIM3 global interrupt	☒	0	0



10:09 م

ENG



25°C صافية

Categories

A->Z

DMA

GPIO

IWDG

NVIC

✓ RCC

⚠ SYS

WWDG

Analog

>

Timers

>

Connectivity

▼

CAN

✓ I2C1

I2C2

SPI1

SPI2

USART1

⊗ USART2

USART3

USB

Computing

>

Middleware and S...

>

I2C1 Mode and Configuration

Mode

I2C I2C

Configuration

Reset Configuration

✓ NVIC Settings

✓ DMA Settings

✓ GPIO Settings

✓ Parameter Settings

✓ User Constants

Configure the below parameters :

Search (Ctrl+F)

◀

▶

i

▼ Master Features

I2C Speed Mode

Standard Mode

I2C Clock Speed (Hz)

100000

▼ Slave Features

Clock No Stretch Mode

Disabled

Primary Address Length selection

7-bit

Dual Address Acknowledged

Disabled

