« See all 48 Products in Family

Allied Vision Alvium G5-1240m, 1/1.7" 12.2MP C-Mount, 5GigE PoE Monochrome Camera

See More by Allied Vision

Stock #23-631 1 In Stock

- 1 +

S$1,190.00

Explore our developer-friendly HTML to PDF API Printed using PDFCrowd HTML to PDF

ADD TO CART

Volume Pricing	
Qty 1+	**S$1,190.00** each
Need More?	Request Quote

+ Add to Saved List

Compare

Product Downloads		
Spec Sheets:pdf	User Manual:pdf	EO Spec Sheet

Spectrum:	Monochrome

General

Type:	Monochrome Camera
Model Number:	Alvium G5-1240m
Manufacturer:	Allied Vision
Camera Series:	Alvium G5

Physical & Mechanical Properties

Dimensions (mm):	60 × 29 × 29
Weight (g):	100
Housing:	Full

Sensor

Image Buffer:	512KB
Sensor Format:	1/1.7"
Resolution (Megapixels):	12.20
Frame Rate (fps):	41.00
Pixels (H x V):	4,024 x 3,036
Pixel Size, H x V (µm):	1.85 x 1.85

Explore our developer-friendly HTML to PDF API Printed using PDFCrowd HTML to PDF

Sensing Area, H x V (mm):	7.44 x 6.61
Imaging Sensor:	Sony IMX226
Type of Sensor:	Progressive Scan CMOS
Shutter Type:	Global
Pixel Depth:	8/10 bit
Exposure Time:	10 µs to 10 s
Dynamic Range (dB):	Not Specified
Machine Vision Standard:	GigE Vision V2.2, GenICam V2.0

Electrical

Power Consumption (W):	External power: 6.1 W at 12 VDC | Power over Ethernet: 6.8 W

Hardware & Interface Connectivity

Interface:	5GigE (PoE)
Connector:	5GigE, RJ45 with Screw Locks
Power Supply:	PoE, 12 to 24 VDC via GPIO, or with external power supply #23-581
GPIOs:	1 opto-isolated input, 1 opto-isolated output, 2 non-isolated GPIOs
Synchronization:	Hardware Trigger (GPIO) or Software Trigger
Interface Port Orientation:	Back Panel
GPIO Connector Type:	10-pin TFM

Threading & Mounting

Mount:	C-Mount
Mounting Threads:	¼"-20 and M6 with Tripod Mount Adapter #14-156

Environmental & Durability Factors

Operating Temperature (°C):	+5 to +60
Storage Temperature (°C):	-20 to +85

Explore our developer-friendly HTML to PDF API Printed using PDFCrowd HTML to PDF

Regulatory Compliance

RoHS 2015:	Compliant
Certificate of Conformance:	View
Reach 240:	Compliant

Product Details

- 4.2 Times More Bandwidth than GigE
- Up to 24.6MP Resolution with Framerates up to 691 FPS
- Onboard Image Processing and Expansive Feature Sets

Allied Vision Alvium G5 5GigE PoE Cameras feature a lightweight, compact form factor and combines the advantages of the established 5GigE Vision standard with the flexibility of the Alvium platform. Powered by ALVIUM® Technology, the sugar cube style camera delivers high image quality at a low power consumption. These cameras feature the latest industrial standard hardware and can easily be integrated into any USB3 Vision or GigE Vision system while ensuring long-term availability and reliability. With precision sensor alignment, enhanced cleanliness, fixed pattern noise correction, and defect pixel correction, resolutions up to 24.6MP and framerates up to 691 FPS are available. Allied Vision Alvium G5 5GigE PoE Cameras feature a gigabit ethernet port on the back panel and are available in a variety of monochrome and color options with either C-Mount or S-Mount lens interfaces all in the compact sugar cube format.

Accessories

Note: Compatible accessories for individual stock numbers may vary. If unsure about which accessories work with your products, please contact us here.

MORE+	Power Over Ethernet (PoE) Single Port injector	☐	#68-469	S Rec
MORE+	Allied Vision Cat6 1G/5GigE Locking Cable, 3m	☐	#23-575	S Rec

Explore our developer-friendly HTML to PDF API Printed using PDFCrowd HTML to PDF

MORE+	Allied Vision Cat6 1G/5GigE Locking Cable, 5m	☐	#23-576	S Rec
MORE+	Allied Vision Cat6 1G/5GigE Locking Cable, 10m	☐	#23-577	S Rec
MORE+	Allied Vision Alvium G1/G5 GPIO Cable, 3m	☐	#23-578	S Rec
MORE+	Allied Vision Alvium G1/G5 GPIO Cable, 5m	☐	#23-579	S Rec
MORE+	Allied Vision Alvium G1/G5 GPIO Cable, 10m	☐	#23-580	S Rec
MORE+	Allied Vision Alvium G1/G5 Power Supply	☐	#23-581	S Rec
MORE+	Allied Vision Alvium G1/G5 Heatsink, Set of 2	☐	#23-643	S Rec

Related Products

Allied Vision Alvium USB 3.0 Cameras

Allied Vision Alvi

Imaging Lens Selector

Explore our developer-friendly HTML to PDF API Printed using PDFCrowd HTML to PDF

Imaging

Grading Search Results...

Factory Automation Telecentric M12

Custom Sensor Camera Model

Number of Horizontal Pixels:

1

Number of Vertical Pixels:

2

Pixel Size (µm):

3

Working Distance (mm):

4

Horizontal Field of View (mm):

5

Disclaimer: Values represent theoretical values from lens design software. Actual lens performance varies due to manufacturing tolerances.

Frequently Purchased Together

Explore our developer-friendly HTML to PDF API Printed using PDFCrowd HTML to PDF

#33-306 - 35mm UC Series Fixed Focal Length Lens

S$342.00

Qty

Sales & Expert Advice

or view regional numbers

LIVE CHAT

EMAIL

Easy-to-Use

QUOTE TOOL

enter stock numbers to begin

Sign-up Today // industry trends, new products, discounts, and technical content

SIGN-UP NOW

Company

Executive Team

Our Locations

Explore our developer-friendly HTML to PDF API Printed using PDFCrowd HTML to PDF

We are Hiring! Apply Now »

Copyright 2024, Edmund Optics Singapore Pte. Ltd, 18 Woodlands Loop #04-00, Singapore 738100

The **FUTURE** Depends On Optics®

;

Explore our developer-friendly HTML to PDF API Printed using PDFCrowd HTML to PDF