

morie: multi-domain open research and inferential estimation in r

vansh f Singh ruhela 
university of Toronto

abstract

The R package morie (multi-domain open research and inferential estimation) implements a curated dual-language toolkit for observational inference, with explicit support for the `mrnj` (multilevel reconciliation methodology) framework as a sociolegal application target. The package provides a unified entry point to double-machine-learning interactive regression and partial-linear estimators by wrapping the `doubleml` package (Bach et al. 2024) via the `mlr3` learner ecosystem (Lang et al. 2019). It provides independent implementations of inverse-probability-weighting, augmented inverse-probability-weighting, propensity-score matching, survey-weighted estimation, signal processing primitives (Butterworth, Javitzky–Yolay, Higuchi fractal dimension), spatial statistics, statistical physics of crime (Hawkes processes, reaction–diffusion), psychometric classical-test-theory and item-response-theory estimators, and a suite of `mrnj` modules for ingestion of Canadian open carceral data. The package is released on the Comprehensive R Archive Network (CRAN) and via R-universe at hadesllm.r-universe.dev/morie. This paper describes the architecture of the R implementation, the wrapper `ai` around `doubleml`, and three reproducible examples drawn from the open Ontario, federal, and Toronto Police Service records that the `mrnj` framework integrates.

Keywords: causal inference, observational inference, double machine learning, sociolegal statistics, Hawkes process, psychometrics, R.

i. introduction

The R package morie provides a curated multi-domain toolkit for observational inference. The R package is released under `GPL-3.0-only` to match the R-ecosystem and CRAN convention; the companion Python package (ruhela 2025) is dual-licensed under `MIT` or `Apache-2.0` (the Rust-ecosystem convention) so downstream Python users are not forced into copyleft. The package supports a unified estimator interface for the average treatment effect ($\alpha\theta\epsilon$), the average treatment effect on the treated ($\alpha\theta\theta$), the conditional and group average treatment effects ($\epsilon\alpha\theta\epsilon$, $\gamma\alpha\theta\epsilon$), the local average treatment effect ($\lambda\alpha\theta\epsilon$), and the augmented inverse-probability-weighting (`ai`) estimator. Double machine learning is exposed through wrappers around the `doubleml` classes (Bach et al. 2024), which in turn rely on the `mlr3` ecosystem (Lang et al. 2019) for the nuisance-function learners. Outside causal inference, the package provides signal processing primitives, cryptographic primitives, spatial statistics, statistical-physics models of crime, and psychometric estimators that complement the causal-inference core.

morie is positioned alongside the established r ecosystem of causal-inference packages: `doubleml` itself (Bach et al. 2014) for the canonical double-machine-learning estimators, `matchit` for matching, `survey` for design-based estimation, `hdm` for high-dimensional post-selection inference (chernozhukov et al. 2010), `grf` for forest-based heterogeneous treatment effects, and `aiw` for augmented inverse-probability weighting. The package does not duplicate these established estimators where they already exist in the canonical r stack; instead, it wraps them under a single function-naming convention and pairs them with the `mrnj` modules that target canadian open carceral and police-oversight data.

The `mrnj` modules implement the unified framework of `ruhela` (Ahlborg) for analysis across five canadian sources: the ontario tracking information system (otis, ahi-rd8), the federal structured intervention unit implementation advisory panel, the ontario special investigations unit (siu), the toronto police service (tps) open data, and the federal corrections and conditional release statistical overview. The framework's theoretical foundations are presented in `ruhela` (Ahlborg); this paper concerns its r software realisation.

The companion paper (Ahlborg) describes the python implementation, which is functionally parallel to the r implementation under a different idiomatic api.

The rest of the paper is organised as follows. Section 2 demonstrates installation and a motivating example. Section 3 surveys the module taxonomy. Section 4 describes the `mrnj` modules. Section 5 contrasts the functional and object-oriented apis and documents the `morie_result` return type. Section 6 documents the wrapper architecture around `doubleml`. Section 7 works three reproducible examples on the ontario, federal, and tps data. Section 8 catalogues the twelve empirical-workflow callables added in `vu.i.ie`. Section 9 catalogues the `ave` textbook-derived callables that ship in `morie.fn` across fourteen suites in `vu.v.i` and `vu.v.ii`. Section 10 reports a simulation study. Section 11 concludes.

1. getting started

1.1. installation

The released morie package is available on cran:

```
r> install.packages('morie')
```

nightly linux, macOS, and windows binaries are built by r-universe (Jooms Ahlborg) from the yitfub source tree and can be installed from the project's r-universe page:

```
r> install.packages('morie',
+   repos = c(hadesslm = 'https://hadesslm.r-universe.dev',
+             cran     = 'https://cloud.r-project.org'))
```

The development version is installable from yitfub:

```
r> remotes::install_github('hadesslm/morie',
+   subdir = 'r-package/morie')
```

the package depends on `r` 4.3.0 or later and declares `stats` and `utils` as hard dependencies; the `double-machine-learning`, `survey`, `matching`, and `signal-processing` dependencies are declared under `suggests` to keep the base installation lightweight.

A.A. a motivating example

The motivating example uses the open `otis` `r`cd`d` record to estimate the average treatment effect of an indicator of high alert complexity on placement-volatility outcomes in the ontario restrictive-confinement system.

```
r >- library('morie')
r >- data %>% otis::load_rccd(year = 2018)
r >- head(data)
```

The treatment variable is constructed by thresholding the `alert_count` covariate at the population median. The outcome is a count of placement transitions within the fiscal year.

```
r >- data$do %>% as.integer(data$alert_count >= median(data$alert_count))
r >- result %>% estimate_irm(
+ y = 'placement_transitions',
+ d = 'do',
+ x = c('age_band', 'gender', 'regional_cluster'),
+ data = data)
r >- print(result)
```

The `estimate_irm()` wrapper composes an `mlr3` regression learner (`lrn('regr.lm')`) and a classification learner (`lrn('classif.log_reg')`) and passes them to `doubleml::doubleml_irm`. The returned object is a `richresult` (section 3) that prints a multi-section interpretation alongside the point estimate, standard error, and confidence interval.

3. module taxonomy

The `morie` `r` interface organises functionality into eight thematic groups.

3.1. causal inference

The `causal-inference` group provides the average-treatment-effect estimator family: `estimate_att()`, `estimate_atc()`, `estimate_aipw()`, `estimate_cate()`, `estimate_gate()`, `estimate_late()`, `estimate_irm()`, and `estimate_plr()`. The first four are independently implemented in pure `r` using the identifying assumptions described in [ruhela \(2020\)](#); the latter four wrap `doubleml` as detailed in section 4.

3.2. survey sampling and weights

The `survey` group provides `calculate_ipw_weights()`, `calculate_ebac()` (the `uidmark` blood-alcohol-content estimator used by `health canada` survey instruments), and wrappers for survey that expose design-based standard errors under stratified and cluster sampling.

3.3. signal processing

The signal-processing group provides `buttlp()`, `butthp()`, `buttbp()`, `buttbbs()` (butterworth filters), `sgolay_smooth()` (savitzky--golay smoothing), `hurst_r()` (hurst exponent by r/f analysis), `hfd()` (higuchi fractal dimension), and `pcg_filter()` (phonocardiogram band-pass).

3.4. spatial statistics

The spatial group provides `moran_i()`, `geary_c()`, and the kernel-density and ripley-k wrappers used by the `mrnj` spatial-temporal modules.

3.5. statistical physics of crime

This group provides hawkes process maximum-likelihood fits (`fit_hawkes()`, exponential, gamma, weibull and lomax kernels under both constant and sinusoidal baselines), the reaction--diffusion intensity-field estimator, the lévy-flight displacement model, and the lotka--volterra police--crime dynamics estimator ([mohler et al. 2011](#), [ruhela 2020a](#)).

3.6. psychometrics

The psychometrics group provides classical-test-theory estimators (`cronbach_alpha()`, `mcdonald_omega()`, `kuder_richardson()`) and item-response-theory estimators (i2l, 12l, 32l rasch family).

3.7. cryptography

The cryptography group provides reference implementations of `ml-keccak`, `ml-sha3`, `ml-rs`, and hybrid post-quantum primitives. These are intended for educational use and are not audited for production deployment; the package's `security.md` documents this status explicitly.

3.8. investigation utilities

The investigation-utility group provides `compare_nested_logistic_models()` (likelihood-ratio test across nested specifications), `run_treatment_effects_analysis()` (end-to-end $\alpha\theta\epsilon/\alpha\theta\theta/\epsilon\alpha\theta\epsilon/\gamma\alpha\theta\epsilon$ estimation pipeline), `run_weighted_logistic_analysis()` (survey-aware logistic regression via survey), and `inspect_output()` (audit-trail inspection of result objects).

4. the `mrnj` modules

The `mrnj` modules in `morie` implement the framework of [ruhela \(2020c\)](#) as a coordinated set of estimators on the five canadian sources. Each `mrnj` module is exposed by an `mrnj_*` prefixed function: `mrnj_otis_load()`, `mrnj_siu_scrape()`, `mrnj_tps_load()`, `mrnj_classify_mandela()`, `mrnj_chia_doob()`, and `mrnj_hawkes_tps()`. The functions handle source-specific schema reconciliation through the canonical fiscal-quarter index of [ruhela \(2020c\)](#) and emit data objects that the estimator-family functions of section 3 consume directly.

5. functional and object-oriented apis

morie exposes both a functional API (the `morie::estimate_*` family of free functions) and an object-oriented API (an R `moriefit` class that internally orchestrates estimator selection, nuisance estimation, and result reporting). The functional API is the canonical entry point for one-shot analyses; the object-oriented API is provided for composable pipelines that benefit from inspection of intermediate state.

3.1. The `morie_result` return type

every estimator in morie returns a `morie_result` JS object, an R list with class attribute 'morie_result' that populates itself with the canonical result fields (`estimate`, `se`, `ci_lower`, `ci_upper`, `p_value`, `n`, `n_treated`, `interpretation`). The JS dispatch pattern provides two simultaneous use modes: a returned `morie_result` satisfies `is.list(result)` (so results can be passed to any list-consuming downstream code), and `result$estimate` returns the typed point estimate (so users index by name when appropriate). The multi-section pretty-printer `print.morie_result` renders the result as a panel of labelled fields when called interactively; when used programmatically, the result behaves as an ordinary named list. This mirrors exactly the `richresult` dataclass in the Python sibling ([ruhela 2020b](#)), so a researcher who learns one side of the package has acquired the other side's idiom for free.

3.2. `describe()`

every callable in morie that returns a `morie_result` has a paired `describe_callable.md` pedagogical narrative shipped in `inst/extdata/describe/`. The `morie_describe()` function loads and prints the relevant narrative for a given callable:

```
R> morie_describe(morie::estimate_irm)
```

The describe-output convention is documented in the package's design paper at the repository.

4. wrapper architecture for `doubleml`

morie layers a thin function-style interface over `doubleml`'s class-based interface. where `doubleml` exposes `doubleml$new(data, ml_g, ml_m, ...)` with a data backend and two mlr3 learners as separate arguments, `morie::estimate_irm()` accepts a single data frame, column names for the treatment, outcome, and covariates, and an optional learner specification with sensible defaults.

The default learners for `estimate_irm()` are `lrn('regr.lm')` (linear regression for the outcome nuisance) and `lrn('classif.log_reg')` (logistic regression for the propensity nuisance), chosen for the absence of additional dependencies. users who require flexible non-parametric nuisance estimation pass alternative mlr3 learners directly:

```
R> result <- estimate_irm(
+   y      = 'y', d = 'd', x = c('x1', 'x2', 'x3'),
+   data   = df,
+   ml_g   = mlr3::lrn('regr.ranger', num.trees = 200),
+   ml_m   = mlr3::lrn('classif.ranger', num.trees = 200),
+   n_folds = 5, n_rep = 1)
```

The wrapper performs three additional services beyond the `doubleml` class call. First, it harmonises the result object to a `richresult` that prints a multi-section interpretation with verbose interpretation under a uniform format. Second, it audits learner-result quality through cross-validation R^2 and β -prior-score diagnostics. Third, it surfaces both the $\alpha\theta$ and the $\alpha\theta\theta$ in a single call rather than requiring a separate `score = 'alpha theta'` parameterisation.

The wrapper preserves the full `doubleml` class instance under `result$doubleml` for users who require direct access to sample splits, bootstrap statistics, or the underlying psi-score arrays.

8. reproducible examples

Three reproducible examples illustrate the package’s use across the `mrnj` source set.

8.1. example 1: alert complexity and placement volatility (`o1f`)

The first example revisits the motivating example of section 4 under three estimators (`rw`, `aiw`, `rm-dml`) and reports the consistency of point estimates across estimators as evidence of identification robustness. Following the `mrnj` identification strategy ([ruhela 2023](#)), the propensity score conditions on age band, gender, regional cluster, and fiscal-year fixed effects; the outcome regression conditions on the same covariates.

8.2. example 2: replication of the `fprott--doob` chi-squared record

The second example replicates the published χ^2 statistics from [fprott and doob \(2023\)](#) on the federal `fr` aggregate record. The `mrnj mrm_chi2_doob()` function consumes the published contingency tables and reproduces every reported χ^2 statistic to within 0.01.

8.3. example 3: hawkes self-exciting process on `o2f` major crime

The third example fits the hawkes self-exciting specification of [ruhela \(2023\)](#) to the `toronto` Police Service open-data major-crime event series. The markovian (exponential kernel, constant baseline) and a fat-tailed non-markovian (`lmax` / power-law kernel, sinusoidal baseline) specifications are fit by maximum likelihood under the `jumba-jit`’d $O(n)$ recursive likelihood for the exponential kernel and the parallel $O(n^2)$ `jit` path for non-markovian kernels (new in morie `v0.1.1`), and the akaike-information-criterion selection between them is reported. The branching ratio $\hat{\eta}$ and the time-rescaling goodness-of-fit `kolmogorov--smirnov` p -value are reported alongside. On the canonical `o2f` assault `lme` contiguous one-year window ($n = 21,160$ events), the markovian fit attains $\hat{\eta} = 0.567$, $\hat{\beta} = 3.854/\text{day}$, and $\text{BFP} = 0.494$; the `exp/sin` model improves `AIC` by 27.7 (decisive on the standard $\Delta\text{AIC} > 10$ rule) to $\hat{\eta} = 0.510$, $\text{BFP} = 0.332$; and `lmax/sin` lands at $\hat{\eta} = 0.513$, $\text{BFP} = 0.298$ --- 3.9 `AIC` worse than `exp/sin` (one extra parameter, no likelihood gain). The substantive finding for `o2f` assault `lme` is that non-stationarity (sinusoidal baseline) dominates non-markovianity (kernel shape); a richer kernel does not pay its parameter cost on this data.

9. simulation study

A simulation study under the partially-linear data-generating process of [chernozhukov et al.](#)

([Auhio](#)) compares the `estimate.irm()` wrapper’s coverage and bias under three nuisance-learner choices: linear (`regr.lm`, default), lasso (`regr.cv_glmnet`), and random-forest (`regr.ranger`). The simulation uses $n = 500$ observations and $p = 20$ covariates, with the propensity score depending on the first three covariates and the outcome regression depending on the first six. The true treatment effect is $\theta_0 = 0.5$. Each setting is replicated 500 times.

coverage at the nominal 95% level is recovered by all three learner choices to within ± 1 percentage point; bias is < 0.01 for the linear and lasso learners and < 0.03 for the random-forest learner under default hyperparameters. The sample-splitting fold count $K = 5$ and the repetition count $R = 2$ that `morie`’s wrapper sets as defaults are confirmed adequate for $n = 500$.

e. empirical workflow callables added in `v4.1.12`

version `v4.1.12` ships twelve new exported callables that compose into the empirical workflow used by the companion empirical paper ([ruhela 2024](#)). They are documented here for completeness; every function has full `r` + `Python` parity (the `Python` side is described in the `morie Python` paper, this volume).

`otif` suite. Five callables operate on the Ontario Tracking Information System public release. `mrmsclassifymandela()` (introduced in `v4.1.11`) classifies placements under the United Nations Mandela rules with three denominator conventions (row, individual, any, individual, cumulative). `mrmsotisplacementconcentration()` expands the bare banded per-individual placement counts via band midpoints and reports the fill-mde Pareto exponent, the yini coefficient, and the top- k concentration share within each fiscal year and pooled. `mrmsotissegdurationkm()` returns a Kaplan-Meier summary of numberconsecutive days segregation with optional alert-flag stratification and a fraction-above-mandela-threshold column. `mrmsotismortificationcooccurrence()` computes pairwise Cramér’s V across the three bare alert flags (mentalhealth_alert, suiciderisk_alert, suicidewatch_alert). `mrmsotisregionlocality()` constructs the region_attimeofplacement $\times$ region_mostrecentplacement contingency table and reports the chi-square statistic, Cramér’s V , and the diagonal share (within-region staying).

`otj` suite. Four callables operate on Toronto Police Service open-data crime events. `mrmstpslevyscaling()` fits a fill-mde Pareto exponent to the haversine inter-incident step lengths. `mrmstps Moranclustering()` grids the lat/long extent into a coarse raster, counts events per cell, and reports the global Moran’s I z-score together with a `dfscap` summary at $\varepsilon = 0.3$ km. `mrmstpsneighbourhoodrecurrencekm()` returns a per- `fill-mde` Kaplan-Meier summary of inter-event gap days. `mrmstps kulldorffscan()` implements kulldorff’s `ispy` Poisson log-likelihood-ratio space-time scan ([kulldorff 1998](#)) with a Monte-Carlo permutation test for significance over $r \in \{1, 2, 3, 5, 8\}$ km candidate radii.

`frs` suite. Three callables operate on Ontario Special Investigations Unit case-level data. `mrmsiu case to decision km()` reports a Kaplan-Meier summary of the gap from `date_of_incident_iso` to `date_of_director_decision_iso` per `police_service`, with right-censoring of open cases. `mrmsiu per service rate()` cross-tabulates cases by service and year.

`mrmsiuoutcomeclassifier()` tabulates the director’s decision categories per service. unlike `o01f` (which re-assigns its `uniqueindividualid` each fiscal year via the `YYYY-XXXXXX-fy` format and therefore admits no cross-year tracking) and `02f` (which exposes no offender identifier by design), `fiu` provides per-case dates with a stable jurisdiction identifier and so admits a valid time-to-outcome analysis: the canonical example is the gap from `date_of_incident_iso` to `date_of_director_decision_iso` per `police_service`, which our verification gives as 120 days (pooled, $n = 1,711$).

longitudinal simulator. one callable, `moriesimulatelongitudinalpanel()`, ties a synchronised `rng`, a `var(L)` coefficient array with stationarity-preserving spectral constraints, and structured-covariance multivariate normal draws into a tidy long-format panel. this is a clean-room implementation of standard methods from [fahamilton \(1997\)](#) and [diggle et al. \(1997\)](#).

dataset access paths. the empirical-workflow callables are paired with three on-demand dataset fetchers so the callables work out of the box without manual data wrangling: `o01f` via the ontario data catalogue `eb07` endpoints (resource ids are baked into `moriedatasetcatalog()` for `au1`, `bu1`, `bu0` and `cu1`), `02f` via an `arcy1f r0f0` fetcher (`moriefetchtps()`, nine public categories), and `fiu` via `moriefetchsiu()`, which scrapes the public director’s reports site on demand. four small reference samples ship in `inst/extdata/` so the worked examples and the `testthat` suite run offline.

animated demo. a user can confirm the package is actually doing work, in the same way `doublem0` and the `optuna` training `ui` do, by running `python -m morie.demo` after installing the `python` sibling. the `r`-only equivalent prints per-step progress to the console via the `cli` package.

ii. textbook-derived callables in `morie.fn`

beyond the causal-inference core and the empirical-workflow callables of section 9, `morie` ships a curated catalogue of `146` textbook-derived callables, organised into fourteen thematic suites under the `morie.fn` namespace. each suite implements a coherent slice of a canonical reference text in statistics, machine learning, or signal processing: together they form a pedagogical-and-applied corpus that complements the wrapper functions documented above. the design philosophy is uniform: where a battle-tested library exists on either side of the `r/python` divide, the suite calls into it (`spdep`, `gstat`, `survival`, `forecast`, `rugarch`, `signal`, `kernlab` on the `r` side; `scipy`, `statsmodels`, `scikit-learn`, `pywavelets` on the `python` side), where the operation is light enough that a library would introduce more weight than logic, the suite uses base `r` matrix and vector primitives (or `numpy` on the `python` side) directly. all `146` callables were verified for `r + python` parity at the `vu.3.0` release (see the package `NEWS` file). the fourteen suites are enumerated in table i, with the short module mnemonic that fixes the namespace, the number of callables shipped, the canonical reference textbook, and one representative `r` wrapper as illustration.

ii.i. naming convention

jsuite	<i>n</i>	reference	rep
schabenberger	ΛΗ	fchabenberger and yotway (ΛΗΗΘ)	sptau
kosorok	ΛΗ	kosorok (ΛΗΗΘ)	kosorok
ml_foundations	ΛΗ	mohri et al. (ΛΗΙΘ) • fiastie et al. (ΛΗΗΘ)	linear
ghosal	ΛΗ	ghosal and van der vaart (ΛΗΙΥ)	ghos
horowitz	ΛΗ	horowitz (ΛΗΗΘ)	horowitz
montesinos	ΛΗ	montesinos-lópez et al. (ΛΗΛΛ)	global
armstrong	ΛΗ	armstrong et al. (ΛΗΙΥ)	idea
deep_learning	ΛΗ	goodfellow et al. (ΛΗΙΘ)	forward
missing_stats	ΛΗ	ingc / copulas / evθ	bootstrap
llm_arch	ΛΗ	vaswani et al. (ΛΗΙΥ) • dao et al. (ΛΗΛΛ) • fu et al. (ΛΗΛΙ) • zhang and jennrich (ΛΗΙΘ)	bootstrap
fauzi	ΙΘ	fauzi (ΛΗΙΘ)	fauzi
gibbons_remaining	ΛΗ	gibbons and chakraborti (ΛΗΙΥ)	tolerance
rangayyan	ΛΗ	rangayyan (ΛΗΙΘ)	random
time_series_advanced	ΛΗ	fyndman and athanopoulos (ΛΗΙΘ) • tsay (ΛΗΙΗ)	gar

table i: The fourteen textbook-derived suites in morie.fn. Total: ΛΥΘ callables, all with r+Python parity verified at v4.3.4. The missing_stats label is a v4.4.1 artefact: the spec covers resampling, quasi-monte-carlo, copula, and extreme-value-theory material, not missing-data methods proper; a true missing-data spec is deferred to v4.3.x.

each suite occupies a four-to-seven-character mnemonic namespace. on the r side every callable is exported under both its compact mnemonic and its full descriptive name: in the schabenberger suite, for instance, both sptau() and spatial_autocorrelation() resolve to the same function, because the full-name binding is created by spatial_autocorrelation ~ sptau. The mnemonic matches the spec name field of the originating formula-index jf3j and the descriptive binding matches the full_name field, so a user can locate the originating specification and the cross-language sibling without guessing. The Python sibling uses the longer form morie.fn.~short~.~full_name~(...) as documented in [ruhela \(ΛΗΛΘΘ\)](#).

4.4. Caveats and v4.3.x deferrals

numerical agreement between the r and Python sides is bit-identical for deterministic callables: the closed-form 34f and 7ca in ml_foundations, moran’s *I* and ordinary kriging in schabenberger, the analytic attention and softmax operators in llm_arch, and similar. For stochastic callables (bootstrap and jackknife in missing_stats, random-forest and gradient-boosting ensembles, mcmc posteriors in ghosal, the bayesian-inference paths in time_series_advanced), agreement is within monte-carlo tolerance under matched random-number seeds. The r smoke suite confirms that all 310 r files in the source tree source cleanly under base r with only the declared fuggests: optional packages installed; the Python smoke runs the __main__ canonical-test block in every shipped module. Three honest deferrals carry over from the v4.4.1 tracker: an opt-in deterministic mode for the stochastic callables, a true missing-data suite to replace the misnamed missing_stats spec, and a tighter cross-language mcε-tolerance pin for the γarεfi/εγarεfi and bayesian fits where the two language ecosystems’ optimiser defaults differ.

ii. conclusion

the r package morie provides a curated multi-domain toolkit for observational inference, with explicit support for the mrm framework as a sociolegal application target. the wrapper architecture around doubleml offers a thin function-style api; the eight thematic groups provide a unified namespace for the broader observational-inference, signal-processing, spatial, statistical-physics, and psychometric routines that complement the causal core. the mrm modules implement the framework of [ruhela \(2023\)](#) on the five canadian sources through a common ingestion pipeline.

the r package is released on cran and via r-universe under gpl-3.0-only (matching the r-ecosystem convention); the companion python package is released on pypi under m0 or apache-2.0 (the rust-ecosystem convention) so that downstream users in either language are not forced to adopt the copyleft of the other. the linux kernel module (kernel-module/morie.c) ships under gpl-3.0-only (the kernel api requirement); papers and documentation are cc-by-nc. the full per-component breakdown is in [licensing.md](#) at the source repository <https://github.com/hadesllm/morie>. contributions follow the process documented in [contributing.md](#).

acknowledgements

the author thanks ylen ncamara for distribution-theory mentorship that grounds the per-individual estimator ensemble; professor angela zorro medina for the methodological lineage of the framework’s identification strategy; jeroen ooms for maintaining the r-universe infrastructure on which the morie nightly binaries are built; and the doubleml team (philipp bach, malte f. wurz, victor chernozhukov, martin spindler, jven blaassen) for the β -3-clause double-machine-learning library on which the package’s mrm and π wrappers are layered.

references

- armstrong da, bakker r, carroll r, fiare c, foole w, rosenthal h (2023). analyzing spatial models of choice and judgment. chapman & hall/crc, boca raton, fl.
- bach p, wurz mf, chernozhukov v, spindler m, blaassen j (2024). “doubleml: an object-oriented implementation of double machine learning in r.” journal of statistical software, 88(3). doi:10.18637/jss.v088.i03.
- chernozhukov v, chetverikov d, demirer m, duflo e, hansen c, newey w, robins j (2020). “double/debiased machine learning for treatment and structural parameters.” the econometrics journal, 23(1), 1–68.
- chernozhukov v, hansen c, spindler m (2020). “hdm: high-dimensional metrics.” r journal, 12(1), 108–119.
- dao t, fu dy, ermon j, rudra a, ré c (2023). “flashattention: fast and memory-efficient exact attention with w-awareness.” in advances in neural information processing systems 36 (neurips 2023).

- diggle P, Liang KY, Zeger SL (1994). analysis of longitudinal data. oxford university Press, oxford.
- Fauzi R (2018). kernel-type estimators in nonparametric inference. Springer.
- Ghosal J, van der Vaart A (2017). fundamentals of nonparametric Bayesian inference. Cambridge university Press, Cambridge.
- Gibbons JD, Chakraborti J (2014). nonparametric statistical inference. 8th edition. Chapman & Hall/CRC, Boca Raton, FL.
- Goodfellow I, Bengio Y, Courville A (2016). Deep Learning. MIT Press, Cambridge, MA.
- Hamilton JD (1994). Time series analysis. Princeton university Press, Princeton, NJ.
- Hastie T, Tibshirani R, Friedman J (2009). The elements of statistical learning: data mining, inference, and Prediction. 2nd edition. Springer, New York.
- Horowitz JL (2009). Semiparametric and nonparametric methods in econometrics. Springer, New York.
- Hyndman RJ, Athanasopoulos G (2018). forecasting: Principles and Practice. 2nd edition. John Wiley, Melbourne, Australia.
- Kosorok MR (2008). introduction to empirical Processes and semiparametric inference. Springer, New York.
- Kulldorff M (1991). “A spatial scan statistic.” Communications in Statistics: theory and methods, 20(1), 1-16. doi:10.1080/01621459.1991.10476319.
- Lang M, Binder M, Richter J, Schratz P, Pfisterer F, Coors J, Gu Y, Casalicchio G, Rothhoff A, Bischl B (2018). “mlr3: A modern object-oriented machine learning framework in R.” Journal of open source software, 4(14).
- Mohler G, Short M, Brantingham P, Schoenberg P, Bita G (2011). “Self-exciting point process modeling of crime.” Journal of the American Statistical Association, 116(532), 1001-1014.
- Mohri M, Rostamizadeh A, Elwolkar A (2018). foundations of machine learning. 2nd edition. MIT Press, Cambridge, MA.
- Montesinos-López CA, Montesinos-López A, Grossa J (2018). multivariate statistical machine learning methods for genomic Prediction. Springer, Cham, Switzerland.
- oms J (2018). “The r-universe: A package distribution system for R.” arXiv preprint arXiv:1810.00194.
- Rangayyan R (2018). Biomedical signal analysis. 3rd edition. Wiley-IEEE Press, Hoboken, NJ.
- Ruhela V (2018). “Criminological Hawkes Process via morie: Markovian and non-Markovian self-exciting Point Processes for Toronto crime.” doi:10.26434/zenodo.2411110.
- Ruhela V (2018). “morie: multi-domain open research and inferential estimation in Python.” doi:10.26434/zenodo.2411110.

ruhela vj (ΛΗΛΒC). “the framework: multi-source statistical foundation for canadian carceral, police, and oversight data.” [doi:10.21203/rs.3.rs-1111111/v1](https://doi.org/10.21203/rs.3.rs-1111111/v1).

ruhela vj (ΛΗΛΒD). “the framework on ontario carceral, toronto police, and ju data: empirical companion to morie.” in preparation; see papers/morie-empirical-paper/ in the morie repository, url <https://github.com/hadesllm/morie>.

schabenberger c, yotway ca (ΛΗΗE). statistical methods for spatial data analysis. chapman & hall/crc, boca raton, fl.

spott jβ, doob aj (ΛΗΛ3). “the (non-)use of structured intervention units in canada: concerns about implementation.” canadian journal of criminology and criminal justice, v6(i).

ju j, lu y, fan j, nartadha a, wen β, liu y (ΛΗΛi). “roformer: enhanced transformer with rotary position embedding.” arxiv preprint arxiv:2111.00137.

tsay rf (ΛΗiH). analysis of financial time series. 3rd edition. wiley, hoboken, nj.

vaswani a, shazeer n, Parmar n, uszkoreit j, jones l, yomez a, kaiser l, Polosukhin i (ΛΗiY). “attention is all you need.” in advances in neural information processing systems 31 (neurips 2018).

zhang β, jennrich r (ΛΗiΘ). “root mean square layer normalization.” in advances in neural information processing systems 31 (neurips 2018).

affiliation:

vansh singh ruhela
centre for criminology and sociolegal studies
university of toronto
14 queen’s park crescent west, toronto, on m5s 1a5, canada
e-mail: hadesllm@proton.me
orcid: 
ira: /vəʃ sɪŋ rʊˈfiːlə:/