

Introduction to RNNs

Outline

- Why Recurrent Neural Networks (RNNs)?
- The Vanilla RNN unit
- The RNN forward pass
- Backpropagation refresher
- The RNN backward pass
- Issues with the Vanilla RNN


Motivation

- Not all problems can be converted into one with fixed-length inputs and outputs
- Problems such as Speech Recognition or Time-series Prediction require a system to store and use context information
 - Simple case: Output YES if the number of 1s is even, else NO
1000010101 – YES, 100011 – NO, ...
- Hard/Impossible to choose a fixed context window
 - There can always be a new sample longer than anything seen


Recurrent Neural Networks (RNNs)

- **Recurrent Neural Networks** take the previous output or hidden states as inputs.
The composite input at time t has some historical information about the happenings at time $T < t$
- RNNs are useful as their intermediate values (state) can store information about past inputs for a time that is not fixed a priori


Sample Feed-forward Network




Sample RNN



Sample RNN




The Vanilla RNN Cell



$$h_t = \tanh W \begin{pmatrix} x_t \\ h_{t-1} \end{pmatrix}$$

The Vanilla RNN Forward




$$h_t = \tanh W \begin{pmatrix} x_t \\ h_{t-1} \end{pmatrix}$$

$$y_t = F(h_t)$$

$$C_t = \text{Loss}(y_t, GT_t)$$

The Vanilla RNN Forward



$$h_t = \tanh W \begin{pmatrix} x_t \\ h_{t-1} \end{pmatrix}$$

$$y_t = F(h_t)$$

$$C_t = \text{Loss}(y_t, \text{GT}_t)$$

----- indicates shared weights


Recurrent Neural Networks (RNNs)

- Note that the weights are shared over time
- Essentially, copies of the RNN cell are made over time (unrolling/unfolding), with different inputs at different time steps


Sentiment Classification

- Classify a restaurant review from Yelp! OR movie review from IMDB OR ... as positive or negative
- **Inputs:** Multiple words, one or more sentences
- **Outputs:** Positive / Negative classification
- “The food was really good”
- “The chicken crossed the road because it was uncooked”


Sentiment Classification




Sentiment Classification




Sentiment Classification




Sentiment Classification



Sentiment Classification



Sentiment Classification



Sentiment Classification




Image Captioning

- Given an image, produce a sentence describing its contents
- **Inputs:** Image feature (from a CNN)
- **Outputs:** Multiple words (let's consider one sentence)



: The dog is hiding

Image Captioning




Image Captioning





Image Captioning



RNN Outputs: Image Captions

A person riding a motorcycle on a dirt road.



Two dogs play in the grass.



A herd of elephants walking across a dry grass field.




A group of young people playing a game of frisbee.



Two hockey players are fighting over the puck.



A close up of a cat laying on a couch.



RNN Outputs: Language Modeling


VIOLA:

Why, Salisbury must find his flesh and thought
That which I am not aps, not a man and in fire,
To show the reining of the raven and the wars
To grace my hand reproach within, and not a fair are
hand,
That Caesar and my goodly father's world;
When I was heaven of presence and our fleets,
We spare with hours, but cut thy council I am great,
Murdered and by thy master's ready there
My power to give thee but so much as hell:
Some service in the noble bondman here,
Would show him to her wine.


KING LEAR:

O, if you were a feeble sight, the
courtesy of your law,
Your sight and several breath, will
wear the gods
With his heads, and my hands are
wonder'd at the deeds,
So drop upon your lordship's head,
and your opinion
Shall be against your honour.

Input – Output Scenarios



The Vanilla RNN Forward



$$h_t = \tanh W \begin{pmatrix} x_t \\ h_{t-1} \end{pmatrix}$$

$$y_t = F(h_t)$$

$$C_t = \text{Loss}(y_t, \text{GT}_t)$$

“Unfold” network through time by making copies at each time-step