



# BIOPRINTING TECHNIQUES

# Bioprinting Techniques and Materials

Bioprinting is a rapidly growing field that uses various techniques to produce three-dimensional (3D) structures and functional biological tissues for medical and scientific applications. The main objective of bioprinting is to mimic the structure and function of human tissues and organs, leading to the development of replacement parts for damaged or diseased organs.








Figure: Schematic representation of 3D bioprinting concept

---

# Comparison between 3D Printer and Bioprinter

The table provide a concise overview of the comparisons, advantages, and 3D printers and bioprinters.

limitations

Table: Comparison of '3D Printers' and 'Bioprinters'

| Aspect             | 3D Printers                                                                                                                                                        | Bioprinters                                                                                                                                                                         |
|--------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Printing Purpose   | General-purpose printing of objects                                                                                                                                | Fabrication of living tissues and organs                                                                                                                                            |
| Materials          | Plastics, metals, ceramics, resins, etc.                                                                                                                           | Bioinks ( <u>hydrogels</u> , extracellular matrices, <u>cell aggregates</u> , etc.)                                                                                                 |
| Applications       | Manufacturing, engineering, product design, architecture, etc.                                                                                                     | Regenerative medicine, tissue engineering, drug development, etc.                                                                                                                   |
| Printing Process   | Additive manufacturing, layer-by-layer deposition                                                                                                                  | Precise deposition of <u>bioinks</u> layer-by-layer                                                                                                                                 |
| Cell Compatibility | N/A                                                                                                                                                                | <u>Bioinks</u> must support cell viability and function                                                                                                                             |
| Challenges         | N/A                                                                                                                                                                | Development of suitable <u>bioinks</u> , cell viability,                                                                                                                            |
| Advantages         | Versatile, wide range of applications<br>Enables rapid prototyping<br>Cost-effective for non-biological objects                                                    | Potential for tissue and organ transplantation<br>Enables tissue engineering and regenerative medicine<br>Can create tissue models for studying diseases                            |
|                    |                                                                                                                                                                    | Potential for personalized medicine and drug testing                                                                                                                                |
| Limitations        | Limited ability to create functional living tissues<br>Limited choice of materials for certain applications<br>Lack of cell compatibility and tissue functionality | Complex and rapidly evolving technology<br>Challenges in developing suitable <u>bioinks</u> and scaling up<br><u>Vascularization</u> and long-term functionality of printed tissues |



(Note:

Cell viability refers to the ability of cells to remain alive and maintain their normal cellular functions.

Vascularization refers to the process of creating functional blood vessel networks within bioprinted tissues or organs)

## Bioprinting Materials

Bioprinting materials, also known as bioinks, are specifically designed to be compatible with living cells and provide a supportive environment for their growth and organization. Here are some examples of commonly used bioprinting materials:

### Hydrogels:

Hydrogels are water-based polymer networks that closely mimic the extracellular matrix (ECM) found in living tissues. They offer excellent biocompatibility, mechanical support, and can be formulated to have similar physical properties to native tissues. Examples of hydrogels used as bioinks include:

- Gelatin-based hydrogels
- Alginate hydrogels
- Fibrin-based hydrogels
- Collagen-based hydrogels

### Cell-laden Aggregates:

In some cases, cells are first aggregated into biomolecules and biomaterials (microtissues) before being incorporated into the bioink. These aggregates provide a physiological environment for the cells and enhance their viability and functionality.




Figure: Schematic representation of formation of cell aggregates


## Decellularized Extracellular Matrix (dECM):

The extracellular matrix (ECM) is a complex network of molecules surrounding cells in tissues and organs. It provides structural support, biochemical signaling, and regulatory functions.

The ECM of tissues can be extracted and processed to remove cellular components, resulting in a decellularized extracellular matrix (dECM). dECM bioinks contain natural signaling molecules and proteins that promote cell attachment, growth, and differentiation. Examples of dECM bioinks include:

- Decellularized porcine small intestine submucosa (SIS)
- Decellularized porcine or bovine dermis
- Decellularized amniotic membrane





I

Figure: Representing extracellular matrix in relation to epithelium, endothelium and connective tissue

## Synthetic Polymer-based Bioinks:

Synthetic polymers can be used to create bioinks with well-defined mechanical properties and degradation rates. These bioinks provide control over various parameters, such as stiffness, porosity, and degradation, to support specific tissue engineering goals. Examples of synthetic polymer-based bioinks include:

- Polyethylene glycol (PEG)-based bioinks
- Polycaprolactone (PCL)-based bioinks
- Poly(lactic-co-glycolic acid) (PLGA)-based bioinks

## Composite Bioinks:

Composite bioinks combine different materials to enhance the bioink's properties, such as mechanical strength, printability, and cell behavior. These bioinks often contain a combination of natural and synthetic materials or a mixture of different biomaterials. Exaples:

- Gelatin-methacryloyl (GelMA) combined with alginate
- Collagen combined with hyaluronic acid (HA)
- Fibrin combined with nanoparticles or growth factors

## Most Commonly used Bioprinting Techniques

Bioprinting techniques involve the precise deposition of bioinks to *create three-* dimensional structures with living cells. Several techniques have been developed to *accomplish* this, each with its own advantages and limitations. Here are some of the most commonly used bioprinting techniques:

### Inkjet-based Bioprinting:

Inkjet bioprinting works similarly to standard inkjet printing. The bioink is loaded into cartridges, and droplets of the bioink are ejected through fine nozzles onto a substrate. The droplets form layers, and the structure is built by depositing subsequent layers. Inkjet bioprinting allows for high-resolution printing and precise control over droplet size, but it may be limited by the viscosity of the bioink and cell viability during the ejection process.






Figure: representing inkjet-based bioprinting



## Extrusion-based Bioprinting:

Extrusion-based bioprinting uses a syringe or a similar mechanism to extrude the bioink through a nozzle. The bioink is deposited layer-by-layer to create the desired structure. This technique is versatile and can handle a wide range of bioinks with varying viscosities, including those with living cells or cell aggregates. It allows for high cell viability and can produce structures with controlled porosity. However, it may have limitations in achieving high resolution and complex geometries.




Figure: Representing extrusion based bioprinting



## Laser-assisted Bioprinting:

Laser-assisted bioprinting utilizes laser energy to precisely deposit bioinks onto a substrate. The bioink is placed on an energy-absorbing layer, and the laser creates a pressure wave that propels the bioink onto the substrate in a controlled manner. This technique offers high resolution, precision, and the ability to print complex structures. It can be used with delicate bioinks and allows for cell viability. However, laser-assisted bioprinting can be relatively slow and may have limitations in terms of bioink viscosity.




Figure: Representing the laser based bioprinting

## Microvalve-based Bioprinting:

Microvalve-based bioprinting employs microvalves to control the deposition of bioinks. The bioink is pushed through microchannels, and the microvalves open and close to release the bioink precisely. This technique provides control over droplet size, deposition speed, and spatial accuracy. It is suitable for a variety of bioink viscosities and can achieve high cell viability. However, the complexity of the system and the need for careful calibration can be limitations.




Figure: Representing microvalve based bioprinting

## Bioprinting with Solid Freeform Fabrication:

Solid Freeform Fabrication (SFF) combines bioprinting with traditional 3D printing methods. It involves the deposition of both bioink and supporting materials to create complex, multi-material structures. SFF techniques such as fused deposition modeling (FDM) or stereolithography (SLA) can be adapted to include bioinks and allow for the incorporation of living cells. This approach provides versatility in material selection and structural design but may require additional post-processing steps to remove supporting materials.




Figure: Representing fused deposition modeling




Figure: Representing stereolithography

## The Basic Steps of Bioprinting Process

### Preparation of the bioink:

The bioink used in bioprinting is a mixture of cells, growth factors, and other biological materials that are formulated to promote cell growth and tissue formation.



### Design of the tissue structure:

The tissue structure to be printed is designed using computer-aided design (CAD) software, which is then used to control the movement of the bioprinter's print head.



### Printing:

The bioprinter dispenses the bioink in a controlled manner, layer by layer, to build up the final tissue structure. The bioink is deposited in a manner that promotes cell survival and tissue formation.



### Incubation:

After printing, the tissue is incubated in a controlled environment, such as a cell incubator, to promote cell growth and tissue formation.

culture



### Assessment:

The printed tissue is assessed for its functional properties, such as cell viability, tissue structure, and tissue function.

I

The field of bioprinting is constantly evolving, and new techniques and materials are being developed to improve the accuracy and reliability of bioprinted tissues and organs.



## 5.2 3D Printing of Ear

3D printing has revolutionized the field of medicine, and one of its applications is the 3D printing of human ears. This process involves using a 3D printer to create an ear-shaped structure using a special material, such as a biocompatible polymer or a hydrogel, as the "ink." The printed ear structure is then seeded with human cartilage cells, which grow and develop into functional ear tissue over time.




Figure: Representing 3D printed ear

The main advantage of 3D printing an ear is that it allows for the creation of an ear that is custom-fitted to an individual patient, based on their specific ear shape and size. It is especially useful for children with congenital ear deformities or individuals who have suffered ear injuries or losses.

Additionally, 3D printing can also be used to create ears that are anatomically and functionally similar to a patient's normal ear, reducing the risk of complications associated with traditional surgical methods.

## Materials Used for 3D Printing of Human Ear

The material used for 3D printing of human ears can vary, depending on the specific technique used and the desired outcome. Some of the most commonly used materials for 3D printing of ears include:

### Hydrogels:

Hydrogels are soft, gel-like materials that are commonly used in bioprinting due to their ability to mimic the mechanical properties of human tissues. They can be used as the "ink" in 3D printing, providing a supportive structure for the cells to grow and develop into functional tissue. Examples of hydrogels used in 3D printing of ears include alginate, gelatin, and collagen. They have been used in the 3D printing of ear structures due to their ability to mimic the mechanical properties of human ear tissue.

### **Biocompatible polymers:**

Biocompatible polymers are synthetic materials that are compatible with human tissues and do not cause adverse reactions. They are commonly used as the "ink" in 3D printing of human ears because they provide a stable structure for the cells to grow and develop into functional tissue. **Polylactide (PLA):** Polylactide is a biocompatible polymer that has been used

in 3D printing of ear structures. This material is hydroxyapatite favored for its biocompatibility and ability to support cell growth.

### Scaffolds:

Scaffolds are structures that provide a supportive framework for the cells to grow and develop. In the case of 3D printing of ears, scaffolds can be used to create a specific shape or structure for the ear tissue to grow around.

### Cell-embedded materials:

Cell-embedded materials are materials that contain living cells, which can be used to seed the 3D printed structure. The cells then grow and develop into functional ear tissue over time.

### Ceramics:

Ceramics, such as hydroxyapatite, can be used in 3D printing of ear structures. This material is a natural component of human bones and has been shown to be biocompatible and effective in 3D printing of bones and other tissues.



# Technological Importance of 3D Printing of Human Ear

## Personalized ear prosthesis:

3D printing allows for the creation of customized ear prostheses that match the unique anatomy of each patient.

## Faster production and lower costs:

Traditional methods of ear prosthesis fabrication can be time-consuming and expensive. 3D printing can reduce the production time and cost of ear prosthesis.

## Biocompatibility:

I

3D printing can use biocompatible materials for the production of ear prostheses, reducing the risk of adverse reactions and improving patient outcomes.

## Medical education:

3D printing of human ears can be used to educate medical students and healthcare professionals on the anatomy and treatment of ear defects and injuries.



## 5.3 3D Printing of Bone

3D printing has revolutionized the field of medicine, and one of its applications is the 3D printing of bones. This process involves using a 3D printer to create a bone-shaped structure using a special material, such as a biocompatible polymer or a ceramic material, as the "ink." The printed bone structure can then be implanted into a patient to replace missing or damaged bone tissue.

There are two main approaches to 3D printing of bones: additive manufacturing and scaffold-based techniques. Additive manufacturing involves building up the bone structure layer by layer, whereas scaffold-based techniques involve creating a porous structure that provides a framework for bone cells to grow and develop.

I

### Additive manufacturing in 3D Printing of Bone

Additive manufacturing involves building up the bone structure layer by layer using biocompatible materials. The layer-by-layer deposition of material enables the creation of complex three-dimensional structures that mimic the natural bone tissue. The process of additive manufacturing in 3D printing of bone involves several key steps.

#### Steps involved in additive manufacturing of 3D Printed Bone

##### Patient Imaging:

The process begins with obtaining accurate imaging data of the patient's bone defect or the area requiring reconstruction. This is typically done using techniques like CT scans or MRI scans.



##### Digital Model Generation:

Using specialized software, the acquired imaging data is processed to create a three-dimensional digital model of the patient's bone structure. This digital model serves as the basis for designing the customized bone scaffold.



##### Scaffold Design:

With the digital model in place, the next step is to design the scaffold or implant. This involves determining the appropriate shape, size, and internal structure of the scaffold to match the patient's anatomy and specific requirements. Software tools are used to create the design, ensuring proper support, porosity, and structural integrity.



### **Material Selection:**

Biocompatible materials suitable for bone tissue engineering are chosen for the 3D printing process. These materials should be capable of supporting cell attachment, growth, and eventual bone regeneration. Common materials include biocompatible polymers, ceramic composites or biodegradable materials.



### **3D Printing Process:**

Once the scaffold design and material selection are finalized, the actual 3D printing process takes place. The chosen technique is used to build the scaffold layer by layer. The 3D printer precisely deposits or fuses the chosen material, following the digital model's specifications.



### **Post-processing:**

After the 3D printing is complete, post-processing steps may be required. This can include removing support structures, cleaning the scaffold, and performing any necessary surface treatments to enhance biocompatibility and optimize the scaffold's properties.



### **Sterilization:**

To ensure the implant is free from contaminants and ready for clinical use, the 3D printed bone scaffold undergoes sterilization using appropriate methods. Common techniques include autoclaving, ethylene oxide sterilization, or gamma irradiation.



### **Surgical Implantation:**

The final step involves the surgical implantation of the 3D printed bone scaffold into the patient. Surgeons carefully position the scaffold in the intended area, ensuring proper alignment and stability. Over time, the scaffold provides support for bone regeneration and integrates with the surrounding tissue.

## Scaffold-Based Techniques in 3D Printing of Bone

Scaffold-based techniques in 3D printing of bone refer to the use of three-dimensional scaffolds as a framework or template for the regeneration of bone tissue. These techniques involve the fabrication of biocompatible and biodegradable scaffolds using 3D printing technology, which can mimic the structure and properties of natural bone.

The scaffold serves as a temporary support structure that provides mechanical stability and guides the growth of new bone tissue. It offers a three-dimensional framework with interconnected pores that allow for cell infiltration, nutrient diffusion, and the deposition of extracellular matrix.



## Steps involved in scaffold-based 3D printing of bone

I

### Design:

A digital model of the desired bone structure or defect is created using computer-aided design (CAD) software. The design takes into account factors such as shape, size, pore architecture, and mechanical properties.



### Material Selection:

Biocompatible and biodegradable materials are chosen for the fabrication of the scaffold. Common materials include synthetic polymers, such as polycaprolactone (PCL) or poly(lactic-co-glycolic acid) (PLGA), and natural polymers, such as collagen or gelatin.



### 3D Printing Process:

The 3D printing process begins by loading the selected material into the 3D printer. The printer then deposits or solidifies the material layer by layer, following the digital design. The printing technology can vary, including extrusion-based methods, inkjet printing, or stereolithography.



### **Pore Formation:**

During the printing process, the scaffold is designed to have a porous structure with interconnected pores. These pores provide space for cell infiltration, nutrient supply, and vascularization. Various techniques can be used to control the pore size, distribution, and interconnectivity.



### **Post-Processing:**

After the scaffold is printed, post-processing steps may be performed to refine the scaffold's properties. This can include removing any support structures, sterilization, and surface treatments to enhance biocompatibility.



### **Cell Seeding and Culture:**

Once the scaffold is prepared, it can be seeded with bone-forming cells, such as mesenchymal stem cells or osteoblasts. The seeded scaffold is then cultured under appropriate conditions to promote cell attachment, proliferation, and the formation of new bone tissue within the scaffold.



### **Implantation:**

Once the scaffold-based construct has undergone sufficient maturation, it can be implanted into the patient's body. The scaffold provides structural support while the surrounding cells and blood vessels infiltrate and replace the scaffold with newly formed bone tissue. Over time, the scaffold degrades, leaving behind functional regenerated bone.



# Materials Used for 3D Printing of Bone

Materials used for 3D printing of bones can vary, depending on the specific 3D printing technique used and the desired outcome. Some of the most commonly used materials for 3D printing of bones include:

## Biocompatible polymers:

Biocompatible polymers are synthetic materials that are compatible with human tissues and do not cause adverse reactions. They can be used as the "ink" in 3D printing, providing a supportive structure for the cells to grow and develop into functional bone tissue. Examples: polyethylene, polycaprolactone, polylactide, and polyvinyl alcohol

## Ceramics:

Ceramics, such as hydroxyapatite, are natural components of human bones and can be used as the "ink" in 3D printing. Hydroxyapatite is a biocompatible material that has been shown to be an effective material for 3D printing of bones. Examples: Hydroxyapatite, Calcium phosphate, Tricalcium phosphate.

## Scaffolds:

Scaffolds are structures that provide a supportive framework for the cells to grow and develop. In the case of 3D printing of bones, scaffolds can be used to create a specific shape or structure for the bone tissue to grow around. Examples: Polyglycolic acid (PGA), Poly-L-lactic acid (PLLA), Polyethylene terephthalate (PET).

## Cell-embedded materials:

Cell-embedded materials are materials that contain living cells, which can be used to seed the 3D printed structure. The cells then grow and develop into functional bone tissue over time. Examples: Gelatine methacryloyl, Alginate. I

## 5.4 3D Printing of Skin

3D printing of skin refers to the process of creating three-dimensional human skin tissue using a 3D printer. The goal of 3D printing skin is to create functional, living tissue that can be used for a variety of purposes, such as cosmetic testing, wound healing, and drug development. The process involves the use of bioprinting technology, where a bioink made from living cells and growth factors is printed in a specific pattern to create the desired tissue structure.



Figure: Image of a 3D printed skin

### The Process of 3D Printing of Skin

The process of 3D printing skin typically involves the following steps:

#### Preparation of the bioink:

A bioink is made by mixing human skin cells, such as fibroblasts and keratinocytes, with a hydrogel matrix that provides a supportive environment for cell growth.



### **Design of the tissue structure:**

The tissue structure to be printed is designed using computer-aided design (CAD) software, which is then used to control the dispensing of the bioink.



### **Printing:**

The bioink is printed layer by layer using a 3D printer to create the desired tissue structure.



### **Incubation:**

After printing, the tissue is incubated in a controlled environment, such as a cell culture incubator, to promote cell growth and tissue formation.



### **Assessment:**

The printed tissue is assessed for its functional properties, such as cell viability, tissue structure, and tissue function.



## Materials used for 3D printing of Skin

### Hydrogels:

Hydrogels, such as alginate and collagen, are hydrophilic materials that can be used to create 3D structures for cell growth. These materials have been used in the 3D printing of skin due to their ability to mimic the mechanical properties and water-retaining capacity of human skin.

### **Polymers:**

Biocompatible polymers, such as polyethylene glycol and polycaprolactone, can be used in 3D printing of skin. These materials are synthetic and biocompatible, making them suitable for use in the creation of 3D printed skin structures.

### Cell-laden hydrogels:

Cell-laden hydrogels are materials that contain living cells and can be used to create 3D printed skin structures. The cells within the hydrogel will grow and develop into functional skin tissue over time.

### **Scaffolds:**

Scaffolds are structures that provide a supportive framework for cells to grow and develop. In the case of 3D printing of skin, scaffolds can be used to create a specific shape or structure for the skin tissue to grow around.

These materials can be used alone or in combination with other materials to create the desired structure and properties for 3D printing of skin. The choice of material will depend on



# Technological Importance of 3D Printing of Human Skin

## Better wound healing:

3D printing of skin can produce customized skin grafts that promote wound healing and reduce the risk of infection. This is particularly important for patients with burns, chronic wounds, or other skin injuries.

## Reduced scarring:

3D printed skin can promote more natural healing and reduce scarring, improving the cosmetic appearance of the skin after injury.

## Replication of skin structure:

3D printing can replicate the structure and properties of natural skin, such as the thickness and elasticity of different layers of the skin. This can improve the functionality and durability of the skin graft.

## Reduced donor site morbidity:

3D printing of skin can reduce the need for skin grafts from other parts of the patient's body, reducing donor site morbidity and promoting faster healing.

## Alternative to animal testing:

3D printing of skin can provide an alternative to animal testing in the cosmetic and pharmaceutical industries, reducing the ethical concerns and improving the accuracy and relevance of testing.

## Research and development:

3D printing of skin can be used in research and development to study the properties and behavior of different skin types, test the effectiveness of new treatments, and develop new skin care products.

## 5.5 3D Printed Foods

3D printed food refers to food items that are created using 3D printing technology. This technology allows for the creation of food items with intricate shapes and designs, which can be customized based on individual preferences and dietary needs. The process of 3D printing food involves the use of edible materials, such as pastes, gels, and powders, which are combined and printed layer by layer to create the final product.

The use of 3D printing in the food industry has the potential to revolutionize the way food is produced, as it allows for the precise control of portion sizes and ingredients, which can be beneficial for individuals with specific dietary needs or restrictions. Additionally, 3D printing technology can be used to create unique and customized food items that would be difficult to achieve using traditional cooking methods.



## Materials used for 3D Printing of Food

### Edible pastes:

Edible pastes, such as pureed fruit, chocolate, and cream cheese, can be used in 3D printing of food. These materials are easily printable and can be used to create intricate shapes and designs.

### Edible gels:

Edible gels, such as agar and gelatin, can be used in 3D printing of food. These materials are flexible and can be used to create 3D structures that are both aesthetically pleasing and functional.

### Edible powders:

Edible powders, such as flour and sugar, can be used in 3D printing of food. These materials can be combined with liquids to form a printable mixture that can be used to create 3D structures.



# Examples of 3D Printed Food

## Sweet and savory snacks:

3D printed snacks, such as crackers, cookies, and chips, can be customized to include intricate shapes and designs.

3D printing technology can be used to create intricate and aesthetically pleasing pastries, such as cakes and cupcakes.

## Decorative garnishes:

3D printing technology can be used to create unique and attractive garnishes for dishes, such as cheese and fruit designs.

## The importance of 3D printing in the food industry

3D printing has gained significant importance in the food industry due to its potential to revolutionize various aspects of food production, customization, and innovation. Here are some key reasons why 3D printing is important in the food industry:

### Customization and Personalization:

3D printing enables the creation of customized and personalized food products. It allows for the precise control of ingredients, textures, flavors, and nutritional content, catering to individual preferences, dietary restrictions, and specific nutritional needs. This customization capability opens up new possibilities for personalized nutrition and addressing food allergies, intolerances, and specific dietary requirements.

### Novelty and Creativity:

3D printing in the food industry allows for the creation of intricate and visually appealing food designs that are difficult to achieve with traditional food preparation methods. It offers the opportunity to experiment with shapes, structures, colors, and patterns, thereby enhancing the dining experience and presentation of food.



### **Enhanced Food Safety:**

With 3D printing, the entire food production process can be tightly controlled and automated, reducing the risk of contamination and human error. The technology allows for the use of fresh, high-quality ingredients and eliminates the need for excessive processing and preservatives. Additionally, 3D printing enables the production of food in a controlled, sterile environment, minimizing the potential for bacterial growth and contamination.

### **Supply Chain Efficiency:**

3D printing has the potential to streamline the food supply chain by enabling on-demand production. It eliminates the need for long-distance transportation and storage of certain food products, reducing food waste and improving overall efficiency. With 3D printing, food can be produced locally, minimizing the time and resources required for distribution.

### **Sustainable Food Production:**

3D printing has the potential to reduce food waste by using precise ingredient measurements and optimizing production processes. It allows for the utilization of alternative food sources and byproducts, reducing the strain on traditional food resources. Furthermore, 3D printing can promote sustainable farming practices by reducing water usage and minimizing environmental impact.

### **Food Innovation and Research:**

3D printing provides a platform for food scientists, chefs, and researchers to explore new culinary concepts, textures, and flavors. It facilitates the development of novel food products and techniques that push the boundaries of traditional food preparation. This innovation can lead to the creation of unique food experiences and contribute to advancements in the field of gastronomy.

---