

Weighted Average of Human Motion Sequences for Improving Rehabilitation Assessment

9th Workshop on Advanced Analytics and Learning on Temporal Data (AALTD),
ECML/PKDD 2024

Ali Ismail-Fawaz¹, Maxime Devanne¹, Stefano Berretti², Jonathan Weber¹
and Germain Forestier^{1,3}

¹IRIMAS, Université Haute-Alsace, Mulhouse, France


²MICC, University of Florence, Florence, Italy

³DSAI, Monash University, Melbourne Australia


November 10, 2024



Presentation Content



Task of Time Series Averaging



Task of Time Series Averaging

Time Series Averaging is a popular domain in machine learning, it can be used for: Time Series Clustering [1], Data Augmentation [2,3], Improving Nearest Neighbour classifier [4], etc.


Samples taken from the ECG5000 dataset.

- 📖 [1] Petitjean, François et al. "A global averaging method for dynamic time warping, with applications to clustering." *Pattern recognition* 2011.
- 📖 [2] Ismail Fawaz, Hassan, et al. "Data augmentation using synthetic data for time series classification with deep residual networks." *AALTD -ECML/PKDD* 2018.
- 📖 [3] Forestier, Germain, et al. "Generating synthetic time series to augment sparse datasets." *IEEE international conference on data mining (ICDM)* 2017.
- 📖 [4] Petitjean, François, et al. "Dynamic time warping averaging of time series allows faster and more accurate classification." *IEEE international conference on data mining (ICDM)* 2014.

Task of Time Series Averaging

Time Series Averaging is a popular domain in machine learning, it can be used for: Time Series Clustering [1], Data Augmentation [2,3], Improving Nearest Neighbour classifier [4], etc.

Set of Time Series from ECG5000 dataset




Samples taken from the ECG5000 dataset.

- [1] Petitjean, François et al. "A global averaging method for dynamic time warping, with applications to clustering." *Pattern recognition* 2011.
- [2] Ismail Fawaz, Hassan, et al. "Data augmentation using synthetic data for time series classification with deep residual networks." *AALTD -ECML/PKDD* 2018.
- [3] Forestier, Germain, et al. "Generating synthetic time series to augment sparse datasets." *IEEE international conference on data mining (ICDM)* 2017.
- [4] Petitjean, François, et al. "Dynamic time warping averaging of time series allows faster and more accurate classification." *IEEE international conference on data mining (ICDM)* 2014.

Task of Time Series Averaging

Time Series Averaging is a popular domain in machine learning, it can be used for: Time Series Clustering [1], Data Augmentation [2,3], Improving Nearest Neighbour classifier [4], etc.

Set of Time Series from ECG5000 dataset




Samples taken from the ECG5000 dataset.

- [1] Petitjean, François et al. "A global averaging method for dynamic time warping, with applications to clustering." *Pattern recognition* 2011.
- [2] Ismail Fawaz, Hassan, et al. "Data augmentation using synthetic data for time series classification with deep residual networks." *AALTD -ECML/PKDD* 2018.
- [3] Forestier, Germain, et al. "Generating synthetic time series to augment sparse datasets." *IEEE international conference on data mining (ICDM)* 2017.
- [4] Petitjean, François, et al. "Dynamic time warping averaging of time series allows faster and more accurate classification." *IEEE international conference on data mining (ICDM)* 2014.

Similarity Measure

Two Input Time Series




Samples taken from the ECG200 dataset.


-  [1] Müller, Meinard. "Dynamic time warping." [Information retrieval for music and motion 2007](#).
-  [3] Zhao, Jiaping, and Laurent Itti. "shapeDTW: Shape dynamic time warping." [Pattern Recognition 2018](#).

Similarity Measure

Two Input Time Series



DTW




Samples taken from the ECG200 dataset.



- [1] Müller, Meinard. "Dynamic time warping." *Information retrieval for music and motion* 2007.
- [3] Zhao, Jiaping, and Laurent Itti. "shapeDTW: Shape dynamic time warping." *Pattern Recognition* 2018.

Similarity Measure

Two Input Time Series




DTW



Samples taken from the ECG200 dataset.

- [1] Müller, Meinard. "Dynamic time warping." *Information retrieval for music and motion* 2007.
- [3] Zhao, Jiaping, and Laurent Itti. "shapeDTW: Shape dynamic time warping." *Pattern Recognition* 2018.


Similarity Measure



Samples taken from the ECG200 dataset.

- [1] Müller, Meinard. "Dynamic time warping." *Information retrieval for music and motion* 2007.
- [3] Zhao, Jiaping, and Laurent Itti. "shapeDTW: Shape dynamic time warping." *Pattern Recognition* 2018.

ShapeDBA: SOTA Averaging Method




Step 1:
Choose an initial
average: a random
series of the set


Sample taken from the Trace dataset.

 Ismail-Fawaz, Ali et al. " ShapeDBA: Generating Effective Time Series Prototypes using ShapeDTW Barycenter Averaging." *AALTD -ECML/PKDD* 2023.

ShapeDBA: SOTA Averaging Method




Step 2:
Find the ShapeDTW path
of the initial series
with all other series



Sample taken from the Trace dataset.

 Ismail-Fawaz, Ali et al. " ShapeDBA: Generating Effective Time Series Prototypes using ShapeDTW Barycenter Averaging." *AALTD -ECML/PKDD* 2023.

ShapeDBA: SOTA Averaging Method




Step 3:
Find for each time
stamp of the average
the barycenter value
with all its associates

Repeat from Step 2
until convergence

Sample taken from the Trace dataset.

 Ismail-Fawaz, Ali et al. " ShapeDBA: Generating Effective Time Series Prototypes using ShapeDTW Barycenter Averaging." *AALTD -ECML/PKDD* 2023.


ShapeDBA: SOTA Averaging Method



Sample taken from the Trace dataset.

 Ismail-Fawaz, Ali et al. " ShapeDBA: Generating Effective Time Series Prototypes using ShapeDTW Barycenter Averaging." [AALTD -ECML/PKDD 2023](#).

Human Motion Skeleton-Based Sequence




Human Motion Skeleton-Based Sequence



Sample taken from the HumanAct12 dataset

 Guo, Chuan, et al. "Action2motion: Conditioned generation of 3d human motions." *Proceedings of the 28th ACM International Conference on Multimedia* 2020.

Human Motion Skeleton-Based Sequence





Sample taken from the HumanAct12 dataset



Guo, Chuan, et al. "Action2motion: Conditioned generation of 3d human motions." *Proceedings of the 28th ACM International Conference on Multimedia* 2020.

Human Motion Skeleton-Based Sequence




Sample taken from the HumanAct12 dataset




Guo, Chuan, et al. "Action2motion: Conditioned generation of 3d human motions." *Proceedings of the 28th ACM International Conference on Multimedia* 2020.

Rehabilitation Assessment



Patient's Recorded Exercises




Samples taken from the Kimore dataset



Capecci, Marianna, et al. "The kimore dataset: Kinematic assessment of movement and clinical scores for remote monitoring of physical rehabilitation." *IEEE Transactions on Neural Systems and Rehabilitation Engineering* 2019.

Patient's Recorded Exercises




Samples taken from the Kimore dataset



Capecci, Marianna, et al. "The kimore dataset: Kinematic assessment of movement and clinical scores for remote monitoring of physical rehabilitation." *IEEE Transactions on Neural Systems and Rehabilitation Engineering* 2019.


Deep Learning for Human Rehabilitation: An Extrinsic Regression Task



Used Architecture: Fully Convolutional Network.

- Wang, Zhiguang, Weizhong Yan, and Tim Oates. "Time series classification from scratch with deep neural networks: A strong baseline." *International joint conference on neural networks (IJCNN)* 2017.


Averaging Augmentation




Averaging Augmentation to Create Synthetic Time Series

How to create synthetic time series ?


- We averaged a set of time series and took the average as a new synthetic object
- We used weighted averages to generate multiple synthetic objects



(a) Set of time series



(b) Average time series



(c) Extended dataset


Samples taken from the ECG200 dataset.

- [1] Petitjean, F., Ketterlin, A., & Gançarski, P. (2011). A global averaging method for dynamic time warping, with applications to clustering. *Pattern Recognition*, 44(3), 678-693.
- [2] Forestier, G., et al. "Generating synthetic time series to augment sparse datasets." 2017 *IEEE International Conference on Data Mining (ICDM)*. IEEE, 2017.
- [3] Ismail-Fawaz, A. et al. "ShapeDBA: Generating Effective Time Series Prototypes using ShapeDTW Barycenter Averaging." *ECML/PKDD Workshop on Advanced Analytics and Learning on Temporal Data*, 2023


Averaging Augmentation to Create Synthetic Time Series

How to create synthetic time series ?


- We averaged a set of time series and took the average as a new synthetic object
- We used weighted averages to generate multiple synthetic objects



(d) Set of time series



(e) Weighted average time series




(f) Extended dataset


Samples taken from the ECG200 dataset.

- [1] Petitjean, F., Ketterlin, A., & Gançarski, P. (2011). A global averaging method for dynamic time warping, with applications to clustering. *Pattern Recognition*, 44(3), 678-693.
- [2] Forestier, G., et al. "Generating synthetic time series to augment sparse datasets." 2017 *IEEE International Conference on Data Mining (ICDM)*. IEEE, 2017.
- [3] Ismail-Fawaz, A. et al. "ShapeDBA: Generating Effective Time Series Prototypes using ShapeDTW Barycenter Averaging." *ECML/PKDD Workshop on Advanced Analytics and Learning on Temporal Data*, 2023


Averaging Augmentation in Case of Regression Tasks




Averaging Augmentation in Case of Regression Tasks




Averaging Augmentation in Case of Regression Tasks




Averaging Augmentation in Case of Regression Tasks




Averaging Augmentation in Case of Regression Tasks




Averaging Augmentation in Case of Regression Tasks



Qualitative Evaluation of Generation



Qualitative Evaluation of Generation




Quantitative Evaluation: Data Extension

1. We define five different train/test splits per exercise, using a cross subject setup
2. ShapeDBA augmentation: For each training sample, we generate one new sample using the reference sample and its N nearest neighbors ($N \in [1, 5]$)
3. Noisy augmentation: For each training sample, we add a Gaussian white noise
4. We perform six experiments training and evaluation is done over the same test set

Training Set	Exercise 1	Exercise 2	Exercise 3	Exercise 4	Exercise 5
MAE					
Ref.	0.206 ± 0.069	0.202 ± 0.037	0.204 ± 0.055	0.184 ± 0.068	0.224 ± 0.058
Ref. + Noise	0.186 ± 0.065	0.172 ± 0.040	0.203 ± 0.045	0.185 ± 0.073	0.229 ± 0.069
Ref. + ShapeDBA NN1	<u>0.167 ± 0.070</u>	<u>0.175 ± 0.030</u>	0.182 ± 0.051	0.141 ± 0.062	0.208 ± 0.079
Ref. + ShapeDBA NN2	0.169 ± 0.057	0.177 ± 0.041	<u>0.194 ± 0.041</u>	<u>0.168 ± 0.056</u>	0.226 ± 0.066
Ref. + ShapeDBA NN3	0.173 ± 0.063	0.183 ± 0.047	<u>0.199 ± 0.058</u>	<u>0.168 ± 0.083</u>	0.225 ± 0.055
Ref. + ShapeDBA NN4	0.168 ± 0.059	0.179 ± 0.043	0.199 ± 0.043	0.180 ± 0.080	0.231 ± 0.060
Ref. + ShapeDBA NN5	0.166 ± 0.067	0.185 ± 0.043	0.201 ± 0.050	0.182 ± 0.089	0.226 ± 0.061
RMSE					
Ref.	0.251 ± 0.083	0.247 ± 0.045	0.248 ± 0.065	0.230 ± 0.083	0.267 ± 0.073
Ref. + Noise	0.203 ± 0.078	0.226 ± 0.043	0.238 ± 0.046	0.227 ± 0.090	0.274 ± 0.092
Ref. + ShapeDBA NN1	<u>0.199 ± 0.087</u>	0.226 ± 0.036	0.214 ± 0.054	0.178 ± 0.074	0.251 ± 0.094
Ref. + ShapeDBA NN2	<u>0.203 ± 0.075</u>	0.232 ± 0.052	<u>0.226 ± 0.044</u>	<u>0.210 ± 0.074</u>	0.268 ± 0.083
Ref. + ShapeDBA NN3	0.205 ± 0.082	0.235 ± 0.050	0.240 ± 0.062	0.214 ± 0.105	0.268 ± 0.066
Ref. + ShapeDBA NN4	0.198 ± 0.071	0.235 ± 0.050	0.234 ± 0.048	0.230 ± 0.105	0.279 ± 0.070
Ref. + ShapeDBA NN5	0.202 ± 0.079	0.230 ± 0.049	0.244 ± 0.057	0.231 ± 0.109	0.280 ± 0.080

Take Away Message



- Paper titled "Weighted Average of Human Motion Sequences for Improving Rehabilitation Assessment"
- Data augmentation / Generation of synthetic temporal data is still an evolving domain, and it should depend on the application such as the case of human motion rehabilitation
- Weighted ShapeDBA allows the association of a contribution value for each sample when producing the average sequence
- We believe in reproducibility
<https://github.com/MSD-IRIMAS/Weighted-ShapeDBA-4-Rehab>
- Contact: ali-el-hadi.ismail-fawaz@uha.fr
- Website: <https://hadifawaz1999.github.io/>