

Weighted Average of Human Motion Sequences for Improving Rehabilitation Assessment

Ali Ismail-Fawaz¹, Maxime Devanne¹, Stefano Berretti², Jonathan Weber¹, and Germain Forestier^{1,3}

¹ IRIMAS, Université de Haute-Alsace, France

² MICC, University of Florence, Italy

³ DSAI, Monash University, Australia
ali-el-hadi.ismail-fawaz@uha.fr

Abstract


Context :

- The specific task of assessing rehabilitation motion is difficult due to the lack of annotated data
- Traditional augmentation techniques often produce meaningless human motion sequences, particularly in the context of rehabilitation
- In rehabilitation assessment, labels are continuous values representing movement quality, making it difficult to assign labels to augmented data


Contribution :

- We investigate the use of ShapeDBA [4] for human skeleton sequences to generate average rehabilitation movements
- We extend the averaging method by a weighting strategy [3, 2] that allows generating more various but yet coherent sequences
- We leverage the weighting strategy for associating meaningful continuous labels to synthetic rehabilitation sequences
- We consider the proposed method for extending a small real-world rehabilitation dataset [1] and evaluate it on an extrinsic regression task

Proposed Generative Setup



Deep Learning for Regression Architecture




References

- [1] Marianna Capecci, Maria Gabriella Ceravolo, Francesco Ferracuti, Sabrina Iarlori, Andrea Monteriu, Luca Romeo, and Federica Verdini. The kimore dataset: Kinematic assessment of movement and clinical scores for remote monitoring of physical rehabilitation. *IEEE Transactions on Neural Systems and Rehabilitation Engineering*, 27(7):1436–1448, 2019.
- [2] G. Forestier, F. Petitjean, G. Webb, H-A. Dau, and E. Keogh. Generating synthetic time series to augment sparse datasets. In *IEEE International Conference on Data Mining (ICDM)*, pages 865–870, 2017.
- [3] Ali Ismail-Fawaz, Maxime Devanne, Stefano Berretti, Jonathan Weber, and Germain Forestier. Weighted elastic barycenter averaging to augment time series data. <https://github.com/MSD-IRIMAS/Augmenting-TSC-Elastic-Averaging>, 2024.
- [4] Ali Ismail-Fawaz, Hassan Ismail Fawaz, François Petitjean, Maxime Devanne, Jonathan Weber, Stefano Berretti, Geoffrey I Webb, and Germain Forestier. Shapedba: Generating effective time series prototypes using shapedtw barycenter averaging. In *International Workshop on Advanced Analytics and Learning on Temporal Data*, pages 127–142. Springer, 2023.

Acknowledgments

This work was supported by the ANR DELEGATION project (grant ANR-21-CE23-0014) of the French Agence Nationale de la Recherche. The authors would like to acknowledge the High Performance Computing Center of the University of Strasbourg for supporting this work by providing scientific support and access to computing resources. Part of the computing resources were funded by the Equipex Equip@Meso project (Programme Investissements d'Avenir) and the CPER Alsacalcul/Big Data. The authors would also like to thank the creators and providers of the Kimore dataset

Article & Source Code



Qualitative & Quantitative Results




Table 1: MAE and RMSE errors obtained for all compared approaches on each exercise separately. Best values are emphasized in bold, while second best values are underlined.

Training Set	Exercise 1	Exercise 2	Exercise 3	Exercise 4	Exercise 5
MAE					
Ref.	0.206 ± 0.069	0.202 ± 0.037	0.204 ± 0.055	0.184 ± 0.068	<u>0.224 ± 0.058</u>
Ref. + Noise	0.186 ± 0.065	0.172 ± 0.040	0.203 ± 0.045	0.185 ± 0.073	0.229 ± 0.069
Ref. + ShapeDBA NN1	0.167 ± 0.070	0.175 ± 0.030	0.182 ± 0.051	0.141 ± 0.062	0.208 ± 0.079
Ref. + ShapeDBA NN2	0.169 ± 0.057	0.177 ± 0.041	<u>0.194 ± 0.041</u>	<u>0.168 ± 0.056</u>	0.226 ± 0.066
Ref. + ShapeDBA NN3	0.173 ± 0.063	0.183 ± 0.047	0.199 ± 0.058	0.168 ± 0.083	0.225 ± 0.055
Ref. + ShapeDBA NN4	0.168 ± 0.059	0.179 ± 0.043	0.199 ± 0.043	0.180 ± 0.080	0.231 ± 0.060
Ref. + ShapeDBA NN5	0.166 ± 0.067	0.185 ± 0.043	0.201 ± 0.050	0.182 ± 0.089	0.226 ± 0.061
RMSE					
Ref.	0.251 ± 0.083	0.247 ± 0.045	0.248 ± 0.065	0.230 ± 0.083	0.267 ± 0.073
Ref. + Noise	0.203 ± 0.078	0.226 ± 0.043	0.238 ± 0.046	0.227 ± 0.090	0.274 ± 0.092
Ref. + ShapeDBA NN1	<u>0.199 ± 0.087</u>	0.226 ± 0.036	0.214 ± 0.054	0.178 ± 0.074	0.251 ± 0.094
Ref. + ShapeDBA NN2	0.203 ± 0.075	0.232 ± 0.052	<u>0.226 ± 0.044</u>	<u>0.210 ± 0.074</u>	0.268 ± 0.083
Ref. + ShapeDBA NN3	0.205 ± 0.082	0.235 ± 0.050	0.240 ± 0.062	0.214 ± 0.105	0.268 ± 0.066
Ref. + ShapeDBA NN4	0.198 ± 0.071	0.235 ± 0.050	0.234 ± 0.048	0.230 ± 0.105	0.279 ± 0.070
Ref. + ShapeDBA NN5	0.202 ± 0.079	0.230 ± 0.049	0.244 ± 0.057	0.231 ± 0.109	0.280 ± 0.080