

(a) Intermediate Depth of Cut

Held-out DOC: 1.5 and 2.0 mm

N01	N02	N03	N04	N05	N06	N07	N08
N09	N10	N11	N12	N13	N14	N15	N16
N17	N18	N19	N20	N21	N22	N23	N24
N25	N26	N27	N28	N29	N30	N31	N32
N33	N34	N35	N36	N37	N38	N39	N40

Train: 25 conditions | Test: 15 conditions

(b) Unseen Speed-Feed

Held-out speed--feed: 1800 rpm / 180 mm min⁻¹

N01	N02	N03	N04	N05	N06	N07	N08
N09	N10	N11	N12	N13	N14	N15	N16
N17	N18	N19	N20	N21	N22	N23	N24
N25	N26	N27	N28	N29	N30	N31	N32
N33	N34	N35	N36	N37	N38	N39	N40

Train: 31 conditions | Test: 9 conditions

(c) Cross-Geometry

Train: Type A (L = 36 mm) | Held-out: Type B (L = 56 mm)

N01	N02	N03	N04	N05	N06	N07	N08
N09	N10	N11	N12	N13	N14	N15	N16
N17	N18	N19	N20	N21	N22	N23	N24
N25	N26	N27	N28	N29	N30	N31	N32
N33	N34	N35	N36	N37	N38	N39	N40

Train: 19 conditions | Test: 21 conditions

Train

Held-out Test