

Homework 2: Reference Sheet

Hadley Stabnau

2026-01-27

Tips and Tricks

- Must load packages at the beginning of the document/before you try to do anything with them.
- If you're curious about a line of code, package, dataset etc., simply type ? followed by the "title" of the thing you're wondering about.
- Message=false takes away the long, unnecessary message that comes with packages like tidyverse.

```
library(tidyverse)
?tidyverse
```

- relocate() moves variables around and by default, moves them to the front.

```
library(nycflights13)
flights |>
  relocate(air_time,)
```

A tibble: 336,776 x 19

	air_time	year	month	day	dep_time	sched_dep_time	dep_delay	arr_time
	<dbl>	<int>	<int>	<int>	<int>	<int>	<dbl>	<int>
1	227	2013	1	1	517	515	2	830
2	227	2013	1	1	533	529	4	850
3	160	2013	1	1	542	540	2	923
4	183	2013	1	1	544	545	-1	1004
5	116	2013	1	1	554	600	-6	812
6	150	2013	1	1	554	558	-4	740
7	158	2013	1	1	555	600	-5	913
8	53	2013	1	1	557	600	-3	709

```

 9      140 2013      1      1      557      600      -3      838
10      138 2013      1      1      558      600      -2      753
# i 336,766 more rows
# i 11 more variables: sched_arr_time <int>, arr_delay <dbl>, carrier <chr>,
#   flight <int>, tailnum <chr>, origin <chr>, dest <chr>, distance <dbl>,
#   hour <dbl>, minute <dbl>, time_hour <dtm>

```

- `rename()` keeps all existing variables and just renames those that you tell it to.

```

flights |>
  rename(tail_num=tailnum)

```

```

# A tibble: 336,776 x 19
   year month   day dep_time sched_dep_time dep_delay arr_time sched_arr_time
   <int> <int> <int>   <int>         <int>         <dbl>   <int>         <int>
1  2013     1     1     517           515           2     830           819
2  2013     1     1     533           529           4     850           830
3  2013     1     1     542           540           2     923           850
4  2013     1     1     544           545          -1    1004          1022
5  2013     1     1     554           600          -6     812           837
6  2013     1     1     554           558          -4     740           728
7  2013     1     1     555           600          -5     913           854
8  2013     1     1     557           600          -3     709           723
9  2013     1     1     557           600          -3     838           846
10 2013     1     1     558           600          -2     753           745
# i 336,766 more rows
# i 11 more variables: arr_delay <dbl>, carrier <chr>, flight <int>,
#   tail_num <chr>, origin <chr>, dest <chr>, air_time <dbl>, distance <dbl>,
#   hour <dbl>, minute <dbl>, time_hour <dtm>

```

- `select()` renames variables, inside of the parenthesis use `=` and put the new name on the LHS and the old name on the RHS. But `select` gets rid of the other columns not being called upon.

```

flights |>
  select(tail_num=tailnum)

```

```

# A tibble: 336,776 x 1
   tail_num
   <chr>
1 N14228
2 N24211

```

3 N619AA
4 N804JB
5 N668DN
6 N39463
7 N516JB
8 N829AS
9 N593JB
10 N3ALAA
i 336,766 more rows