

universität freiburg



7TH ENZYMEML WORKSHOP · RÜDESHEIM · HANDS-ON SESSION 2 · 16 SEPTEMBER 2026


From measurement to kinetic modelling

Max Häußler

University of Freiburg

Last year the code was the hurdle


Previous hands-on sessions: we installed, read the docs and wrote the analysis code ourselves



- Failing installs and unfamiliar code: a hurdle for everyone who does not code daily
- So the data stayed unstructured, and the contemporary methods out of reach
- **Since then:** the models got better, and so did the harnesses that let them run tools

From 23 to 53 in one year

The two labs traded the lead several times; the biggest single step was Fable 5 in June 2026



- The Intelligence Index is an independent score from 0 to 100 that combines many tests of knowledge, reasoning, coding and agentic work, with every model tested the same way.
- Shown are the flagship models of Anthropic and OpenAI that anyone can use, each at its strongest public setting.


Artificial Analysis Intelligence Index v4.3, artificialanalysis.ai; release dates from the vendors

The assistant types, you decide




One page is enough

From a one-page card, today's models write working code for our tools




Blind to your data

Where the peak is, which model is right, when a result is wrong



You decide and check


The decisions and the checks stay with the scientist; the assistant executes



EnzymeML in between

One document carries the data between the steps and the tools

Tools act, skills instruct, you decide




- Tools let the model read the data and run code; skills tell it how our libraries turn data into insight

WORKFLOW


Two tasks, one document in between

Task 1 ends with the EnzymeML document; task 2 starts from it




Chromhandler: from peak tables to concentrations

Reads the instrument's exports, assigns and calibrates one peak per compound, writes EnzymeML




Catalax: from time courses to kinetic parameters

Builds the ODE model from a rate law and samples the posterior of its parameters



THE EXPERIMENT

ManNAc + PEP → Neu5Ac + Pi, followed by HPLC



- Reactions sampled over time and followed by HPLC-PDA at 215 nm
- What you get is the instrument's peak table per injection, not the raw trace
- Only the product Neu5Ac is quantified; calibration standards with known concentrations
- How many reactions, which conditions, how they were varied: that is in the data

Data: Çakar et al. (2024) Kinetic characterization of two neuraminic acid synthases and evaluation of their application potential. Appl. Microbiol. Biotechnol. 108, 446 · doi:10.1007/s00253-024-13277-1

TODAY

What we do today

- **Task 1:** from the peak tables to an EnzymeML document (Chromhandler)
- **Task 2:** from the EnzymeML document to k_{cat} and K_M by Bayesian inference (Catalax)
- A live demo of each task first, then you work in pairs
- The checks in the task card say when you are done
- At the end we compare everybody's parameters and discuss

One repository, two ways to work

tinyurl.com/enzymeml2026 · start with the README

With a language model

- **Any chat model**, free or by subscription: ChatGPT, Claude, Gemini, ...
- **Paste** the tool card and the task card; run the code, paste errors back
- **The checks** decide when you are done
- **notebooks/** are the reference solutions, checkpoints/ the result of task 1

Without writing code

- **Open the Colab link**: a prepared notebook, tools installed, data loaded
- **Run it cell by cell**; change a window, a prior, a series
- **Ask the model in Colab** to explain any cell

TASK 1

Task 1: from chromatograms to EnzymeML

Result: an EnzymeML document with the Neu5Ac time course of every reaction

- **Plot the data:** all peaks of all injections; where does Neu5Ac elute?
- **Check how the kinetic assay was designed:** how many reactions, what was varied, what was fixed?
- **Calibrate:** what are the calibration parameters, and how well does the line fit?
- **Set the retention window** for the reactions (it differs from the standards) and assign the peak
- **Export the EnzymeML document:** every reaction with all its time points; which reactions form product?

How to do it

- **Coding assistant on your machine** (Claude Code, Codex, Cursor, ...): open the repository, give it `briefs/chromhandler.md` and `briefs/task_1_chromatograms_to_enzymeml.md`, then say: let's start with task 1
- **Chat assistant only** (ChatGPT, Claude, Gemini, ...): open the Colab starter notebook from the README, paste the two cards into the chat, run its code in the notebook
- **No assistant that runs code?** team up with someone who has one
- **Repository, data and cards:**
tinyurl.com/enzymeml2026

TASK 2

Task 2: kinetic parameters by Bayesian inference


$$v = k_{\text{cat}} \cdot [\text{NeuS}] \cdot [\text{ManNAc}] \cdot [\text{PEP}] / ((K_M^{\text{ManNAc}} + [\text{ManNAc}]) (K_M^{\text{PEP}} + [\text{PEP}]))$$

- **Plot the time courses** from the EnzymeML document
- **Define the model and the priors:** the enzyme is in the rate law, only Neu5Ac is measured
- **Infer the kinetic parameters:** k_{cat} , K_M^{ManNAc} and K_M^{PEP} , each with its uncertainty
- **Check the sampler:** do the chains agree, divergences, posterior clear of the prior bounds?
- **What is the correlation between the kinetic parameters?**
- **Does one model describe both series?** plot data and model together

How to do it

- **Coding assistant on your machine** (Claude Code, Codex, Cursor, ...): open the repository, give it `briefs/catalax.md` and `briefs/task_2_kinetic_model.md`, then say: let's start with task 2
- **Chat assistant only** (ChatGPT, Claude, Gemini, ...): open the Colab starter notebook from the README, paste the two cards into the chat, run its code in the notebook
- **No assistant that runs code?** team up with someone who has one
- **No result from task 1?** start from `checkpoints/neus_enzymeml.json`
- **Repository, data and cards:** tinyurl.com/enzymeml2026

The reference fit, and an open question



Parameter	Posterior mean $\pm$ sd
k_{cat}	$364 \pm 6 \text{ min}^{-1}$ (6.1 s^{-1} , 9.4 U/mg)
K_M^{ManNAc}	$1.53 \pm 0.19 \text{ mM}$
K_M^{PEP}	$0.59 \pm 0.07 \text{ mM}$

- One shared k_{cat} over-predicts the ManNAc series and under-predicts the PEP series
- The two series were measured on different days and differ by roughly 25 % in activity
- What would you do next?

What to take home

- A one-page card is enough for an assistant to drive our tools
- The decisions and the checks stay with the scientist
- The cards are reusable as SKILL.md or AGENTS.md in coding agents
- What did not work for you today is the most useful feedback for us

Thank you

tinyurl.com/enzymeml2026

MAX HÄUBLER · UNIVERSITY OF FREIBURG



universität freiburg

